IDEC





IDEC

RH2B-UTAC24V

Part Number:

Manufacturer/Brand:

Product description Datasheets: RoHs Status

Ship From Shipment Way RH2B-UTAC24V

IDEC

RELAY GEN PURPOSE DPDT 10A 24V

RH2B-UTAC24V.pdf

Lead free / RoHS Compliant Hong Kong

DHL/Fedex/TNT/UPS/EMS

REQUEST FOR QUOTATION

Image may be representation. See specifications for product details.

PART NUMBER MANUFACTURER IDEC DESCRIPTION RELAY GEN PURPOSE DPDT 10A 24V Lead Free STATUS / ROHS STATUS Load free / ROHS Compilant DATA SHEET TURN ON VOLTAGE (MAX) 19.2 VAC TURN OF VOLTAGE (MIN) 7.2 VAC TERMINATION STYLE Quida Connect - 0.187" (4.7mm) SWITTCHING VOLTAGE 240VAC, 30VDC - Max SERIES RH RELAYS TIME 20ms RELAY TYPE General Purpose PACKAGING DERATING TEMPERATURE 2.5°C ~ 70°C OPERATE TIME MOUNTING TYPE Chassis Mount MANUFACTURER STANDARD LEAD TIME 4 Weeks Lead free / ROHS Compilant FEATURES - DETAILED DESCRIPTION General Purpose Relay DPDT (2 Form C) 24VAC Call Chassis Mount CONTACT MATERIAL Silver Cadmium Oxide (AgCdD) CONTACT RATING (CURRENT) LOAD RESISTANCE 201L FORM COLL VOLTAGE 24VAC COLL TYPE Non Latching COLL RESISTANCE 153 Ohms COLL CURRENT 50.0mA		Specifications of RH2B-UTAC24V
MANUFACTURER DESCRIPTION RELAY GEN PURPOSE DPDT 10A 24V LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compilant DATA SHEET TURN ON VOLTAGE (MAX) 19.2 VAC TURN ON FVOLTAGE (MIN) 7.2 VAC TERMINATION STYLE Quick Connect - 0.187" (4.7mm) SWITCHING VOLTAGE RELAY ETIME RELAGE TIME ZOMS RELAY TYPE General Purpose PACKAGING Bulk OTHER NAMES 1885-1594 OPERATING TEMPERATURE 20ms MOUNTING TYPE Chassis Mount MANUFACTURER STANDARD LEAD TIME 4 Weeks LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compilant FEATURES - DETAILED DESCRIPTION General Purpose Relay DPDT (2 Form C) 24VAC Coil Chassis Mount CONTACT RATING (CURRENT) CONTACT RATING (CURRENT) COIL VOLTAGE 24VAC COIL VOLTAGE 24VAC COIL POWER COIL POWER - COIL POWER - COIL POWER - COIL POWER		
DESCRIPTION RELAY GEN PURPOSE DPDT 10A 24V LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant DATA SHEET RINE ROMAN 19.2 VAC TURN ON VOLTAGE (MAX) 19.2 VAC TURN OFF VOLTAGE (MIN) 7.2 VAC TERMINATION STYLE Quick Connect - 0.187' (4.7mm) SWITCHING VOLTAGE 240VAC, 30VDC - Max SERIES RH RELEASE TIME 20ms RELAY TYPE General Purpose PACKAGING Bulk OTHER NAMES 1885-1594 OPERATURG TEMPERATURE -25°C ~ 70°C OPERATE TIME 20ms MOUNTING TYPE Chassis Mount MANUFACTURER STANDARD LEAD TIME 4 Weeks LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant FEATURES - DETAILED DESCRIPTION General Purpose Relay DPDT (2 Form C) 24VAC Coil Chassis Mount CONTACT RATING (CURRENT) 10A CONTACT RATING (CURRENT) 10A CONTACT RATING (CURRENT) 10A CONTACT RATING (CURRENT) 24VAC COIL YOUT AGE 24VAC COIL TYPE NO LASSISTANCE 153 Ohms COLL POWER -	PART NUMBER	RH2B-UTAC24V
LEAD FREE STATUS / ROHS STATUS LEad free / ROHS Compliant DATA SHEET TURN ON VOLTAGE (MAX) 19.2 VAC TURN OFF VOLTAGE (MIN) 7.2 VAC TERMINATION STYLE Quick Connect - 0.187" (4.7mm) SWITCHING VOLTAGE 240VAC, 30VDC - Max SERIES RH RELEASE TIME 20ms RELAY TYPE General Purpose PACKAGING DHER NAMES 1865-1594 OPERATING TEMPERATURE -25°C ~ 70°C OPERATE TIME 20ms MOUNTING TYPE Chassis Mount MANUFACTURER STANDARD LEAD TIME 4 Weeks LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant FEATURES - DETAILED DESCRIPTION General Purpose Reley DPDT (2 Form C) 24VAC Coil Chassis Mount CONTACT MATERIAL Silver Cadmium Oxide (AgCdO) CONTACT MATERIAL SILVER CADMIUM OXIDER COIL YOUTAGE 24VAC COIL TYPE Non Latching COIL RESISTANCE 153 Ohms COIL POWER	MANUFACTURER	IDEC
TURN ON VOLTAGE (MAX) TURN OF VOLTAGE (MIN) 7.2 VAC TERMINATION STYLE Quidk Connect - 0.187" (4.7mm) SWITCHING VOLTAGE 240VAC, 30VDC - Max SERIES RH RELEASE TIME 20ms RELAY TYPE General Purpose Bulk OTHER NAMES OPERATING TEMPERATURE 22°C ~ 7°C OPERATE TIME 20ms MOUNTING TYPE Chassis Mount MANUFACTURER STANDARD LEAD TIME 4 Weeks LEAD FREE STATUS / ROHS STATUS LEAD FREE STATUS / ROHS STATUS DETAILED DESCRIPTION CONTACT RATING (CURRENT) CONTACT MATERIAL SIEVE CAdmium Oxide (AgCdO) CONTACT MATERIAL SIEVE COLL FORM COLL FORM COLL FORM COLL RESISTANCE 153 Ohms COLL POWER - 1885 STANCE 153 Ohms COLL POWER	DESCRIPTION	RELAY GEN PURPOSE DPDT 10A 24V
TURN ON VOLTAGE (MIN) 7.2 VAC TERMINATION STYLE QUIck Connect - 0.187" (4.7mm) SWITCHING VOLTAGE 240VAC, 30VDC - Max SERIES RH RELEASE TIME 20ms RELAY TYPE General Purpose Bulk OTHER NAMES 1885-1594 OPERATING TEMPERATURE 20ms MOUNTING TYPE Chassis Mount MANUFACTURER STANDARD LEAD TIME LEAD FREE STATUS / ROHS STATUS LEAD free FRATURES - DETAILED DESCRIPTION General Purpose Relay DPDT (2 Form C) 24VAC Coil Chassis Mount CONTACT MATERIAL Silver Cadmium Oxide (AgCdO) CONTACT FORM DPDT (2 Form C) COLL YOLTAGE 24VAC COLL RESISTANCE 153 Ohms COLL POWER - COLL POWER - TEMPINATION STATUS 19.2 VAC 24VAC COLL POWER - COLL POWER - COLL POWER - CARSISTANCE 153 Ohms - COLL POWER - CARSISTANCE - COLL POWER - C	LEAD FREE STATUS / ROHS STATUS	Lead free / RoHS Compliant
TURN OFF VOLTAGE (MIN) TERMINATION STYLE Quick Connect - 0.187" (4.7mm) SMITCHING VOLTAGE 240VAC, 30VDC - Max RELESS RH RELEASE TIME 20ms RELAY TYPE General Purpose PACKAGING Bulk OTHER NAMES 1885-1594 OPERATING TEMPERATURE -25°C ~ 70°C OPERATE TIME MOUNTING TYPE Chassis Mount MANUFACTURER STANDARD LEAD TIME 4 Weeks LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant FEATURES - DETAILED DESCRIPTION General Purpose Relay DPDT (2 Form C) 24VAC Coil Chassis Mount CONTACT MATERIAL Silver Cadmium Oxide (AgCdO) CONTACT MATERIAL SILVER SHACE COIL YOLTAGE OUL TYPE NON LAICHING COIL RESISTANCE 153 Ohms COIL POWER - VANC Quick Connect - 0.187" (4.7mm) AND AND AND AND AND AND AND AN	DATA SHEET	RH2B-UTAC24V.pdf
TERMINATION STYLE Quick Connect - 0.187" (4.7mm) SWITCHING VOLTAGE 240VAC, 30VDC - Max SERIES RH RELEASE TIME 20ms RELAY TYPE General Purpose PACKAGING Bulk OTHER NAMES 1885-1594 OPERATING TEMPERATURE -25°C ~ 70°C OPERATE TIME 20ms MOUNTING TYPE Chassis Mount MANUFACTURER STANDARD LEAD TIME 4 Weeks LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant FEATURES - DETAILED DESCRIPTION General Purpose Relay DPDT (2 Form C) 24VAC Coil Chassis Mount CONTACT MATERIAL Silver Cadmium Oxide (AgCdO) CONTACT FORM DPDT (2 Form C) COIL YOLTAGE 24VAC COIL TYPE Non Latching COIL POWER -	TURN ON VOLTAGE (MAX)	19.2 VAC
SERIES RH RELEASE TIME 20ms RELAY TYPE General Purpose Bulk OTHER NAMES 1885-1594 OPERATING TEMPERATURE -25°C ~ 70°C OPERATE TIME 20ms MOUNTING TYPE Chassis Mount MANUFACTURER STANDARD LEAD TIME 4 Weeks LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant FEATURES - DETAILED DESCRIPTION General Purpose Relay DPDT (2 Form C) 24VAC Coil Chassis Mount CONTACT RATING (CURRENT) 10A CONTACT MATERIAL Silver Cadmium Oxide (AgCdO) CONTACT FORM DPDT (2 Form C) COIL YOLTAGE 24VAC COIL TYPE Non Latching COIL RESISTANCE 153 Ohms COIL POWER -	TURN OFF VOLTAGE (MIN)	7.2 VAC
RELASE TIME 20ms RELAY TYPE General Purpose PACKAGING Bulk OTHER NAMES 1885-1594 OPERATING TEMPERATURE -25°C ~ 70°C OPERATE TIME 20ms MOUNTING TYPE Chassis Mount MANUFACTURER STANDARD LEAD TIME 4 Weeks LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant FEATURES - DETAILED DESCRIPTION General Purpose Relay DPDT (2 Form C) 24VAC Coil Chassis Mount CONTACT RATING (CURRENT) 10A CONTACT MATERIAL Silver Cadmium Oxide (AgCdO) CONTACT FORM DPDT (2 Form C) COIL VOLTAGE 24VAC COIL TYPE Non Latching COIL RESISTANCE 153 Ohms COIL POWER -	TERMINATION STYLE	Quick Connect - 0.187" (4.7mm)
RELAY TYPE General Purpose Bulk OTHER NAMES Bulk OTHER NAMES 1885-1594 OPERATING TEMPERATURE -25°C ~ 70°C OPERATE TIME ZOMS MOUNTING TYPE Chassis Mount MANUFACTURER STANDARD LEAD TIME LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant FEATURES - DETAILED DESCRIPTION General Purpose Relay DPDT (2 Form C) 24VAC Coil Chassis Mount CONTACT RATING (CURRENT) LONTACT FORM DPDT (2 Form C) COIL VOLTAGE 24VAC COIL TYPE Non Latching COIL RESISTANCE 153 Ohms COIL POWER Bulk General Purpose General Purpose General Purpose Relay DPDT (2 Form C) 24VAC Coil Chassis Mount CONTACT FORM DPDT (2 Form C) COIL VOLTAGE	SWITCHING VOLTAGE	240VAC, 30VDC - Max
RELAY TYPE PACKAGING Bulk OTHER NAMES 1885-1594 OPERATING TEMPERATURE -25°C ~ 70°C OPERATE TIME 20ms MOUNTING TYPE Chassis Mount MANUFACTURER STANDARD LEAD TIME 4 Weeks LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant FEATURES - DETAILED DESCRIPTION General Purpose Relay DPDT (2 Form C) 24VAC Coil Chassis Mount CONTACT RATING (CURRENT) CONTACT MATERIAL Silver Cadmium Oxide (AgCdO) CONTACT FORM DPDT (2 Form C) COIL YOLTAGE 24VAC COIL TYPE Non Latching COIL RESISTANCE - General Purpose Romeral Purpose Romer	SERIES	RH
PACKAGING OTHER NAMES 1885-1594 OPERATING TEMPERATURE -25°C ~ 70°C OPERATE TIME 20ms MOUNTING TYPE Chassis Mount MANUFACTURER STANDARD LEAD TIME LEAD FREE STATUS / ROHS STATUS LEAD FREE STATUS / ROHS STATUS LEAD FREE STATUS / ROHS STATUS DETAILED DESCRIPTION General Purpose Relay DPDT (2 Form C) 24VAC Coil Chassis Mount CONTACT RATING (CURRENT) CONTACT MATERIAL Silver Cadmium Oxide (AgCdO) CONTACT FORM DPDT (2 Form C) COIL VOLTAGE 24VAC COIL TYPE Non Latching COIL RESISTANCE 153 Ohms COIL POWER	RELEASE TIME	20ms
OTHER NAMES OPERATING TEMPERATURE -25°C ~ 70°C OPERATE TIME 20ms MOUNTING TYPE Chassis Mount MANUFACTURER STANDARD LEAD TIME LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant FEATURES - DETAILED DESCRIPTION General Purpose Relay DPDT (2 Form C) 24VAC Coil Chassis Mount CONTACT RATING (CURRENT) CONTACT MATERIAL Silver Cadmium Oxide (AgCdO) CONTACT FORM DPDT (2 Form C) COIL VOLTAGE 24VAC COIL TYPE Non Latching COIL RESISTANCE 153 Ohms COIL POWER	RELAY TYPE	General Purpose
OPERATING TEMPERATURE OPERATE TIME 20ms MOUNTING TYPE Chassis Mount MANUFACTURER STANDARD LEAD TIME 4 Weeks LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant FEATURES - DETAILED DESCRIPTION General Purpose Relay DPDT (2 Form C) 24VAC Coil Chassis Mount CONTACT RATING (CURRENT) 10A CONTACT MATERIAL Silver Cadmium Oxide (AgCdO) CONTACT FORM DPDT (2 Form C) COIL VOLTAGE 24VAC COIL TYPE Non Latching COIL RESISTANCE 153 Ohms COIL POWER -	PACKAGING	Bulk
OPERATE TIME MOUNTING TYPE Chassis Mount MANUFACTURER STANDARD LEAD TIME 4 Weeks LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant FEATURES - DETAILED DESCRIPTION General Purpose Relay DPDT (2 Form C) 24VAC Coil Chassis Mount CONTACT RATING (CURRENT) 10A CONTACT MATERIAL Silver Cadmium Oxide (AgCdO) CONTACT FORM DPDT (2 Form C) COIL VOLTAGE 24VAC COIL TYPE Non Latching COIL RESISTANCE 153 Ohms COIL POWER	OTHER NAMES	1885-1594
MOUNTING TYPE Chassis Mount MANUFACTURER STANDARD LEAD TIME 4 Weeks LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant FEATURES - DETAILED DESCRIPTION General Purpose Relay DPDT (2 Form C) 24VAC Coil Chassis Mount CONTACT RATING (CURRENT) 10A CONTACT MATERIAL Silver Cadmium Oxide (AgCdO) CONTACT FORM DPDT (2 Form C) COIL VOLTAGE 24VAC COIL TYPE Non Latching COIL RESISTANCE 153 Ohms COIL POWER	OPERATING TEMPERATURE	-25°C ~ 70°C
MANUFACTURER STANDARD LEAD TIME 4 Weeks LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant FEATURES - DETAILED DESCRIPTION General Purpose Relay DPDT (2 Form C) 24VAC Coil Chassis Mount CONTACT RATING (CURRENT) 10A CONTACT MATERIAL Silver Cadmium Oxide (AgCdO) CONTACT FORM DPDT (2 Form C) COIL VOLTAGE 24VAC COIL TYPE Non Latching COIL RESISTANCE 153 Ohms COIL POWER -	OPERATE TIME	20ms
Lead free / RoHS Compliant FEATURES - DETAILED DESCRIPTION General Purpose Relay DPDT (2 Form C) 24VAC Coil Chassis Mount CONTACT RATING (CURRENT) 10A CONTACT MATERIAL Silver Cadmium Oxide (AgCdO) CONTACT FORM DPDT (2 Form C) COIL VOLTAGE 24VAC COIL TYPE Non Latching COIL RESISTANCE 153 Ohms COIL POWER -	MOUNTING TYPE	Chassis Mount
FEATURES DETAILED DESCRIPTION General Purpose Relay DPDT (2 Form C) 24VAC Coil Chassis Mount CONTACT RATING (CURRENT) 10A CONTACT MATERIAL Silver Cadmium Oxide (AgCdO) CONTACT FORM DPDT (2 Form C) COIL VOLTAGE 24VAC COIL TYPE Non Latching COIL RESISTANCE 153 Ohms COIL POWER -	MANUFACTURER STANDARD LEAD TIME	4 Weeks
DETAILED DESCRIPTION General Purpose Relay DPDT (2 Form C) 24VAC Coil Chassis Mount 10A CONTACT MATERIAL Silver Cadmium Oxide (AgCdO) CONTACT FORM DPDT (2 Form C) COIL VOLTAGE 24VAC COIL TYPE Non Latching COIL RESISTANCE 153 Ohms COIL POWER -	LEAD FREE STATUS / ROHS STATUS	Lead free / RoHS Compliant
CONTACT RATING (CURRENT) 10A CONTACT MATERIAL Silver Cadmium Oxide (AgCdO) CONTACT FORM DPDT (2 Form C) COIL VOLTAGE 24VAC COIL TYPE Non Latching COIL RESISTANCE 153 Ohms COIL POWER -	FEATURES	-
CONTACT MATERIAL CONTACT FORM DPDT (2 Form C) COIL VOLTAGE COIL TYPE Non Latching COIL RESISTANCE 153 Ohms COIL POWER -	DETAILED DESCRIPTION	General Purpose Relay DPDT (2 Form C) 24VAC Coil Chassis Mount
CONTACT FORM COIL VOLTAGE COIL TYPE Non Latching COIL RESISTANCE 153 Ohms COIL POWER DPDT (2 Form C) 24VAC 154VAC Non Latching	CONTACT RATING (CURRENT)	10A
COIL VOLTAGE COIL TYPE Non Latching COIL RESISTANCE 153 Ohms COIL POWER -	CONTACT MATERIAL	Silver Cadmium Oxide (AgCdO)
COIL TYPE Non Latching COIL RESISTANCE 153 Ohms COIL POWER -	CONTACT FORM	DPDT (2 Form C)
COIL RESISTANCE 153 Ohms COIL POWER -	COIL VOLTAGE	24VAC
COIL POWER -	COIL TYPE	Non Latching
	COIL RESISTANCE	153 Ohms
COIL CURRENT 50.0mA	COIL POWER	-
	COIL CURRENT	50.0mA

Related Tags

· · · · · · · · · · · · · · · · · · ·		
IDEC RH2B-UTAC24V	RH2B-UTAC24V Distributor	RH2B-UTAC24V Supplier
RH2B-UTAC24V Price	RH2B-UTAC24V Pictures	RH2B-UTAC24V Image
RH2B-UTAC24V PDF Datasheet	RH2B-UTAC24V Download Datasheet	RH2B-UTAC24V Datasheet
RH2B-UTAC24V Stock	Buy RH2B-UTAC24V	Buy IDEC RH2B-UTAC24V
IDEC RH2B-UTAC24V	IDEC Supplier	IDEC Distributor
IDEC RH2B-UTAC24V		

Related Products



RH2B-UTDC24V Manufacturers: IDEC

Description: RELAY GEN PURPOSE DPDT 10A 24V In stock: 19 pcs

RFQ



RH2V2-UDC100-110V

Manufacturers: IDEC

Description: RELAY GEN PURPOSE DPDT 10A 110V In stock: 20 pcs

RFQ



RH2V2-UDC24V

Manufacturers: IDEC

Description: RELAY GEN PURPOSE DPDT 10A 24V In stock: 50 pcs

RFQ



RH2V2-UDC12V

Manufacturers: IDEC Description: RELAY GEN PURPOSE DPDT 10A 12V

In stock: 17 pcs

RFQ



RH2B-UTAC110-120V

Manufacturers: IDEC

Description: RELAY GEN PURPOSE DPDT 10A 120V In stock: 20 pcs

RFQ



RH2B-UTAC220-240V

Manufacturers: IDEC

Description: RELAY GEN PURPOSE DPDT 10A 240V In stock: 30 pcs

RFQ



RH2B-UTDC12V Manufacturers: IDEC

Description: RELAY GEN PURPOSE DPDT 10A 12V In stock: 38 pcs

RFQ



RH2B-ULDC12V

Manufacturers: IDEC Description: RELAY GEN PURPOSE DPDT 10A 12V

In stock: 17 pcs **RFQ**



RH2B-ULCDC24V Manufacturers: IDEC

Description: RELAY GEN PURPOSE DPDT 10A 24V In stock: 8 pcs

RFQ



Manufacturers: IDEC Description: RELAY GEN PURPOSE DPDT 10A 120V

RH2V2-UAC110-120V

In stock: 27 pcs

RFQ



RH2B-ULDC24V Manufacturers: IDEC Description: RELAY GEN PURPOSE DPDT 10A 24V

In stock: 419 pcs

RFQ



RH2B-ULD-DC24V Manufacturers: IDEC

RFQ

Description: RELAY GEN PURPOSE DPDT 10A 24V In stock: 37 pcs



Copyright © 2020 Reliable Distributor of Electronic Components - Ocean-Components.com











