

B. 300 series stainless steel backplate (0.015" thick). Manufacturing date code is stamped into stainless steel back plate.

ITEM	Description	CIRCUMF Min	ERENCE Max	Width	Links Inside	Links Outside
<u>09043</u>	Band Only, Large	7.25"	13"	.630"	40	41
<u>09044</u>	Band Only, Medium	6.5"	12"	.630"	36	37
<u>09045</u>	Band Only, Small	5.5"	10"	.630"	30	31
<u>09086</u>	Band w/6' Coil Cord, Large	7.25"	13"	.630"	40	41
<u>09087</u>	Band w/6' Coil Cord, Medium	6.5"	12"	.630"	36	37
<u>09088</u>	Band w/6' Coil Cord, Small	5.5"	10"	.630"	30	31

- C. 4mm snap stud machined from 300 series stainless steel. Fits to 4mm spring loaded medical type socket. Coil cord disengages from snap with 1-5 lbs. of perpendicular force. Durable, providing long life well beyond that of sheet metal snaps.
- D. Premium metal expansion wrist strap. Inside links are constructed of 300 Series Stainless Steel. Width of links is 0.630".
- E. .002" polyphenylsulfone sheet is laminated to each link before assembly. Provides >5,000 volt RMS insulation per ASTM D149. Will not flake or peel.
- F. Underwriters' Laboratory listed 90P1C.

Meets or exceeds requirements of EOS/ESD-S1-1987.



Specifications and procedures subject to change without notice.





