		Copyright FCI	0) FC FClconnect	.com യ	$\left(\begin{array}{c} \\ \end{array}\right)$	Þ	()	
form: A3 1 2	PACKAGING SPECIFICATION See :- GS-14-1139	Packaging as per GS-14-920 <u>PRODUCT SPECIFICATION</u> See :- GS-12-433	"This LF product meets European Union Directives and other country regulations as described in GS-22-008" The housing will withstand exposure to 260°C peak temperature for 30 seconds in a convection,infra-red or vapor reflow oven solder application.	A-2.00mm COMPATIBLE FOR 1.6mm PCB RoHS INFORMATIONS	HEIGHT OF TERMINATION	S-SOCKET TYPE OF TERMINATION 13-ANGLED SPILL PITCH 2.54 FOOT PRINT 10.40 EUROPE	NO.OF CONTACTS		1 2 3
	dr dr ANISH.SALAM 2007-12-04 and angr ANISH.SALAM 2009-08-23 sheet revision c ch ANISH.SALAM 2009-08-23 index sheet 2 1 angr anish.salam 2009-08-23	$\begin{array}{ c c c c c c c c c c c c c c c c c c c$	5	6-500 Mating/Un-mating perfo		RV->LIF METAL PEG+F.SCREW LOCK UNC 4 RL->LIF METAL PEG+ INSERT M3+METAL BR RX->LIF METAL PEG+ INSERT UNC 4-40 +ME	09- TRA	6 × × 0 9 F	

	5 6
D	08-23 Vype Product Customer Drawing
ſJ	TA-D A/S FEMALE PIP CONNECTOR EUROPE VERSION no sheet 1 (C-DD-0106
	e projection product family DELTA-D cified ⊕-← title
0	
	performance
ω	PLATING
	+METAL BRACKET
	- BRACKET
PDM: F	C 4 40+METAL BRACKET
Rev:C	MOUNTING OPTIONS
_⊅ st	TRAY PACKING
atus: <mark>Rel</mark>	KAGING SPECIFICATION
eased	SEE NOTE RoHS
Printed: Jan 1	
8, 2011	

σ

σ

