



- Computer with DisplayPort 1.2-compatible graphics card (e.g. AMD Radeon with AMD Eyefinity)
 required for video wall mode. Backward compatible with most DisplayPort 1.1a equipment running
 current graphics drivers with feature set limited to that of your equipment. Compatibility with older
 graphics cards not guaranteed.
- MST compliant DisplayPort 1.2 graphics cards are limited to a bandwidth of 21.6 Gbps amongst all monitors, with higher resolution monitors using up more bandwidth. 1080p monitors will use up approximately 22% of bandwidth, whereas 4K monitors will use 40% or more. As each monitor will be different, it is necessary to verify the percentage of bandwidth being used by each monitor in the display settings interface for your graphics card. If the total percentage of bandwidth taken up by all of the connected monitors exceeds 100%, an image will not display on one or more of them.

3-Port DisplayPort 1.2 to HDMI Multi-Stream Transport (MST) Hub, 3840 x 2160 (4K x 2K) @ 60 Hz UHD, TAA

MODEL NUMBER: B156-003-HD-V2









CLONE OR DUPLICATE MODE



Displays the same image on 3 HDMI monitors, extends the desktop across all three, or combines all into one large monitor. Ideal for digital signage in schools, churches, conference rooms, trade shows and retail outlets.

Description

The B156-003-HD-V2 3-Port DisplayPort 1.2 to HDMI MST Hub connects up to three HDMI monitors to the DisplayPort output on your computer. Ideal for digital signage in schools, churches, conference rooms, trade shows, hotels and retail outlets, this hub allows you to display the same image on all three monitors, extend the desktop across them, or combine all three as one large monitor in video wall mode.

The B156-003-HD-V2 is compliant with DisplayPort 1.2 and backward compatible with versions 1.1 and 1.1a with the feature set being limited to that of your equipment. It supports Ultra High Definition (UHD) video resolutions up to $3840 \times 2160 \text{ (4K} \times 2K)$ at 60 Hz. In video wall mode, it supports expanded resolutions, such as 5760×1080 in a horizontal 1 x 3 monitor configuration or 1920×3240 in a vertical 3 x 1 configuration.

This MST hub also supports HDCP, EDID, DDC and 48-bit Deep Color (16 bits per channel), as well as DTS-HD, Dolby TrueHD and 7.1-channel surround sound audio. It works with all operating systems. Plug-

Highlights

- Supports UHD video resolutions up to 3840 x 2160 (4K x 2K) @ 60 Hz
- Built-in 6 in. cable connects directly to DisplayPort source
- Supports up to 48-bit Deep Color (16 bits per channel)
- Works with all operating systems
- Supports DTS-HD, Dolby TrueHD and 7.1-channel surround sound

System Requirements

- Computer with DisplayPort 1.2compatible graphics card (e.g. AMD Radeon with AMD Eyefinity) required for video wall mode.
- Backward compatible with most
 DisplayPort 1.1a equipment
 running current graphics drivers
 with feature set limited to that of
 your equipment. Compatibility
 with older graphics cards not
 guaranteed.
- Mac OS X does not support MST for NVIDIA and Intel Graphics Processor Units, limiting video display on connected monitors to mirror mode.
- MST compliant graphics cards are limited to a bandwidth of 21.6 Gbps amongst all monitors, with higher resolution monitors using up more bandwidth.
 1080p monitors will use up



and-play convenience means no software or drivers are needed. A built-in six-inch cable connects directly to a DisplayPort source. LEDs indicate when the monitors are receiving a signal. The B156-003-HD-V2 complies with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases.

Features

Connects Up to 3 HDMI Monitors to Your Computer's DisplayPort Output

- Ideal for digital signs in schools, churches, conference rooms, trade shows and retail settings
- Displays same image on 3 monitors simultaneously in mirror mode
- Extends desktop across 3 monitors in extended mode
- Combines 3 monitors into one large monitor in video wall mode
- Built-in 6 in. cable connects directly to DisplayPort source
- LEDs indicate when monitors are receiving a signal

Meets the Latest Performance Standards

- Supports UHD video resolutions up to 3840 x 2160 (4K x 2K) @ 60 Hz
- Supports expanded resolutions in video wall mode, such as 5760 x 1080 in horizontal 1 x 3 configuration
- Supports HDCP, EDID and DDC
- Supports 48-bit Deep Color (16 bits per channel)
- Supports DTS-HD, Dolby TrueHD and 7.1-channel surround sound audio

Easy to Use Almost Anywhere

- · Works with all operating systems
- Plug and play—no software or drivers required

TAA Compliant

• Complies with Federal Trade Agreements Act (TAA) for GSA Schedule purchases

approximately 22% of bandwidth, whereas 4K monitors will use 40% or more. As each monitor will be different, it is necessary to verify the percentage of bandwidth being used by each monitor in the display settings interface for your graphics card. If the total percentage of bandwidth taken up by all of the connected monitors exceeds 100%, an image will not display on one or more of them.

• Monitor(s) with HDMI input.

Package Includes

- B156-003-HD-V2 3-Port
 DisplayPort 1.2 to HDMI MST
 Hub
- External power supply w/NEMA
 1-15P plug and 5 ft. cord (Input:
 100–240V, 50/60 Hz, 0.5A;
 Output: 5V, 2A)
- Owner's manual

Specifications

OVERVIEW		
UPC Code	037332193346	
AC Adapter	Input: 100-240V, 50/60Hz, 0.5A; Output: 5V, 2A, 5 ft.	
Technology	HDMI (All types); DisplayPort (all types)	
PHYSICAL		
Shipping Dimensions (hwd / in.)	8.10 x 2.17 x 6.40	
Shipping Dimensions (hwd / cm)	20.57 x 5.51 x 16.26	
Shipping Weight (lbs.)	0.70	





Shipping Weight (kg)	0.32	
Unit Dimensions (hwd / in.)	0.94 x 4.3 x 3	
Unit Dimensions (hwd / cm)	2.4 x 10.9 x 7.62	
Unit Weight (lbs.)	0.25	
Unit Weight (kg)	0.11	
Color	Black	
CONNECTIONS		
Ports	3	
Side A - Connector 1	DISPLAYPORT (MALE)	
Side B - Connector 1	(3) HDMI (FEMALE)	
CERTIFICATIONS		
Approvals	FCC, RoHS, and REACH	
WARRANTY		
Product Warranty Period (Worldwide)	3-year limited warranty	

© 2018 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: https://www.tripplite.com/products/product-certification-agencies