



Micro Commercial Components 20736 Marilla Street Chatsworth CA 91311

Phone: (818) 701-4933 Fax: (818) 701-4939

SK4200L

Features

- Halogen free available upon request by adding suffix "-HF"
- Lead Free Finish/RoHS Compliant(Note 1) ("P" Suffix designates RoHS Compliant. See ordering information)
- Epoxy meets UL 94 V-0 flammability rating
- Moisture Sensitivity Level 1
- For Surface Mount Applications
- Easy Pick And Place
- High Temp Soldering: 260 °C for 10 Seconds At Terminals

Maximum Ratings

- Operating Temperature: -55°C to +150°C
 Storage Temperature: -55°C to +150°C
- Maximum Thermal Resistance; 11°C/W Junction To Lead


MCC	Device	Maximum	Maximum	Maximum
Catalog	Marking	Recurrent	RMS	DC
Number		Peak Reverse	Voltage	Blocking
		Voltage	-	Voltage
SK4200L	SK4200	200V	140V	200V

Electrical Characteristics @ 25°C Unless Otherwise Specified


Average Forward Current	$I_{F(AV)}$	4.0A	T _L = 70°C
Peak Forward Surge Current	I _{FSM}	100A	8.3ms, half sine
Maximum Instantaneous Forward Voltage	V _F	.86V	I _{FM} = 4.0A; T _J = 25°C
Maximum DC Reverse Current At Rated DC Blocking Voltage	I _R	0.5mA	T _J = 25°C
Maximum Reverse Recovery Time	T _{rr}	35ns	I _F =0.5A, I _R =1.0A, I _{rr} =0.25A

Notes: 1. High Temperature Solder Exemption Applied, see EU Directive Annex Notes 7.

4 Amp Schottky Rectifier 200 Volts



DIMENSIONS							
	INCHES		MM				
DIM	MIN	MAX	MIN	MAX	NOTE		
Α	.260	.280	6.60	7.11			
В	.220	.245	5.59	6.22			
С	.006	.012	0.15	0.31			
D	.030	.060	0.76	1.52			
Е	.305	.320	7.75	8.13			
F	.079	.103	2.00	2.62			
G	.108	.128	2.75	3.25			
Н	.002	.008	0.050	0.203			





SK4200L




Figure 1. Typical Forward Voltage

Figure 2. Typical Capacitance




Figure 3. Typical Reverse Current

Figure 4. Maximum Reverse Current



SK4200L




Figure 5. Derating Curve



Ordering Information :

Device	Packing
Part Number-TP	Tape&Reel: 3Kpcs/Reel

Note: Adding "-HF" suffix for halogen free, eg. Part Number-TP-HF

IMPORTANT NOTICE

Micro Commercial Components Corp. reserves the right to make changes without further notice to any product herein to make corrections, modifications, enhancements, improvements, or other changes. **Micro Commercial Components Corp.** does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold **Micro Commercial Components Corp.** and all the companies whose products are represented on our website, harmless against all damages.

LIFE SUPPORT

MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of Micro Commercial Components Corporation.

CUSTOMER AWARENESS

Counterfeiting of semiconductor parts is a growing problem in the industry. Micro Commercial Components (MCC) is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. MCC strongly encourages customers to purchase MCC parts either directly from MCC or from Authorized MCC Distributors who are listed by country on our web page cited below. Products customers buy either from MCC directly or from Authorized MCC Distributors are genuine parts, have full traceability, meet MCC's quality standards for handling and storage. MCC will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources. MCC is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.