



Wiha Screw Holding Screwdrivers



398 Slotted Screw-Holding Screwdriver, With Wiha-Square Handle
Blade CVM steel, hardened, black finish. Clamping sleeve polyamide. Wiha-square handle cellulose-acetate, impact resistant.

Item	↕	↕	↔	↔	↔	↔	↔	↔
No.	mm	Inch	mm	Inch	mm	Inch	lbs.	pkg.
398 25	2.5	.10	75	3.0	160	6.3	.07	10
398 30	3.0	.12	100	3.9	195	7.6	.11	10
398 40	4.0	.16	125	5.0	230	9.0	.18	10
398 50	5.0	.20	150	5.9	265	10.4	.25	10
398 60	6.0	.24	175	6.9	290	11.4	.30	10



397 Phillips Screw-Holding Screwdriver, With Wiha-Square Handle
Blade CVM steel, hardened, black finish. Clamping sleeve polyamide. Wiha-square handle cellulose-acetate, impact resistant.

Item	+	↔	↔	↔	↔	↔	↔	↔
No.	Size	mm	Inch	mm	Inch	lbs.	pkg.	
397 00	0	100	3.9	195	7.6	.11	10	
397 01	1	125	5.0	230	9.0	.18	10	
397 02	2	175	7.0	290	11.4	.30	10	

Wiha Magnetizer/Demagnetizer

Magnetize or Demagnetize tools and small parts instantly

Shatterproof Box is made from high quality plastic

Uses 2 C8 industrial permanent magnets



(+) to Magnetize

(-) to Demagnetize

400 10 Magnetizer and Demagnetizer

To magnetize and demagnetize steel screwdriver blades, tweezers and similar tools. Box high quality plastic, shock-resistant, green, cadmium free.

Application:

To magnetize, lead tool slowly through the (+) opening, to demagnetize guide tool slowly through the (-) opening.

Item		↔
No.	Dimensions	lbs.
400 10	2.1" x 2.0" x 1.1"	.30

(Parts under 1" Length or 1/8" Diameter may not demagnetize)

Wiha Screw Holding Screwdriver Sets



398 92 Set 5 Pcs. Screw Holding Slotted & Phillips Screwdriver Set Blade chrome-vanadium-molybdenum steel, hardened, black finish. Wiha square handle cellulose-acetate, impact resistant. With spring load clamping sleeve to hold screw securely.

Item	↕	↔	+	↔	↔		
No.	mm	mm	Size	mm	lbs.		
398 92	398 25	2.5	75	397 00	0	100	.87
	398 30	3.0	100	397 01	1	125	
	398 40	4.0	125				



398 96 Set 8 Pcs. Screw Holding Slotted & Phillips Screwdriver Set Blade chrome-vanadium-molybdenum steel, hardened, black finish. Wiha square handle cellulose-acetate, impact resistant. With spring load clamping sleeve to hold screw securely.

Item	↕	↔	+	↔	↔		
No.	mm	mm	Size	mm	lbs.		
398 96	398 25	2.5	75	397 00	0	100	1.80
	398 30	3.0	100	397 01	1	125	
	398 40	4.0	125	397 02	2	175	
	398 50	5.0	150				
	398 60	6.0	175				