

Housing - HC-STA-B24-BWSC-ELC-AL - 1411330

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



HEAVYCON B24 panel mounting base, with single locking latch, with plastic protective cover, with flat gasket, salt-water-resistant aluminum, conductive profile gasket.

Why buy this product



Key Commercial Data

Packing unit	1 STK		
GTIN	4 046356 927505		
GTIN	4046356927505		

Technical data

Dimensions

Height	30.5 mm
Width	53 mm
Length	140.5 mm
Length of the assembly cutout	113 mm
Width of the assembly cutout	35 mm

Ambient conditions

Degree of protection of housing (IP)	IP66
	IP67
Ambient temperature (operation)	-40 °C 125 °C

General

Note	For contact inserts HC-B24, BB46, D64, DD108, M	
Size	B24	
Housing type	Panel mounting base	



Housing - HC-STA-B24-BWSC-ELC-AL - 1411330

Technical data

General

Color	gray aluminum		
Locking type	with single locking latch		
Torque	1.5 Nm 2 Nm (Mounting screw)		
Screw connection	none		
Protective cover	yes		
Housing material	Die-cast aluminum, salt water resistant		
Housing surface material	uncoated		
Seal material	NBR, conductive		
Material lock	Polyamide		
Material, protective cover	РА		
Environmental Product Compliance			

China RoHS	Environmentally friendly use period: unlimited = EFUP-e	
	No hazardous substances above threshold values	

Drawings





Dimensional drawing

Dimensional drawing



Mounting cutout

Approvals

Approvals

Approvals			
GL / EAC			
Ex Approvals			

Approval details



Housing - HC-STA-B24-BWSC-ELC-AL - 1411330

Approvals



Phoenix Contact 2018 © - all rights reserved http://www.phoenixcontact.com

PHOENIX CONTACT GmbH & Co. KG Flachsmarktstr. 8 32825 Blomberg Germany Tel. +49 5235 300 Fax +49 5235 3 41200 http://www.phoenixcontact.com