

**Description**: 25x25x4mm GPS/Glonass Pin

Mount


**PART NUMBER: W3223** 

Series: Ceramic Patch



# Features:

- 1575/1602MHz Dualband singe feed antenna
- RHCP Polarization
- Zenith Gain +4dBiC
- Pin mounting
- Tray packing




# **Applications:**

- GPS and Glonass satellite receivers
- Tracking, Navigation, Satellite Positioning
- Fleet management
- Asset tracking

All dimensions are in mm / inches

Issue: 1652

In the effort to improve our products, we reserve the right to make changes judged to be necessary. CONFIDENTIAL AND PROPRIETARY INFORMATION



Pulse Worldwide Headquarters 12220 World Trade Drive San Diego, CA 92128 USA Tel:1-858-674-8100 Pulse/Larsen Antennas 18110 SE 34<sup>th</sup> St Bldg 2 Suite 250 Vancouver, WA 98683 USA Tel: 1-360-944-7551

Europe Headquarters Pulse GmbH & Do, KG Zeppelinstrasse 15 Herrenberg, Germany Tel: 49 7032 7806 0 Pulse (Suzhou) Wireless Products Co, Inc. 99 Huo Ju Road(#29 Bldg,4<sup>th</sup> Phase Suzhou New District Jiangsu Province, Suzhou 215009 PR China Tel: 86 512 6807 9998



**Description**: 25x25x4mm GPS/Glonass Pin

Mount

**PART NUMBER: W3223** 

**Series: Ceramic Patch** 

### **ELECTRICAL SPECIFICATIONS**

Frequency 1575.42±1.023/1602.5625±4 MHz

Nominal Impedance 50  $\Omega$ 

Return Loss\* <-10 dB

RHCP Gain (typical)\* 4 dBiC

Zenith Axial Ratio(typical)\*

3.8

Polarization: RHCP

\* Measured on 70 x 70 mm reference board

<sup>\*</sup> Test the antenna on 70mmX70mm metal plane



**Description**: 25x25x4mm GPS/Glonass Pin

Mount

**PART NUMBER: W3223** 

**Series: Ceramic Patch** 

## **MECHANICAL SPECIFICATIONS**

Material Ceramic

Metallization Silver

Size 25 x 24 x 4 mm

Weight 9.3 g

Mounting type Pin feed

## **ENVIRONMENTAL SPECIFICATIONS**

Operating temperature

-40/+85 ° C




**Description**: 25x25x4mm GPS/Glonass Pin

Mount

**PART NUMBER: W3223** 

**Series: Ceramic Patch** 

# **MECHANICAL DRAWING**




Adhesive Transfer Tape Specification TAPE: Nitto 5000NS 22\*22\*0.16mm

Thickness: 0.16 ± 5% mm

Release Liner: 0.1mm (typ.) printed paper or paper

Dimension: mm



Patch bottom

Tolerance: ±0.2mm





**Description**: 25x25x4mm GPS/Glonass Pin


Mount

**PART NUMBER: W3223** 

**Series: Ceramic Patch** 

## **OTHER SPECIFICATIONS**

# **Test Condition Ground Plane (Example for PCB 1 mm)**







**Description**: 25x25x4mm GPS/Glonass Pin

Mount


**PART NUMBER: W3223** 

**Series: Ceramic Patch** 

## **CHARTS**



# Return Loss



# **Total Radiation Efficiency**

Issue: 1652




**Description**: 25x25x4mm GPS/Glonass Pin

Mount


**PART NUMBER: W3223** 

**Series: Ceramic Patch** 

#### **CHARTS**



# Zenith RHCP Gain



GPS Radiation pattern on 70mmX70mm metal plane

Issue: 1652






**Description**: 25x25x4mm GPS/Glonass Pin

Mount

**PART NUMBER: W3223** 

**Series: Ceramic Patch** 

## **CHARTS**



Glonass Radiation pattern on 70mmX70mm metal plane





Description: 25x25x4mm GPS/Glonass Pin

Mount

**PART NUMBER: W3223** 

Series: Ceramic Patch

#### **PACKAGING**

Tray packing 50PCS/Tray 200PCS/small carton box 800PCS/big carton box

Big box dimensions (MM): 472x240x290