

# Part Number: 5000UP



Audio Cable, 2 Conductor 12 AWG, BC, Unshielded, CM

## Product Description

Commercial Audio Cable, Rated-CL3, 2-12 AWG highly flexible stranded bare copper conductors with PVC insulation, PVC jacket with ripcord

## **Technical Specifications**

### **Product Overview**

| Environmental Space:               | Indoor (Not Riser or Plenum) |
|------------------------------------|------------------------------|
| Physical Characteristics (Overall) |                              |

### Conductor

| AWG                | Stranding  | Material                       | No. of Conductors |
|--------------------|------------|--------------------------------|-------------------|
| 12                 | 65x30      | Bare High-Conductivity ETP Cop | per 2             |
| Conductor Count: 2 |            | 2                              |                   |
| Condu              | ctor Size: | 12 A                           | WG                |

#### Insulation

| Material                 | Nominal Wall Thickness |
|--------------------------|------------------------|
| PVC - Polyvinyl Chloride | 0.02 in                |

### Color Chart



### **Outer Shield Material**

Material Unshielded

### Outer Jacket Material

| Material                    | Nominal Diameter | Nominal Wall Thickness | Ripcord |
|-----------------------------|------------------|------------------------|---------|
| PVC - Polyvinyl<br>Chloride | 0.302 in         | 0.018 in               | Yes     |

### **Construction and Dimensions**

Twists

3 twist/ft

### **Electrical Characteristics**

### Conductor DCR

| Nominal Conductor DCR |
|-----------------------|
| 1.56 Ohm/1000ft       |

#### Capacitance

| Nom. Capacitance Conductor to Conductor |                       |
|---|-----------------------|
| 32 pF/ft                                |                       |
| Shielding:                              | Multiple or Specialty |

#### Inductance

Nominal Inductance

0.16 µH/ft

## Current

Max. Recommended Current [A] 26 Amps per conductor @ 25°C

### Voltage

UL Voltage Rating 300 V RMS

## **Temperature Range**

| UL Temp Rating:       | 75°C           |
|-----------------------|----------------|
| Operating Temp Range: | -20°C To +75°C |

## **Mechanical Characteristics**

| Bulk Cable Weight:               | 59 lbs/1000ft |
|----------------------------------|---------------|
| Max Recommended Pulling Tension: | 169 lbs       |
| Min Bend Radius/Minor Axis:      | 3 in          |

### **Standards**

| NEC/(UL) Specification: | CL3 |
|-------------------------|-----|
| CPR Euroclass:          | Eca |

## **Applicable Environmental and Other Programs**

| EU Directive 2000/53/EC (ELV):        | Yes                           |
|---------------------------------------|-------------------------------|
| EU Directive 2003/96/EC (BFR):        | Yes                           |
| EU Directive 2011/65/EU (ROHS II):    | Yes                           |
| EU Directive 2012/19/EU (WEEE):       | Yes                           |
| EU Directive Compliance:              | EU Directive 2003/11/EC (BFR) |
| EU CE Mark:                           | Yes                           |
| EU RoHS Compliance Date (yyyy-mm-dd): | 2005-04-01                    |
| CA Prop 65 (CJ for Wire & Cable):     | Yes                           |
|                                       |                               |
| MII Order #39 (China RoHS):           | Yes                           |

## Flammability, LS0H, Toxicity Testing

| UL Flammability:   | UL1685 UL Loading |
|--------------------|-------------------|
| UL voltage rating: | 300 V RMS         |

No

## Plenum/Non-Plenum

| Plenum (Y/N): |  |
|---------------|--|
|---------------|--|

### **Part Number**

### Variants

| Item #         | Color       | Footnote |
|----------------|-------------|----------|
| 5000UP 0101000 | Black       | С        |
| 5000UP 010500  | Black       |          |
| 5000UP 010U500 | Black       |          |
| 5000UP D151000 | Blue        |          |
| 5000UP D15500  | Blue        | С        |
| 5000UP 0081000 | Gray        |          |
| 5000UP 008500  | Gray        | С        |
| 5000UP 0051000 | Green, Dark | С        |
| 5000UP 0091000 | White       |          |
| 5000UP 009U500 | White       |          |
| Footnote:      |             |          |

#### © 2018 Belden, Inc

#### All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulators based on their individual usage of the product.