APPLICAE	BLE STAND	DARD									
OPERATING TEMPERATUR		55°C TO 95				RAGE		_	-10 °C TO 60 °C ©		
RATING	TEMPERATURE RANGE		-55 °C TO 85 °C ⊕				PERATURE RANGE RATING HUMIDITY		10 0 10 00		
	VOLTAGE		50 V AC		RANG	RANGE			95 % RH MAX.		
CURRENT		0.3 A				(NO DEW CONDENSATION I				PERMIT	TED)
			SPEC	IFICA	MOIT	S					
ITI	EM	TEST METHOD				REQUIREMENTS					AT
CONSTRU	JCTION										
		VISUALLY AND BY MEASURING INSTRUMENT.				ACCO	RDING T	O DRAV	VING.	×	×
MARKING		CONFIRMED VISUALLY.								×	×
ELECTRIC CHARACT							60 mΩ MAX.				
INSULATION		100 V DC				100 MΩ MIN.					-
RESISTANCES						100 11111					
VOLTAGE PROOF		150 V AC FOR 1 min.				NO FLASHOVER OR BREAKDOWN.					×
	CAL CHAR			INFOTO	5	INIOED	TION 50	DOE	00.11.14.17	×	
INSERTION AND WITHDRAWAL FORCE		MEASURED BY APPLICABLE CONNECTOR.				INSERTION FORCE: 90 N MAX. WITHDRAWAL FORCE: 6 N MIN.					_
MECHANICAL		50 TIMES INSERTIONS AND EXTRACTIONS.				\bigcirc CONTACT RESISTANCE: 70 m Ω MAX.					_
OPERATION						② NO DAMAGE, CRACK AND LOOSENESS OF PARTS.					
VIBRATION		FREQUENCY 10 TO 55 Hz,				NO ELECTRICAL DISCONTINUITY OF					-
VIBIO (TIOI)		SINGLE AMPLITUDE : 0.75 mm,				1 µs MIN.					
		AT 10 CYCLES FOR 3 DIRECTIONS.				O NO DAMAGE, CRACK AND LOOSENESS					
SHOCK		490 m/s ² , DURATION OF PULSE 11 ms AT 3 TIMES FOR 3 DIRECTIONS.				OF PARTS.					_
ENVIRON	MENTAL C										
DAMP HEAT			DAT 40±2°C, 90 ~ 95	5 %, 96	h.	① COI	NTACT F	RESIST	ANCE: 70 mΩ MAX.	×	-
(STEADY STATE)						② INSULATION RESISTANCE:100 MΩ MIN.					
RAPID CHANGE OF TEMPERATURE		TEMPERATURE -55 \rightarrow +15 \sim +35 \rightarrow +85 \rightarrow +15 \sim +35 \circ C TIME 30 \rightarrow 2 \sim 3 \rightarrow 30 \rightarrow 2 \sim 3 min.					DAMAGI PARTS.	E, CRA	CK AND LOOSENES	3 ×	-
I LIWII LIXAIX			5 CYCLES.	2 -5 11		OF	FARTS.				
DRY HEAT		EXPOSED AT 85 °C , 96 h.				\oplus CONTACT RESISTANCE: 70 m Ω MAX.				×	-
COLD		EXPOSED AT - 55 °C , 96 h.				© NO DAMAGE, CRACK AND LOOSENESS OF PARTS.				3 ×	_
CORROSION SALT MIST						NO HEAVY CORROSION.				×	-
SULPHUR DIOXIDE		48 h. EXPOSED IN 10 PPM FOR 96 h.				① CONTACT RESISTANCE: 70 mΩ MAX.					-
DECICTANCE TO		(TEST STANDARD: JIS C 0090)				② NO HEAVY CORROSION.					
RESISTANCE TO SOLDERING HEAT		1) REFLOW SOLDERING : 250 °C MAX, : 220 °C MIN.				NO MELTING OF RESIN WHICH AFFECTS THE PERFORMANCE OF COMPORNENT. A NEW UNIFORM COATING OF SOLDER SHALL					_
SOLDERABILITY		FOR 60 s 2) SOLDERING IRONS : 360 °C,									
											_
		FOR 5 s SOLDERED AT SOLDER TEMPERATURE,									<u> </u>
SOLDERABILITY		240±3°C,FOR IMMERSION DURATION, 3 s.				OVER A MINIMUM OF 95 % OF THE SURFACE BEING IMMERSED.					
COUN	T DF	ESCRIPTION	ON OF REVISIONS		DESIG	SNED	IED		CHECKED		ATE
A											
			RISE INCLUDED WHEN ENERGIZED.			APPROVE		VED	HS.OKAWA	.OKAWA 06.09	
(2)		: INDICATES A LONG-TERM STORAGE STATE SED PRODUCT BEFORE THE BOARD MOUNTED.				CHECKED		ŒD	HS.OZAWA	06.09.2	
						DESIGNE		1ED	KY.NAKAMURA	06.09.2	
Unless otherwise specified, re			refer to JIS C 5402.			DRAWN		/N	SY.KAMIGA	06.09.2	
Note QT:Qualification Test AT:Ass			urance Test X:Applicable Test			RAWING NO.			ELC4-152094-22		
HS	SI	PECIFICATION SHEET			PART NO.		F	X11L	 1LA-100P/10-SV (92		
11.7	HIR	OSE ELECTRIC CO., LTD.			CODE	CODE NO. C			573-0004-2-92		
FORM HD0011-	0 1										