HellermannTyton

Specification Sheet

Part Number: TAG15T3-DTH

HellermannTyton Thermal Transfer Labels, 1.0" x .50", 3 Across, PET, White, 10,000/roll

Article Number	596-00035
Туре	TAG15T3
Color	White (WH)
Features & Benefits	 White polyester is glossy, allowing for the highest resolution and print contrast. The acrylic-based adhesive bonds to a wide variety of substrates and can withstand high temperatures long term.
Quantity Per	roll
Product Description	HellermannTyton white polyester labels are ideal for marking small electrical and electronic components, such as EPROMS', Integrated circuits, as well as the circuit board itself. Printed labels can withstand the soldering process and survive flux removal when the board is washed. HellermannTyton's 822 material is designed for use on flat surfaces and can also be used to identify connectors, buttons and just about anything requiring permanent, durable, high temperature and UV resistant marking.

Short Description Thermal Transfer Labels, 1.0" x .50", 3 Across, PET, White, 10,000/roll **Global Part Name** TAG15T3-PET-WH Width W (Imperial) 1.0 Width W (Metric) 25.4 **Bundle Diameter Min (Imperial)** .81 **Bundle Diameter Min (Metric)** 2.80 **Bundle Diameter Max (Imperial)** 10.87 Bundle Diameter Max (Metric) 47.50 Thickness T (Metric) 64.0 Height H (Imperial) 0.5 Height H (Metric) 12.7 85.09 Width of Liner (Metric) Width of Liner (imperial) 3.35

Material Polyester (PET)

Adhesive	Acrylic
Halogen free	No
Adhesive Operating Temperature	-40°F to +194°F (-40°C to +90°C)
Operating Temperature (Metric)	-40°F to +140°F (-40°C to +60°C)
Reach Complaint(Article 33)	Yes
ROHS Complaint	Yes
Package Quantity(Imperial)	10000
Package Quantity (Metric)	10000
Customs Number	3919102055
Labels per Column	1
Labels per Row	3
Weight (Metric)	0.521
Weight (Imperial)	1.14

© 2018 HellermannTyton. All rights reserved.