




— .635 [16.13] МАХ — .535 [13.59] MAX .650 [16.51] MAX .510 [12.95] STEWART PATENTED

В





.100 [2.54] (2)-.050 [1.27] (3) .125 [3.18]ø.035 [0.89] ±.003 [0.08] (4) -**♦** Ø.006 [0.15] PIN# 1 $\phi \frac{.128 \ [3.25]}{.125 \ [3.18]}$ -.400 [10.16] ф Ø.006 [0.15] P.C.B. RECOMMENDED HOLE LAYOUT SEEN FROM COMPONENT SIDE ALL CENTERLINE DIMENSIONS ARE BASIC.



NOTES:

- 1. CONNECTOR MATERIALS: HOUSING: THERMOPLASTIC UL94 V-0 CONTACTS: COPPER ALLOY CONTACT PLATING: SELECTIVE GOLD IN CONTACT AREA SEE CHART FOR PART NUMBER
- 2. FOR PRODUCT SPECIFICATIONS SEE PR026-01.
- 3. DIMENSIONS AND TOLERANCES COMPLY WITH TIA-1096 STANDARD.

30 MICRO-INCHES [0.76um]	SS65600-001F
CONTACT PLATING IN MATING AREA	PART NUMBER

DO NOT SCALE DRAWING DRAWING IS SUBJECT TO CHANGE WITHOUT NOTICE DIMENSIONS: INCHES [METRIC] UNLESS OTHERWISE SPECIFIED TOLERANCES ARE ±.005 [0.13]
ANGLES ARE ± 1° SHEET NO. 1 OF 1

THIRD ANGLE PROJECTION

CONNECTOR

11118 Susquehanna Trail South Glen Rock, PA 17327-9199 (717) 235-7512

http://www.stewartconnector.com

FOUR CONTACT, SIX POSITION VERTICAL MOUNT JACK FLANGED

THIS DRAWING AND THE SUBJECT MATTER SHOWN THEREON ARE CONFIDENTIAL AND THE PROPRIETARY PROPERTY OF STEWART CONNECTOR AND SHALL NOT BE REPRODUCED, COPIED, OR USED IN ANY MANNER WITHOUT PRIOR WRITTEN CONSENT OF STEWART CONNECTOR. ONE OR MORE U.S. PATENTS MAY APPLY TO THIS PRODUCT. FOR DETAILS, PLEASE VISIT: HTTP://BELFUSE.COM/STEWART/STEWART_PATENTS/

DATE 2-8-05 APPD BY: DATE 2-22-05 REV. CT650008F

RoHS

AutoCAD