# LP1S-27S-209-Z Details PDF





LP1S-27S-209-Z

Part Number:	LP1S-27S-209-Z	
Manufacturer/Brand:	Copal Electronics	
Product description	SWITCH PUSHBUTTON DPDT 3A 125V	
Datasheets:	pp LP1S-27S-209-Z.pdf	
RoHs Status	Lead free / RoHS Compliant	
Ship From	Hong Kong	
Shipment Way	DHL/Fedex/TNT/UPS/EMS	

**REQUEST FOR QUOTATION** 

Image may be representation. See specifications for product details.

PART NUMBER   LPI5-275-209-Z     MANUFACTURER   Copal Electronics     DESCRIPTION   SWITCH PUSHBUTTON DPDT 3A 129V     LEAD FREE ESTATUS / ROHS STATUS   Lead free / RahS Compliant     DATA SHEET   SWITCH PUSHBUTTON DPDT 3A 129V     VOLTAGE RATING - DC   30V     VOLTAGE RATING - AC   129V     TOPE   Sandard, Iluminated     TOPE   Sandard, Iluminated     SWITCH PUNCTION   On-On     SWITCH FUNCTION   ILuminated     INCRESS FUNCTION   ILumination     ONE SWITCH TONE		Specifications of LP1S-27S-209-Z
MANUFACTURERCopal ElectronicsDESCRIPTIONSWITCH PUSHEUTTON DPOT 3A 125VLEAD FREE STATUS / ROHS STATUSLead free / ROHS CompliantDATA SHEFTSol (DISS-275-209-2.pdf)VOLTAGE RATING - DC30VVOLTAGE RATING - AC125VYPPStandard, IlluminatedTERMINATION STALEPC PinSMITCH FUNCTIONOn-OnSMITCH FUNCTIONOn-OnPAREL CUTOUT DIMENSIONS-PAREL CUTOUT DIMENSIONS-PAREL CUTOUT DIMENSIONS-PORTING TEMPERATURE563-1468-5OTHER NUMES553-1468-5OTHER NUMES1100-0MOUNTING TYPE1100-0MOUNTING TYPE1100-0MOUNTING TYPE1100-0MOUNTING TYPE1100-0ILLUMINATION STATUS1100-0ILLUMINATION TYPE, COLOR2 VDCILLUMINATION TYPE, COLOR1200-0ILLUMINATION TYPE, COLOR30,000 CyclesILLUMINATION TYPE, COLOR30,000 Cycles <td></td> <td></td>		
PESCRIPTIONSWITCH PUSHBUTTON DPDT 3A 125VLEAD RREE STATUS / ROHS STATUSLead free / RoHS CompliantDATA SHEETSU P15-275-209-2.pdfVOLTAGE RATING - DC30VVOLTAGE RATING - AC125VTYPESandard, IlluminatedTREMINATION STYLEPC PnSWITCH FUNCTIONOn-OnSERESLPPACKGINGTubeOTHER KAMES652-1468-5OTHER LANES652-1468-5OTHER KAMES652-1468-5MOUNTING TYPETurough HoleMOUNTING TYPE1(Unlimited)MOUNTING TYPE1(Unlimited)MOUNTING TYPE1(Unlimited)ILLUMINATION VOLTAGE (NOMINAL)2VOCLEAD RREE STATUS / ROHS STATUSLead free / RoHS CompliantLUMINATION TYPE, COLORLED, RealILLUMINATION TYPE, COLOR2, NOCLILUMINATION TYPE, COLOR6, NOCLED RREE STATUS / ROHS STATUSLead free / RoHS CompliantLILUMINATION TYPE, COLOR2, NOCLILUMINATION TYPE, COLOR6, NOCLILUMINATION TYPE, COLOR1, ONOC CyclesLILUMINATION TYPE, COLOR3, ONC/CyclesLILUMINATION TYPE, COLOR3, ONC/CyclesCOLOR - ACTUATOR/(CAPGearCIRCUT0POT	PART NUMBER	LP1S-27S-209-Z
LEAD FREE STATUS / ROHS STATUSLead free / RoHS CompliantDATA SHEETGU LPIS-275-209-2.pdfVOLTAGE RATING - DC30VVOLTAGE RATING - AC125VTYPEStandard, IlluminatedTERMINATION STYLEPC PinSWITCH FUNCTIONOn-On-OnSERESUPPAREL CUTOUT DIMENSIONS-PACKAGINGSG31468-5OPHERATURE TEMPERATURE6531468-5OPHERATURE SEMISITIVITY LEVEL (MSL)1 (Unlimited)MOUNTING TYPEThrough HoleMOUNTING TYPE0MANUFACTURER STATUS / ROHS STATUSLed free / RoHS CompliantILLUMINATION VOLTAGE (NOMINAL)2 VPCILLUMINATION TYPE, COLORLED, REGILLUMINATION TYPE, COLORLED, REGILLUMINATION TYPE, COLOR2 VPCILLUMINATION TYPE, COLORACTUALILLUMINATION TYPE, COLORACTUAL	MANUFACTURER	Copal Electronics
DATA SHEETDip 15-279-20-2.pdfVOLTAGE RATING - DC30VVOLTAGE RATING - AC125VTYPEStandard, IlluminatedTERMINATION STYLEPC PinSWITCH FUNCTIONOn-OnSERIESLPPANEL CUTOUT DIMENSIONS-PACKAGINGTubeOTHER NAMES563-1468-5OPERATING TEMPERATURE-MOISTURE SENSITIVITY LEVEL (MSL)1 (Unlimited)MOISTURE SENSITIVITY LEVEL (MSL)1 (Unlimited)MICHARDICAL LIFE-INAGES RATORS TATUOS AD LEAD TIME9 WeeksLEAD FREE STATUS / RONS STATUSLed free / RoHS CompliantINGRESS RATORS (LIFE)-ILLUMINATION VOLTAGE (NOMINAL)2 VDCILLUMINATION TYPE, COLORLED, RedELECTRICAL LIFE0,000 CyclesELECTRICAL LIFE0,000 CyclesIELECTRICAL LIFE0,000 CyclesIELECTRI	DESCRIPTION	SWITCH PUSHBUTTON DPDT 3A 125V
VOLTAGE RATING - DCOVVOLTAGE RATING - AC125VTYPEStandard, IlluminatedTERMINATION STYLEPC PinSWITCH FUNCTIONOn-OnSERIESLPPANEL CUTOUT DIMENSIONS-PACKAGINGTubeOTHER MARES503-1468-5OTHER MARES15°C ~ 6°CMOUTING TYPEThrough HoleMOISTURE SENSITIVITY LEVEL (MSL)1 (Unimed)MANUFACTURER STANDARD LEAD TIME9 WeekSILLMINATION VOLTAGE (NOMINAL)2 VOCILLUMINATION VOLTAGE (NOMINAL)2 VOCILLUMINATION VOLTAGE (NOMINAL)2 NOCELECTRICAL LIFE-ELECTRICAL LIFE30,000 CyclesILLUMINATION YPE, COLORALAC/DC)CURRENT RATING3 (AC/DC)CURRENT RATING3 (AC/DC)CURRENT RATINGCearCUCOR - ACTUATOR/CAPDPDT	LEAD FREE STATUS / ROHS STATUS	Lead free / RoHS Compliant
VOLTAGE RATING - AC125VYTPEStandard, IlluminatedTERMINATION STYLEPC PinSWITCH FUNCTIONOn-OnSERIESLPPAREL CUTOUT DIMENSIONS-PACKAGINGTubeOPERATING TEMPERATURE15°C ~ 60°CMOUNTING TYPEThrough HoleMOUNTING TYPE1(Unlimited)MOUNTING TYPE9 WeeksIEAD FREE STATUS / ROHS STATUSLead free / RoHS CompliantINGRESS PROTECTION-ILLUMINATION VOLTAGE (NOMINAL)2 VDCILLUMINATION TYPE, COLORED, RedFEATURES-ELECTRICAL LIFE30,000 CyclesIECTRICAL LIFE30,000 CyclesICURRENT RATING3 (AC/DC)COLOR - ACTUATOR/CAPGearICULUTDPDTICURATION COLORCear	DATA SHEET	m LP1S-27S-209-Z.pdf
TYPESandard, IlluminatedTERMINATION STYLEPC PinSWITCH FUNCTIONOn-OnSERIESIPPANEL CUTOUT DIMENSIONS-PACKAGINGTubeOPERATING TEMPERATURE633-1468-5OPERATING TEMPERATURE15°C ~ 60°CMOUNTING TYPEThrough HoleMOUNTING TYPE0MOISTURE SENSITIVITY LEVEL (MSL)1 (Unlimited)MECHANICAL LIFE-NANUFACTURER STANDARD LEAD TIME9 WeeksLEAD FREE STATUS / ROHS STATUSLead free / RoHS CompliantILLUMINATION VOLTAGE (NOMINAL)2 VDCILLUMINATION TYPE, COLORIED, RedFEATURES-ELECTRICAL LIFE30,000 CyclesDETAILED DESCRIPTION9 Mexhuton Switch DPDT Standard, Illuminated Through HoleICURENT RATING3A (AC/OC)COLOR - ACTUATOR/CAPGearICRUITDPDT	VOLTAGE RATING - DC	30V
TERMINATION STYLEPC PinSWITCH FUNCTIONOn-OnSERIESLPPANEL CUTOUT DIMENSIONS-PACKAGINGTubeOTHER NAMES563-1468-5OPERATING TEMPERATURE-15°C ~ 6°°CMOUNTING TYPEThrough HoleMOUNTING TYPE1 (Unlimited)MOUNTING TYPE9 WeeksIEAD REEE STATUS / ROHS STATUS-ILLUMINATION VOLTAGE (NOMINAL)9 VOCILLUMINATION VOLTAGE (NOMINAL)2 VOCILLUMINATION TYPE, COLOR-IEAT RES-EATURES9.000 CyclesIECTRICAL LIFE30.000 CyclesICURENT RATINGYushutton Switch DPDT Standard, Illuminated Through HoleCORRENT RATINGA(C/DC)COLOR - ACTUATOR/CAPGearIRCUITPDPT	VOLTAGE RATING - AC	125V
SWITCH FUNCTIONOn-OnSERIESLPPAREL CUTOUT DIMENSIONS-PACKAGINGTubePACKAGING563-1468-5OTHER NAMES563-1468-5OPERATING TEMPERATURE-15°C ~ 60°CMOUNTING TYPEThrough HoleMOUNTING TYPE1 (Unlimited)MOUNTING TYPE9 WeeksILLMINACTURER STANDARD LEAD TIME9 WeeksLEAD FREE STATUS / ROHS STATUSLead free / RoHS CompliantILLMINATION YDFE, COLOR4FEATURES-ELECTRICAL LIFE30,000 CyclesILLMINATION TYPE, COLORPushbutton Switch DPDT Standard, Illuminated Through HoleCURRENT RATING3A (AC/DC)CURRENT RATINGDPDT	TYPE	Standard, Illuminated
SERIESLPPANEL CUTOUT DIMENSIONS-PACKAGINGTubeOTHER NAMES563-1468-5OPERATING TEMPERATURE-15°C ~ 60°CMOUNTING TYPEThrough HoleMOISTURE SENSITIVITY LEVEL (MSL)1 (Unlimited)MECHANICAL LIFE-MANUFACTURER STANDARD LEAD TIME9 WeeksLEAD FREE STATUS / ROHS STATUSLead free / ROHS CompliantINGRESS PROTECTION-ILUMINATION VOLTAGE (NOMINAL)2 VDCILUMINATION TYPE, COLORLED, RedELECTRICAL LIFE0,000 CyclesDETAILED DESCRIPTION3 (AC/DC)CURRENT RATING3 (AC/DC)CURRENT RATINGDETAILED CALLINECURCUTDPDT	TERMINATION STYLE	PC Pin
PANEL CUTOUT DIMENSIONS-PACKAGINGTubePACKAGING563-1468-5OPERATING TEMPERATURE653-1468-5MOUNTING TYPE15°C ~ 6°°CMOUNTING TYPE1 (Unlimited)MOISTURE SENSITIVITY LEVEL (MSL)1 (Unlimited)MECHANICAL LIFE-MANUFACTURER STANDARD LEAD TIME9 WeeksLEAD FREE STATUS / ROHS STATUSLead free / RoHS CompliantINGRESS PROTECTION-ILLUMINATION VOLTAGE (NOMINAL)2 VDCILLUMINATION VOLTAGE (NOMINAL)0,000 CyclesELECTRICAL LIFE0,0000 CyclesCURRENT RATING3A (AC/DC)CURRENT RATINGClearCUOGN - ACTUATOR/CAPDPDT	SWITCH FUNCTION	On-On
PACKAGINGTubePACKAGING563-1468-5OPERATING TEMPERATURE-15°C ~ 60°CMOUNTING TYPEThrough HoleMOISTURE SENSITIVITY LEVEL (MSL)1 (Unlimited)MECHANICAL LIFE-MANUFACTURER STANDARD LEAD TIME9 WeeksLEAD FREE STATUS / ROHS STATUSLead free / ROHS CompliantILUMINATION VOLTAGE (NOMINAL)2 VDCILUMINATION TYPE, COLORLED, RedFEATURES-ELECTRICAL LIFE30,000 CyclesCURRENT RATING3A (AC/DC)CURRENT RATINGGearCUOG - ACTUATOR/CAPDPDT	SERIES	LP
OTHER NAMES563-1468-5OPERATING TEMPERATURE-15°C ~ 60°CMOUNTING TYPEThrough HoleMOISTURE SENSITIVITY LEVEL (MSL)1 (Unlimited)MECHANICAL LIFE-MANUFACTURER STANDARD LEAD TIME9 WeeksLEAD FREE STATUS / ROHS STATUSLead free / ROHS CompliantINGRESS PROTECTION-ILLUMINATION VOLTAGE (NOMINAL)2 VDCILLUMINATION TYPE, COLORLED, RedELECTRICAL LIFE3,000 CyclesELECTRICAL LIFE30,000 CyclesCURRENT RATINGCAC/DC)COLOR - ACTUATOR/CAPGearCULUTDPDT	PANEL CUTOUT DIMENSIONS	-
OPERATING TEMPERATURE-15°C ~ 60°CMOUNTING TYPEThrough HoleMOISTURE SENSITIVITY LEVEL (MSL)1 (Unlimited)MECHANICAL LIFE-MANUFACTURER STANDARD LEAD TIME9 WeeksLEAD FREE STATUS / ROHS STATUSLead free / ROHS CompliantILLUMINATION VOLTAGE (NOMINAL)2 VDCILLUMINATION TYPE, COLORLED, RedFEATURES-LECTRICAL LIFE30,000 CyclesDETAILED DESCRIPTION3A (AC/DC)CURRENT RATINGClearCOLOR - ACTUATOR/CAPDPDTDETAILED DESCRIPTIONClear	PACKAGING	Tube
MOUNTING TYPEThrough HoleMOISTURE SENSITIVITY LEVEL (MSL)1 (Unlimited)MECHANICAL LIFE-MANUFACTURER STANDARD LEAD TIME9 WeeksLEAD FREE STATUS / ROHS STATUSLead free / ROHS CompliantILLUMINATION VOLTAGE (NOMINAL)2 VDCILLUMINATION TYPE, COLORLED, RedFEATURES3,000 CyclesDETAILED DESCRIPTION30,000 CyclesCURRENT RATING3A (AC/DC)CURRENT RATINGClearCOLOR - ACTUATOR/CAPDPDTDETAILED COLORDPDT	OTHER NAMES	563-1468-5
MOISTURE SENSITIVITY LEVEL (MSL)1 (Unlimited)MECHANICAL LIFE-MANUFACTURER STANDARD LEAD TIME9 WeeksLEAD FREE STATUS / ROHS STATUSLead free / ROHS CompliantINGRESS PROTECTION-ILLUMINATION VOLTAGE (NOMINAL)2 VDCILLUMINATION TYPE, COLORLED, RedFEATURES-IELECTRICAL LIFE30,000 CyclesICURRENT RATING3A (AC/DC)COLOR - ACTUATOR/CAPClearICRUITDPT	OPERATING TEMPERATURE	-15°C ~ 60°C
MECHANICAL LIFE-MANUFACTURER STANDARD LEAD TIME9 WeksLEAD FREE STATUS / ROHS STATUSLead free / ROHS CompliantINGRESS PROTECTION-ILLUMINATION VOLTAGE (NOMINAL)2 VDCILLUMINATION TYPE, COLORLED, RedFEATURES-ELECTRICAL LIFE30,000 CyclesDETAILED DESCRIPTIONSA (AC/DC)COLOR - ACTUATOR/CAPCearICRUITDPDT	MOUNTING TYPE	Through Hole
MANUFACTURER STANDARD LEAD TIME9 WeeksLEAD FREE STATUS / ROHS STATUSLead free / ROHS CompliantINGRESS PROTECTION-ILLUMINATION VOLTAGE (NOMINAL)2 VDCILLUMINATION TYPE, COLORLED, RedFEATURES-ELECTRICAL LIFE30,000 CyclesDETAILED DESCRIPTIONVushbutton Switch DPDT Standard, Illuminated Through HoleCURRENT RATINGClearFOLOR - ACTUATOR/CAPDPDT	MOISTURE SENSITIVITY LEVEL (MSL)	1 (Unlimited)
LEAD FREE STATUS / ROHS STATUSLead free / RoHS CompliantINGRESS PROTECTION-ILLUMINATION VOLTAGE (NOMINAL)2 VDCILLUMINATION TYPE, COLORLED, RedFEATURES-ELECTRICAL LIFE30,000 CyclesDETAILED DESCRIPTIONVenbutton Switch DPDT Standard, Illuminated Through HoleCURRENT RATINGClearCICCUITDPDT	MECHANICAL LIFE	-
INGRESS PROTECTION-ILLUMINATION VOLTAGE (NOMINAL)2 VDCILLUMINATION TYPE, COLORLED, RedFEATURES-FLECTRICAL LIFE30,000 CyclesDETAILED DESCRIPTIONVeshbutton SWitch DPDT Standard, Illuminated Through HoleCURRENT RATINGA (AC/DC)COLOR - ACTUATOR/CAPDeDTCIRCUITDPDT	MANUFACTURER STANDARD LEAD TIME	9 Weeks
ILLUMINATION VOLTAGE (NOMINAL)2 VDCILLUMINATION TYPE, COLORLED, RedFEATURES-ELECTRICAL LIFE30,000 CyclesDETAILED DESCRIPTIONVushbutton Switch DPDT Standard, Illuminated Through HoleCURRENT RATINGA (AC/DC)COLOR - ACTUATOR/CAPDPDTCIRCUITDPDT	LEAD FREE STATUS / ROHS STATUS	Lead free / RoHS Compliant
ILLUMINATION TYPE, COLORLED, RedFEATURES-FEATURES30,000 CyclesDETAILED DESCRIPTIONPushbutton Switch DPDT Standard, Illuminated Through HoleCURRENT RATING3A (AC/DC)COLOR - ACTUATOR/CAPClearCIRCUITDPDT	INGRESS PROTECTION	-
FEATURES-ELECTRICAL LIFE30,000 CyclesDETAILED DESCRIPTIONPushbutton Subich DPDT Standard, Illuminated Through HoleCURRENT RATING3A (AC/DC)COLOR - ACTUATOR/CAPClearDIRDUITDPDT	ILLUMINATION VOLTAGE (NOMINAL)	2 VDC
ELECTRICAL LIFE30,000 CyclesDETAILED DESCRIPTIONPushbutton Switch DPDT Standard, Illuminated Through HoleCURRENT RATING3A (AC/DC)COLOR - ACTUATOR/CAPClearCIRCUITDPDT	ILLUMINATION TYPE, COLOR	LED, Red
DETAILED DESCRIPTION Pushbutton Switch DPDT Standard, Illuminated Through Hole   CURRENT RATING 3A (AC/DC)   COLOR - ACTUATOR/CAP Clear   CIRCUIT DPDT	FEATURES	-
CURRENT RATING 3A (AC/DC)   COLOR - ACTUATOR/CAP Clear   CIRCUIT DPDT	ELECTRICAL LIFE	30,000 Cycles
COLOR - ACTUATOR/CAPClearCIRCUITDPDT	DETAILED DESCRIPTION	Pushbutton Switch DPDT Standard, Illuminated Through Hole
CIRCUIT DPDT	CURRENT RATING	3A (AC/DC)
	COLOR - ACTUATOR/CAP	Clear
ACTUATOR TYPE Square Button	CIRCUIT	DPDT
Square, Button	ACTUATOR TYPE	Square, Button

# **Related Tags**

Copal Electronics LP1S-27S-209-Z	LP1S-27S-209-Z Distributor	LP1S-27S-209-Z Supplier
LP1S-27S-209-Z Price	LP1S-27S-209-Z Pictures	LP1S-27S-209-Z Image
LP1S-27S-209-Z PDF Datasheet	LP1S-27S-209-Z Download Datasheet	LP1S-27S-209-Z Datasheet
LP1S-27S-209-Z Stock	Buy LP1S-27S-209-Z	Buy Copal Electronics LP1S-27S-209-Z
Copal Electronics LP1S-27S-209-Z	Copal Electronics Supplier	Copal Electronics Distributor
Copal Electronics LP1S-27S-209-Z	Copal Electronics Inc. LP1S-27S-209-Z	Nidec Copal Electronics LP1S-27S-209-Z

# **Related Products**



### LP1S-27S-G-Z Manufacturers: Copal Electronics Description: SWITCH PUSHBUTTON DPDT 3A 125V In stock: 90 pcs

RFQ



#### LP1S-26S-889-Z

Manufacturers: Copal Electronics Description: SWITCH PUSHBUTTON DPDT 3A 125V In stock: 99 pcs

RFQ



### LP1S-27S-229-Z

Manufacturers: Copal Electronics Description: SWITCH PUSHBUTTON DPDT 3A 125V In stock: 30 pcs

RFQ



### LP1S-27S-509-Z

Manufacturers: Copal Electronics Description: SWITCH PUSHBUTTON DPDT 3A 125V In stock: 64 pcs

RFQ




### LP1S-26S-809-Z

RFQ

Manufacturers: Copal Electronics Description: SWITCH PUSHBUTTON DPDT 3A 125V In stock: 98 pcs



#### LP1S-26S-559-Z



RFQ



# LP1S-26S-W-Z



Manufacturers: Copal Electronics Description: SWITCH PUSHBUTTON DPDT 3A 125V In stock: 81 pcs

RFQ



Manufacturers: Copal Electronics Description: SWITCH PUSHBUTTON DPDT 3A 125V In stock: 27 pcs

RFQ



# LP1S-27S-809-Z

Manufacturers: Copal Electronics Description: SWITCH PUSHBUTTON DPDT 3A 125V In stock: 100 pcs

RFQ

LP1S-27S-889-Z



LP1S-26S-R-Z

Manufacturers: Copal Electronics Description: SWITCH PUSHBUTTON DPDT 3A 125V In stock: Out stock

RFQ



## Manufacturers: Copal Electronics Description: SWITCH PUSHBUTTON DPDT 3A 125V In stock: 85 pcs

RFQ



LP1S-27S-559-Z

Manufacturers: Copal Electronics Description: SWITCH PUSHBUTTON DPDT 3A 125V In stock: 61 pcs

RFQ

#### Copyright @ 2020 Reliable Distributor of Electronic Components - Ocean-Components.com

E-mail: Info@Ocean-Components.com

Address: Room 2102, Connaught Commercial Building, 185 Wan Chai Rd, Wan Chai, Hong Kong

