

CeK	C&K	
<b>C</b> &K		
	8	

# MB05L1NCQD

Part Number:		
Manufacturer/Brand:		
Product description		
Datasheets:		
RoHs Status		
Ship From		
Shipment Way		

### MB05L1NCQD

C&K SWITCH ROTARY 5POS 250MA 125V MB05L1NCQD.pdf

Lead free / RoHS Compliant Hong Kong DHL/Fedex/TNT/UPS/EMS

## **REQUEST FOR QUOTATION**

Image may be representation. See specifications for product details.

ART NUMBERWORLINCQDPART NUMBERK082LINCQDPART NUMBERK082LINCQD, 2007DESCRIPTIONK087LINCQD, 2007DATA SHEFTK087LINCQD, 2007VOLTAGE RATING - AC287VOLTAGE RATING - AC280VOLTAGE RATING - AC280VOLTAGE RATING - AC280VOLTAGE RATING - AC280VOLTAGE RATING - AC280OPERATING TONSCORAGE - SAMORANUMBER OF POSITIONS280NUMBER OF POSITIONS2NUMBER OF POSITIONS2NUMBER OF POSITIONS2NUMBER OF POSITIONS1NUMBER OF POSITIONS2NUMBER OF POSITIONS2NUMBER OF POSITIONS2NUMBER OF POSITIONS2NUMBER OF POSITIONS1NUMBER OF POSITIONS1NUMBER OF POSITIONS2NUMBER OF POSITIONS2NUMBER OF POSITIONS1NUMBER OF POSITIONS2NUMBER OF POSITIONS2N		Specifications of MB05L1NCQD
NAUFACTURERCKKDESCRIPTIONSUTCH ROTARY SPOS 250MA 125VLEAD FREE STATUS / ROHS STATUSLead free / RoHS CompliantDATA SHEETSM0511KCDD.adfVOLTAGE RATING - DC28VVOLTAGE RATING - AC29VVOLTAGE RATING - ACPC PinSRIESMPUREL CUTOUT DIMENSIONSCreater - 6.0mm DiaOTHER NAMESNUBEL SCOP-INDOFERATING FORCE2.80NUMERE OF POSTIONSSCOLOGYNUMERE OF POSTIONS1NUMERE OF POSTIONS1NOUTTING TYPE1NUMERE OF POSTIONS1NUMERE OF PO		
DESCRIPTIONSWITCH ROTARY SPOS 250MA 125VLEAD FREE STATUS / ROHS STATUSLead free / ROHS CompliantDATA SHEETImmodel Robe / ROHS CompliantVOLTAGE RATUNG - DC20VVOLTAGE RATUNG - ACISVTERMILATION STYLEPC PInRANEL CUTOUP DIMENSIONSMEDSLISCOD-NoOPHER TAMES OF COLOR DIMENSIONSMEDSLISCOD-NoOPHERATING FORCE2.8800 ~ S.041gfmNUMBER OF POSITIONSSNUMBER OF POSITIONSSNUMBER OF POSITIONS1MOUNTING TYPEPanel Mann, Through HoleNUMBER OF POSITIONSImmediated Robei Robe	PART NUMBER	MB05L1NCQD
LEAD FREE STATUS / ROHS STATUSLead fee/ RohS CompliantDATA SHEETRW03LINCQD.pdfVOLTAGE RATING - DC28VVOLTAGE RATING - AC25VTERMINATION STYLEPC PinSRIESMPAREL CUTOUT DIMENSIONSCircular - 6.00m DiaOTHER INAMESRS00 - S.041gfmOPERATING FORCE2.880 ~ S.041gfmNUMBER OF POSITIONSSNUMBER OF POSITIONSSNUMBER OF POSITIONSAle Mont, Through HoleMOUTTING TYPEBael Mont, Through HoleMOUTTING TYPEAle Mont, Through HoleMOUTTING TYPES (SCO)MUMER OF POSITIONSI (Unimited)MUMER OF POSITIONSI (Unimited)MUMITIC TYPEI (Unimited)MUMITIC TYPEI (Unimited)IDSTUE SENSITIVIT LEVEL (MSL)I (Unimited)IDSTUE SENSITIVIT LEVEL (MSL)I (Unimited)IDSTUE SENSITIVIT LEVEL (MSL)I (SCO)IDSTUE SENSITIVIT LEVEL (MSL)I (SCO) <td>MANUFACTURER</td> <td>C&amp;K</td>	MANUFACTURER	C&K
DAT SHERTImmediateVOLTAGE RATING - DC28VVOLTAGE RATING - AC25VTERMINATION STYLEPC PISRIESMPAREL CUTOUT DIMENSIONSColler - 6,60m DiaO'THR MAMES2880 ~ 5,041gmO'THR MAMES2880 ~ 5,041gmNUMER OF POSITIONSSNUMER OF POSITIONSSNUMER OF POSITIONS20NUMER OF POSITIONS1NUMER OF POSITIONS1NOTING TIFUTS1NUMER OF POSITIONS1NOTING TIFUTS1NOTING TIFUTS1NOTING TIFUTS1NOTING TIFUTS1NOTING TIFUTS1NOTING	DESCRIPTION	SWITCH ROTARY 5POS 250MA 125V
Autrace RATING - DCBXVOLTAGE RATING - ACESVVOLTAGE RATING - ACESVTERMINATION STYLEPA PIAPAREL CUTOUT DIMENSIONSGroular - 6.0mm DiaOTHER NAMESGroular - 6.0mm DiaOTHER NAMESBSSLSCOO-NDOFEATING FORCE2.880 - 5.041gmNUMBER OF POSITIONSSNUMBER OF POSITIONSSNUMPR CUTURE STATUS / ROMIS TATUSSPOSITIONSFARAPOSITIONSSPOSITIONSSPOSITIONSSONG NODEST2DOM (AC/DC) 125VAC PARIE) MOUNT, M	LEAD FREE STATUS / ROHS STATUS	Lead free / RoHS Compliant
VolTAGE RATING-ACI29VTERNINATION STYLEPC PIGSRIESMPAREL CUTOUT DIMENSIONSCorder - 6.00m DiaOTHER NAMESSBSLISCOD-SOLOPERATING FORCE2800 ~ 5.04 gmNUMEEG POSITIONSSNUMEEG POSITIONSSNUMEEG POSITIONSGMUMEEG POSITIONSSNUMEEG POSITIONSGMUMEEG POSITIONSIAINONITIONEMUMEEG POSITIONSSMUMEEG POSITIONSSMUMEEG POSITIONSSMUMEEG POSITIONSGMUMEEG POSITIONSSMUMEEG POSITIONSSMUMEEG POSITIONSSMUMEEG POSITIONSSMUMEEG POSITIONSSMUMEEG POSITIONSSMUMEEG POSITIONSSMUMEEG POSITIONSSMUMEEG POSITIONSSMUMEEG STATUS POSITIONSSMUREEG POSITIONSSMUREEG POSITIONSSPOSITIONSSMUREEG POSITIONSSMUREEGUERIPTIONSCUTACT TIMINGSCUTACT TIMINGS <td< td=""><td>DATA SHEET</td><td>MB05L1NCQD.pdf</td></td<>	DATA SHEET	MB05L1NCQD.pdf
TERNINATION STYLEPC PinSERIESMPANEL CUTOUT DIMENSIONSCorder - 600m DiaOTHER NAMESSBSLISCQD-NDOPERATION FORCE2.800 ~ 5.041g/mNUMBER OF DOESTIONSSNUMBER OF DOESTEDEX2NUMBER OF DECK1MUNDER OF DECKRel Mount, Through HoleMUNDER OF DECK1MUNDER SENSITIVITY LEVEL (MSL)I (Minicu)MUNDER SENSITIVITY LEVEL (MSL)I (Minicu)MUNDER SENSITIVITY LEVEL (MSL)I (Minicu)IDEX SENSITIVITY LEVEL (MSL)	VOLTAGE RATING - DC	28V
SRIESMPARLE CUTOLIT DIMENSIONSGrokar - Gordm Diaor HER NAMESBislisSQD-NDOPERATING FORCE280 ~ 5041gmNUMERC PR OSTIONSSNUMERC PR OSTIONS2NUMERC PR OSTIONS1NUMERC PR OSTIONS1MURER OF DESKMININGUMNUMERC PR OSTIONS1MURER OF DESK1MURER STATUST LIVEL (MSL)1MURATURES STATUST LIVEL (MSL)1MURATURES TANDARD LEAD TIME1MURATURES TANDARD LEAD T	VOLTAGE RATING - AC	125V
PARLE CUTOUT DIMENSIONSGinalar 6.00m Diaorther NAMESMisSLISCQD-NDOPERATING FORCE2.880 ~ 5.041gmNUMER OF POSITIONS5NUMER OF POSITIONS2NUMER OF POSITIONS1MURER STANDARD LEAD TIME1MURAR ATRONG NOR STATUS1INDEX STOPS1FORTINES1MURER STATUS NOR STATUS1IDEX STOPS1POTATEL DESCRIPTION1AURANCE2COTACT MING1COTACT TIMING2004 (ACQC)COTACT FINISH2004 (ACQC)COTACT FINISH2004 (ACQC)COTACT FINISH2004 (ACQC)COTACT FINISH2004 (ACQC)CAUTA POSICIONES2004 (ACQC)COTACT FINISH2004 (ACQC)CAUTA FINISH2004 (ACQC)CAUT	TERMINATION STYLE	PC Pin
oTHER NAMESMB0SLISCQD-NDOTHER NAMESS80 ~ 5.04 JgmNUMER OF POSTIONSSNUMBER OF POSTIONS2NUMBER OF POLSS FER DECK2NUMBER OF DOLSS FER DECK10NUMBER OF DOLSS FER DECKInfologationMOUNTING TYPEMIGNUTHONG MIGNEMOUNTING TYPEInfologationMOUNTING TYPEInfologationMOUNTING TYPEInfologationMANUFACTURER STANDARD LEAD TIMEInfologationIADARS TATUS / FORSTATUSInfologationIADEX STOPSInfologationIATURESInfologationIATURESInfologationICTRATE NATINGInfologationICTRATE NATINGInfologationICTRATE NATINGInfologationICTRATE NATINGInfologationICTRATE TATINGInfologationICTRATE TATINGInfologationICTRATE TATINGInfologationICTRATE NATINGInfologationICTRATE NATINGInfologationICTRATE NATINGInfologationICTRATE TATINGInfologationICTRATE TATING<	SERIES	М
Diffex MarkesMBDSL1SCQD-NDOPERATING FORCE2.880 ~ 5.041gfmNUMBER OF POSITIONS5NUMBER OF POLES PER DECK2NUMBER OF DOLES PER DECK1MOUNTING TYPEPanel Mount, Through HoleMOUNTING TYPE101/mited CompliantMANUFACTURER STANDARD LEAD TIME13WeskLEAD FREE STATUS / ROHS STATUSEad free / ROHS CompliantINDEX STOPSFacePETATLED DESCKIPTIONAnay Wick J. Sposition DPST 250mA (AC/DC) 125VAC Panel Mount, Through HoleDEPTH BEHIND PANELJOAN (AC/DC)CONTACT THINGSion (AC/DC)CONTACT THINGSion (AC/DC)CONTACT FINISHSionCONTACT FINISHSionCALCUT FINISHPSTANGE OF THREWSion (AC/DC)CALCUT FINISHSionCALCUT FINISH <td< td=""><td>PANEL CUTOUT DIMENSIONS</td><td>Circular - 6.60mm Dia</td></td<>	PANEL CUTOUT DIMENSIONS	Circular - 6.60mm Dia
NUMBER OF POSITIONSSNUMBER OF POLES PER DECK2NUMBER OF POLES PER DECK1MUMBER OF DECKSPael Mour, Through HoleMOUNTING TYPEPael Mour, Through HoleMOUNTING TYPE(Unlimited)MOUNTING TYPE13 WecksMAUFACTURER STANDARD LEAD TIMELead Free / RoHS CompliantINDEX STOPSFeadFEATURES-DETAILED DESCRIPTIONAcary Schlich DPST D20MA (A/C)C) 125VA Panel Mount, Through HoleDETH BEHIND PANEL0000 (ACIC)CONTACT TIMINGSon (AC/C)CCONTACT TIMINGOper AlloyCONTACT FINISHSineCONTACT FINISHSineCONTACT FINISHSineCONTACT FINISHGPSANGLE OF THROWSineCONTACT FINISHGPSANGLE OF THROWBitl (317mm Dail)ANGLE OF THROWBitl (317mm Dail)ANGLE OF THROWBitl (317mm Dail)	OTHER NAMES	
NUMBER OF POLES PER DECK2NUMBER OF POLES PER DECK1MUMBER OF DECKSPanel Mount, Through HoleMOUNTING TYPEInfinitedMOUNTING TYPEInfinitedMOUSTURE SENSITIVIT, LEVEL (MSL)InfinitedMANUFACTURER STANDARD LEAD TIMEInfinitedLEAD FREE STATUS / ROHS STATUSInfinitedIDEX STOPSFxadPEATURESInfinitedDETAILED DESCRIPTIONInfinitedCURRENT RATINGInfinitedCURRENT RATINGSom (Ac/OC)CUNTACT TIMINGInfinited BBM)CONTACT TIMINGInfinited BBM)CUNTACT FINISHInfinited BBMCURLET PER DECKInfinited BBMCURLET PER DECKInfinited BBMCURLET RATINGInfinited BBMCURLET REALInfinited BBMCURLET	OPERATING FORCE	2.880 ~ 5.041gfm
NUMBER OF DECKS1NUMBER OF DECKSPael Mount Though HoleMOUNTING TYPEInformationMOSTURE SENSITIVIT LEVEL (MSL)InformationMANUFACTURER STANDAR DE LAD TIMEInformationLEAD FREE STATUS / ROHS STATUSInfor Angle CompliantINDEX STOPSFradFATURES-DETAILED DESCRIPTIONRole Schlich DESCRIPTIONCONTACT TIMINGOnschlich DESCRIPTIONCONTACT TIMINGSchlich DESCRIPTIONCONTACT TIMINGSilenCONTACT FINISHSilenCONTACT FINISHSilenCONTACT FINISHSilenANGLE OF THROWSilenANGLE OF THROWSilenANGLE OF THROWSilenANGLE OF THROWBilenANGLE OF THROWSilenANGLE	NUMBER OF POSITIONS	5
MOUNTING TYPEPanel Mount, Through HoleMOISTURE SENSITIVT LEVEL (MSL)1 (Unimited)MANUFACTURER STANDARD LEAD TIME13 WeksLEAD FREE STATUS / ROHS STATUSEad free / ROHS CompliantINDEX STOPSFiedFEATURES-DETAILED DESCRIPTIONRotary Switch S Position DPST 250mA (AC/DC) 125VAC Panel Mount, Through Hole)DEPTH BEHIND PANEL040maCORRENT RATINGSion (AC/DC)CONTACT TIMINGOn-Shorting (BBM)CONTACT FINISHSiveCONTACT FINISHSiveCARENT RATINGSiveCARLING FINISHSiveCARLING FINISHSiveANGLE OF THROWBGANGLE OF THROWBGANGLE OF THROWBGANGLE OF THROWBtANGLE OF THROWBtA	NUMBER OF POLES PER DECK	2
MOISTURE SENSITIVITY LEVEL (MSL)I (Unlimice)MANUFACTURER STANDARD LEAD TIMEI SVeksLEAD FREE STATUS / ROHS STATUSLead free / RoHS CompliantINDEX STOPSFixedFEATURES-DETAILED DESCRIPTIONRoty Sveht S Postion DPS T 250mA (A/C/DC) 125VAC Panel Mount, Through HoleDETH BEHIND PANEL20mA (A/C/DC)CORTACT TIMINGSona (A/C/DC)CONTACT TIMINGSona (A/C/DC)CONTACT FINISHSiveCONTACT FINISHSiveANGLE OF THROWBYANGLE OF THROW	NUMBER OF DECKS	1
MANUFACTURER STANDARD LEAD TIME3 WeeksLAD FREE STATUS / ROHS STATUSLeaf fee / ROHS CompliantINDEX STOPSFxedFATURES-DETAILED DESCRIPTIONRols Status / ROHS Status / ROHSCURRENT RATINGS0m (AC/DC)CONTACT TIMINGNo-Shorting (BBM)CONTACT FINISHSilverCROUT OF CECKDFTANGLE OF THROWSilverANGLE OF THROWSilverCARLENT RATINGDFTCONTACT TIMINGSilverCONTACT TIMINGSilverCARCUT PER DECKDFTANGLE OF THROWSilverANGLE OF THROWSilverCARLENT RATINGSilverCARLENT RATINGSilver	MOUNTING TYPE	Panel Mount, Through Hole
LEAD FREE STATUS / ROHS STATUSLead free / ROHS CompliantINDEX STOPSFixalFEATURES-DETAILED DESCRIPTIONRotary Stotich DPS 200m (AC/DC) 125VAC Panel Mount, Through HoleDEPTH BEHIND PANEL0142mmCURRENT RATINGS0m (AC/DC)CONTACT TIMINGCompany (Sum)CONTACT FINISHGuper AllongCONTACT FINISHSiveANGLE OF THROWSiveANGLE OF THROW <td>MOISTURE SENSITIVITY LEVEL (MSL)</td> <td>1 (Unlimited)</td>	MOISTURE SENSITIVITY LEVEL (MSL)	1 (Unlimited)
INDEX STOPSFixedFATURES-DETAILED DESCRIPTIONRotary Switch 5 Position DPST 250mA (AC/DC) 125VAC Panel Mount, Through HoleDEPTH BEHIND PANEL0.42mmCURRENT RATINGS0mA (AC/DC)CONTACT TIMINGNon-Shorting (BBM)CONTACT FINISHOper AlloyCONTACT FINISHSilverANGLE OF THROWSP5ANGLE OF THROWBited (3.1mm Edua)ANGLE OF THROWBited (3.1mm Edua)	MANUFACTURER STANDARD LEAD TIME	13 Weeks
FATURES-PEATURESRary Switch SPAStion DPST 250mA (AC/DC) 125VAC Panel Mount, Through HoleDETH BEHIND PANEL0.42mmCURRENT RATINGS0mA (AC/DC)CONTACT TIMINGNo-Shoring (BBM)CONTACT FINISHCoper AlloyCONTACT FINISHSilverCIRCUIT PER DECKD9TANGLE OF THROWSilverANGLE OF THROWSilverANGLE OF THROWBillerANGLE OF THROWBILL OF THROWANGLE OF THROW </td <td>LEAD FREE STATUS / ROHS STATUS</td> <td>Lead free / RoHS Compliant</td>	LEAD FREE STATUS / ROHS STATUS	Lead free / RoHS Compliant
DETAILED DESCRIPTIONRoary Section DPST 250mA (AC/DC) 125VAC Panel Mount, Through HoleDEPTH BEHIND PANEL0.42mmCURRENT RATING250mA (AC/DC)CONTACT TIMINGNon-Shorting (BBM)CONTACT MATERIALCoper AlloyCONTACT FINISHBiverCIRCUIT PER DECKDSTANGLE OF THROWScole (BL)ATUATOR TYPEBide (BL)	INDEX STOPS	Fixed
DEPTH BEHIND PANEL10.42mmCURRENT RATING50mA (AC/DC)CONTACT TIMINGNo-Shorting (BBM)CONTACT FINISHCoper AlloyCONTACT FINISHSilverCIRCUIT PER DECKDP5ANGLE OF THROWSilver AlloyANGLE OF THROWBited (3.17mm Dia)	FEATURES	-
CURRENT RATING250mA (AC/DC)CONTACT TIMINGNon-Shorting (BBM)CONTACT MATERIALCoper AlloyCONTACT FINISHSilverCIRCUIT PER DECKDFTANGLE OF THROWSilverANGLE OF THROWBite (3.17mm Dia)ANGLE OF THROWBite (3.17mm Dia)	DETAILED DESCRIPTION	Rotary Switch 5 Position DP5T 250mA (AC/DC) 125VAC Panel Mount, Through Hole
CONTACT TIMINGNon-Shorting (BBM)CONTACT MATERIALCoper AlloyCONTACT FINISHSilverCRCUIT PER DECKDP5TANGLE OF THROWSi <sup>o</sup> ATUATOR TYPEHated (S1.17mm Dia)	DEPTH BEHIND PANEL	10.42mm
CONTACT MATERIALCoper AlloyCONTACT FINISHSilverCIRCUIT PER DECKDP5ANGLE OF THROWG°ACTUATOR TYPEBitley (1.1)	CURRENT RATING	250mA (AC/DC)
CONTACT FINISHSilverCIRCUIT PER DECKDP5TANGLE OF THROWG°ACTUATOR TYPEFlated (3.17mm Dia)	CONTACT TIMING	Non-Shorting (BBM)
CIRCUIT PER DECKDP5TANGLE OF THROW36°ACTUATOR TYPEFlatted (3.17mm Dia)	CONTACT MATERIAL	Copper Alloy
ANGLE OF THROW36°ACTUATOR TYPEFlatted (3.17mm Dia)	CONTACT FINISH	Silver
ACTUATOR TYPE Flatted (3.17mm Dia)	CIRCUIT PER DECK	DP5T
	ANGLE OF THROW	36°
ACTUATOR LENGTH 10.16mm	ACTUATOR TYPE	Flatted (3.17mm Dia)
	ACTUATOR LENGTH	10.16mm

# **Related Tags**

C&K MB05L1NCQD	MB05L1NCQD Distributor	MB05L1NCQD Supplier
MB05L1NCQD Price	MB05L1NCQD Pictures	MB05L1NCQD Image
MB05L1NCQD PDF Datasheet	MB05L1NCQD Download Datasheet	MB05L1NCQD Datasheet
MB05L1NCQD Stock	Buy MB05L1NCQD	Buy C&K MB05L1NCQD
C&K MB05L1NCQD	C&K Supplier	C&K Distributor
C&K MB05L1NCQD	C&K Components MB05L1NCQD	

# **Related Products**



### MB05L1NZQD

Manufacturers: C&K Description: SWITCH ROTARY 5POS 250MA 125V In stock: Out stock

RFQ

### MB04S3NCQD

MB05L2NCQD

Manufacturers: C&K Description: SWITCH ROTARY 4POS 250MA 125V In stock: Out stock

RFQ



## MB05L1NCGD

Manufacturers: C&K Description: SWITCH ROTARY 5POS 250MA 125V In stock: 23 pcs

RFQ

# **C&K**

**C**&K

Manufacturers: C&K Description: SWITCH ROTARY 5POS 250MA 125V In stock: Out stock

RFQ

### MB05FTR



Manufacturers: Sensitron Semiconductor / SMC Diode Solutions Description: BRIDGE RECT 1PHASE 50V 500MA MBF In stock: Out stock

## MB05L1NZQF



Manufacturers: C&K Description: SWITCH ROTARY 5POS 250MA 125V In stock: 49 pcs

RFQ

### MB05L1NCQF

RFQ



Manufacturers: C&K Description: SWITCH ROTARY 5POS 250MA 125V In stock: Out stock

RFQ

#### MB05L1NCGF

MB04S1NZQF



Manufacturers: C&K Description: SWITCH ROTARY 5POS 250MA 125V In stock: Out stock

RFQ

## MB05L1NZGF



Manufacturers: C&K Description: SWITCH ROTARY 5POS 250MA 125V In stock: Out stock

RFQ



Manufacturers: C&K Description: SWITCH ROTARY 4POS 250MA 125V In stock: Out stock

RFQ



### Copyright © 2020 Reliable Distributor of Electronic Components - Ocean-Components.com

E-mail: Info@Ocean-Components.com

Address: Room 2102, Connaught Commercial Building, 185 Wan Chai Rd, Wan Chai, Hong Kong

