



Image may be representation. See specifications for

product details.

# **CRD10RM0SB**

Part Number:	CRD10RM0SB	
Manufacturer/Brand:	С&К	
Product description	SWITCH ROTARY DIP BCD 0.40VA 20V	
Datasheets:	CRD10RM0SB.pdf	
RoHs Status	Lead free / RoHS Compliant	
Ship From	Hong Kong	
Shipment Way	DHL/Fedex/TNT/UPS/EMS	

## **REQUEST FOR QUOTATION**

MANUFACTURERCakDESCRIPTIONSMITCH ROTARY DIP BCD 0.40VA 20VLEAD FREE STATUS / ROHS STATUSLead free / RahS CompliantDATA SHETCall CompliantWASHABLEYesVOLTAGE RATINGQIWAC/CCVOLTAGE RATINGQIWAC/CCPREMINATION STULEGUID (2.54mm), FullPRICKDOI (2.54mm), FullPARCMARINEYesPRICKCOID (2.54mm), FullPARCMARINECOID (2.54mm), FullPARCMARINEYes </th <th></th> <th>Specifications of CRD10RM0SB</th>		Specifications of CRD10RM0SB
MANUFACTURERC&KDESCRIPTIONSWITCH ROTARY DIP BCD 0.40VA 20VLEAD FREE STATUS / ROHS STATUSLead free / ROHS CompliantDATA SHEFTCCD10RM058.pdfWASHABLEYesVOLTACE RATINGGUN/Q'OCTERMINATION STULEGUN (2.5 kmm), FullPRICEGUN (2.5 kmm), FullPACKACINGTufeROMCONCINGSCOOTHER NAMESCCNOTHER NAMESSCNOTHER NAMESSCN <td< th=""><th></th><th></th></td<>		
DESCRIPTIONSWITCH ROTARY DIP BCD 0.400X 20VLEAD FREE STATUS / ROHS STATUSLead free / RoHS CompliantDATA SHEETCB 0.108M058.pdfWASHABLEYasVOLTAGE RATINGSUAC//CCTERMINATION STVLEGUI WINGSERIESCD 000 (2.54mm), FullPACKAGINGTubePACKAGINGCD 000 (2.54mm), FullPACKAGINGCD 000 (2.54mm), FullPACKAGINGSUGV (2.54mm), FullPACKAGINGCD 000 (2.54mm), FullPACKAGINGCD 000 (2.54mm), FullPACKAGINGSufface MountPACKAGINGSufface MountNUMBER OF POSITIONS10MOUNTING TYPESufface MountMOUNTING TYPESufface MountLEAD FREE STATUS / ROHS STATUSSufface MountLEAD FREE STATUS / ROHS STATUSSufface CompliantHEIGHT ABOVE BOARDSufface PLANES CompliantLEAD FREE STATUS / ROHS STATUSSufface ROHS COMPLIANTLEAD FREE STATUS / ROHS	PART NUMBER	CRD10RM0SB
LEAD FREE STATUS / ROHS STATUS         Lead free / RohS Complant           DATA SHEET         CRIDERHOSE.pdf           WASHABLE         Via           VOLTAGE RATING         20VAC/DC           SERLES         Gul Wing           SERLES         CRID (2.54mm), Full           PACKAGING         1.00° (2.54mm), Full           PACKAGING         CRID (2.54mm), Full           PACKAGING         Saface Addit (2.54mm), Full           PACKAGING YERE<	MANUFACTURER	C&K
ATA SHET© CDDRMOSE, pdfWASHABLEYesVILTAGE RATINGXUAC/DCTERMINATION STYLEGLM WingSERIESCDPTCH0.100° (2.54mm), FullPACKAGINGTubeOTHER NAMESCDDI NEMOSOTHER NAMES-20°C ~ 85°CNUMBER OF POSITIONS10MOUTTING TEMPERATURESaface MountMOUTTING TYPE10.1011MOUTTING TYPE30.000 SepsMANDAFCTURER STATUS10.900 SepsMANDAFCTURER STATUS / RONS Safation30.91 (1.001m)LEAD TER STATUS / RONS STATUS10.91 (1.001m)ELECTRICAL LIFE0.3007 (1.001m)ELECTRICAL LIFE0.3007 (1.001m)ELECTRICAL LIFE0.3007 (1.001m)ELECTRICAL LIFE0.3007 (1.001m)ELECTRICAL LIFE0.3007 (1.001m)ELECTRICAL LIFE0.3007 SepsELECTRICAL LIFE0.3000 SepsELECTRICAL LIFE0.3000 SepsELECTRICAL LIFE0.3000 SepsELECTRICAL LIFE0.9000 SepsELECTRICAL LIFE0.9000 SepsCONTACT FINISH0.404CONTACT FINISH6.404CONTACT	DESCRIPTION	SWITCH ROTARY DIP BCD 0.40VA 20V
WashinabianVashinabianVouctage ratingvouctage ratingseruesseruesseruesvouctage ratingvouctage rating <td>LEAD FREE STATUS / ROHS STATUS</td> <td>Lead free / RoHS Compliant</td>	LEAD FREE STATUS / ROHS STATUS	Lead free / RoHS Compliant
Voltrage RATING20XAC/DCTERMINATION STYLEGull WingSERIESCRDPTCH0.00° (2.54mm, FullPACKAGINGTubeOPERATING TEMPERATURE-0°C ~ 0°C ~	DATA SHEET	CRD10RM0SB.pdf
TERMINATION STYLEGal WagSERIESKDSERIESKDPTCHL00°(254mn), FullPACKAGINGTobOTHER NAMESCRD10RM0SBOPERATING TEMPERATURESC° ~ 85°	WASHABLE	Yes
SRIESOPPACKAGINGGL09 (2,54mm), FullPACKAGINGTubePACKAGINGCR010RM058OTHER NAMESCR010RM058OPERATING TEMPERATURE20°C ~ 8°CNUMBER OF POSITIONS0MOUTING TYPESurface MountMOUTING TYPE(Unlimited)MOUTING SITURE SENSITIVITY LEVEL (MSL)(Unlimited)MOUTING TYPE0.900 StepsMANUFACTURER STANDARD LEAD TIME16 WeeksLENGTH0.93° (10.00m)LENGTH0.93° (10.00m)LEIGHT ABOVE BOARD2001 StepsELECTRICAL LIFE0.900 StepsCONTACT HATERIAL0.900 S	VOLTAGE RATING	20VAC/DC
PTCH6.00° (2.49m), FullPACKAGINGTubePACKAGINGCRONINGRADESAorther NAMESCRONINGRADESAOPERATING TEMPERATURE-0°C ~ 8°CNUMBER OF POSITIONS0MOUTING TYPEConface MountMOUTING TYPEUnlimitedMOUTING SENSITIVITY LEVEL (MSL)0.000 StepsMANUPACTURER STANDARD LEAD TIME0.000 StepsLENGTH0.000 StepsLENGTH0.000 StepsLENGTH0.000 StepsLEIGT ADAVE BOARD0.000 StepsLEIGT ADAVE BOARD0.000 StepsELECTRICL LIFE0.000 StepsELECTRICL LIFE0.000 StepsELECTRICL LIFE0.000 StepsELECTRICL LIFE0.000 StepsELECTRICL LIFE0.000 StepsELECTRICL LIFE0.000 StepsCONTACT MATERIAL0.000 StepsCONTACT MATERIAL0.000 StepsCONTACT FINISH0.000 StepsCO	TERMINATION STYLE	Gull Wing
PACKAGINGTubeOTHER NAMESCROITONSOPERATING TEMPERATURE-20°C & 8°CNUMBER OF POSITIONS0MOUNTING TYPESurface MountMOUNTING TYPE10/InitedMOUNTING TYPE10/InitedMOUNTING TYPE0.000 StepsMANUFACTURER STANDARD LEAD TIME16/WeksLENGTH0.393° (10.00m)LEAD FREE STATUS / ROHS STATUSCad free / ROHS CompliantHEGHT ABOVE BOARD201° (6.88m)ELECTRICAL LIFE0.000 StepsELECTRICAL LIFE0.000 StepsCONTACT MATERIALGelCONTACT MATERIALGoldCONTACT FINISHGoldCONTACT FINISHGoldCONTACT FINISHStepsensensensensensensensensensensensensens	SERIES	CRD
OTHER NAMESCRD/DRMOSB CKN6173OPERATING TEMPERATURE20°C ~ 85°CNUMEER OF POSITIONS10MOUNTING TYPESurface MountMOUNTING TYPE(Iulimited)MOUNTING TYPE3000 StepsMANUFACTURER STANDARD LEAD TIME6000 StepsLENGTH0.393° (10.00mm)LENGTH0.303 StepsLENGTH0.303 StepsLENGTH0.303 StepsLENGTH0.303 StepsLENGTH0.303 StepsLENGTH0.303 StepsLENGTH0.303 StepsLENGTH0.303 StepsLENGTH0.303 StepsLENGTH0.300 StepsLENGTH0.300 StepsLEIGTING LIFE0.300 StepsLEIGTING LIFE0.300 StepsLEIGTING LIFE0.404CONTACT MATERIAL0.404CONTACT MATERIAL604CONTACT FINISHGuine Contact MaterialCONTACT FINISHSchlencencencencencencencencencencencencence	PITCH	0.100" (2.54mm), Full
OTHER NAMESCKN6173OPERATING TEMPERATURE-20°C ~ 85°CNUMBER OF POSITIONS10MOUNTING TYPESurface MountMOUNTING TYPE(Inlimited)MOISTURE SENSITIVITY LEVEL (MSL)(Inlimited)MCHANICAL LIFE30,00 StepsMANUFACTURER STANDARD LEAD TIME16 WeeksLEINGTH0.393" (10.00m)LEAD FREE STATUS / ROHS STATUSLead free / ROHS CompliantHEIGHT ABOVE BOARD0.271" (6.88m)ELECTRICAL LIFE0.000 StepsELECTRICAL LIFEDip South BCD 10 Position Surface Mount Rotary for Tool Actuator 0.4VA 20VAC/DCCURRENT RATINGGoldCURRENT RATINGGoldCONTACT FINISHGoldBODY MATERIALPolyneynes Suffice (PSP)BODY MATERIALPolyneynes Suffice (PSP)BODY MATERIALRotary For ToolBODY MATERIALSouth FODBODY MATERIAL <t< td=""><td>PACKAGING</td><td>Tube</td></t<>	PACKAGING	Tube
NUMBER OF POSITIONS10MOUNTING TYPESurface MountMOINTING TYPE(Inlimited)MOINTING TYPE(Inlimited)MOINTING TYPE30,000 StepsMANUFACTURER STANDARD LEAD TIME6 WeeksLENGTH0.303° (10.00mm)LENGTHCadfree / RoHS CompliantLEAD FREE STATUS / ROHS STATUSKed free / RoHS CompliantLEAD FREE STATUS / ROHS STATUS2.21° (6.88mm)EECTRICAL LIFE0.900 StepsELECTRICAL LIFE0.900 StepsCURRENT RATING0.900 StepsCURRENT RATING0.900 StepsCURRENT RATING0.900 StepsCONTACT MATERIAL0.900 StepsCONTACT MATERIAL6.4VACONTACT MATERIAL6.04CONTACT FINISH6.04CONTACT FINISH6.04BODY MATERIALPolybenylene Sulfide (PPS)BODY MATERIALRoty TOOIRATATORT YPERaty for Tool	OTHER NAMES	
MOUNTING TYPESurface MountMOUNTING TYPESurface MountMOUNTING TYPE1 (Unlimited)MOUNTING TYPE3,000 StepsMANUFACTURER STANDARD LEAD TIME16 WeeksLENGTH0,303° (10.00mm)LEAD FREE STATUS / ROHS STATUSLed free / ROHS CompliantLEAD FREE STATUS / ROHS STATUS0,211° (6.88mm)LEIGTH ABOVE BOARD0,211° (6.88mm)ELECTRICAL LIFE0,000 StepsELECTRICAL LIFE0,000 StepsCURRENT RATING0,4VACONTACT FINISHGoldCONTACT FINISHGoldCONTACT FINISHGoldBODY MATERIALSuphenyensulfide (PPS)RATUATOR TYPERaty for Tool	OPERATING TEMPERATURE	-20°C ~ 85°C
MOISTURE SENSITIVITY LEVEL (MSL)I (Unlimited)MOISTURE SENSITIVITY LEVEL (MSL)3,000 StepsMANUFACTURER STANDARD LEAD TIME16 WeeksLENGTH0.393' (10.00mm)LENGTHLead free / RoHS CompliantLENGTH0.271' (6.88mm)FEATURES9/000 StepsELECTRICAL LIFE0.900 StepsELECTRICAL LIFE0.900 StepsCURRENT RATING0.4VACONTACT MATERIALGoldCONTACT FINISHGoldCONTACT FINISHGoldBODY MATERIALPhyphenyens Suffice (PPS)RATURESPhyphenyens Suffice (PPS)	NUMBER OF POSITIONS	10
MECHANICAL LIFE30,000 StepsMANUFACTURER STANDARD LEAD TIME60 WeskLENGTH0.393" (10.00mm)LEAD FREE STATUS / ROHS STATUSLead free / ROHS CompliantLEAD FREE STATUS / ROHS STATUS0.271" (6.88mm)FEATURESProcess SealedELECTRICAL LIFE0.000 StepsDETAILED DESCRIPTIONDip Switch BCD 10 Position Surface Mount Rotary for Tool Actuator 0.4VA 20VAC/DCCURRENT RATING0.4VACONTACT MATERIALBerlium CopperCONTACT FINISHGoldCURCUTPipohenjenis Sulfide (PPS)BODY MATERIALPipohenjenis Sulfide (PPS)RATURTS NEWRotary for Tool	MOUNTING TYPE	Surface Mount
MANUFACTURER STANDARD LEAD TIME16 WeeksLENGTH.33° (1.00mm)LENGTH.630° (0.00mpliatLEAD FREE STATUS / ROHS STATUS.640° (ROHS)HEIGHT ABOVE BOARD.021° (6.88mm)FEATURESProcess SealedELECTRICAL LIFE.0000 StepsCURRENT RATING.04VACONTACT MATERIAL.640° (ROHS)CONTACT FINISH.600CONTACT FINISH.600BODY MATERIAL.600 StepsBODY MATERIAL.600 StepsACUARDANCE.600 StepsCONTACT NATERIAL.600 StepsCONTACT FINISH.600 StepsBODY MATERIAL.600 StepsBODY MATERIAL.600 StepsACUARDANCE.600 StepsBODY MATERIAL.600 StepsACUARDANCE.600 StepsACUARDANCE.600 StepsBODY MATERIAL.600 StepsACUARDANCE.600 StepsACUARDANC	MOISTURE SENSITIVITY LEVEL (MSL)	1 (Unlimited)
LENGTH 0.393° (10.00mm) LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant LEGHT ABOVE BOARD 0.21° (6.88mm) FEATURES PORES Status Process	MECHANICAL LIFE	30,000 Steps
LEAD FREE STATUS / ROHS STATUSLead free / RoHS CompliantHEIGHT ABOVE BOARD0.271" (6.88mm)FEATURESProcess SealedELECTRICAL LIFE0,000 StepsDETAILED DESCRIPTIONDip Switch BCD 10 Position Surface Mount Rotary for Tool Actuator 0.4VA 20VAC/DCCURRENT RATING0.4VACONTACT MATERIALBerylium CopperCONTACT FINISHGoldBCDMATERIALBODY MATERIALPolypenylene Sulfide (PPS)ACTUATOR TYPERotary for Tool	MANUFACTURER STANDARD LEAD TIME	16 Weeks
HEIGHT ABOVE BOARD0.271 (6.88mm)FEATURESPocess SealedELECTRICAL LIFE0,000 StepsDETAILED DESCRIPTIONDip Switch BCD 10 Position Surface Mount Rotary for Tool Actuator 0.4VA 20VAC/DCCURRENT RATING0.4VACONTACT MATERIALBeyllium CopperCONTACT FINISHGodBCD MATERIALBCDBODY MATERIALPolypenselified (PPS)ACTUATOR TYPEBcargo Tool	LENGTH	0.393" (10.00mm)
FEATURESProcess SealedELECTRICAL LIFE2,000 StepsDETAILED DESCRIPTIONDip Switch BCD 10 Position Surface Mount Rotary for Tool Actuator 0.4VA 20VAC/DCCURRENT RATING0.4VACONTACT MATERIALBerylium CopperCONTACT FINISHGoldCIRCUITBCDBODY MATERIALPolypengengengengengengengengengengengengenge	LEAD FREE STATUS / ROHS STATUS	Lead free / RoHS Compliant
ELECTRICAL LIFE20,000 StepsDETAILED DESCRIPTIONDip Switch BCD 10 Position Surface Mount Rotary for Tool Actuator 0.4VA 20VAC/DCCURRENT RATING0.4VACONTACT MATERIALBeyllium CopperCONTACT FINISHGoldCIRCUITBCDBODY MATERIALPolypenselinde (PPS)ACTUATOR TYPERotary for Tool	HEIGHT ABOVE BOARD	0.271" (6.88mm)
DETAILED DESCRIPTIONDip Switch BCD 10 Position Surface Mount Rotary for Tool Actuator 0.4VA 20VAC/DCCURRENT RATING0.4VACONTACT MATERIALBeryllium CopperCONTACT FINISHGoldCIRCUITBCDBODY MATERIALPolypheng Suffade (PPS)ACTUATOR TYPERotary for Tool	FEATURES	Process Sealed
CURRENT RATING0.4VACONTACT MATERIALBeryllium CopperCONTACT FINISHGoldCIRCUITBCDBODY MATERIALPolyphenylene Sulfide (PPS)ACTUATOR TYPERotary for Tool	ELECTRICAL LIFE	20,000 Steps
CONTACT MATERIALBeryllium CopperCONTACT FINISHGoldCIRCUITBCDBODY MATERIALPolyphenylene Sulfide (PPS)ACTUATOR TYPERotary for Tool	DETAILED DESCRIPTION	Dip Switch BCD 10 Position Surface Mount Rotary for Tool Actuator 0.4VA 20VAC/DC
CONTACT FINISH       Gold         CIRCUIT       BCD         BODY MATERIAL       Polyphenylene Sulfide (PPS)         ACTUATOR TYPE       Rotary fronol	CURRENT RATING	0.4VA
CIRCUITBCDBODY MATERIALPolyphenylene Sulfide (PPS)ACTUATOR TYPERotary for Tool	CONTACT MATERIAL	Beryllium Copper
BODY MATERIAL     Polyphenylene Sulfide (PPS)       ACTUATOR TYPE     Rotary for Tool	CONTACT FINISH	Gold
ACTUATOR TYPE Rotary for Tool	CIRCUIT	BCD
	BODY MATERIAL	Polyphenylene Sulfide (PPS)
ACTUATOR LEVEL Flush, Recessed	ACTUATOR TYPE	Rotary for Tool
	ACTUATOR LEVEL	Flush, Recessed

# **Related Tags**

C&K CRD10RM0SB	CRD10RM0SB Distributor	CRD10RM0SB Supplier
CRD10RM0SB Price	CRD10RM0SB Pictures	CRD10RM0SB Image
CRD10RM0SB PDF Datasheet	CRD10RM0SB Download Datasheet	CRD10RM0SB Datasheet
CRD10RM0SB Stock	Buy CRD10RM0SB	Buy C&K CRD10RM0SB
C&K CRD10RM0SB	C&K Supplier	C&K Distributor
C&K CRD10RM0SB	C&K Components CRD10RM0SB	

# **Related Products**



## **CRD10RM0SK**

Manufacturers: C&K Description: SWITCH ROTARY DIP BCD 0.40VA 20V In stock: Out stock

RFQ



## CRD10RM0AK

CRD1171-2

Manufacturers: C&K Description: SWITCH ROTARY DIP BCD 0.40VA 20V In stock: Out stock

RFQ

#### CRD10RM0SKR



Manufacturers: C&K Description: SWITCH ROTARY DIP BCD 0.40VA 20V In stock: Out stock

RFQ



## Manufacturers: Cirrus Logic Description: EVAL BOARD EV2 CRD1171

In stock: Out stock



## CRD10RW1CB Manufacturers: C&K Description: SWITCH ROTARY DIP BCD 0.40VA 20V In stock: Out stock



## **CRD10RM0CK**

Manufacturers: C&K Description: SWITCH ROTARY DIP BCD 0.40VA 20V In stock: Out stock

RFQ



#### **CRD10RM0SBR**

RFQ

Manufacturers: C&K Description: SWITCH ROTARY DIP BCD 0.40VA 20V In stock: Out stock

RFQ

#### **CRD10RL1AB**



Manufacturers: C&K Description: SWITCH ROTARY DIP BCD 0.40VA 20V In stock: Out stock

RFQ

# CRD10RW1AB CRD10RM0AB Manufacturers: C&K Manufacturers: C&K Description: SWITCH ROTARY DIP BCD 0.40VA 20V Manufacturers: C&K In stock: Out stock Description: SWITCH ROTARY DIP BCD 0.40VA 20V In stock: Out stock RFQ



#### **CRD10RM0CB**

Manufacturers: C&K Description: SWITCH ROTARY DIP BCD 0.40VA 20V In stock: Out stock

RFQ



Manufacturers: C&K Description: SWITCH ROTARY DIP BCD 0.40VA 20V In stock: Out stock

RFQ

**CRD10RL1CB** 

#### Copyright © 2020 Reliable Distributor of Electronic Components - Ocean-Components.com

E-mail: Info@Ocean-Components.com

Address: Room 2102, Connaught Commercial Building, 185 Wan Chai Rd, Wan Chai, Hong Kong

