

7211J2V4BE2

Manufacturer/Brand:

Product description

Datasheets:

RoHs Status Ship From Shipment Way 7211J2V4BE2

C&K

SWITCH ROCKER SP3T 0.4VA 20V

1.7211J2V4BE2.pdf 2.7211J2V4BE2.pdf 3.7211J2V4BE2.pdf

Lead free / RoHS Compliant Hong Kong

DHL/Fedex/TNT/UPS/EMS

REQUEST FOR QUOTATION

Image may be representation. See specifications for product details.

C&K

PART NUMBER 721112V4BE2 MANUFACTURER CCK DESCRIPTION SWITCH ROCKER SP3T 0.4WA 20V LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant DATA SHEET		
MANUFACTURER CRIK DESCRIPTION SWITCH ROCKER SP3T 0.4VA 20V LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant DATA SHEET □ 1.721112V48PE2.pdf □ 2.721112V48PE2.pdf □ 2.721112V48PE2.pdf VOLTAGE RATING - DC 20V VOLTAGE RATING - AC 20V SWITCH FUNCTION On-On-On SERIES 7000 PANEL CUTOUT DIMENSIONS - PACKAGING Bulk OPERATING TEMPERATURE -30°C ~ 85°C MOUNTING TYPE Through Hole MOUNTING TYPE Through Hole MOUNTING SENSITIVITY LEVEL (MSL) 1 (Unlimited) MECHANICAL LIFE - MANUFACTURER STANDARD LEAD TIME 11 Weeks LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant INGERSS PROTECTION - ILLUMINATION TYPE, COLOR - FEATURES Jumper needed to achieve triple throw ELECTRICAL LIFE 40,000 Cycles DETAILED DESCRIPTION Rocker Switch SP3T 0.4VA (AC/DC) 20V Through Hole CURRENT RATING 0.4VA		Specifications of 7211J2V4BE2
MANUFACTURER DESCRIPTION SWITCH ROCKER SP3T 0.4VA 20V Lead Free STATUS / ROHS STATUS Lead free / RoHS Compliant 2 1.721112V4BE2.pdf 2 2.721112V4BE2.pdf 2 3.721112V4BE2.pdf 3 3.72112V4BE2.pdf 2 7.72112V4BE2.pdf 2 7.72112V4BE2.pdf 3 3.72112V4BE2.pdf 2 7.72112V4BE2.pdf 3 7.72112V4BE2.pdf VOLTAGE RATING - DC VOLTAGE RATING - AC 20V VOLTAGE RATING - AC 20V TERMINATION STYLE PC Pin SWITCH FUNCTION On-On-On SERIES 7000 PANEL CUTOUT DIMENSIONS - PACKAGING Bulk OPERATING TEMPERATURE - 30°C ~ 8°C MOUNTING TYPE MOUSTURE SENSITIVITY LEVEL (MSL) MECHANICAL LIFE - MANUFACTURER STANDARD LEAD TIME 11 Weeks LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant ILLUMINATION VOLTAGE (NOMINAL) - ILLUMINATION YPE, COLOR - FEATURES JUMPER PROCESSES FROTECTION ROCKER SWITCH SP3T 0.4VA (AC/DC) 20V Through Hole CURRENT RATING 0.4VA (AC/DC) COLOR - ACTUATOR/CAP Black CIRCUIT SP3T ACTUATOR TYPE Paddle		
DESCRIPTION LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant DATA SHEET DATA		
LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant 1.721112V4BE2.pdf		
DATA SHEET DATA STAILLANDER DATA SHEET		
DATA SHEET 2.7211J2V4BE2.pdf 3.7211J2V4BE2.pdf 3.7211J2V4BE2.pdf VOLTAGE RATING - DC VOLTAGE RATING - AC 20V VOLTAGE RATING - AC 20V TERMINATION STYLE PC Pin SWITCH FUNCTION On-On-On SERIES 7000 PANEL CUTOUT DIMENSIONS - PACKAGING Bulk OPERATING TEMPERATURE -30°C ~ 85°C MOUNTING TYPE Through Hole MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) MECHANICAL LIFE - MANUFACTURER STANDARD LEAD TIME 11 Weeks LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant INGRESS PROTECTION - ILLUMINATION VOLTAGE (NOMINAL) - ILLUMINATION TYPE, COLOR - FEATURES Jumper needed to achieve triple throw ELECTRICAL LIFE 40,000 Cycles DETAILED DESCRIPTION Rocker Switch SP3T 0.4VA (AC/DC) 20V Through Hole CURRENT RATING 0.4VA (AC/DC) COLOR - ACTUATOR/CAP Black CIRCUIT SP3T Actual Time Paddle CURLING TEMPER SPACE Paddle CIRCUIT Paddle Paddle CURLING TYPE Paddle Paddle Paddle CURLING TYPE Paddle Paddle CURLING TYPE Paddle Paddle Paddle Paddle CURLING TYPE Paddle Paddle Paddle Paddle Paddle CURLING TYPE Paddle Paddle Paddle Paddle Paddle Paddle Paddle Paddle CURLING TYPE Paddle Paddle	LEAD FREE STATUS / ROHS STATUS	
VOLTAGE RATING - AC TERMINATION STYLE PC PIN SWITCH FUNCTION On-On-On SERIES 7000 PANEL CUTOUT DIMENSIONS - PACKAGING Bulk OPERATING TEMPERATURE -30°C ~ 85°C MOUNTING TYPE Through Hole MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) MECHANICAL LIFE - MANUFACTURER STANDARD LEAD TIME 11 Weeks LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant INGRESS PROTECTION - ILLUMINATION VOLTAGE (NOMINAL) - ILLUMINATION TYPE, COLOR FEATURES JUMPER needed to achieve triple throw ELECTRICAL LIFE 40,000 Cycles DETAILED DESCRIPTION ROCKER SWITCH SP3T 0.4VA (AC/DC) 20V Through Hole CURRENT RATING 0.4VA (AC/DC) COLOR - ACTUATOR/CAP Black CIRCUIT SP3T ACTUATOR TYPE Paddle	DATA SHEET	2.7211J2V4BE2.pdf
TERMINATION STYLE SWITCH FUNCTION On-On-On SERIES 7000 PANEL CUTOUT DIMENSIONS - PACKAGING BUIK OPERATING TEMPERATURE -30°C ~ 85°C MOUNTING TYPE Through Hole MOISTURE SENSITIVITY LEVEL (MSL) MECHANICAL LIFE -1 Weeks LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant INGRESS PROTECTION - ILLUMINATION VOLTAGE (NOMINAL) - ILLUMINATION TYPE, COLOR FEATURES Jumper needed to achieve triple throw ELECTRICAL LIFE 40,000 Cycles DETAILED DESCRIPTION Rocker Switch SP3T 0.4VA (AC/DC) 20V Through Hole CURRENT RATING 0.4VA (AC/DC) COLOR - ACTUATOR/CAP Black CIRCUIT Paddile	VOLTAGE RATING - DC	20V
SWITCH FUNCTION On-On-On SERIES 7000 PANEL CUTOUT DIMENSIONS - PACKAGING Bulk OPERATING TEMPERATURE -30°C ~ 85°C MOUNTING TYPE Through Hole MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) MECHANICAL LIFE - MANUFACTURER STANDARD LEAD TIME 11 Weeks LEAD FREE STATUS / ROHS STATUS LEAD TIME 11 Weeks LEAD FREE STATUS / ROHS STATUS LEAD TIME 11 Weeks LILUMINATION VOLTAGE (NOMINAL) - ILLUMINATION TYPE, COLOR - FEATURES JUMPER PROBLEM 14 40,000 Cycles ELECTRICAL LIFE 40,000 Cycles DETAILED DESCRIPTION ROCKE SWITCH SP3T 0.4VA (AC/DC) 20V Through Hole CURRENT RATING 0.4VA (AC/DC) COLOR - ACTUATOR/CAP Black CIRCUIT 92ddle	VOLTAGE RATING - AC	20V
PANEL CUTOUT DIMENSIONS - PACKAGING Bulk OPERATING TEMPERATURE -30°C ~ 85°C MOUNTING TYPE Through Hole MOISTURE SENSITIVITY LEVEL (MSL) MECHANICAL LIFE - MANUFACTURER STANDARD LEAD TIME 11 Weeks LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant INGRESS PROTECTION - ILLUMINATION VOLTAGE (NOMINAL) - ILLUMINATION TYPE, COLOR FEATURES Jumper needed to achieve triple throw ELECTRICAL LIFE 40,000 Cycles DETAILED DESCRIPTION ROCKER Switch SP3T 0.4VA (AC/DC) 20V Through Hole CURRENT RATING O.4VA (AC/DC) COLOR - ACTUATOR/CAP Black CIRCUIT SP3T ACTUATOR TYPE Paddle	TERMINATION STYLE	PC Pin
PANEL CUTOUT DIMENSIONS - PACKAGING Bulk OPERATING TEMPERATURE -30°C ~ 85°C MOUNTING TYPE Through Hole MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) MECHANICAL LIFE - MANUFACTURER STANDARD LEAD TIME 11 Weeks LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant INGRESS PROTECTION - ILLUMINATION VOLTAGE (NOMINAL) - ILLUMINATION TYPE, COLOR - FEATURES Jumper needed to achieve triple throw ELECTRICAL LIFE 40,000 Cycles DETAILED DESCRIPTION Rocker Switch SP3T 0.4VA (AC/DC) 20V Through Hole CURRENT RATING COLOR - ACTUATOR/CAP Black ELECTRICAL TYPE Paddle	SWITCH FUNCTION	On-On-On
PACKAGING PACKAGING PACKAGING POPERATING TEMPERATURE -30°C ~ 85°C MOUNTING TYPE Through Hole MOISTURE SENSITIVITY LEVEL (MSL) MECHANICAL LIFE - MANUFACTURER STANDARD LEAD TIME LEAD FREE STATUS / ROHS STATUS LEAd free / ROHS Compliant INGRESS PROTECTION ILLUMINATION VOLTAGE (NOMINAL) ILLUMINATION TYPE, COLOR FEATURES Jumper needed to achieve triple throw ELECTRICAL LIFE 40,000 Cycles DETAILED DESCRIPTION ROCKER Switch SP3T 0.4VA (AC/DC) 20V Through Hole CURRENT RATING O.4VA (AC/DC) COLOR - ACTUATOR/CAP Black CIRCUIT SP3T ACTUATOR TYPE Paddle	SERIES	7000
OPERATING TEMPERATURE A30°C ~ 85°C MOUNTING TYPE Through Hole MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) MECHANICAL LIFE - MANUFACTURER STANDARD LEAD TIME 11 Weeks LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant INGRESS PROTECTION ILLUMINATION VOLTAGE (NOMINAL) ILLUMINATION TYPE, COLOR FEATURES Jumper needed to achieve triple throw ELECTRICAL LIFE 40,000 Cycles DETAILED DESCRIPTION ROCKER SWItch SP3T 0.4VA (AC/DC) 20V Through Hole CURRENT RATING O.4VA (AC/DC) COLOR - ACTUATOR/CAP Black CIRCUIT SP3T ACTUATOR TYPE Paddle	PANEL CUTOUT DIMENSIONS	-
MOUNTING TYPE Through Hole MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) MECHANICAL LIFE - MANUFACTURER STANDARD LEAD TIME 11 Weeks LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant INGRESS PROTECTION - ILLUMINATION VOLTAGE (NOMINAL) - ILLUMINATION TYPE, COLOR - FEATURES JUMPER NEEDED 1 (MOUNT NO CYCLES NOW SWITCH SP3T 0.4VA (AC/DC) 20V Through Hole CURRENT RATING 0.4VA (AC/DC) COLOR - ACTUATOR/CAP Black CIRCUIT SP3T ACTUATOR TYPE PADDLE TO THE METHOD SITE OF THE	PACKAGING	Bulk
MOISTURE SENSITIVITY LEVEL (MSL) MECHANICAL LIFE - MANUFACTURER STANDARD LEAD TIME LEAD FREE STATUS / ROHS STATUS LUMINATION VOLTAGE (NOMINAL) - LLUMINATION TYPE, COLOR FEATURES Jumper needed to achieve triple throw ELECTRICAL LIFE 40,000 Cycles DETAILED DESCRIPTION Rocker Switch SP3T 0.4VA (AC/DC) 20V Through Hole CURRENT RATING CURRENT RATING CURRENT RATING CURRENT RATING CIRCUIT SP3T ACTUATOR TYPE Paddle	OPERATING TEMPERATURE	-30°C ~ 85°C
MECHANICAL LIFE MANUFACTURER STANDARD LEAD TIME LEAD FREE STATUS / ROHS STATUS LEAD FREE STATUS / ROHS STATUS LEAD FREE STATUS / ROHS STATUS LLUMINATION VOLTAGE (NOMINAL) LLUMINATION TYPE, COLOR FEATURES Jumper needed to achieve triple throw ELECTRICAL LIFE 40,000 Cycles DETAILED DESCRIPTION Rocker Switch SP3T 0.4VA (AC/DC) 20V Through Hole CURRENT RATING COLOR - ACTUATOR/CAP Black CIRCUIT SP3T ACTUATOR TYPE Paddle	MOUNTING TYPE	Through Hole
MANUFACTURER STANDARD LEAD TIME LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant INGRESS PROTECTION - ILLUMINATION VOLTAGE (NOMINAL) ILLUMINATION TYPE, COLOR FEATURES Jumper needed to achieve triple throw ELECTRICAL LIFE 40,000 Cycles DETAILED DESCRIPTION Rocker Switch SP3T 0.4VA (AC/DC) 20V Through Hole CURRENT RATING 0.4VA (AC/DC) COLOR - ACTUATOR/CAP Black CIRCUIT SP3T ACTUATOR TYPE Paddle	MOISTURE SENSITIVITY LEVEL (MSL)	1 (Unlimited)
LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant ILLUMINATION VOLTAGE (NOMINAL) ILLUMINATION TYPE, COLOR FEATURES Jumper needed to achieve triple throw ELECTRICAL LIFE 40,000 Cycles DETAILED DESCRIPTION Rocker Switch SP3T 0.4VA (AC/DC) 20V Through Hole CURRENT RATING 0.4VA (AC/DC) COLOR - ACTUATOR/CAP Black CIRCUIT SP3T ACTUATOR TYPE Paddle	MECHANICAL LIFE	-
ILLUMINATION VOLTAGE (NOMINAL) ILLUMINATION TYPE, COLOR FEATURES FEATURES Jumper needed to achieve triple throw ELECTRICAL LIFE 40,000 Cycles DETAILED DESCRIPTION Rocker Switch SP3T 0.4VA (AC/DC) 20V Through Hole CURRENT RATING 0.4VA (AC/DC) COLOR - ACTUATOR/CAP Black CIRCUIT SP3T ACTUATOR TYPE Paddle	MANUFACTURER STANDARD LEAD TIME	11 Weeks
ILLUMINATION VOLTAGE (NOMINAL) ILLUMINATION TYPE, COLOR FEATURES Jumper needed to achieve triple throw ELECTRICAL LIFE 40,000 Cycles DETAILED DESCRIPTION Rocker Switch SP3T 0.4VA (AC/DC) 20V Through Hole CURRENT RATING 0.4VA (AC/DC) COLOR - ACTUATOR/CAP Black CIRCUIT SP3T ACTUATOR TYPE Paddle	LEAD FREE STATUS / ROHS STATUS	Lead free / RoHS Compliant
FEATURES Jumper needed to achieve triple throw ELECTRICAL LIFE 40,000 Cycles DETAILED DESCRIPTION Rocker Switch SP3T 0.4VA (AC/DC) 20V Through Hole CURRENT RATING 0.4VA (AC/DC) COLOR - ACTUATOR/CAP Black CIRCUIT SP3T ACTUATOR TYPE Paddle	INGRESS PROTECTION	-
FEATURES Jumper needed to achieve triple throw ELECTRICAL LIFE 40,000 Cycles DETAILED DESCRIPTION Rocker Switch SP3T 0.4VA (AC/DC) 20V Through Hole CURRENT RATING 0.4VA (AC/DC) COLOR - ACTUATOR/CAP Black CIRCUIT SP3T ACTUATOR TYPE Paddle	ILLUMINATION VOLTAGE (NOMINAL)	-
ELECTRICAL LIFE 40,000 Cycles DETAILED DESCRIPTION Rocker Switch SP3T 0.4VA (AC/DC) 20V Through Hole CURRENT RATING 0.4VA (AC/DC) COLOR - ACTUATOR/CAP Black CIRCUIT SP3T ACTUATOR TYPE Paddle	ILLUMINATION TYPE, COLOR	-
DETAILED DESCRIPTION Rocker Switch SP3T 0.4VA (AC/DC) 20V Through Hole CURRENT RATING 0.4VA (AC/DC) COLOR - ACTUATOR/CAP Black CIRCUIT SP3T ACTUATOR TYPE Paddle	FEATURES	Jumper needed to achieve triple throw
CURRENT RATING 0.4VA (AC/DC) COLOR - ACTUATOR/CAP Black CIRCUIT SP3T ACTUATOR TYPE Paddle	ELECTRICAL LIFE	40,000 Cycles
COLOR - ACTUATOR/CAP CIRCUIT SP3T ACTUATOR TYPE Paddle	DETAILED DESCRIPTION	Rocker Switch SP3T 0.4VA (AC/DC) 20V Through Hole
CIRCUIT SP3T ACTUATOR TYPE Paddle	CURRENT RATING	0.4VA (AC/DC)
ACTUATOR TYPE Paddle	COLOR - ACTUATOR/CAP	Black
	CIRCUIT	SP3T
ACTUATOR MARKING No Marking	ACTUATOR TYPE	Paddle
	ACTUATOR MARKING	No Marking

Related Tags

C&K 7211J2V4BE2	7211J2V4BE2 Distributor	7211J2V4BE2 Supplier
7211J2V4BE2 Price	7211J2V4BE2 Pictures	7211J2V4BE2 Image
7211J2V4BE2 PDF Datasheet	7211J2V4BE2 Download Datasheet	7211J2V4BE2 Datasheet
7211J2V4BE2 Stock	Buy 7211J2V4BE2	Buy C&K 7211J2V4BE2
C&K 7211J2V4BE2	C&K Supplier	C&K Distributor
C&K 7211J2V4BE2	C&K Components 7211J2V4BE2	

Related Products



7211J2CQE2

Manufacturers: C&K

Description: SWITCH ROCKER SP3T 5A 120V In stock: Out stock

RFQ

7211J2V3BE2 Manufacturers: C&K

Description: SWITCH ROCKER SP3T 0.4VA 20V In stock: Out stock

RFQ



7211J2V6QE2

Manufacturers: C&K

Description: SWITCH ROCKER SP3T 5A 120V In stock: Out stock

RFQ



7211J2V3QE2 Manufacturers: C&K

Description: SWITCH ROCKER SP3T 5A 120V In stock: Out stock

RFQ



7211J2V6BE2 Manufacturers: C&K

Description: SWITCH ROCKER SP3T 0.4VA 20V In stock: Out stock

RFQ



7211J2V5BE1 Manufacturers: C&K

Description: SWITCH ROCKER SP3T 0.4VA 20V In stock: Out stock

RFQ



Manufacturers: C&K

Description: SWITCH ROCKER SP3T 0.4VA 20V In stock: Out stock

RFQ



Manufacturers: C&K Description: SWITCH ROCKER SP3T 0.4VA 20V

In stock: Out stock

RFQ



Manufacturers: C&K

7211J2WBE2

Description: SWITCH ROCKER SP3T 0.4VA 20V In stock: Out stock

RFQ



Manufacturers: C&K Description: SWITCH ROCKER SP3T 5A 120V

7211J2V6QE3

In stock: Out stock

RFQ





Manufacturers: C&K Description: SWITCH ROCKER SP3T 5A 120V

7211J2CGE2

In stock: Out stock

RFQ





Description: SWITCH ROCKER SP3T 5A 120V In stock: Out stock

RFQ













Copyright © 2020 Reliable Distributor of Electronic Components - Ocean-Components.com