

Omron Automation & Safety

MY4Z-02-DC24

Part Number:

Manufacturer/Brand:

Product description

Datasheets: RoHs Status

Ship From Shipment Way MY4Z-02-DC24

Omron Automation & Safety

RELAY GEN PURPOSE 4PDT 3A 24V

MY4Z-02-DC24.pdf Lead free / RoHS Compliant

Hong Kong DHL/Fedex/TNT/UPS/EMS

REQUEST FOR QUOTATION

Image may be representation. See specifications for product details.

MANUFACTURER DESCRIPTION RELAY GEN PURPOSE 4PDT 3A 24V LEAD FREE STATUS / ROHS STATUS LEAD FREE STATUS / ROHS STATUS LEAD FREE STATUS / ROHS STATUS DATA SHEET 10 MY4Z-02-DCJ4.pdf 10 NO VOLTAGE (MIN) 2.4 VDC TERMINATION STYLE PC Pin SWITCHING VOLTAGE (MIN) 2.5 VDC. TERMINATION STYLE PC Pin SWITCHING VOLTAGE (MIN) 2.6 VDR RELEASE TIME 2.0 MY RELEASE TIME 2.0 MS RELEASE TIME 2.0 MS RELEAV TYPE PACKAGING MY4Z-02-DCZ4-ND		
MANUFACTURER DESCRIPTION RELAY GEN PURPOSE 4PDT 3A 24V LEAD FREE STATUS / ROHS STATUS LEAD FREE STATUS / ROHS STATUS LEAD FREE STATUS / ROHS STATUS DATA SHEET 10 MY4Z-02-DCJ4.pdf 10 NO VOLTAGE (MIN) 2.4 VDC TERMINATION STYLE PC Pin SWITCHING VOLTAGE (MIN) 2.5 VDC. TERMINATION STYLE PC Pin SWITCHING VOLTAGE (MIN) 2.6 VDR RELEASE TIME 2.0 MY RELEASE TIME 2.0 MS RELEASE TIME 2.0 MS RELEAV TYPE PACKAGING MY4Z-02-DCZ4-ND		Specifications of MY4Z-02-DC24
MANUFACTURER DESCRIPTION RELAY GEN PURPOSE 4PDT 3A 24V LEAD FREE STATUS / ROHS STATUS LEAD FREE STATUS / ROHS STATUS LEAD FREE STATUS / ROHS STATUS DATA SHEET 10 MY4Z-02-DCJ4.pdf 10 NO VOLTAGE (MIN) 2.4 VDC TERMINATION STYLE PC Pin SWITCHING VOLTAGE (MIN) 2.5 VDC. TERMINATION STYLE PC Pin SWITCHING VOLTAGE (MIN) 2.6 VDR RELEASE TIME 2.0 MY RELEASE TIME 2.0 MS RELEASE TIME 2.0 MS RELEAV TYPE PACKAGING MY4Z-02-DCZ4-ND		
DESCRIPTION LEAD FREE STATUS / ROHS STATUS DATA SHEET TURN ON VOLTAGE (MAX) 19.2 VDC 1URN OFF VOLTAGE (MIN) 2.4 VDC TERMINATION STYLE PC PIN SWITCHING VOLTAGE (MIN) 2.5 VDC TERMINATION STYLE PC PIN SWITCHING VOLTAGE MY RELEASE TIME 20ms RELAY EMPROSE BUIK RELAY TYPE General Purpose BUIK AVEZ-02-DC24-NID MY4Z-02-DC24-NID M	PART NUMBER	MY4Z-02-DC24
Lead free / RoHS Compliant DATA SHEET TURN ON VOLTAGE (MAX) 19,2 VDC TURN ON FOULTAGE (MIN) 2,4 VDC TURN OF FOULTAGE (MIN) 2,4 VDC TURN OF VOLTAGE (MIN) 2,5 VDC 1,4 VDC TURN OF PORTOR TURN OF PO	MANUFACTURER	Omron Automation & Safety
DATA SHEET TURN ON VOLTAGE (MAX) 19.2 VDC TURN OF VOLTAGE (MIN) 2.4 VDC TERMINATION STYLE PC PIN SWITCHING VOLTAGE (MIN) 250VAC, 125VDC - Max SERIES MY RELEASE TIME 20ms RELAY TYPE General Purpose PACKAGING OTHER NAMES OTHER NAMES OTHER NAMES OPERATING TEMPERATURE 20ms MY42-02-DC24-ND MY42-02-DC2	DESCRIPTION	RELAY GEN PURPOSE 4PDT 3A 24V
TURN ON VOLTAGE (MAX) 19.2 VDC TURN OFF VOLTAGE (MIN) 2.4 VDC TERNINATION STYLE PC PIN SWITCHING VOLTAGE SWITCHING VOLTAGE SERIES MY RELEASE TIME 20ms RELAY TYPE General Purpose PACKAGING WHY42-02-DC24-ND MY42-02-DC24-ND MY42-0	LEAD FREE STATUS / ROHS STATUS	Lead free / RoHS Compliant
TURN OFF VOLTAGE (MIN) 2.4 VDC TERMINATION STYLE PC PIN SWITCHING VOLTAGE SERIES MY RELEASE TIME 20ms RELAY TYPE BOHER NAMES COTHER NAMES COPERATING TEMPERATURE COPERATE TIME MOUNTING TYPE MOUNTING SENSITIVITY LEVEL (MSL) MANUFACTURER STANDARD LEAD TIME 5 Weeks LEAD FREE STATUS / ROHS STATUS LEAD FREE STATUS / ROHS STATUS DETAILED DESCRIPTION General Purpose Relay 4PDT (4 Form C) 24VDC Coll Through Hole CONTACT RATING (CURRENT) AA CONTACT RATING (CURRENT) AB CONTACT FORM CONTACT FORM 4PDT (4 Form C) COLL VOLTAGE COLL VOLTAGE COLL VOLTAGE COLL VOLTAGE COLL VOLTAGE COLL TYPE NON LAEthing COLL TYPE NON LAETHING 650 Ohms	DATA SHEET	MY4Z-02-DC24.pdf
TERMINATION STYLE SWITCHING VOLTAGE SWITCHING VOLTAGE SERIES MY RELEASE TIME RELEASE TIME RELAY TYPE General Purpose PACKAGING BUIK MY4Z-02-DC24-ND MY4Z02-DC24-ND MY4Z02-DC4-ND MY4Z02-DC24-ND MY4Z02-DC24-ND MY4Z02-DC24-ND MY4Z02-DC4-ND MY4	TURN ON VOLTAGE (MAX)	19.2 VDC
SVETCHING VOLTAGE SERIES MY RELEASE TIME COMB RELAY TYPE General Purpose Bulk MY4Z-02-DC24-ND MY4Z02DC24 Z10479 OPERATING TEMPERATURE OPERATE TIME OPERATE TIME OPERATE SENSITIVITY LEVEL (MSL) MANUFACTURER STANDARD LEAD TIME LEAD FREE STATUS / ROHS STATUS DETAILED DESCRIPTION CONTACT RATING (CURRENT) ABOUT A SINCE (SWER (AB) CONTACT RATING (CURRENT) OPERATE FORM OCONTACT FORM APDT (4 Form C) COLL RESISTANCE 650 Ohms COLL RESISTANCE 650 Ohms OMS AMALIANCE SENSITIVES APD (4 FORM) APD (4 Form C) COLL RESISTANCE 650 Ohms	TURN OFF VOLTAGE (MIN)	2.4 VDC
SERIES MY RELASE TIME 20ms RELAY TYPE General Purpose PACKAGING Bulk OTHER NAMES MY42-02-DC24-ND MY4202DC24 Z10479 OPERATING TEMPERATURE -55°C ~ 70°C OPERATE TIME 20ms MOUNTING TYPE Through Hole MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) MANUFACTURER STANDARD LEAD TIME 5 Weeks LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant FEATURES - DETAILED DESCRIPTION General Purpose Relay 4PDT (4 Form C) 24VDC Coil Through Hole CONTACT RATING (CURRENT) 3A CONTACT FORM 4PDT (4 Form C) COIL VOLTAGE 24VDC COIL VOLTAGE 50 Ohms	TERMINATION STYLE	PC Pin
RELAY TYPE General Purpose Bulk OTHER NAMES MY4202-DC24-ND MY4202-DC24 Z10479 OPERATING TEMPERATURE OFFEATURE OFFEATURE OFFEATURE MOUNTING TYPE MOISTURE SENSITIVITY LEVEL (MSL) MANUFACTURER STANDARD LEAD TIME LEAD FREE STATUS / ROHS STATUS LEAD FREE STATUS / ROHS STATUS LEAD FREE STATUS / ROHS STATUS DETAILED DESCRIPTION OCONTACT RATING (CURRENT) CONTACT PARTING (CURRENT) SIVER (Ag) CONTACT FORM OCONTACT FORM OCON	SWITCHING VOLTAGE	250VAC, 125VDC - Max
RELAY TYPE PACKAGING BUMY4Z-02-DC24-ND MY4Z-02-DC24-ND MY4Z0ZDC24 Z10479 OPERATING TEMPERATURE OPERATURE OPERATURE OPERATURE OPERATURE MOUNTING TYPE MOUNTING TYPE MOUNTING TYPE MANUFACTURER STANDARD LEAD TIME S Weeks LEAD FREE STATUS / ROHS STATUS LEAD FREE STATUS / ROHS STATUS DETAILED DESCRIPTION ORIGINATING (CURRENT) AA CONTACT RATING (CURRENT) SIIVEr (Ag) CONTACT FORM ADDIT (4 Form C) COLL VOLTAGE COLL VOLTAGE COLL VOLTAGE COLL VOLTAGE COLL VOLTAGE COLL TYPE NON LEACHING BY492-02-DC24-ND MY42-02-DC24-ND MY42-DC2-DC24-ND MY42-DC2-DC24-ND MY42-DC2-DC24-ND MY42-DC2-DC24-ND MY42-DC2-DC24-ND MY42-DC2-DC24-ND MY42-DC2-D	SERIES	MY
Bulk OTHER NAMES MY4Z-0Z-DCZ4-ND MY4Z0ZDCZ4 Z10479 OPERATING TEMPERATURE -55°C ~ 70°C OPERATE TIME MOUNTING TYPE Through Hole MOISTURE SENSITIVITY LEVEL (MSL) MANUFACTURER STANDARD LEAD TIME LEAD FREE STATUS / ROHS STATUS LEAd free / ROHS Compliant FEATURES DETAILED DESCRIPTION General Purpose Relay 4PDT (4 Form C) 24VDC Coil Through Hole CONTACT RATING (CURRENT) CONTACT MATERIAL CONTACT FORM 4PDT (4 Form C) COIL VOLTAGE COIL YOLTAGE COIL TYPE Non Latching COLSESISTANCE MY4Z-0Z-DCZ4-ND MY4Z-0Z-DCZ4-ND MY4Z-0ZD-CZ24-ND MY4Z0ZD-CZ24-ND MY4Z0ZD-CZ	RELEASE TIME	20ms
OTHER NAMES MY4Z-02-DCZ4-ND MY4Z02DC24 Z10479 OPERATING TEMPERATURE -55°C ~ 70°C OPERATING TYPE Through Hole MOINTING TYPE THROUGH Hole 5 Weeks LEAD FREE STATUS / ROHS STATUS LEAd free / ROHS Compliant FEATURES - DETAILED DESCRIPTION General Purpose Relay 4PDT (4 Form C) 24VDC Coil Through Hole CONTACT RATING (CURRENT) 3A CONTACT MATERIAL CONTACT MATERIAL CONTACT FORM 4PDT (4 Form C) COIL VOLTAGE COIL TYPE NON Latching COIL TYPE NON Latching COIL RESISTANCE	RELAY TYPE	General Purpose
OTHER NAMES MY4220ZC24 Z10479 OPERATING TEMPERATURE -55°C ~ 70°C OPERATE TIME MOUNTING TYPE MOUNTING TYPE MOISTURE SENSITIVITY LEVEL (MSL) MANUFACTURER STANDARD LEAD TIME S Weeks LEAD FREE STATUS / ROHS STATUS LEAd free / ROHS Compliant FEATURES - DETAILED DESCRIPTION General Purpose Relay 4PDT (4 Form C) 24VDC Coil Through Hole CONTACT RATING (CURRENT) CONTACT MATERIAL CONTACT MATERIAL CONTACT FORM 4PDT (4 Form C) COIL YOLTAGE COIL TYPE NON Latching COIL RESISTANCE 650 Ohms	PACKAGING	Bulk
OPERATE TIME 20ms MOUNTING TYPE Through Hole MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) MANUFACTURER STANDARD LEAD TIME 5 Weeks LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant FEATURES - DETAILED DESCRIPTION General Purpose Relay 4PDT (4 Form C) 24VDC Coil Through Hole CONTACT RATING (CURRENT) 3A CONTACT RATING (CURRENT) Silver (Ag) CONTACT FORM 4PDT (4 Form C) COIL VOLTAGE 24VDC COIL TYPE Non Latching COIL RESISTANCE 650 Ohms	OTHER NAMES	MY4Z02DC24
MOUNTING TYPE MOUNTING TYPE MOUNTING TYPE MOUNTING TYPE MANUFACTURER SENSITIVITY LEVEL (MSL) MANUFACTURER STANDARD LEAD TIME 5 Weeks LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant FEATURES DETAILED DESCRIPTION General Purpose Relay 4PDT (4 Form C) 24VDC Coil Through Hole CONTACT RATING (CURRENT) 3A CONTACT MATERIAL Silver (Ag) CONTACT FORM 4PDT (4 Form C) COIL YOLTAGE 24VDC COIL TYPE Non Latching COIL RESISTANCE 650 Ohms	OPERATING TEMPERATURE	-55°C ∼ 70°C
MOISTURE SENSITIVITY LEVEL (MSL) MANUFACTURER STANDARD LEAD TIME 5 Weeks LEAD FREE STATUS / ROHS STATUS LEAD free / ROHS Compliant FEATURES DETAILED DESCRIPTION General Purpose Relay 4PDT (4 Form C) 24VDC Coil Through Hole CONTACT RATING (CURRENT) 3A CONTACT MATERIAL Silver (Ag) CONTACT FORM 4PDT (4 Form C) COIL VOLTAGE 24VDC COIL TYPE Non Latching 650 Ohms	OPERATE TIME	20ms
MANUFACTURER STANDARD LEAD TIME 5 Weeks LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant FEATURES - CONTACT RATING (CURRENT) 3A CONTACT MATERIAL Sliver (Ag) CONTACT FORM 4PDT (4 Form C) COIL VOLTAGE 24VDC COIL TYPE Non Latching COIL RESISTANCE 5 Weeks Lead free / RoHS Compliant Lead free / RoHS Compliant Lead free / RoHS Compliant FEATURES - COHS Compliant APOLIC	MOUNTING TYPE	Through Hole
LEAD FREE STATUS / ROHS STATUS FEATURES - DETAILED DESCRIPTION General Purpose Relay 4PDT (4 Form C) 24VDC Coil Through Hole CONTACT RATING (CURRENT) 3A CONTACT MATERIAL CONTACT FORM 4PDT (4 Form C) COIL VOLTAGE COIL TYPE Non Latching COIL RESISTANCE	MOISTURE SENSITIVITY LEVEL (MSL)	1 (Unlimited)
FEATURES DETAILED DESCRIPTION General Purpose Relay 4PDT (4 Form C) 24VDC Coil Through Hole CONTACT RATING (CURRENT) 3A CONTACT MATERIAL CONTACT FORM 4PDT (4 Form C) COIL VOLTAGE COIL TYPE Non Latching COIL RESISTANCE	MANUFACTURER STANDARD LEAD TIME	5 Weeks
DETAILED DESCRIPTION General Purpose Relay 4PDT (4 Form C) 24VDC Coil Through Hole CONTACT RATING (CURRENT) 3A CONTACT MATERIAL CONTACT FORM 4PDT (4 Form C) COIL VOLTAGE COIL TYPE Non Latching COIL RESISTANCE General Purpose Relay 4PDT (4 Form C) 24VDC Non Latching 650 Ohms	LEAD FREE STATUS / ROHS STATUS	Lead free / RoHS Compliant
CONTACT RATING (CURRENT) Silver (Ag) CONTACT FORM COIL VOLTAGE COIL TYPE COIL RESISTANCE 3A APDT (A Form C) 4PDT (4 Form C) 24VDC Non Latching 650 Ohms	FEATURES	-
CONTACT MATERIAL CONTACT FORM COIL VOLTAGE COIL TYPE COIL RESISTANCE Silver (Ag) APDT (4 Form C) 24VDC 24VDC Non Latching 650 Ohms	DETAILED DESCRIPTION	General Purpose Relay 4PDT (4 Form C) 24VDC Coil Through Hole
CONTACT FORM 4PDT (4 Form C) COIL VOLTAGE 24VDC COIL TYPE Non Latching COIL RESISTANCE 650 Ohms	CONTACT RATING (CURRENT)	3A
COIL VOLTAGE COIL TYPE Non Latching COIL RESISTANCE 650 Ohms	CONTACT MATERIAL	Silver (Ag)
COIL TYPE Non Latching COIL RESISTANCE 650 Ohms	CONTACT FORM	4PDT (4 Form C)
COIL RESISTANCE 650 Ohms	COIL VOLTAGE	24VDC
	COIL TYPE	Non Latching
COIL POWER 900 mW	COIL RESISTANCE	650 Ohms
***************************************	COIL POWER	900 mW

Related Tags

36.9mA

Omron Automation & Safety MY4Z-02-DC24	MY4Z-02-DC24 Distributor	MY4Z-02-DC24 Supplier
MY4Z-02-DC24 Price	MY4Z-02-DC24 Pictures	MY4Z-02-DC24 Image
MY4Z-02-DC24 PDF Datasheet	MY4Z-02-DC24 Download Datasheet	MY4Z-02-DC24 Datasheet
MY4Z-02-DC24 Stock	Buy MY4Z-02-DC24	Buy Omron Automation & Safety MY4Z-02-DC24
Omron Automation & Safety MY4Z-02-DC24	Omron Automation & Safety Supplier	Omron Automation & Safety Distributor
Omron Automation & Safety MY4Z-02-DC24	Omron Automation and Safety MY4Z-02-DC24	

Related Products



COIL CURRENT

MY4Z-02-DC100/110

Manufacturers: Omron Automation & Safety Description: RELAY GEN PUR 100/110VDC PCB

In stock: Out stock

RFQ



MY4Z-D DC12

Manufacturers: Omron Automation & Safety Description: RELAY GEN PUR 4PDT 12VDC W/DIO

In stock: Out stock

RFQ



MY4Z-02-DC12

Manufacturers: Omron Automation & Safety Description: RELAY GEN PUR 4PDT 12VDC PCB

In stock: Out stock

RFQ



MY4Z-D DC100/110 Manufacturers: Omron Automation & Safety

Description: RELAY GP 4PDT 100/110VDC W/DIO In stock: Out stock

RFQ



MY4Z-AC110/120-EL

Description: RELAY GEN PURPOSE 4PDT 3A 120V In stock: Out stock

Manufacturers: Omron Automation & Safety

RFQ



MY4Z-02-AC100/110 Manufacturers: Omron Automation & Safety

Description: RELAY GEN PUR 100/110VAC PCB In stock: Out stock

RFQ



MY4Z-AC110/120 Manufacturers: Omron Automation & Safety

Description: RELAY GEN PURPOSE 4PDT 3A 120V In stock: 19 pcs

RFQ



MY4Z-CBG AC100/110 Manufacturers: Omron Automation & Safety

Description: RELAY 4PDT 110V In stock: 7 pcs

RFQ



MY4Z DC48 (S)

Description: RELAY GEN PURPOSE 4PDT 3A 48V In stock: Out stock

Manufacturers: Omron Automation & Safety

RFQ



Manufacturers: Omron Automation & Safety Description: RELAY GEN PUR 200/220VAC PCB

MY4Z-02-AC200/220

In stock: Out stock **RFQ**



E-mail: Info@Ocean-Components.com


Manufacturers: Omron Automation & Safety Description: RELAY GENERAL PURPOSE 4PDT 3A 6V

MY4Z DC6 (S)

In stock: Out stock

RFQ





MY4Z-02-DC48

Description: RELAY GEN PURPOSE 4PDT 3A 48V In stock: Out stock

RFQ













