



C&K

## 7103P3H3CBE22

Part Number:

Manufacturer/Brand:

Product description Datasheets:

RoHs Status Ship From Shipment Way 7103P3H3CBE22

C&K

SWITCH TOGGLE SPDT 0.4VA 20V

7103P3H3CBE22.pdf

Lead free / RoHS Compliant

Hong Kong DHL/Fedex/TNT/UPS/EMS



**REQUEST FOR QUOTATION** 

Image may be representation. See specifications for product details.

Specifications of 7103P3H3CBE22  PART NUMBER 7103P3H3CBE22  MANUFACTURER C&K DESCRIPTION SWITCH TOGGLE SPOT 0.4WA 20V  LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compilant  DATA SHEET  VOLTAGE RATING - DC 20V  VOLTAGE RATING - AC 20V  TERMINATION STYLE PC PR SWITCH FUNCTION On-OFF-On  SERIES 7000 PANEL CUTOUT DIMENSIONS Circular - 6.35mm Dia  PACKAGING Bulk OPERATING TEMPERATURE -30°C ~ 85°C  MOUNTING TYPE Panel Mount MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) MANUFACTURER STANDARD LEAD TIME 11 Weeks LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compilant  INGRESS PROTECTION - ILLUMINATION YOLTAGE (NOMINAL) - ILLUMINATION TYPE, COLOR - ILLUMINATION TYPE, COLOR - ILLUMINATION TYPE, COLOR - ILLUMINATION ON-TIME HOLD SWITCH SPOT Penel Mount CURRENT RATING 0.4WA (AC/DC) CIRCUIT BUSHING THREAD 1/4-40 ACTUATOR TYPE Flat Anti-Rotation			
MANUFACTURER  DESCRIPTION  SWITCH TOGGLE SPOT 0.4VA 20V  LEAD FREE STATUS / ROHS STATUS  LEAD free / ROHS Compilant  DATA SHEET  □ 7103P3H3CBE22.pdf  VOLTAGE RATING - DC  20V  VOLTAGE RATING - AC  TERMINATION STYLE  PC PIN  SWITCH FUNCTION  On-Off-On  SERIES  7000  PANEL CUTOUT DIMENSIONS  Circular - 6.35mm Dia  Bulk  OPERATING TEMPERATURE  A30°C ~ 85°C  MOUNTING TYPE  Panel Mount  MOISTURE SENSITIVITY LEVEL (MSL)  I (Unlimited)  MANUFACTURER STATUS / ROHS STATUS  LEAD FREE STATUS / ROHS STATUS  LEAD FREE STATUS / ROHS STATUS  LEAD free / ROHS Compilant  INGRESS PROTECTION  -  ILLUMINATION VOLTAGE (NOMINAL)  TELLUMINATION  Non-Illuminated  EFEATURES  Black Actuator  ELECTRICAL LIFE  40,000 Cycles  DETAILED DESCRIPTION  TOGGLE SPOT  CURRENT RATING  0.4VA (AC/DC)  CIRCUIT  SPDT  BUSHING THREAD  1/4-40		Specifications of 7103P3H3CBE22	
MANUFACTURER  DESCRIPTION  SWITCH TOGGLE SPDT 0.4WA 20V  LEAD FREE STATUS / ROHS STATUS  LEAD free FROMS Compilant  DATA SHEET  1 10393H3CBE22.pdf  VOLTAGE RATING - DC  VOLTAGE RATING - AC  20V  TERMINATION STYLE  PC PIN  SWITCH FUNCTION  On-Off-On  SERIES  7000  PANEL CUTOUT DIMENSIONS  Circular - 6.35mm Dia  Bulk  OPERATING TEMPERATURE  A30°C ~ 85°C  MOUNTING TYPE  PANEL MOUNTING  PANEL MOUNTI			
DESCRIPTION SWITCH TOGGLE SPDT 0.4VA 20V  LEAD FREE STATUS / ROHS STATUS  Lead free / ROHS Compliant  DATA SHEET  TOTO 10393H3CBE22.pdf  VOLTAGE RATING - DC  20V  VOLTAGE RATING - AC  20V  TERMINATION STYLE  PC PIN  SWITCH FUNCTION  On-Off-On  SERIES  7000  PANEL CUTOUT DIMENSIONS  Circular - 6.35mm Dia  Bulk  OPERATING TEMPERATURE  -30°C ~ 85°C  MOUNTING TYPE  PANEL MOUNTING TYPE  PANEL MOUNTING TYPE  NOISTURE SENSITIVITY LEVEL (MSL)  1 (Unlimited)  MANUFACTURER STANDARD LEAD TIME  11 Weeks  LEAD FREE STATUS / ROHS STATUS  Lead free / ROHS Compliant  ILLUMINATION VOLTAGE (NOMINAL)  -  ILLUMINATION TYPE, COLOR  ILLUMINATION  Non-Illuminated  FEATURES  Black Actuator  ELECTRICAL LIFE  40,000 Cycles  DETAILED DESCRIPTION  TOGGle Switch SPDT Panel Mount  CURRENT RATING  0.4VA (AC/DC)  CIRCUIT  SPDT  BUSHING THREAD	PART NUMBER	7103P3H3CBE22	
LEAD FREE STATUS / ROHS STATUS  LEAd free / RoHS Compliant  DATA SHEET  VOLTAGE RATING - DC  VOLTAGE RATING - AC  ZOV  TERMINATION STYLE  PC Pin  SWITCH FUNCTION  On-Off-On  SERIES  7000  PANEL CUTOUT DIMENSIONS  Circular - 6.35mm Dia  PACKAGING  DERATING TYPE  MOUNTING TYPE  MOUNTING TYPE  MOUNTING TYPE  MOUNTING TYPE  MANUFACTURER STATUS / ROHS STATUS  LEAD FREE STATUS / ROHS STATUS  LEAD FREE STATUS / ROHS STATUS  LEAD FREE STATUS / ROHS STATUS  LLUMINATION VOLTAGE (NOMINAL)  ILLUMINATION VOLTAGE (NOMINAL)  FEATURES  Black Actuator  LLUMINATION  FEATURES  Black Actuator  ELECTRICAL LIFE  40,000 Cycles  DETAILED DESCRIPTION  Toggle Switch SPDT Panel Mount  CURRENT RATING  0.4VA (AC/DC)  CIRCUIT  SPDT  BUSHING THREAD	MANUFACTURER	C&K	
DATA SHEET  VOLTAGE RATING - DC  20V  VOLTAGE RATING - AC  20V  TERMINATION STYLE  PC PIN  SWITCH FUNCTION  On-Off-On  SERIES  7000  PANEL CUTOUT DIMENSIONS  Circular - 6.35mm Dia  PACKAGING  DPERATING TEMPERATURE  -30°C ~ 85°C  MOUNTING TYPE  Panel Mount  MOISTURE SENSITIVITY LEVEL (MSL)  MANUFACTURER STANDARD LEAD TIME  LEAD FREE STATUS / ROHS STATUS  LILUMINATION VOLTAGE (NOMINAL)  ILLUMINATION TYPE, COLOR  PETURES  Black Actuator  ELECTRICAL LIFE  40,000 Cycles  DETAILED DESCRIPTION  Toggle Switch SPDT Panel Mount  CURRENT RATING  0.4VA (AC/DC)  CIRCUIT  SPDT  BUSHING THREAD	DESCRIPTION	SWITCH TOGGLE SPDT 0.4VA 20V	
VOLTAGE RATING - DC     20V       VOLTAGE RATING - AC     20V       TERMINATION STYLE     PC PIN       SWITCH FUNCTION     On-Off-On       SERIES     7000       PANEL CUTOUT DIMENSIONS     Circular - 6.35mm Dia       PACKAGING     Bulk       OPERATING TEMPERATURE     -30°C ~ 85°C       MOUNTING TYPE     Panel Mount       MOISTURE SENSITIVITY LEVEL (MSL)     1 (Unlimited)       MANUFACTURER STANDARD LEAD TIME     11 Weeks       LEAD FREE STATUS / ROHS STATUS     Lead free / ROHS Compliant       INGRESS PROTECTION     -       ILLUMINATION VOLTAGE (NOMINAL)     -       ILLUMINATION TYPE, COLOR     -       ILLUMINATION     Non-Illuminated       FEATURES     Black Actuator       ELECTRICAL LIFE     40,000 Cycles       DETAILED DESCRIPTION     Toggle Switch SPDT Panel Mount       CURENT RATING     0.4VA (AC/DC)       CIRCUIT     SPDT       BUSHING THREAD     1/4-40	LEAD FREE STATUS / ROHS STATUS	Lead free / RoHS Compliant	
VOLTAGE RATING - AC       20V         TERMINATION STYLE       PC Pin         SWITCH FUNCTION       On-Off-On         SERIES       7000         PANEL CUTOUT DIMENSIONS       Circular - 6.35mm Dia         PACKAGING       Bulk         OPERATING TEMPERATURE       -30°C ~ 85°C         MOUNTING TYPE       Panel Mount         MOISTURE SENSITIVITY LEVEL (MSL)       1 (Unlimited)         MANUFACTURER STANDARD LEAD TIME       11 Weeks         LEAD FREE STATUS / ROHS STATUS       Lead free / RoHS Compliant         INGRESS PROTECTION       -         ILLUMINATION VOLTAGE (NOMINAL)       -         ILLUMINATION TYPE, COLOR       -         ILLUMINATION TYPE, COLOR       -         ILLUMINATION       Non-Illuminated         Black Actuator       ELECTRICAL LIFE       40,000 Cycles         DETAILED DESCRIPTION       Toggle Switch SPDT Panel Mount       CURRENT RATING       0.4VA (AC/DC)         CIRCUIT       SPDT         BUSHING THREAD       1/4-40	DATA SHEET	7103P3H3CBE22.pdf	
TERMINATION STYLE  SWITCH FUNCTION  On-Off-On  SERIES  7000  PANEL CUTOUT DIMENSIONS  Circular - 6.35mm Dia  PACKAGING  OPERATING TEMPERATURE  -30°C ~ 85°C  MOUNTING TYPE  Panel Mount  MOISTURE SENSITIVITY LEVEL (MSL)  MANUFACTURER STANDARD LEAD TIME  LEAD FREE STATUS / ROHS STATUS  LEAD FREE STATUS / ROHS STATUS  LLUMINATION VOLTAGE (NOMINAL)  ILLUMINATION TYPE, COLOR  ILLUMINATION  PEATURES  Black Actuator  ELECTRICAL LIFE  40,000 Cycles  DETAILED DESCRIPTION  CURRENT RATING  0.4VA (AC/DC)  CIRCUIT  SPDT  BUSHING THREAD	VOLTAGE RATING - DC	20V	
SWITCH FUNCTION On-Off-On  SERIES 7000  PANEL CUTOUT DIMENSIONS CIrcular - 6.35mm Dia  PACKAGING Bulk OPERATING TEMPERATURE -30°C ~ 85°C  MOUNTING TYPE Panel Mount  MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited)  MANUFACTURER STANDARD LEAD TIME 11 Weeks  LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant  INGRESS PROTECTION -  ILLUMINATION VOLTAGE (NOMINAL) -  ILLUMINATION TYPE, COLOR -  ILLUMINATION Non-Illuminated  FEATURES Black Actuator  ELECTRICAL LIFE 40,000 Cycles  DETAILED DESCRIPTION TOggle Switch SPDT Panel Mount  CURRENT RATING 0.4VA (AC/DC)  CIRCUIT SPDT  BUSHING THREAD 1/4-40	VOLTAGE RATING - AC	20V	
SERIES 7000  PANEL CUTOUT DIMENSIONS Circular - 6.35mm Dia  PACKAGING Bulk  OPERATING TEMPERATURE -30°C ~ 85°C  MOUNTING TYPE Panel Mount  MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited)  MANUFACTURER STANDARD LEAD TIME 11 Weeks  LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant  INGRESS PROTECTION -  ILLUMINATION VOLTAGE (NOMINAL) -  ILLUMINATION TYPE, COLOR -  ILLUMINATION Non-Illuminated  FEATURES Black Actuator  ELECTRICAL LIFE 40,000 Cycles  DETAILED DESCRIPTION TORGIE SWitch SPDT Panel Mount  CURRENT RATING 0.4VA (AC/DC)  CIRCUIT SPDT  BUSHING THREAD 1/4-40	TERMINATION STYLE	PC Pin	
PACKAGING Bulk  OPERATING TEMPERATURE -30°C ~ 85°C  MOUNTING TYPE Panel Mount  MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited)  MANUFACTURER STANDARD LEAD TIME 11 Weeks  LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant  INGRESS PROTECTION -  ILLUMINATION VOLTAGE (NOMINAL) -  ILLUMINATION TYPE, COLOR -  ILLUMINATION Non-Illuminated  FEATURES Black Actuator  ELECTRICAL LIFE 40,000 Cycles  DETAILED DESCRIPTION TOggle Switch SPDT Panel Mount  CURRENT RATING 0.4VA (AC/DC)  CIRCUIT SPDT  BUSHING THREAD 1/4-40	SWITCH FUNCTION	On-Off-On	
PACKAGING  OPERATING TEMPERATURE  -30°C ~ 85°C  MOUNTING TYPE  Panel Mount  MOISTURE SENSITIVITY LEVEL (MSL)  I (Unlimited)  MANUFACTURER STANDARD LEAD TIME  11 Weeks  LEAD FREE STATUS / ROHS STATUS  Lead free / ROHS Compliant  INGRESS PROTECTION  - ILLUMINATION VOLTAGE (NOMINAL)  - ILLUMINATION TYPE, COLOR  - ILLUMINATION  Non-Illuminated  FEATURES  Black Actuator  ELECTRICAL LIFE  40,000 Cycles  DETAILED DESCRIPTION  Toggle Switch SPDT Panel Mount  CURRENT RATING  0.4VA (AC/DC)  CIRCUIT  SPDT  BUSHING THREAD	SERIES	7000	
OPERATING TEMPERATURE -30°C ~ 85°C  MOUNTING TYPE Panel Mount  MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited)  MANUFACTURER STANDARD LEAD TIME 11 Weeks  LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant  INGRESS PROTECTION - ILLUMINATION VOLTAGE (NOMINAL) - ILLUMINATION TYPE, COLOR - ILLUMINATION Non-Illuminated  FEATURES Black Actuator  ELECTRICAL LIFE 40,000 Cycles  DETAILED DESCRIPTION Toggle Switch SPDT Panel Mount  CURRENT RATING 0.4VA (AC/DC)  CIRCUIT SPDT  BUSHING THREAD 1/4-40	PANEL CUTOUT DIMENSIONS	Circular - 6.35mm Dia	
MOUNTING TYPE  MOISTURE SENSITIVITY LEVEL (MSL)  I (Unlimited)  MANUFACTURER STANDARD LEAD TIME  11 Weeks  LEAD FREE STATUS / ROHS STATUS  LEAd free / ROHS Compliant  INGRESS PROTECTION  - ILLUMINATION VOLTAGE (NOMINAL)  ILLUMINATION TYPE, COLOR  ILLUMINATION  Non-Illuminated  FEATURES  Black Actuator  ELECTRICAL LIFE  40,000 Cycles  DETAILED DESCRIPTION  Toggle Switch SPDT Panel Mount  CURRENT RATING  0.4VA (AC/DC)  CIRCUIT  SPDT  BUSHING THREAD	PACKAGING	Bulk	
MOISTURE SENSITIVITY LEVEL (MSL)  MANUFACTURER STANDARD LEAD TIME  11 Weeks  LEAD FREE STATUS / ROHS STATUS  LEAd free / ROHS Compliant  INGRESS PROTECTION  ILLUMINATION VOLTAGE (NOMINAL)  ILLUMINATION TYPE, COLOR  ILLUMINATION  Non-Illuminated  FEATURES  Black Actuator  ELECTRICAL LIFE  40,000 Cycles  DETAILED DESCRIPTION  Toggle Switch SPDT Panel Mount  CURRENT RATING  0.4VA (AC/DC)  CIRCUIT  SPDT  BUSHING THREAD	OPERATING TEMPERATURE	-30°C ~ 85°C	
MANUFACTURER STANDARD LEAD TIME 11 Weeks  LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant  INGRESS PROTECTION -  ILLUMINATION VOLTAGE (NOMINAL) -  ILLUMINATION TYPE, COLOR -  ILLUMINATION TYPE, COLOR Non-Illuminated  FEATURES Black Actuator  ELECTRICAL LIFE 40,000 Cycles  DETAILED DESCRIPTION TOGGLE SWitch SPDT Panel Mount  CURRENT RATING 0.4VA (AC/DC)  CIRCUIT SPDT  BUSHING THREAD 1/4-40	MOUNTING TYPE	Panel Mount	
LEAD FREE STATUS / ROHS STATUSLead free / RoHS CompliantINGRESS PROTECTION-ILLUMINATION VOLTAGE (NOMINAL)-ILLUMINATION TYPE, COLOR-ILLUMINATIONNon-IlluminatedFEATURESBlack ActuatorELECTRICAL LIFE40,000 CyclesDETAILED DESCRIPTIONToggle Switch SPDT Panel MountCURRENT RATING0.4VA (AC/DC)CIRCUITSPDTBUSHING THREAD1/4-40	MOISTURE SENSITIVITY LEVEL (MSL)	1 (Unlimited)	
ILLUMINATION VOLTAGE (NOMINAL)  ILLUMINATION TYPE, COLOR  ILLUMINATION  Non-Illuminated  FEATURES  ELECTRICAL LIFE  DETAILED DESCRIPTION  CURRENT RATING  CURCUIT  SPDT  BUSHING THREAD	MANUFACTURER STANDARD LEAD TIME	11 Weeks	
ILLUMINATION VOLTAGE (NOMINAL)-ILLUMINATION TYPE, COLOR-ILLUMINATIONNon-IlluminatedFEATURESBlack ActuatorELECTRICAL LIFE40,000 CyclesDETAILED DESCRIPTIONToggle Switch SPDT Panel MountCURRENT RATING0.4VA (AC/DC)CIRCUITSPDTBUSHING THREAD1/4-40	LEAD FREE STATUS / ROHS STATUS	Lead free / RoHS Compliant	
ILLUMINATION TYPE, COLOR-ILLUMINATIONNon-IlluminatedFEATURESBlack ActuatorELECTRICAL LIFE40,000 CyclesDETAILED DESCRIPTIONToggle Switch SPDT Panel MountCURRENT RATING0.4VA (AC/DC)CIRCUITSPDTBUSHING THREAD1/4-40	INGRESS PROTECTION	-	
ILLUMINATIONNon-IlluminatedFEATURESBlack ActuatorELECTRICAL LIFE40,000 CyclesDETAILED DESCRIPTIONToggle Switch SPDT Panel MountCURRENT RATING0.4VA (AC/DC)CIRCUITSPDTBUSHING THREAD1/4-40	ILLUMINATION VOLTAGE (NOMINAL)	-	
FEATURESBlack ActuatorELECTRICAL LIFE40,000 CyclesDETAILED DESCRIPTIONToggle Switch SPDT Panel MountCURRENT RATING0.4VA (AC/DC)CIRCUITSPDTBUSHING THREAD1/4-40	ILLUMINATION TYPE, COLOR	-	
ELECTRICAL LIFE 40,000 Cycles  DETAILED DESCRIPTION Toggle Switch SPDT Panel Mount  CURRENT RATING 0.4VA (AC/DC)  CIRCUIT SPDT  BUSHING THREAD 1/4-40	ILLUMINATION	Non-Illuminated	
DETAILED DESCRIPTION  CURRENT RATING  CIRCUIT  BUSHING THREAD  Toggle Switch SPDT Panel Mount  0.4VA (AC/DC)  SPDT  1/4-40	FEATURES	Black Actuator	
CURRENT RATING 0.4VA (AC/DC)  CIRCUIT SPDT  BUSHING THREAD 1/4-40	ELECTRICAL LIFE	40,000 Cycles	
CIRCUIT SPDT BUSHING THREAD 1/4-40	DETAILED DESCRIPTION	Toggle Switch SPDT Panel Mount	
BUSHING THREAD 1/4-40	CURRENT RATING	0.4VA (AC/DC)	
	CIRCUIT	SPDT	
ACTUATOR TYPE Flat Anti-Rotation	BUSHING THREAD	1/4-40	
	ACTUATOR TYPE	Flat Anti-Rotation	
ACTUATOR MATERIAL Brass	ACTUATOR MATERIAL	Brass	
ACTUATOR LENGTH 10.92mm	ACTUATOR LENGTH	10.92mm	

# **Related Tags**

C&K 7103P3H3CBE22	7103P3H3CBE22 Distributor	7103P3H3CBE22 Supplier
7103P3H3CBE22 Price	7103P3H3CBE22 Pictures	7103P3H3CBE22 Image
7103P3H3CBE22 PDF Datasheet	7103P3H3CBE22 Download Datasheet	7103P3H3CBE22 Datasheet
7103P3H3CBE22 Stock	Buy 7103P3H3CBE22	Buy C&K 7103P3H3CBE22
C&K 7103P3H3CBE22	C&K Supplier	C&K Distributor
C&K 7103P3H3CBE22	C&K Components 7103P3H3CBE22	

# **Related Products**



### 7103P3H3ZQE2 Manufacturers: C&K

Description: SWITCH TOGGLE SPDT 5A 120V In stock: Out stock

**RFQ** 

## 7103P3HV2QE Manufacturers: C&K

Description: SWITCH TOGGLE SPDT 5A 120V

In stock: Out stock

**RFQ** 

# **7103P3DZQES**

Manufacturers: C&K

Description: SWITCH TOGGLE SPDT 5A 120V In stock: Out stock

**RFQ** 



# **7103P3HCGE2**

Manufacturers: C&K Description: SWITCH TOGGLE SPDT 5A 120V

In stock: Out stock

**RFQ** 



# **7103P3DZQE2**

Manufacturers: C&K

Description: SWITCH TOGGLE SPDT 5A 120V In stock: Out stock

**RFQ** 

## 7103P3H3CQE

Manufacturers: C&K Description: SWITCH TOGGLE SPDT 5A 120V

In stock: Out stock

**RFQ** 



#### 7103P3H3CBE2 Manufacturers: C&K

Description: SWITCH TOGGLE SPDT 0.4VA 20V In stock: Out stock

**RFQ** 



#### **7103P3H3AV2BE** Manufacturers: C&K

Description: SWITCH TOGGLE SPDT 0.4VA 20V

In stock: Out stock

**RFQ** 



## **7103P3H3ZGES** Manufacturers: C&K

Description: SWITCH TOGGLE SPDT 5A 120V In stock: Out stock

**RFQ** 



### **7103P3H3AV2QE** Manufacturers: C&K

Description: SWITCH TOGGLE SPDT 5A 120V In stock: Out stock

**RFQ** 



### **7103P3HCQE** Manufacturers: C&K

Description: SWITCH TOGGLE SPDT 5A 120V

In stock: Out stock **RFQ** 



## **7103P3H3A2BE**

Manufacturers: C&K

Description: SWITCH TOGGLE SPDT 0.4VA 20V In stock: Out stock

**RFQ** 



Address: Room 2102, Connaught Commercial Building, 185 Wan Chai Rd, Wan Chai, Hong Kong











