



Image may be representation. See specifications for product details.

A1SAV1

Part Number:

Manufacturer/Brand:

Product description Datasheets:

Ship From Shipment Way

RoHs Status

A1SAV1

NKK Switches

SWITCH TOGGLE SPDT 0.4VA 28V

Lead free / RoHS Compliant

A1SAV1.pdf

Hong Kong DHL/Fedex/TNT/UPS/EMS

REQUEST FOR QUOTATION

Specifications of A1SAV1

ASAVI MANUFACTURER MKK Switches DESCRIPTION SWITCH TOGGLE SPDT 0.4WA 28V LEAD REEE STATUS / ROHS STATUS ALSAVI.pdf VOLTAGE RATTING - DC 28V VOLTAGE RATTING - AC 28V VOLTAGE RATTING - AC TERMINATION STYLE PC PI SWITCH FUNCTION On-Off-Morn SERIES A APAMEL CUTOUT DIMENSIONS - ACAGGING Bulk POPERATTING TEMPERATURE MOUNTING TYPE MOUNTING TYPE MOUNTING TYPE MOUNTING TYPE MOUNTING SERISTITYITY LEVEL (MSL) 1 (Willimited) MANUFACTURER STANDARD LEAD TIME 13 Weeks LEAD REEE STATUS / ROHS STATUS LEAD REEE STATUS / ROHS STATUS LEAD REE STATUS / ROHS STATUS LEAD REE STATUS / ROHS STATUS LEAD REEE STATUS / ROHS		Specifications of ATSAV1
DESCRIPTION LEAD FREE STATUS / ROMS STATUS LEAD FREE STATUS / ROMS STATUS DATA SHEET VOLTAGE RATING - DC 28V VOLTAGE RATING - AC 28V VOLTAGE RATING - AC 28V TERMINATION STYLE PC Pin SWITCH FUNCTION On-OFF-Mom SERIES A A ARA ARA PARALE CUTUOT DIMENSIONS PACKAGING DEPARTING THREAD MOUNTING TYPE MOUNTING TYPE MOUNTING TYPE MOUNTING TYPE MOUNTING STATUS LEAD FREE STATUS / ROHS STATUS LILLUMINATION VOLTAGE (NOMINAL) FEATURES PROCESS PROTECTION FEATURES PROCESS Sealed ELECTRICAL LIFE DETAIL LIFE DETAIL LIFE DETAIL LIFE DETAIL LIFE VALUE OF SAME AND HELD FROM THE STATUS AND HELD	PART NUMBER	A1SAV1
Lead free / RoHS Compliant DATA SHEET DATA SHEET DATA SHEET DOLASE RATING - DC 28V VOLTAGE RATING - AC 28V VOLTAGE RATING - AC 28V TERMINATION STYLE PC PIN SWITCH FUNCTION ON-Off-Mom SERIES A PANALL CUTOUT DIMENSIONS PACKAGING BUBL OPERATING THMERATURE AOVC - 85°C MOUNTING TYPE MOUNTING TYPE MOUNTING TYPE MOUNTING SHATILY LEVEL (MSL) I (Unlimited) MANUPACTURER STATUS / ROHS STATUS LEAD FREE STATUS / ROHS STATUS LEAD FREE STATUS / ROHS STATUS LEAD FREE STATUS / ROHS STATUS LILUMINATION VOLTAGE (NOMINAL) ILLUMINATION YDPE, COLOR ILLUMINATION YDPE, COLOR IELLUMINATION YDPE, COLOR FEATURES PROCESS PROTECTION FREATURES PROCESS Sealed ELECTRICAL LIFE SO,000 Cycles DETAILED DESCRIPTION CURRENT RATING CURRE	MANUFACTURER	NKK Switches
DATA SHEET VOLTAGE RATING - DC ZBV VOLTAGE RATING - AC ZBV VOLTAGE RATING - AC ZBV TERMINATION STYLE PC PIN SWITCH FUNCTION ON-Off-Mon SERIES A A PANEL CUTOUT DIMENSIONS - PACKAGING Bulk OPERATING TEMPERATURE 30°C ~ 85°C MOUNTING TEMPERATURE Through Hole, Right Angle, Vertical THOUGH TURNING TYPE MOUSTURE SENSITYLY LEVEL (MSL) I (Unlimited) MANUFACTURER STANDARD LEAD TIME LEAD FREE STATUS / ROHS STATUS LILUMINATION TYPE, COLOR LILUMINATION NOn-Illuminated FEATURES ELECTRICAL LIFE 50,000 Cycles DETAILED DESCRIPTION TOGGE SWITCH SPOTT Through Hole, Right Angle, Vertical CURENT RATING U-4VA (AC/DC) CIRCUIT WARRING Through Warning Information WARNING: This product can expose you to chemicals including Antimony oxide (Antimony throode), Lead, and Nickel (Metallic) which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to wind and three of the California to cause cancer and birth defects or other reproductive harm. For more information go to wind and three of the California to cause cancer and birth defects or other reproductive harm. For more information go to wind and three of the California to cause cancer and birth defects or other reproductive harm. For more information go to wind and three of the California to cause cancer and birth defects or other reproductive harm. For more information go to wind and three of the California to cause cancer and birth defects or other reproductive harm. For more information go to wind and three of the California to cause cancer and birth defects or other reproductive harm. For more information go to wind and three of the California to cause cancer and birth defects or other reproductive harm. For more information go to wind and three of the	DESCRIPTION	SWITCH TOGGLE SPDT 0.4VA 28V
VOLTAGE RATING - DC 28V VOLTAGE RATING - AC 28V VOLTAGE RATING - AC 28V TERMINATION STYLE PC PIN SWITCH FUNCTION On-Off-Mom SERIES A PANEL CUTOUT DIMENSIONS - CASS**C MOUNTING TYPE THOUGH TYPE MOUNTING TYPE THOUGH TYPE MOUNTING TYPE THOUGH TYPE THOUGH TYPE MOUNTING TYPE THOUGH TYPE MOUNTING TYPE THOUGH TYPE MOUNTING TYPE THOUGH TYPE MOUNTING TYPE THOUGH TYPE THOUG	LEAD FREE STATUS / ROHS STATUS	Lead free / RoHS Compliant
VOLTAGE RATING - AC 28V TERMINATION STYLE PC PIN SWITCH FUNCTION On-Off-Mom SERIES A PARLE CUTOUT DIMENSIONS - PACKAGING Bulk OPERATING TEMPERATURE -30°C ~ 85°C MOUNTING TYPE Through Hole, Right Angle, Vertical MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) MANUFACTURER STANDARD LEAD TIME 13 Weeks LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant ILLUMINATION VOLTAGE (MOMINAL) - ILLUMINATION TYPE, COLOR - ILLUMINATION TYPE, COLOR Non-Illuminated FEATURES Process Sealed ELECTICAL LIFE 50,000 Cycles DETAILED DESCRIPTION Toggle Switch SPDT Through Hole, Right Angle, Vertical CURRENT RATING 0.4VA (AC/DC) CRILLIFORNIA PROP 65 Warning Information WARNING: This product can expose you to chemicals including Antimony oxide (Antimony Trioxide), Lead, and Nickei (Metallic) which are known to the State of California to cause cannel antity the defects or other reproductive harm. For more information go to www. P65warnings.ca.gov.	DATA SHEET	A1SAV1.pdf
FREMINATION STYLE SWITCH FUNCTION ON-OIF-Mom SERIES A A PANEL CUTOUT DIMENSIONS - PACKAGING BUİK OPERATING TEMPERATURE A30°C ~ 85°C MOUNTING TYPE MOISTURE SENSITIVITY LEVEL (MSL) MANUFACTURER STANDARD LEAD TIME LEAD FREE STATUS / ROHS STATUS LILUMINATION VOLTAGE (NOMINAL) LILUMINATION TYPE, COLOR LILUMINATION TYPE, COLOR EETITURES EETITURES ETITURES ETITURES ETITURES ETITURES ELECTRICAL LIFE DETAILED DESCRIPTION CURRENT RATING CURR	VOLTAGE RATING - DC	28V
SERIES A A PANEL CUTOUT DIMENSIONS - PACKAGING BUIK OPERATING TEMPERATURE 30°C ~ 85°C MOUNTING TYPE Through Hole, Right Angle, Vertical MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) MANUFACTURER STANDARD LEAD TIME 13 Weeks LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant ILLUMINATION VOLTAGE (NOMINAL) - ILLUMINATION TYPE, COLOR - ILLUMINATION TYPE, COLOR Process Sealed ELECTRICAL LIFE 50,000 Cycles DETAILED DESCRIPTION TOGGE SWith SPDT Through Hole, Right Angle, Vertical CURRENT RATING 0.4VA (AC/DC) CIRCUIT SPDT Warning Information WARNING: This product can expose you to chemicals including Antimony oxide (Antimony trioxide), Lead, and Nickel (Metallic) which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www. PSSwarnings.ca.gov. BUSHING THREAD ALLED TEXTS AS STATUS Standard Round One of the metallic product can expose you to chemicals including Antimony oxide (Antimony trioxide), Lead, and Nickel (Metallic) which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www. PSSwarnings.ca.gov. BUSHING THREAD ALLED TEXTS AS A STANDARD AND AND AND AND AND AND AND AND AND AN	VOLTAGE RATING - AC	28V
SERIES A A PANEL CUTOUT DIMENSIONS - PACKAGING BUIK OPERATING TEMPERATURE -30°C ~ 85°C MOUNTING TYPE Through Hole, Right Angle, Vertical MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) MANUFACTURER STANDARD LEAD TIME 13 Weeks LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant INGRESS PROTECTION - ILLUMINATION VOLTAGE (NOMINAL) - ILLUMINATION TYPE, COLOR - ILLUMINATION TO TYPE, COLOR - ILLUMINATION	TERMINATION STYLE	PC Pin
PACKAGING Bulk OPERATING TEMPERATURE 30°C ~ 85°C MOUNTING TYPE Through Hole, Right Angle, Vertical MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) MANUFACTURER STANDARD LEAD TIME 13 Weeks LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant LILLIMINATION VOLTAGE (NOMINAL) LILLIMINATION TYPE, COLOR LILLIMINATION TYPE, COLOR ELECTRICAL LIFE SCALUFE SCALUF	SWITCH FUNCTION	On-Off-Mom
PACKAGING Bulk OPERATING TEMPERATURE -30°C ~ 85°C MOUNTING TYPE Through Hole, Right Angle, Vertical MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) MANUFACTURER STANDARD LEAD TIME 13 Weeks LEAD FREE STATUS / ROHS STATUS LEAd free / RoHS Compliant INGRESS PROTECTION - LEAd free / RoHS Compliant LILLIMINATION VOLTAGE (NOMINAL) LILLIMINATION TYPE, COLOR LILLIMINATION TYPE, COLOR Process Sealed ELECTRICAL LIFE 50,000 Cycles DETAILED DESCRIPTION TOGGLE (NOMINAL) TOGGLE SWITCH SMITH	SERIES	A
MOUNTING TYPE MOUNTING TYPE Through Hole, Right Angle, Vertical MOISTURE SENSITIVITY LEVEL (MSL) MANUFACTURER STANDARD LEAD TIME LEAD FREE STATUS / ROHS STATUS LEAD FREE STATUS / ROHS STATUS LEAD FREE STATUS / ROHS STATUS LLUMINATION VOLTAGE (NOMINAL) LLUMINATION YOLTAGE (NOMINAL) LLUMINATION YOLTAGE (NOMINAL) LEAD FREE STATUS / ROHS STATUS LLUMINATION NOn-Illuminated FEATURES Process Sealed ELECTRICAL LIFE DETAILED DESCRIPTION Toggle Switch SPDT Through Hole, Right Angle, Vertical CURRENT RATING CURRENT RATING CALIFORNIA PROP 65 BUSHING THREAD Unthreaded, Square ACTUATOR TYPE Standard Round ACTUATOR TYPE TARGARD TOUR STANDARD THOUGH HOLE, Right Angle, Vertical CURRENT reproductive harm. For more information go to www.P65wernings.ca.gov. BUSHING THREAD ACTUATOR TYPE Standard Round	PANEL CUTOUT DIMENSIONS	-
MOUNTING TYPE MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) MANUFACTURER STANDARD LEAD TIME 13 Weeks LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant INGRESS PROTECTION 1 LLUMINATION VOLTAGE (NOMINAL) 1 LLUMINATION TYPE, COLOR 1 LLUMINATION Non-Illuminated FEATURES Process Sealed ELECTRICAL LIFE 50,000 Cycles ELECTRICAL LIFE DETAILED DESCRIPTION Toggle Switch SPDT Through Hole, Right Angle, Vertical CURRENT RATING CURRENT RATING CALIFORNIA PROP 65 Warning Information WARNING: This product can expose you to chemicals including Antimony oxide (Antimony trioxide), Lead, and Nickel (Metallic) which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65warnings.ca.gov. BUSHING THREAD ACUATOR TYPE Standard Round	PACKAGING	Bulk
MOISTURE SENSITIVITY LEVEL (MSL) MANUFACTURER STANDARD LEAD TIME 13 Weeks LEAD FREE STATUS / ROHS STATUS LEAd free / ROHS Compliant INGRESS PROTECTION - ILLUMINATION VOLTAGE (NOMINAL) ILLUMINATION TYPE, COLOR ILLUMINATION Non-Illuminated FEATURES Process Sealed ELECTRICAL LIFE 50,000 Cycles DETAILED DESCRIPTION Toggle Switch SPDT Through Hole, Right Angle, Vertical CURRENT RATING CURRENT RATING CALIFORNIA PROP 65 Warning Information WARNING: This product can expose you to chemicals including Antimony oxide (Antimony trioxide), Lead, and Nickel (Metallic) which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65warnings.ca.gov. BUSHING THREAD ACTUATOR TYPE \$ 10 Unlimited) 1 Weeks Lead free / ROHS ACHAGO COMPINION 1 Weeks Lead free / ROHS Compliant 2 Weeks Lead free / ROHS Compliant 1 Weeks Lead free / ROHS Compliant 2 Weeks Lead free / ROHS Compliant	OPERATING TEMPERATURE	-30°C ~ 85°C
MANUFACTURER STANDARD LEAD TIME LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant INGRESS PROTECTION - ILLUMINATION VOLTAGE (NOMINAL) - ILLUMINATION TYPE, COLOR ILLUMINATION Non-Illuminated FEATURES Process Sealed ELECTRICAL LIFE 50,000 Cycles DETAILED DESCRIPTION Toggle Switch SPDT Through Hole, Right Angle, Vertical CURRENT RATING 0.4VA (AC/DC) CIRCUIT SPDT Warning Information WARNING: This product can expose you to chemicals including Antimony oxide (Antimony trioxide), Lead, and Nickel (Metallic) which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65warnings.ca.gov. BUSHING THREAD ACTUATOR TYPE Standard Round	MOUNTING TYPE	Through Hole, Right Angle, Vertical
LEAD FREE STATUS / ROHS STATUS INGRESS PROTECTION ILLUMINATION VOLTAGE (NOMINAL) ILLUMINATION TYPE, COLOR ILLUMINATION NOn-Illuminated FEATURES Process Sealed ELECTRICAL LIFE 50,000 Cycles DETAILED DESCRIPTION Toggle Switch SPDT Through Hole, Right Angle, Vertical CURRENT RATING CURRENT RATING CALIFORNIA PROP 65 Warning Information WARNING: This product can expose you to chemicals including Antimony voidd (Antimony trioxide), Lead, and Nickel (Metallic) which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65warnings.ca.gov. BUSHING THREAD ACTUATOR TYPE Lead free / ROHS Compliant - California to Cause cancer and birth defects or other reproductive harm. For more information go to www.P65warnings.ca.gov.	MOISTURE SENSITIVITY LEVEL (MSL)	1 (Unlimited)
INGRESS PROTECTION	MANUFACTURER STANDARD LEAD TIME	13 Weeks
ILLUMINATION VOLTAGE (NOMINAL) - ILLUMINATION TYPE, COLOR - ILLUMINATION Non-Illuminated FEATURES Process Sealed ELECTRICAL LIFE 50,000 Cycles DETAILED DESCRIPTION Toggle Switch SPDT Through Hole, Right Angle, Vertical CURRENT RATING 0.4VA (AC/DC) CIRCUIT SPDT CALIFORNIA PROP 65 Warning Information WARNING: This product can expose you to chemicals including Antimony oxide (Antimony trioxide), Lead, and Nickel (Metallic) which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65warnings.ca.gov. BUSHING THREAD Unthreaded, Square ACTUATOR TYPE Standard Round	LEAD FREE STATUS / ROHS STATUS	Lead free / RoHS Compliant
ILLUMINATION TYPE, COLOR - ILLUMINATION Non-Illuminated FEATURES Process Sealed ELECTRICAL LIFE 50,000 Cycles DETAILED DESCRIPTION Toggle Switch SPDT Through Hole, Right Angle, Vertical CURRENT RATING 0.4VA (AC/DC) CIRCUIT SPDT CALIFORNIA PROP 65 Warning Information WARNING: This product can expose you to chemicals including Antimony oxide (Antimony trioxide), Lead, and Nickel (Metallic) which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65warnings.ca.gov. BUSHING THREAD Unthreaded, Square ACTUATOR TYPE Standard Round	INGRESS PROTECTION	-
ILLUMINATION Non-Illuminated FEATURES Process Sealed ELECTRICAL LIFE 50,000 Cycles DETAILED DESCRIPTION Toggle Switch SPDT Through Hole, Right Angle, Vertical CURRENT RATING 0.4VA (AC/DC) CIRCUIT SPDT CALIFORNIA PROP 65 Warning Information WARNING: This product can expose you to chemicals including Antimony oxide (Antimony trioxide), Lead, and Nickel (Metallic) which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65warnings.ca.gov. BUSHING THREAD Unthreaded, Square ACTUATOR TYPE Standard Round	ILLUMINATION VOLTAGE (NOMINAL)	-
FEATURES FEATURES Process Sealed ELECTRICAL LIFE 50,000 Cycles DETAILED DESCRIPTION Toggle Switch SPDT Through Hole, Right Angle, Vertical CURRENT RATING 0.4VA (AC/DC) CIRCUIT SPDT Warning Information WARNING: This product can expose you to chemicals including Antimony oxide (Antimony trioxide), Lead, and Nickel (Metallic) which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65warnings.ca.gov. BUSHING THREAD ACTUATOR TYPE Standard Round	ILLUMINATION TYPE, COLOR	-
ELECTRICAL LIFE DETAILED DESCRIPTION Toggle Switch SPDT Through Hole, Right Angle, Vertical O.4VA (AC/DC) CIRCUIT SPDT Warning Information WARNING: This product can expose you to chemicals including Antimony oxide (Antimony trioxide), Lead, and Nickel (Metallic) which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65warnings.ca.gov. BUSHING THREAD ACTUATOR TYPE Standard Round	ILLUMINATION	Non-Illuminated
DETAILED DESCRIPTION Toggle Switch SPDT Through Hole, Right Angle, Vertical O.4VA (AC/DC) CIRCUIT SPDT Warning Information WARNING: This product can expose you to chemicals including Antimony oxide (Antimony trioxide), Lead, and Nickel (Metallic) which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65warnings.ca.gov. BUSHING THREAD ACTUATOR TYPE Standard Round	FEATURES	Process Sealed
CURRENT RATING O.4VA (AC/DC) CIRCUIT SPDT Warning Information WARNING: This product can expose you to chemicals including Antimony oxide (Antimony trioxide), Lead, and Nickel (Metallic) which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65warnings.ca.gov. BUSHING THREAD ACTUATOR TYPE Standard Round	ELECTRICAL LIFE	50,000 Cycles
CALIFORNIA PROP 65 CALIFORNIA PROP 65 Warning Information WARNING: This product can expose you to chemicals including Antimony oxide (Antimony trioxide), Lead, and Nickel (Metallic) which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65warnings.ca.gov. BUSHING THREAD Unthreaded, Square ACTUATOR TYPE Standard Round	DETAILED DESCRIPTION	Toggle Switch SPDT Through Hole, Right Angle, Vertical
Warning Information WARNING: This product can expose you to chemicals including Antimony oxide (Antimony trioxide), Lead, and Nickel (Metallic) which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65warnings.ca.gov. BUSHING THREAD Unthreaded, Square ACTUATOR TYPE Standard Round	CURRENT RATING	0.4VA (AC/DC)
CALIFORNIA PROP 65 (Antimony trioxide), Lead, and Nickel (Metallic) which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65warnings.ca.gov. BUSHING THREAD Unthreaded, Square Standard Round	CIRCUIT	SPDT
ACTUATOR TYPE Standard Round	CALIFORNIA PROP 65	(Antimony trioxide), Lead, and Nickel (Metallic) which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to
	BUSHING THREAD	Unthreaded, Square
ACTUATOR MATERIAL Brass, Nickel Plated	ACTUATOR TYPE	Standard Round
	ACTUATOR MATERIAL	Brass, Nickel Plated

Related Tags

10.00mm

NKK Switches A1SAV1	A1SAV1 Distributor	A1SAV1 Supplier
A1SAV1 Price	A1SAV1 Pictures	A1SAV1 Image
A1SAV1 PDF Datasheet	A1SAV1 Download Datasheet	A1SAV1 Datasheet
A1SAV1 Stock	Buy A1SAV1	Buy NKK Switches A1SAV1
NKK Switches A1SAV1	NKK Switches Supplier	NKK Switches Distributor
NKK Switches A1SAV1		

Related Products



ACTUATOR LENGTH

A1S4SHV

Manufacturers: Knowles Voltronics

Description: CAP TRIMMER 0.45-4.0PF 250V SMD In stock: Out stock

RFQ



A1S8

Manufacturers: Knowles Voltronics Description: CAP TRIMMER 0.5-8.0PF 125V SMD

In stock: Out stock

RFQ



A1SJH

Manufacturers: NKK Switches Description: SWITCH TOGGLE SPDT 0.4VA 28V

In stock: 8 pcs

RFQ



A1SEW

Manufacturers: NKK Switches Description: SWITCH TOGGLE SPDT 0.4VA 28V

In stock: Out stock

RFQ



A1S8S

Manufacturers: Knowles Voltronics Description: CAP TRIMMER 0.5-8.0PF 125V SMD

In stock: Out stock

RFQ



A1SHW

Manufacturers: NKK Switches Description: SWITCH TOGGLE SPDT 0.4VA 28V

In stock: Out stock

RFQ



A1S8HV

Description: CAP TRIMMER 0.5-8.0PF 125V SMD In stock: Out stock

Manufacturers: Knowles Voltronics

RFQ



A1S4S Manufacturers: Knowles Voltronics

Description: CAP TRIMMER 0.45-4.0PF 250V SMD

In stock: Out stock **RFQ**



A1SAV Manufacturers: NKK Switches

Description: SWITCH TOGGLE SPDT 0.4VA 28V In stock: Out stock

RFQ



A1SJV Manufacturers: NKK Switches

Description: SWITCH TOGGLE SPDT 0.4VA 28V In stock: 9 pcs

RFQ






Manufacturers: NKK Switches

A1SKH

Description: SWITCH ROCKER SPDT 0.4VA 28V In stock: Out stock

RFQ





In stock: Out stock

RFQ









