

100AWSP4T1B4M1QE

Part Number: Manufacturer/Brand:

Product description Datasheets: RoHs Status

Ship From Shipment Way 100AWSP4T1B4M1QE

E-Switch

SWITCH TOGGLE SPDT 5A 120V 100AWSP4T1B4M1QE.pdf

Lead free / RoHS Compliant

Hong Kong

DHL/Fedex/TNT/UPS/EMS

REQUEST FOR QUOTATION

Image may be representation. See specifications for product details.

ART NUMBER IANUFACTURER E-Switch SWITCH TOGGLE SPDT 5A 120V Lead free / RoHS Compliant ATA SHEET OLTAGE RATING - DC OLTAGE RATING - DC OLTAGE RATING - AC ERMINATION STYLE Solder Lug WITCH FUNCTION Mom-Off-Mom ERIES 100A ANAL CUTOUT DIMENSIONS - ACKAGING Bulk PERATING TEMPERATURE -30°C ~ 85°C IOUNTING TYPE - IOUSTURE SENSITIVITY LEVEL (MSL) IANUFACTURER STANDARD LEAD TIME PEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant INFO - Dust Tight, Waterproof LUMINATION VOLTAGE (NOMINAL) - LUMINATION TYPE, COLOR - LUMINATION TYPE, COLOR EATURES EAD REE STATUS / ROHS STATUS LECTRICAL LIFE 30,000 Cycles Toggle Switch SPDT SA (AC/DC) IRCUIT USHING THEAD Unthreaded CTUATOR MATERIAL Brass, Chrome Plated		Specifications of 100AWSP4T1B4M1QE
E-Switch SWITCH TOGGLE SPDT 5A 120V EAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant ATA SHEET OLTAGE RATING - DC 28V OLTAGE RATING - AC 120V ERMINATION STYLE Solder Lug WITCH FUNCTION Mom-Off-Mom ERIES 100A ANAL CUTOUT DIMENSIONS - ACKAGING Bulk PERATING TEMPERATURE -30°C ~ 85°C 10UNTING TYPE -10UNTING		Specifications of 100/11101 1110
E-Switch SWITCH TOGGLE SPDT 5A 120V EAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant ATA SHEET OLTAGE RATING - DC 28V OLTAGE RATING - DC 28V OLTAGE RATING - AC ERMINATION STYLE Solder Lug WITCH FUNCTION Mom-Off-Mom ERIES 100A ANALL CUTOUT DIMENSIONS - ACKAGING Bulk PERATING TEMPERATURE - 10UNTING TYPE - 10UNTING TOPS EAP FREE STATUS / ROHS STATUS Lead free / RoHS Compliant NGRESS PROTECTION 1P67 - Dust Tight, Waterproof LUMINATION VOLTAGE (NOMINAL) - LUMINATION TYPE, COLOR EATURES EPONY Sealed Terminals LECTRICAL LIFE 30,000 Cycles ETAILED DESCRIPTION TOGGIE SWItch SPDT URRENT RATING SA (AC/DC) IRCUIT USHING THREAD Unthreaded CTUATOR TYPE Standard Round CTUATOR MATERIAL	PART NUMBER	100AWSP4T1B4M1QE
Lead free / RoHS Compliant ATA SHEET OLTAGE RATING - DC 28V OLTAGE RATING - AC 120V ERMINATION STYLE Solder Lug WITCH FUNCTION Mom-Off-Mom ERIES 100A ANEL CUTOUT DIMENSIONS -ACKAGING Bulk PERAITING TEMPERATURE -30°C ~ 85°C IOUNTING TYPE -IOUSTURE SENSITIVITY LEVEL (MSL) IAUNFACTURER STANDARD LEAD TIME PEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant INGRESS PROTECTION IP67 - Dust Tight, Waterproof LLUMINATION VOLTAGE (NOMINAL) LLUMINATION TYPE, COLOR EATURES Epoxy Sealed Terminals LECTRICAL LIFE 30,000 Cycles TOGGLE SWITCH STANDA LUMINATION TOGGLE SWITCH SPDT URRENT RATING SA (AC/DC) SPDT USHING THEAD CTUATOR MATERIAL Brass, Chrome Plated	MANUFACTURER	
DOLTAGE RATING - DC 28V OLTAGE RATING - AC 120V ERMINATION STYLE Solder Lug WITCH FUNCTION Mom-Off-Mom ERIES 100A ANAL CUTOUT DIMENSIONS - ACKAGING Bulk PERATING TEMPERATURE -30°C ~ 85°C IOUNTING TYPE -IOUSTURE SENSITIVITY LEVEL (MSL) LIANUFACTURER STANDARD LEAD TIME EAD FREE STATUS / ROHS STATUS LEAD FREE STATUS / ROHS STATUS LEAD FREE STATUS / ROHS COMMINAL) LUMINATION VOLTAGE (NOMINAL) LUMINATION TYPE, COLOR EATURES EPOXY Sealed Terminals LECTRICAL LIFE 30,000 Cycles ETAILED DESCRIPTION TOggle Switch SPDT UNCHIONATION TYPE UNCHIONATION TOggle Switch SPDT UNCHIONATION TYPE UNCHIONATION VOLTAGE (NOMINAL) LUMINATION TOGGLE SWITCH SPDT UNCHIONATION VOLTAGE (NOMINAL) LECTRICAL LIFE 30,000 Cycles ETAILED DESCRIPTION TOggle Switch SPDT UNCHIONATION TYPE UNCHIONATERIAL STANDARD ROHS UNCHIONATERIAL Brass, Chrome Plated	DESCRIPTION	SWITCH TOGGLE SPDT 5A 120V
OLTAGE RATING - DC OLTAGE RATING - AC 120V Solder Lug WITCH FUNCTION Mom-Off-Mom ERIES 100A ANAL CUTOUT DIMENSIONS -ACKAGING Bulk PERATING TEMPERATURE -30°C ~ 85°C 100UNTING TYPE -10ISTURE SENSITIVITY LEVEL (MSL) IANUFACTURER STANDARD LEAD TIME PEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant NGRESS PROTECTION IP67 - Dust Tight, Waterproof LUMINATION VOLTAGE (NOMINAL) -LUMINATION TYPE, COLOR EATURES Epoxy Sealed Terminals LECTRICAL LIFE 30,000 Cycles ETAILED DESCRIPTION Toggle Switch SPDT USHING THREAD Unthreaded CTUATOR MATERIAL Brass, Chrome Plated	LEAD FREE STATUS / ROHS STATUS	Lead free / RoHS Compliant
DITAGE RATING - AC ERMINATION STYLE Solder Lug WITCH FUNCTION Mom-Off-Mom ERIES 100A ANEL CUTOUT DIMENSIONS - ACKAGING BUIK PERATING TEMPERATURE -30°C ~ 85°C 100INTING TYPE - 10ISTURE SENSITIVITY LEVEL (MSL) IANUFACTURER STANDARD LEAD TIME PEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant NGRESS PROTECTION IP67 - Dust Tight, Waterproof LUMINATION VOLTAGE (NOMINAL) - LLUMINATION TYPE, COLOR EATURES EPOXY Sealed Terminals LECTRICAL LIFE 30,000 Cycles ETAILED DESCRIPTION Toggle Switch SPDT URRENT RATING SA (AC/DC) LIUMING THREAD Unthreaded CTUATOR MATERIAL Brass, Chrome Plated	DATA SHEET	100AWSP4T1B4M1QE.pdf
ERMINATION STYLE WITCH FUNCTION Mom-Off-Mom ERIES 100A ANEL CUTOUT DIMENSIONS -ACKAGING Bulk PERATING TEMPERATURE -30°C ~ 85°C ROUNTING TYPE -ROISTURE SENSITIVITY LEVEL (MSL) IANUFACTURER STANDARD LEAD TIME EAD FREE STATUS / ROHS STATUS LEAD FREE STATUS / ROHS STATUS LUMINATION VOLTAGE (NOMINAL) LUMINATION TYPE, COLOR EATURES EATURES EPOXY Sealed Terminals LECTRICAL LIFE SOURCE SWITCH SPDT URRENT RATING 5A (AC/DC) IRCUIT USHING THREAD CIUATOR MATERIAL Brass, Chrome Plated	VOLTAGE RATING - DC	28V
WITCH FUNCTION Mom-Off-Mom ERIES 100A ANEL CUTOUT DIMENSIONS -ACKAGING Bulk PERATING TEMPERATURE -30°C ~ 85°C ROUNTING TYPE -ROUSTURE SENSITIVITY LEVEL (MSL) IANUFACTURER STANDARD LEAD TIME EAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant NORESS PROTECTION LUMINATION VOLTAGE (NOMINAL) LUMINATION TYPE, COLOR -LUMINATION EATURES EPOXY Sealed Terminals LECTRICAL LIFE SOURCE STATUS LECTRICAL LIFE SETABLED DESCRIPTION URRENT RATING TOGGIE SWItch SPDT USHING THREAD Unthreaded CTUATOR MATERIAL Brass, Chrome Plated	VOLTAGE RATING - AC	120V
ERIES 100A ANEL CUTOUT DIMENSIONS ACKAGING Bulk PERATING TEMPERATURE -30°C ~ 85°C ROUNTING TYPE - ROISTURE SENSITIVITY LEVEL (MSL) IANUFACTURER STANDARD LEAD TIME PEAD FREE STATUS / ROHS STATUS LEAD FREE STATUS / ROHS STATUS LUMINATION VOLTAGE (NOMINAL) LLUMINATION TYPE, COLOR - LLUMINATION EATURES EDOXY Sealed Terminals LECTRICAL LIFE 30,000 Cycles TOGGIE Switch SPDT URRENT RATING LIVENING THREAD Unthreaded CTUATOR MATERIAL Brass, Chrome Plated	TERMINATION STYLE	Solder Lug
ANEL CUTOUT DIMENSIONS ACKAGING Bulk PERATING TEMPERATURE -30°C ~ 85°C DOUNTING TYPE - DOISTURE SENSITIVITY LEVEL (MSL) IANUFACTURER STANDARD LEAD TIME 9 Weeks EAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant IP67 - Dust Tight, Waterproof LUMINATION VOLTAGE (NOMINAL) - LUMINATION TYPE, COLOR LUMINATION NOn-Illuminated EATURES EPOXY Sealed Terminals LECTRICAL LIFE 30,000 Cycles DETAILED DESCRIPTION TOGGIE Switch SPDT URRENT RATING SA (AC/DC) IRCUIT USHING THREAD Unthreaded CTUATOR MATERIAL Brass, Chrome Plated	SWITCH FUNCTION	Mom-Off-Mom
Bulk PERATING TEMPERATURE -30°C ~ 85°C DOUNTING TYPE - DOISTURE SENSITIVITY LEVEL (MSL) IANUFACTURER STANDARD LEAD TIME PEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant NGRESS PROTECTION IP67 - Dust Tight, Waterproof - LLUMINATION VOLTAGE (NOMINAL) - LLUMINATION TYPE, COLOR LUMINATION Non-Illuminated EATURES EPOXY Sealed Terminals LECTRICAL LIFE 30,000 Cycles PETAILED DESCRIPTION TOGGIE Switch SPDT URRENT RATING SA (AC/DC) IRCUIT USHING THREAD Unthreaded CTUATOR MATERIAL Brass, Chrome Plated	SERIES	100A
APPERATING TEMPERATURE -30°C ~ 85°C	PANEL CUTOUT DIMENSIONS	-
IOUNTING TYPE IOISTURE SENSITIVITY LEVEL (MSL) IANUFACTURER STANDARD LEAD TIME IOISTURE SENSITIVITY LEVEL (MSL) IANUFACTURER STANDARD LEAD TIME IOISTURE STANDARD LEAD TIME IOISTURES PROTECTION IP67 - Dust Tight, Waterproof IP67 - Dust Tight, Waterproof IOISTURE, Waterproof I	PACKAGING	Bulk
IOISTURE SENSITIVITY LEVEL (MSL) IANUFACTURER STANDARD LEAD TIME 9 Weeks EAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant IP67 - Dust Tight, Waterproof LUMINATION VOLTAGE (NOMINAL) - LUMINATION TYPE, COLOR EATURES EATURES EPOXY Sealed Terminals LECTRICAL LIFE 30,000 Cycles EATURED DESCRIPTION TOGGIE Switch SPDT URRENT RATING IRCUIT USHING THREAD Unthreaded CTUATOR MATERIAL Brass, Chrome Plated	OPERATING TEMPERATURE	-30°C ~ 85°C
IANUFACTURER STANDARD LEAD TIME EAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant IP67 - Dust Tight, Waterproof LUMINATION VOLTAGE (NOMINAL) - LUMINATION TYPE, COLOR LUMINATION Non-Illuminated EATURES Epoxy Sealed Terminals LECTRICAL LIFE 30,000 Cycles ETAILED DESCRIPTION Toggle Switch SPDT URRENT RATING SA (AC/DC) IRCUIT USHING THREAD Unthreaded CTUATOR MATERIAL Brass, Chrome Plated	MOUNTING TYPE	-
Lead free / RoHS Compliant NGRESS PROTECTION IP67 - Dust Tight, Waterproof LUMINATION VOLTAGE (NOMINAL) LUMINATION TYPE, COLOR LUMINATION Non-Illuminated EATURES Epoxy Sealed Terminals LECTRICAL LIFE 30,000 Cycles ETAILED DESCRIPTION Toggle Switch SPDT URRENT RATING IRCUIT USHING THREAD Unthreaded CTUATOR TYPE CTUATOR MATERIAL Lead free / RoHS Compliant IP67 - Dust Tight, Waterproof - Lead free / RoHS Compliant IP67 - Dust Tight, Waterproof - 1P67 - Dus	MOISTURE SENSITIVITY LEVEL (MSL)	1 (Unlimited)
NGRESS PROTECTION IP67 - Dust Tight, Waterproof LLUMINATION VOLTAGE (NOMINAL) - LLUMINATION TYPE, COLOR - LLUMINATION Non-Illuminated EATURES Epoxy Sealed Terminals LECTRICAL LIFE 30,000 Cycles ETAILED DESCRIPTION Toggle Switch SPDT URRENT RATING 5A (AC/DC) IRCUIT USHING THREAD Unthreaded CTUATOR TYPE Standard Round Brass, Chrome Plated	MANUFACTURER STANDARD LEAD TIME	9 Weeks
LLUMINATION VOLTAGE (NOMINAL) LLUMINATION TYPE, COLOR LLUMINATION Non-Illuminated EATURES Epoxy Sealed Terminals LECTRICAL LIFE 30,000 Cycles ETAILED DESCRIPTION Toggle Switch SPDT URRENT RATING 5A (AC/DC) IRCUIT USHING THREAD CTUATOR TYPE Standard Round Brass, Chrome Plated	LEAD FREE STATUS / ROHS STATUS	Lead free / RoHS Compliant
LLUMINATION TYPE, COLOR LLUMINATION Non-Illuminated EATURES Epoxy Sealed Terminals LECTRICAL LIFE 30,000 Cycles Toggle Switch SPDT URRENT RATING 5A (AC/DC) IRCUIT USHING THREAD CTUATOR TYPE Standard Round CTUATOR MATERIAL Non-Illuminated Epoxy Sealed Terminals 30,000 Cycles Toggle Switch SPDT Unthreaded Standard Round Brass, Chrome Plated	INGRESS PROTECTION	IP67 - Dust Tight, Waterproof
EATURES EDOXY Sealed Terminals LECTRICAL LIFE 30,000 Cycles ETAILED DESCRIPTION Toggle Switch SPDT URRENT RATING 5A (AC/DC) IRCUIT USHING THREAD Unthreaded CTUATOR TYPE Standard Round CTUATOR MATERIAL Non-Illuminated Toggle Switch SPDT Unthreaded SPDT URRENT RATING SPDT URRENT RATING STANDARD	ILLUMINATION VOLTAGE (NOMINAL)	-
EATURES LECTRICAL LIFE 30,000 Cycles Toggle Switch SPDT URRENT RATING 5A (AC/DC) IRCUIT USHING THREAD CTUATOR TYPE CTUATOR MATERIAL Epoxy Sealed Terminals 30,000 Cycles Toggle Switch SPDT Toggle Switch SPDT Unthreaded SPDT Unthreaded Standard Round Brass, Chrome Plated	ILLUMINATION TYPE, COLOR	-
LECTRICAL LIFE 30,000 Cycles Toggle Switch SPDT URRENT RATING 5A (AC/DC) IRCUIT USHING THREAD Unthreaded CTUATOR TYPE Standard Round Brass, Chrome Plated	ILLUMINATION	Non-Illuminated
Toggle Switch SPDT URRENT RATING 5A (AC/DC) IRCUIT USHING THREAD Unthreaded CTUATOR TYPE Standard Round Brass, Chrome Plated	FEATURES	Epoxy Sealed Terminals
URRENT RATING 5A (AC/DC) IRCUIT USHING THREAD Unthreaded CTUATOR TYPE Standard Round CTUATOR MATERIAL Brass, Chrome Plated	ELECTRICAL LIFE	30,000 Cycles
USHING THREAD Unthreaded CTUATOR TYPE Standard Round CTUATOR MATERIAL Brass, Chrome Plated	DETAILED DESCRIPTION	Toggle Switch SPDT
USHING THREAD Unthreaded CTUATOR TYPE Standard Round CTUATOR MATERIAL Brass, Chrome Plated	CURRENT RATING	5A (AC/DC)
CTUATOR TYPE Standard Round CTUATOR MATERIAL Brass, Chrome Plated	CIRCUIT	SPDT
CTUATOR MATERIAL Brass, Chrome Plated	BUSHING THREAD	Unthreaded
	ACTUATOR TYPE	Standard Round
CTUATOR LENGTH 12.70mm	ACTUATOR MATERIAL	Brass, Chrome Plated
	ACTUATOR LENGTH	12.70mm

Related Tags

E-Switch 100AWSP4T1B4M1QE	100AWSP4T1B4M1QE Distributor	100AWSP4T1B4M1QE Supplier
100AWSP4T1B4M1QE Price	100AWSP4T1B4M1QE Pictures	100AWSP4T1B4M1QE Image
100AWSP4T1B4M1QE PDF Datasheet	100AWSP4T1B4M1QE Download Datasheet	100AWSP4T1B4M1QE Datasheet
100AWSP4T1B4M1QE Stock	Buy 100AWSP4T1B4M1QE	Buy E-Switch 100AWSP4T1B4M1QE
E-Switch 100AWSP4T1B4M1QE	E-Switch Supplier	E-Switch Distributor
E-Switch 100AWSP4T1B4M1QE		

Related Products



100AWSP4T1B1M1QEH Manufacturers: E-Switch

Description: SWITCH TOGGLE SPDT 5A 120V

In stock: Out stock **RFQ**



100AWSP4T1B4VS2QE Manufacturers: E-Switch

Description: SWITCH TOGGLE SPDT 5A 120V In stock: Out stock

RFQ



100AWSP3T2B4M7RE Manufacturers: E-Switch

Description: SWITCH TOGGLE SPDT 0.4VA 20V

In stock: Out stock

RFQ



100AWSP4T1B4M2RE Manufacturers: E-Switch

Description: SWITCH TOGGLE SPDT 0.4VA 20V

In stock: Out stock

RFQ



100AWSP3T2B4M2QE Manufacturers: E-Switch

Description: SWITCH TOGGLE SPDT 5A 120V In stock: Out stock

RFQ



100AWSP4T2B4M6RE Manufacturers: E-Switch

Description: SWITCH TOGGLE SPDT 0.4VA 20V In stock: Out stock

RFQ



Manufacturers: E-Switch Description: SWITCH TOGGLE SPDT 5A 120V

100AWSP3T2B4VS2QE

In stock: Out stock

RFQ



100AWSP3T1B4VS21RE Manufacturers: E-Switch

Description: SWITCH TOGGLE SPDT 0.4VA 20V In stock: Out stock

RFQ



Manufacturers: E-Switch Description: SWITCH TOGGLE SPDT 5A 120V

100AWSP3T2B4M6QE

In stock: Out stock

RFQ

Manufacturers: E-Switch Description: SWITCH TOGGLE SPDT 0.4VA 20V

In stock: Out stock

100AWSP4T2B4M7QE

Manufacturers: E-Switch

RFQ

In stock: Out stock

100AWSP4T1B4VS2RE

RFQ

Description: SWITCH TOGGLE SPDT 5A 120V



Manufacturers: E-Switch

100AWSP4T2B4M1QE

Description: SWITCH TOGGLE SPDT 5A 120V In stock: Out stock

RFQ













