



C&K

KMT213GHFLFG

Part Number:

Manufacturer/Brand:

Product description

RoHs Status Ship From

Datasheets:

Shipment Way

KMT213GHFLFG

C&K

SWITCH TACTILE SPST-NO 0.01A 32V

KMT213GHFLFG.pdf

Lead free / RoHS Compliant

Hong Kong

DHL/Fedex/TNT/UPS/EMS



Image may be representation. See specifications for product details.

Specifications of KMT213GHFLFG

REQUEST FOR QUOTATION

ANNUFACTURER C&X SWITCH TACTILE SPST-NO 0.01A 32V LEAD FREE STATUS / ROHS STATUS LLUMINATION VOLTAGE (NOMINAL) LLUMINATION VOLTAGE (NOMINAL) LLUMINATION VOLTAGE (NOMINAL) LEAD FREE STATUS / ROHS STATUS LEAD FREE STATUS / ROHS STATUS LLUMINATION VOLTAGE (NOMINAL) LLUMINATION VOLTAGE (NOMINAL) LEAD FREE STATUS / ROHS STATUS LEAD FREE STATUS / ROHS STATUS LLUMINATION NON-Illuminated EATURES GROUNDING PIN Tactile Switch SPST-NO Top Actuated Surfacture of Top Actuated Surfacture of Top Actuated Surfacture of Top Actuated LICULATOR RATERIAL - CTUATOR RATERIAL - CTUATOR MATERIAL - CTUATOR M		Specifications of KH1213GH El G
SWITCH TACTILE SPST-NO 0.01A 32V EAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant WATA SHEET ERMINATION STYLE GUII WING WITCH TRAVEL 0.13mm WITCH FUNCTION Off-Mom RERIES KMT ACKAGING Tape & Reel (TR) 3.00mm x 2.60mm KMT213G HF LFG Y34H21310FP V34H21310FP V34H21310FP V34H21310FP V34H21310FP SURFACTING TEMPERATURE A0°C ~ 125°C DIPERATING TEMPERATURE 100gf MOUNTING TYPE SURFACE MOUNT MOUSTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) MECHANICAL LIFE MANUFACTURER STANDARD LEAD TIME BE WEEKS EAD FREE STATUS / ROHS STATUS LEAD FREE STATUS / ROHS STATUS LEAD FREE STATUS / ROHS STATUS LEAD FREE STATUS / ROHS COMPLIANT LILUMINATION VOLTAGE (NOMINAL) LILUMINATION VOLTAGE (NOMINAL) EATURES GROUNDING PIN TACTILE SWITCH SPST-NO TOP Actuated Surface COLUATOR TYPE STANDARD STANDARD COLUATOR ORIENTATION TOP ACTUATOR TYPE STANDARD COLUATOR ORIENTATION TOP ACTUATOR MATERIAL - COLUATOR MATERIAL - COLUATOR MATERIAL - LEAD FREE STATUS / ROHS COMPLIANT TOP ACTUATOR MATERIAL - COLUATOR MATERIAL - LIUMTOR TYPE STANDARD COLUATOR MATERIAL - COLUATOR MATERIAL - LEAD FREE STATUS / ROHS COMPLIANT COLUATOR MATERIAL - LEAD FREE STATUS / ROHS COMPLIANT COLUATOR MATERIAL - LEAD FREE STATUS / ROHS COMPLIANT COLUATOR MATERIAL - LEAD FREE SPST-NO STANDARD STANDARD STANDARD COLUATOR MATERIAL - COLUATOR MATERIAL - LEAD FREE SPST-NO STANDARD STANDARD COLUATOR TYPE STANDARD COLUATOR MATERIAL - LEAD FREE SPST-NO STANDARD STANDARD COLUATOR TYPE STANDARD COLUATOR TYPE STANDARD COLUATOR TYPE STANDARD COLUATOR MATERIAL - LEAD FREE SPST-NO STANDARD COLUATOR MATERIAL - LEAD FREE SPST-NO STANDARD COLUATOR TYPE STANDARD COLUATOR TY	PART NUMBER	KMT213GHFLFG
Lead free / ROHS Compliant ATA SHEET ERMINATION STYLE GUII Wing WITCH TRAVEL 0.13mm Off-Mom WITCH FUNCTION Off-Mom ACKAGING Tape & Reel (TR) 3.00mm x 2.60mm MITCH STYLE OUTLINE 3.00mm x 2.60mm MITCH PLFG Y34H21310FP ACKAGING OUTLINE 3.00mm x 2.60mm MITCH STYLE WITCH STYLE WITCH STYLE UNITING TEMPERATURE AGOC ~ 125°C DOUGF HOUNTING TYPE SURFACE Mount UNITING TYPE SURFACE MOUNT UNITING TYPE SURFACE MOUNT SECHANICAL LIFE 150,000 Cycles AND FREE STATUS / ROHS STATUS Lead free / ROHS Compliant NORESS PROTECTION - LLUMINATION VOLTAGE (NOMINAL) LLUMINATION VOLTAGE (NOMINAL) EATURES GROUNDING PIN Tactile Switch SPST-NO Top Actuated Surface COULATOR TYPE STANDARD COULATOR ORIENTATION Top Actuated COULATOR ORIENTATION TOP ACTUATOR MATERIAL COULATOR MATERIAL - COULATOR MATERIAL - COULATOR MATERIAL - COULATOR MATERIAL - - - - - - - - - - - - -	MANUFACTURER	C&K
TATA SHEET TERMINATION STYLE GUII Wing UNITCH TRAVEL 0.13mm Off-Mom WITCH FUNCTION Off-Mom ERIES KMT ACKAGING Tape & Reel (TR) 3.00mm x 2.60mm KMT213G HF LFG Y34H21310FP OPERATING TEMPERATURE A0°C ~ 125°C OPERATING TEMPERATURE OUNTING TYPE SURface Mount OUNTING TYPE SURface Mount OUNTING TYPE SURface Mount OUNTING TYPE SURFACE A000 Cycles IANUFACTURER STANDARD LEAD TIME EAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant NORESS PROTECTION - LLUMINATION VOLTAGE (NOMINAL) LLUMINATION VOLTAGE (NOMINAL) LLUMINATION SOPTIAL SENSITIVION TACTILE SWITCH SPST-NO TOP Actuated Surface OUNTACT RATING @ VOLTAGE COUNTACT RATING @ VOL	DESCRIPTION	SWITCH TACTILE SPST-NO 0.01A 32V
Gull Wing WITCH TRAVEL 0.13mm WITCH FUNCTION Off-Mom ERIES KMT ACKAGING Tape & Reel (TR) 3.00mm x 2.60mm KMT213G HF LFG Y34H21310FP PERATING TEMPERATURE -40°C ~ 125°C PERATING TORE FOUNTING TYPE SURface Mount 1 (Unlimited) MECHANICAL LIFE 150,000 Cycles MANUFACTURER STANDARD LEAD TIME 8 Weeks EAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant NGRESS PROTECTION - LLUMINATION VOLTAGE (NOMINAL) LEUMINATION TYPE, COLOR LLUMINATION FACILIZATION FOUNTACT RATING ® VOLTAGE LICUIT SPST-NO CITUATOR ORIENTATION Top Actuated CITUATOR ORIENTATION OFF-Mom Off-Mom KMT Tape & Reel (TR) 3.0mm AMT Tape & Reel (TR) 3.0mm AMT Tape & Reel (TR) 3.0mm AMT Tape & Reel Tape & Reel Top Actuated O.13mm Off-Mom CITUATOR MATERIAL O.13mm Off-Mom CITUATOR MATERIAL O.13mm Off-Mom CITUATOR MATERIAL O.13mm O.13m	LEAD FREE STATUS / ROHS STATUS	Lead free / RoHS Compliant
WITCH FRAVEL WITCH FUNCTION Off-Mom ERIES KMT Tape & Reel (TR) JOUNTINE JOUNTINE JOUNTINE JOUNTING TEMPERATURE JOUNTING TEMPERATURE JOUNTING TYPE JOUNTING TYPE JOUNTING TYPE JOUNTING TYPE JOUNTING TYPE JOUNTING THE SENSITIVITY LEVEL (MSL) JOUNTING TYPE JOUNTING THE SENSITIVITY LEVEL (MSL) JOUNTING TYPE JOUNTING THE SENSITIVITY LEVEL (MSL) JOUNTING TYPE JOUNT SHAPE JOUNT	DATA SHEET	KMT213GHFLFG.pdf
WITCH FUNCTION Off-Mom ERIES KMT ACKAGING Tape & Reel (TR) 3.00mm x 2.60mm MT213G HF LFG Y34H21310FP -40°C ~ 125°C DEFERTING TEMPERATURE -40°C ~ 125°C DEFERTING TOUGH MULTING TYPE SURFACE MOUNT MECHANICAL LIFE 150,000 Cycles MANUFACTURER STANDARD LEAD TIME 8 Weeks EAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant NGRESS PROTECTION - LLUMINATION VOLTAGE (NOMINAL) LUMINATION TYPE, COLOR EATURES Grounding Pin Tactile Switch SPST-NO Top Actuated Surface Mount CONTACT RATING @ VOLTAGE CITUATOR ORIENTATION Top Actuated CITUATOR MATERIAL - OFFICIAL CITUATOR MATERIAL - CITUATOR MATERIAL - OFFICIAL CITUATOR MATERIAL - - - - - - - - - - - - -	TERMINATION STYLE	Gull Wing
KMT ACKAGING Tape & Reel (TR) 3.00mm x 2.60mm KMT213G HF LFG Y34H21310FP -40°C ~ 125°C DEFRATING TEMPERATURE 40°C ~ 125°C DEFRATING FORCE TOUNTING TYPE MOISTURE SENSITIVITY LEVEL (MSL) MICHANICAL LIFE 150,000 Cycles MANUFACTURER STANDARD LEAD TIME 8 Weeks EAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant NGRESS PROTECTION LILUMINATION VOLTAGE (NOMINAL) LELUMINATION TYPE, COLOR EATURES Grounding Pin Tactile Switch SPST-NO Top Actuated Surface Medical Country PE COUNTACT RATING ® VOLTAGE COUNTACT RATING ® VOLTAGE COUNTACT RATING ® VOLTAGE COUNTACT RATING ® VOLTAGE COUNTACT ORIENTATION Top Actuated COUNTACT NATERIAL - COUNTACT MATERIAL - COUNTACT MATERIAL	SWITCH TRAVEL	0.13mm
Tape & Reel (TR) 3.00mm x 2.60mm KMT213G HF LFG Y34H21310FP A0°C ~ 125°C DPERATING TEMPERATURE 40°C ~ 125°C DIVIDING TYPE Surface Mount 1 (Unlimited) 1 (Unlimited	SWITCH FUNCTION	Off-Mom
AUTLINE 3.00mm x 2.60mm KMT213G HF LFG Y34H21310FP PPERATING TEMPERATURE -40°C ~ 125°C DPERATING FORCE 100gf MOUNTING TYPE Surface Mount MISTURE SENSITIVITY LEVEL (MSL) MECHANICAL LIFE 150,000 Cycles MANUFACTURER STANDARD LEAD TIME 8 Weeks EAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant NGRESS PROTECTION - LLUMINATION VOLTAGE (NOMINAL) LLUMINATION TYPE, COLOR EATURES Grounding Pin Tactile Switch SPST-NO Top Actuated Surface Me CONTACT RATING @ VOLTAGE COUTACT RATING @ VOLTAGE COUTACT RATING @ VOLTAGE COUTACT ORIENTATION Top Actuated COUTACT MATERIAL - 3.00mm x 2.60mm KMT213G HF LFG Y34H21310FP Y34H21310F	SERIES	KMT
KMT213G HF LFG Y34H21310FP PPERATING TEMPERATURE -40°C ~ 125°C 100gf 100urting type Surface Mount 10isture sensitivity level (MSL) 1 (Unlimited) 150,000 Cycles 14ANUFACTURER STANDARD LEAD TIME 8 Weeks EAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant NGRESS PROTECTION - LLUMINATION VOLTAGE (NOMINAL) LEUMINATION TYPE, COLOR EATURES Grounding Pin Tactile Switch SPST-NO Top Actuated Surface Me CONTACT RATING @ VOLTAGE CITUATOR TYPE Standard CTUATOR MATERIAL - KMT213G HF LFG Y34H21310FP -40°C ~ 125°C 100gf 10undinity 10und	PACKAGING	Tape & Reel (TR)
Y34H21310FP PERATING TEMPERATURE -40°C ~ 125°C DEFERATING FORCE 100gf SURFACE Mount 10INTING TYPE SURFACE Mount 1 (Unlimited) 1ECHANICAL LIFE 150,000 Cycles 1ANUFACTURER STANDARD LEAD TIME 8 Weeks EAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant NGRESS PROTECTION - LLUMINATION VOLTAGE (NOMINAL) LLUMINATION TYPE, COLOR LLUMINATION NOn-Illuminated Grounding Pin Tactile Switch SPST-NO Top Actuated Surface Mount CONTACT RATING @ VOLTAGE CULUATOR TYPE Standard Top Actuated CCTUATOR MATERIAL - 100gf Surface Mount 1 (Unlimited) 1 (Unlimite	OUTLINE	3.00mm x 2.60mm
DPERATING FORCE 100JTING TYPE Surface Mount 100JSTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) 150,000 Cycles 150,000 Cycle	OTHER NAMES	
Surface Mount 10 ISTURE SENSITIVITY LEVEL (MSL) 11 (Unlimited) 150,000 Cycles 150,000 Cycl	OPERATING TEMPERATURE	-40°C ∼ 125°C
1 (Unlimited) 2 (Unlimited) 1 (Unl	OPERATING FORCE	100gf
INTERCHANICAL LIFE 150,000 Cycles 8 Weeks EAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant	MOUNTING TYPE	Surface Mount
ANNUFACTURER STANDARD LEAD TIME EAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant - LLUMINATION VOLTAGE (NOMINAL) - LLUMINATION TYPE, COLOR LLUMINATION EATURES Grounding Pin Tactile Switch SPST-NO Top Actuated Surface Month Contact Rating @ Voltage CONTACT RATING @ Voltage CONTACT RATING @ Voltage COUTAGE SERICUIT SPST-NO COUTAGE Standard COUTAGE Standard COUTAGE TOP Actuated COUTAGE STANDARD COUTAG	MOISTURE SENSITIVITY LEVEL (MSL)	1 (Unlimited)
Lead free / RoHS Compliant NGRESS PROTECTION - LLUMINATION VOLTAGE (NOMINAL) - LLUMINATION TYPE, COLOR - LLUMINATION EATURES Grounding Pin Tactile Switch SPST-NO Top Actuated Surface Metalogy CONTACT RATING @ VOLTAGE CIRCUIT SPST-NO CITUATOR TYPE Standard COULTAGE CO	MECHANICAL LIFE	150,000 Cycles
NGRESS PROTECTION LLUMINATION VOLTAGE (NOMINAL) LLUMINATION TYPE, COLOR - LLUMINATION Non-Illuminated Grounding Pin Tactile Switch SPST-NO Top Actuated Surface Monotonia (Countage) CONTACT RATING @ VOLTAGE CONTACT RATING @ VOLTAGE COUNTACT RATION COUNTACT TYPE Standard COUNTACT ORIENTATION Top Actuated COUNTACT MATERIAL - COUNTACT MATERIAL	MANUFACTURER STANDARD LEAD TIME	8 Weeks
LLUMINATION VOLTAGE (NOMINAL) LLUMINATION TYPE, COLOR LLUMINATION Non-Illuminated FEATURES Grounding Pin Tactile Switch SPST-NO Top Actuated Surface Monoportation Setation of the surface of the s	LEAD FREE STATUS / ROHS STATUS	Lead free / RoHS Compliant
LLUMINATION TYPE, COLOR CEATURES Grounding Pin Tactile Switch SPST-NO Top Actuated Surface Moreontact Rating @ VOLTAGE CONTACT RATING @ VOLTAGE CIRCUIT SPST-NO COUNTACT TYPE Standard COUNTACT ORIENTATION Top Actuated COUNTACT ORIENTATION Top Actuated COUNTACT RATING @ VOLTAGE	INGRESS PROTECTION	-
Non-Illuminated EATURES Grounding Pin Tactile Switch SPST-NO Top Actuated Surface Months and the surface Months	ILLUMINATION VOLTAGE (NOMINAL)	-
Grounding Pin Tactile Switch SPST-NO Top Actuated Surface Moreon Top Actuated CONTACT RATING @ VOLTAGE CONTACT RATING @ VOLTAGE SPST-NO STRCUIT SPST-NO Standard Top Actuated COULTON MATERIAL	LLUMINATION TYPE, COLOR	-
Tactile Switch SPST-NO Top Actuated Surface Months and Surface Months	ILLUMINATION	Non-Illuminated
CONTACT RATING @ VOLTAGE CONTACT RATING RATI	FEATURES	Grounding Pin
SPST-NO SCTUATOR TYPE Standard Top Actuated CTUATOR MATERIAL -	DETAILED DESCRIPTION	Tactile Switch SPST-NO Top Actuated Surface M
CCTUATOR TYPE Standard CCTUATOR ORIENTATION Top Actuated CCTUATOR MATERIAL -	CONTACT RATING @ VOLTAGE	0.01A @ 32VDC
CTUATOR ORIENTATION Top Actuated CTUATOR MATERIAL -	CIRCUIT	SPST-NO
CTUATOR MATERIAL -	ACTUATOR TYPE	Standard
	ACTUATOR ORIENTATION	Top Actuated
CTUATOR LENGTH, RIGHT ANGLE -	ACTUATOR MATERIAL	-
	ACTUATOR LENGTH, RIGHT ANGLE	-

Related Tags

0.65mm

C&K KMT213GHFLFG	KMT213GHFLFG Distributor	KMT213GHFLFG Supplier
KMT213GHFLFG Price	KMT213GHFLFG Pictures	KMT213GHFLFG Image
KMT213GHFLFG PDF Datasheet	KMT213GHFLFG Download Datasheet	KMT213GHFLFG Datasheet
KMT213GHFLFG Stock	Buy KMT213GHFLFG	Buy C&K KMT213GHFLFG
C&K KMT213GHFLFG	C&K Supplier	C&K Distributor
C&K KMT213GHFLFG	C&K Components KMT213GHFLFG	

Related Products



KMT221NG HF LFS

Manufacturers: C&K

ACTUATOR HEIGHT OFF PCB, VERTICAL

Description: SWITCH TACTILE SPST-NO 0.05A 32V

In stock: Out stock **RFQ**



KMT15-51212

Manufacturers: TDK-Lambda Americas, Inc. Description: PWR SUP MEDICAL 5V/+12V/-12V 15W

In stock: 48 pcs

RFQ



KMT0D1NGJLHS

Manufacturers: C&K Description: SWITCH TACTILE In stock: Out stock

RFQ



KMT40-51212

Manufacturers: TDK-Lambda Americas, Inc. Description: PWR SUP MEDICAL 5V/+12V/-12V 40W

In stock: 14 pcs **RFQ**



KMT223GHFLFG Manufacturers: C&K

Description: SWITCH TACTILE SPST-NO 0.01A 32V In stock: Out stock

Manufacturers: TDK-Lambda Americas, Inc.

RFQ



KMT221G HF LFS

Manufacturers: C&K Description: SWITCH TACTILE SPST-NO 0.05A 32V

In stock: Out stock

RFQ



KMT15-51515

Description: PWR SUP MEDICAL 5V/+15V/-15V 15W In stock: 141 pcs

RFQ



KMT223NGHFLFG Manufacturers: C&K

Description: SWITCH TACTILE SPST-NO 0.01A 32V In stock: Out stock

RFQ



KMT211NG HF LFS

Manufacturers: C&K

Description: SWITCH TACTILE SPST-NO 0.05A 32V In stock: Out stock

RFQ



Manufacturers: C&K

Description: SWITCH TACTILE SPST-NO 0.01A 32V In stock: Out stock

KMT213NGHFLFG

RFQ



KMT211G HF LFS

Manufacturers: C&K Description: SWITCH TACTILE SPST-NO 0.05A 32V In stock: Out stock

RFQ



KMT072NGJLHS Manufacturers: C&K

Description: SWITCH TACTILE SPST-NO 0.05A 32V

RFQ

In stock: Out stock









