



Image may be representation. See specifications for product details.

DC1C-A1RB

Part Number:

Manufacturer/Brand:

Product description

RoHs Status

Datasheets:

Ship From Shipment Way DC1C-A1RB

Cherry Switches (ZF Electronics)

SWITCH SNAP ACTION SPDT 5A 125V

DC1C-A1RB.pdf

Lead free / RoHS Compliant Hong Kong

DHL/Fedex/TNT/UPS/EMS

REQUEST FOR QUOTATION

CART NUMBER DCIC-AIRB Cherry Switches (ZF Electronics) SWITCH SNAP ACTION SPDT 5A 125V Lead free / ROHS Compliant DESCRIPTION SWITCH SNAP ACTION SPDT 5A 125V Lead free / ROHS Compliant DCIC-AIRB.pdf AND ACTION SPDT 5A 125V Lead free / ROHS Compliant DCIC-AIRB.pdf AND ACTION SPDT 5A 125V Lead free / ROHS Compliant DCIC-AIRB.pdf AND ACTION SPDT 5A 125V Lead free / ROHS Compliant DCIC-AIRB.pdf AND ACTION SPDT 5A 125V Lead free / ROHS Compliant DCIC-AIRB.pdf AND ACTION SPDT 5A 125V Lead free / ROHS COMPLIANCE DCIC-AIRB.pdf AND ACTION SPDT 5A 125V Lead free / ROHS COMPLIANCE DCIC-AIRB.pdf AND ACTION SPDT 5A 125V Lead free / ROHS COMPLIANCE Lead Free / ROHS Compliant DURRENT RATING SA (AC), LA (DC) DEPARTING TAING SA (AC), LA (DC)		Specifications of DC1C-A1RB
AMUFACTURER Cherry Switches (2F Electronics) SWITCH SNAP ACTION SPDT 5A 125V Lead free / RoHS Compliant DATA SHEET DE DCIC-AIRB.pdf DC		Specifications of Determination
SWITCH SNAP ACTION SPDT SA 125V	PART NUMBER	DC1C-A1RB
Lead free / RoHS Compliant DATA SHEET DATA SHEET DATA SHEET DOLC-AIRB.pdf ABW COLTAGE RATING - DC 48W COLTAGE RATING - AC 125V CERMINATION STYLE Solder Lug DOC CELEASE FORCE DC RELEASE FORCE CRETAVEL 0.178" (4.5mm) CACKAGING Bulk COLTAGE RATING - AC CRETAVEL 0.060" (1.5mm) CHEGG COLTABB COLTA	MANUFACTURER	Cherry Switches (ZF Electronics)
CATA SHEET CDCC-ATRB.pdf VOLTAGE RATING - DC 48V VOLTAGE RATING - AC 125V SERMINATION STYLE Solder Lug SWITCH FUNCTION On-Mom SERIES DC RELEASE FORCE - PRETAVEL 0.178" (4.5mm) PACKAGING Bulk OVERTRAVEL 0.060" (1.5mm) OTHER NAMES CH606 OPERATING TEMPERATURE -40°C ~ 120°C OPERATING FORCE 92gf MOUNTING TYPE Chassis Mount MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) MECHANICAL LIFE 1,000,000 Cycles MANUFACTURER STANDARD LEAD TIME 39 Weeks LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant NGRESS PROTECTION 1P67 - Dust Tight, Waterproof PERATURES - SECURITY ACTURER 6,000 Cycles SUFFERENTIAL TRAVEL 0.020" (0.5mm) SURRENT RATING SA (AC), 1A (DC)	DESCRIPTION	SWITCH SNAP ACTION SPDT 5A 125V
ABY ABY ABY ABY ABY ABY ABY ABY	LEAD FREE STATUS / ROHS STATUS	Lead free / RoHS Compliant
FERMINATION STYLE Solder Lug On-Mom On-Mom SERIES DC RELEASE FORCE	DATA SHEET	DC1C-A1RB.pdf
Solder Lug On-Mom On-Mom DC RELEASE FORCE RELEASE FORCE RETRAVEL O.178" (4.5mm) DOCACKAGING BUIK OVERTRAVEL O.060" (1.5mm) OTHER NAMES OPERATING TEMPERATURE OPERATING POSITION ORGEN OPERATING FORCE OPERATING FORCE OPERATING FORCE OPERATING FORCE OPERATING FORCE OPERATING SOLDE OPERATING FORCE OPERATING FORCE OPERATING FORCE OPERATING FORCE OPERATING SOLDE OPERATURE OPERA	VOLTAGE RATING - DC	48V
On-Mom SERIES DC SERIES DC SERIES CO.178" (4.5mm) SPETRAVEL CO.178" (4.5mm) SPETRATING TEMPERATURE CO.178" (4.5mm) SPETRATING TEMPERATURE CO.178" (4.5mm) SPETRATING POSITION CO.178" (4.5mm) SPETRATING POSITION CO.178" (4.5mm) SPETRATING POSITION CO.178" (4.5mm) SPETRATING PORCE SPETRATIVITY LEVEL (MSL) (4.6mm) SPETRATING FORCE SPETRATIVITY LEVEL (MSL) (4.6mm) SPETRATING PORCE CO.178" (4.5mm) SPETRATIVITY LEVEL (MSL) (4.5mm) SPETRATIVE (4.5mm) SPETRATIVE (4.5mm) SPETRATIVE (4.5mm) SPETRATIVE (4.5mm) SPETRATIVE (4.5mm) SPETRAT	VOLTAGE RATING - AC	125V
DC RELEASE FORCE ROLL 158mm) ROLL 158mm) ROLL 158mm) ROPERATING TEMPERATURE A0°C ~ 120°C ROLL 15.8mm) ROPERATING FORCE ROLL 15.8mm) ROLL	TERMINATION STYLE	Solder Lug
RELEASE FORCE PRETRAVEL 0.178" (4.5mm) Bulk OVERTRAVEL 0.060" (1.5mm) OTHER NAMES OPERATING TEMPERATURE -40°C ~ 120°C OPERATING POSITION 0.622" (15.8mm) OPERATING FORCE 92gf OUNITING TYPE Chassis Mount I (Unlimited) MICCHANICAL LIFE MANUFACTURER SENSITIVITY LEVEL (MSL) I (Unlimited) MECHANICAL LIFE MANUFACTURER STANDARD LEAD TIME BEAD FREE STATUS / ROHS STATUS LEAD FREE STATUS / ROHS STATU	SWITCH FUNCTION	On-Mom
PRETRAVEL ACKAGING Bulk COVERTRAVEL 0.060" (1.5mm) CHHER NAMES CHHER NAMES CHERATURE -40°C ~ 120°C CHERATURE POSITION 0.622" (15.8mm) CHERATURE POSITION 0.622" (15.8mm) CHERATURE SENSITIVITY LEVEL (MSL) MECHANICAL LIFE MANUFACTURER STANDARD LEAD TIME JAMAUFACTURER STANDARD LEAD TIME JEAD FREE STATUS / ROHS STATUS LEAD FREE STATUS	SERIES	DC
Bulk OVERTRAVEL O.060" (1.5mm) CH606 DC1CA1RB ODERATING TEMPERATURE OPERATING TEMPERATURE OPERATING POSITION OE2" (15.8mm) OPERATING FORCE 92gf MOUNTING TYPE Chassis Mount I (Unlimited) I	RELEASE FORCE	-
DVERTRAVEL OLGON OTHER NAMES OPERATING TEMPERATURE 40°C ~ 120°C OPERATING POSITION OLEZ" (15.8mm) OPERATING FORCE OPERATING FORCE OLOUNTING TYPE Chassis Mount (IUIIImited) (IUCIIIMITED) (IUCIIMITED) (IUCIIMITED) (IUCIIMITED) (IUCI	PRETRAVEL	0.178" (4.5mm)
CH606 DC1CA1RB PERATING TEMPERATURE 40°C ~ 120°C DEPERATING POSITION 0.622" (15.8mm) DEPERATING FORCE 92gf MOUNTING TYPE Chassis Mount 1 (Unlimited) MECHANICAL LIFE 1,000,000 Cycles MANUFACTURER STANDARD LEAD TIME 39 Weeks LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant NGRESS PROTECTION 1P67 - Dust Tight, Waterproof LEATURES LECTRICAL LIFE 6,000 Cycles DIFFERENTIAL TRAVEL 0.020" (0.5mm) DEPERATING SPDT CHICKITE SPDT	PACKAGING	Bulk
DCICAIRB PERATING TEMPERATURE -40°C ~ 120°C DEPERATING POSITION 0.622" (15.8mm) PERATING FORCE 92gf MOUNTING TYPE Chassis Mount (MOISTURE SENSITIVITY LEVEL (MSL) MECHANICAL LIFE 1,000,000 Cycles MANUFACTURER STANDARD LEAD TIME 39 Weeks LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant NGRESS PROTECTION 1P67 - Dust Tight, Waterproof EATURES LECTRICAL LIFE 6,000 Cycles DIFFERENTIAL TRAVEL 0.020" (0.5mm) DURRENT RATING 5A (AC), 1A (DC) SPDT	OVERTRAVEL	0.060" (1.5mm)
DPERATING POSITION DPERATING FORCE POSITION DEPERATING FORCE DISPERATING POSITION DISPE	OTHER NAMES	
PERATING FORCE 92gf MOUNTING TYPE Chassis Mount MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) MECHANICAL LIFE 1,000,000 Cycles MANUFACTURER STANDARD LEAD TIME 39 Weeks LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant NGRESS PROTECTION 1P67 - Dust Tight, Waterproof EATURES	OPERATING TEMPERATURE	-40°C ~ 120°C
Chassis Mount MOUNTING TYPE Chassis Mount (MOISTURE SENSITIVITY LEVEL (MSL) (MOUNTING TYPE) (MOUNTING T	OPERATING POSITION	0.622" (15.8mm)
MOISTURE SENSITIVITY LEVEL (MSL) MECHANICAL LIFE 1,000,000 Cycles MANUFACTURER STANDARD LEAD TIME 39 Weeks LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant NGRESS PROTECTION 1P67 - Dust Tight, Waterproof FEATURES LECTRICAL LIFE 6,000 Cycles 0.020" (0.5mm) CURRENT RATING 5A (AC), 1A (DC) SPDT	OPERATING FORCE	92gf
MECHANICAL LIFE MANUFACTURER STANDARD LEAD TIME MANUFACTURER STATUS / ROHS STATUS Lead free / RoHS Compliant NGRESS PROTECTION PF67 - Dust Tight, Waterproof ELECTRICAL LIFE 6,000 Cycles DIFFERENTIAL TRAVEL 0.020" (0.5mm) CURRENT RATING SPDT	MOUNTING TYPE	Chassis Mount
MANUFACTURER STANDARD LEAD TIME 39 Weeks Lead free / RoHS Compliant NGRESS PROTECTION IP67 - Dust Tight, Waterproof FEATURES - ELECTRICAL LIFE 6,000 Cycles OLIFFERENTIAL TRAVEL OLIVERIA TRATING 5A (AC), 1A (DC) SPDT	MOISTURE SENSITIVITY LEVEL (MSL)	1 (Unlimited)
Lead free / RoHS Compliant NGRESS PROTECTION IP67 - Dust Tight, Waterproof FEATURES - ELECTRICAL LIFE OLOFFERENTIAL TRAVEL CURRENT RATING ELECTRICAL SPDT SPDT	MECHANICAL LIFE	1,000,000 Cycles
IP67 - Dust Tight, Waterproof FEATURES - ELECTRICAL LIFE 6,000 Cycles DIFFERENTIAL TRAVEL 0.020" (0.5mm) CURRENT RATING 5A (AC), 1A (DC) ELECTRICAL LIFE SPDT	MANUFACTURER STANDARD LEAD TIME	39 Weeks
FEATURES - 6,000 Cycles DIFFERENTIAL TRAVEL 0.020" (0.5mm) CURRENT RATING 5A (AC), 1A (DC) CIRCUIT SPDT	LEAD FREE STATUS / ROHS STATUS	Lead free / RoHS Compliant
ELECTRICAL LIFE 6,000 Cycles 0.020" (0.5mm) CURRENT RATING 5A (AC), 1A (DC) EIRCUIT SPDT	INGRESS PROTECTION	IP67 - Dust Tight, Waterproof
OLIFFERENTIAL TRAVEL OLOGO (0.5mm) SURRENT RATING SA (AC), 1A (DC) SPDT	FEATURES	-
CURRENT RATING 5A (AC), 1A (DC) CIRCUIT SPDT	ELECTRICAL LIFE	6,000 Cycles
CIRCUIT SPDT	DIFFERENTIAL TRAVEL	0.020" (0.5mm)
	CURRENT RATING	5A (AC), 1A (DC)
ACTUATOR TYPE Lever, Roller	CIRCUIT	SPDT
·	ACTUATOR TYPE	Lever, Roller

Related Tags

Cherry Switches (ZF Electronics) DC1C-A1RB	DC1C-A1RB Distributor	DC1C-A1RB Supplier
DC1C-A1RB Price	DC1C-A1RB Pictures	DC1C-A1RB Image
DC1C-A1RB PDF Datasheet	DC1C-A1RB Download Datasheet	DC1C-A1RB Datasheet
DC1C-A1RB Stock	Buy DC1C-A1RB	Buy Cherry Switches (ZF Electronics) DC1C-A1RB
Cherry Switches (ZF Electronics) DC1C-A1RB	Cherry Switches (ZF Electronics) Supplier	Cherry Switches (ZF Electronics) Distributor
Cherry Switches (ZF Electronics) DC1C-A1RB	Cherry Switches (ZF Electronics) DC1C-A1RB	ZF Electronics DC1C-A1RB

Related Products



DC1997A-B

Manufacturers: ADI (Analog Devices, Inc.) Description: BOARD EVAL FOR LTC3838EUHF

In stock: 2 pcs

RFQ



DC19977-3

Manufacturers: Cinch Connectivity Solutions Description: PART HAS BEEN DISCONTINUED

In stock: Out stock

RFQ



DC1996A-F

Manufacturers: ADI (Analog Devices, Inc.) Description: BOARD EVAL FOR LTC2321-12

In stock: 3 pcs

RFQ



DC1997A-A

Manufacturers: ADI (Analog Devices, Inc.) Description: BOARD EVAL FOR LTC3838EUHF

In stock: 2 pcs

RFQ



DC1999A

Manufacturers: ADI (Analog Devices, Inc.) Description: LTC3111 DEMO BOARD

In stock: 2 pcs

RFQ



DC1DVISST30300B

Description: HARNESS HDMI/DVI In stock: Out stock

Manufacturers: JAE Electronics, Inc.

RFQ



Manufacturers: ADI (Analog Devices, Inc.)

Description: BOARD EVAL FOR LTC2323-12

In stock: 3 pcs

RFQ



Manufacturers: JAE Electronics, Inc. Description: CABLE HDMI 1.5M AWG30 In stock: 151 pcs

RFQ



DC1996A-D Manufacturers: ADI (Analog Devices, Inc.)

Description: BOARD EVAL FOR LTC2321-14 In stock: 3 pcs

RFQ



DC19977-3

Manufacturers: Cannon Description: DSUB DC METAL B/S 90 D CAD In stock: Out stock

RFQ



DC1C-A1AA

Manufacturers: Cherry Switches (ZF Electronics) Description: SWITCH SNAP ACTION SPDT 5A 125V In stock: Out stock

RFQ



DC1C-A1LB

In stock: Out stock

Manufacturers: Cherry Switches (ZF Electronics)

Description: SWITCH SNAP ACTION SPDT 5A 125V

RFQ













