SI8382PF-IU Details PDF





product details.

Energy Micro (Silicon Labs)



Image may be representation. See specifications for

RoHs Status

Ship From

Datasheets:

Shipment Way

Part Number:

SI8382PF-IU

Manufacturer/Brand:

Product description

SI8382PF-IU Energy Micro (Silicon Labs) DGTL ISO 2.5KV 8CH 20QSOP SI8382PF-IU.pdf Lead free / RoHS Compliant Hong Kong DHL/Fedex/TNT/UPS/EMS


REQUEST FOR QUOTATION

THER NAMES336-3622-5PERATING TEMPERATURE-40°C ~ 125°CJMBER OF CHANNELS8OUNTING TYPESurface MountOUNTING TYPE6 (Time on Labe)ANUFACTURER STANDARD LEAD TIME6 WeeksAD FREE STATUS / ROHS STATUSLead free / ROHOLATED POWERNoPUTS - SIDE 1/SIDE 28/0ETAILED DESCRIPTIONGeneral Purpose	8CH 20QSOP Compliant
ANUFACTURER Energy Micro (S ESCRIPTION DGTL ISO 2.5KV AD FREE STATUS / ROHS STATUS Lead free / ROH ATA SHEET SIGUATION 2.25 V ~ 5.5 V DLTAGE - SUPPLY 2.25 V ~ 5.5 V DLTAGE - ISOLATION 2.000Vrms PE General Purpose CHNOLOGY Capacitive Coup PIPLIER DEVICE PACKAGE 20-QSOP ERIES SE / FALL TIME (TYP) 3.9ns, 3.7ns SE / FALL TIME (TYP) 3.9ns, 3.7ns CAGAGING 1.000000000000000000000000000000000000	8CH 20QSOP Compliant
ESCRIPTION DETL ISO 2.5KV AD FREE STATUS / ROHS STATUS Lead free / ROH ATA SHEET 2.25 V ~ 5.5 V DUTAGE - SUPPLY 2.25 V ~ 5.5 V DUTAGE - ISOLATION 2.00Vrms PE General Purpose ECHNOLOGY Capacitive Coup IPPLIER DEVICE PACKAGE 20-QSOP IRIES CIPPLIER DEVICE PACKAGE - SUPPLY 3.9ns, 3.7ns RIES WIDTH DISTORTION (MAX) - C CAGGING - C CKAGGING 1.000 CKAGGING 1.0000 CKAGGING 1.000 CKAGGING	8CH 20QSOP Compliant
AD FREE STATUS / ROHS STATUSLead free / RoHATA SHEETSI8382PF-ILALTAGE - SUPPLY2.25 V ~ 5.5 VDLTAGE - ISOLATION2500VrmsPEGeneral PurposeCHNOLOGYCapacitive CoupPPLIER DEVICE PACKAGE20-QSOPRIES-SE / FALL TIME (TYP)3.9ns, 3.7nsJLSE WIDTH DISTORTION (MAX)-CKAGE / CASE20-SSOP (0.154)CKAGE / CASE20-SSOP (0.154)CHARLS336-3622-5PERATING TEMPERATURE40°C ~ 125°CJUBER OF CHANNELS8DUNTING TYPESurface MountDISTURE SENSITIVITY LEVEL (MSL)6 (Time on Labe)AD FREE STATUS / ROHS STATUSLead free / ROHOLATED POWERNoPUTS - SIDE 1/SIDE 28/0ETAILED DESCRIPTIONGeneral Purpose	Compliant
ATA SHEETS18382PF-11ATA SHEET2.25 V ~ 5.5 VALTAGE - SUPPLY2.50 VrmsPEGeneral PurposeCHNOLOGYCapacitive CoupIPPLIER DEVICE PACKAGE20-QSOPRRIES-SE / FALL TIME (TYP)3.9ns, 3.7nsIJSE WIDTH DISTORTION (MAX)-CAGAGATION DELAY TPLH / TPHL (MAX)-CKAGGINGTubeCKAGE / CASE20-SSOP (0.154)THER NAMES336-3622-5VIDBER OF CHANNELS8CUNTING TYPE6 (Time on Labe)CATOR FREE STATUS / ROHS STATUSLead free / ROHOLATED POWERNoPUTS - SIDE 1/SIDE 28/0ETAILED DESCRIPTIONSensal Purpose	
Durage - SUPPLY2.25 V ~ 5.5 VSULTAGE - ISOLATION2500VrmsPEGeneral PurposeCCHNOLOGYCapacitive CoupPPLIER DEVICE PACKAGE20-QSOPRIES-SE / FALL TIME (TYP)3.9ns, 3.7nsJLSE WIDTH DISTORTION (MAX)-CAGAGATION DELAY TPLH / TPHL (MAX)-CKAGE / CASE20-SSOP (0.154CKAGE / CASE36-3622-5PERATING TEMPERATURE36-3622-5DUNTING TYPESurface MountDISTURE SENSITIVITY LEVEL (MSL)6 (Time on LabeANUFACTURER STANDARD LEAD TIME6 WeeksAD FREE STATUS / ROHS STATUSLead free / ROHOLATED POWERNoPUTS - SIDE 1/SIDE 28/0	odf
Dut AGE - ISOLATION2500VrmsPPEGeneral PurposePPLIER DEVICE PACKAGECapacitive CoupPPLIER DEVICE PACKAGE0-QSOPPRLIES-SE / FALL TIME (TYP)3.9ns, 3.7nsSE / FALL TIME (TYP)-SOPAGATION DELAY TPLH / TPHL (MAX)-CKAGE / CASE0-SSOP (0.154)CKAGE / CASE36-3622-5PERATING TEMPERATURE36-3622-5PERATING TEMPERATURE36-3622-5OUNTING TYPESurface MountOLSTURE SENSITIVITY LEVEL (MSL)6 (Time on LabeANUFACTURER STANDARD LEAD TIME6 WeeksAD FREE STATUS / ROHS STATUSLead free / ROHOLATED POWERNoPUTS - SIDE 1/SIDE 28/0	
PPEGeneral PurposeCCNOLOGYCapacitive CoupPPLIER DEVICE PACKAGE20-QSOPRIES-SE / FALL TIME (TYP)3.9ns, 3.7nsJLSE WIDTH DISTORTION (MAX)-COPAGATION DELAY TPLH / TPHL (MAX)-CKAGINGTubeCKAGE / CASE20-SSOP (0.154THER NAMES336-3622-5PERATING TEMPERATURE40°C ~ 125°CJMBER OF CHANNELS8CUNTING TYPESurface MountOLATED POWER6 (Time on LabePUTS - SIDE 1/SIDE 28/0ETATLED DESCRIPTION8/0	
CHNOLOGYCapacitive CoupIPPLIER DEVICE PACKAGE20-QSOPIRIES-SE / FALL TIME (TYP)3.9ns, 3.7nsILSE WIDTH DISTORTION (MAX)-ROPAGATION DELAY TPLH / TPHL (MAX)-RCKAGINGTubeRCKAGING20-SSOP (0.154ACKAGING20-SSOP (0.154MBER OF CHANNELS36-3622-5PERATING TEMPERATURE40°C ~ 125°CJMBER OF CHANNELS8OUNTING TYPESurface MountOLSTURE SENSITIVITY LEVEL (MSL)6 (Time on LabeAD FREE STATUS / ROHS STATUSLead free / ROHOLATED POWERNoPUTS - SIDE 1/SIDE 28/0	
PPPLIER DEVICE PACKAGE20-QSOPRRIES-SE / FALL TIME (TYP)3.9ns, 3.7nsJLSE WIDTH DISTORTION (MAX)-COPAGATION DELAY TPLH / TPHL (MAX)-CKAGINGTubeCKAGE / CASE20-SSOP (0.154)CKAGE / CASE363-3622-5PERATING TEMPERATURE-40°C ~ 125°CJMBER OF CHANNELS8CUNTING TYPESurface MountOLSTURE SENSITIVITY LEVEL (MSL)6 (Time on Labe)AD FREE STATUS / ROHS STATUSLead free / ROHOLATED POWERNoPUTS - SIDE 1/SIDE 28/0ETAILED DESCRIPTIONGeneral Purpose	
RIES-SE / FALL TIME (TYP)3.9ns, 3.7nsSE / FALL TIME (TYP)3.9ns, 3.7nsSILSE WIDTH DISTORTION (MAX)-COPAGATION DELAY TPLH / TPHL (MAX)-COPAGATION DELAY TPLH / TPHL (MAX)-CKAGE / CASE20-SSOP (0.154CKAGE / CASE20-SSOP (0.154CKAGE / CASE336-3622-5PERATING TEMPERATURE-40°C ~ 125°CJMBER OF CHANNELS8OUNTING TYPESurface MountOLSTURE SENSITIVITY LEVEL (MSL)6 (Time on LabeANUFACTURER STANDARD LEAD TIME6 WeeksCOLATED POWERNoPUTS - SIDE 1/SIDE 28/0ETAILED DESCRIPTIONGeneral Purpose	ng
SE / FALL TIME (TYP) 3.9ns, 3.7ns ALSE WIDTH DISTORTION (MAX) - COPAGATION DELAY TPLH / TPHL (MAX) - CACAGGING TUPE ACKAGING UDE ACKAGE / CASE 20-SSOP (0.154 THER NAMES 20-SSOP (0.154 THER NAMES 336-3622-5 PERATING TEMPERATURE 40°C ~ 125°C ADVE ALSE STATUS TEMPERATURE 51 DISTURE SENSITIVITY LEVEL (MSL) 61 AD FREE STATUS / ROHS STATUS 64 AD FREE STATUS / ROHS STATUS 164 AD FREE STATUS / ROHS AD FREE S	
ALSE WIDTH DISTORTION (MAX)	
COPAGATION DELAY TPLH / TPHL (MAX)-ACKAGINGTubeACKAGING20-SSOP (0.154ACKAGE / CASE20-SSOP (0.154ACKAGE / CASE336-3622-5APERATING TEMPERATURE-40°C ~ 125°CJMBER OF CHANNELS8OUNTING TYPESurface MountOLATED POWER6 (Time on LaberANUFACTURER STATUS / ROHS STATUS6 WeeksOLATED POWERNoPUTS - SIDE 1/SIDE 28/0ETAILED DESCRIPTIONGeneral Purpose	
ACKAGING Tube ACKAGE / CASE 20-SSOP (0.154 THER NAMES 36-3622-5 PERATING TEMPERATURE 40°C ~ 125°C DIBER OF CHANNELS 8 DUNTING TYPE 84 ANUFACTURER STANDARD LEAD TIME 60'C (1) ANUFACTURER STANDARD LEAD TIME 60'C (1) ANUFACTURER STANDARD LEAD TIME 10'C (1) ANUFACTURER STANDARD 10'	
ACKAGE / CASE 20-SSOP (0.154 THER NAMES 336-3622-5 PERATING TEMPERATURE -40°C ~ 125°C JMBER OF CHANNELS 8 JUNTING TYPE 8 JUNTING TYPE 6 JUNTING TYPE 6 JUNTING TYPE 6 JUNTING TYPE 6 JUNTING TYPE 6 JUNTING TYPE 7 JUNTING TYPE 7 JUNTI	
THER NAMES336-3622-5PERATING TEMPERATURE-40°C ~ 125°CJMBER OF CHANNELS8OUNTING TYPESurface MountOUNTING TYPE6 (Time on Labe)ANUFACTURER STANDARD LEAD TIME6 WeeksAD FREE STATUS / ROHS STATUSLead free / ROHOLATED POWERNoPUTS - SIDE 1/SIDE 28/0ETAILED DESCRIPTIONGeneral Purpose	
PERATING TEMPERATURE -40°C ~ 125°C JMBER OF CHANNELS 8 OUNTING TYPE SURFACE MOUNT OLSTURE SENSITIVITY LEVEL (MSL) 6 (Time on Labe ANUFACTURER STANDARD LEAD TIME 6 Weeks AD FREE STATUS / ROHS STATUS LEAD TIME 16 Weeks OLATED POWER NO PUTS - SIDE 1/SIDE 2 8/0 ETAILED DESCRIPTION 6 General Purpose	3.90mm Width)
JMBER OF CHANNELS8OUNTING TYPESurface MountOLSTURE SENSITIVITY LEVEL (MSL)6 (Time on LabelANUFACTURER STANDARD LEAD TIME6 WeeksAD FREE STATUS / ROHS STATUSLead free / ROHOLATED POWERNoPUTS - SIDE 1/SIDE 28/0ETAILED DESCRIPTIONGeneral Purpose	
SUNTING TYPESurface MountDISTURE SENSITIVITY LEVEL (MSL)6 (Time on Label 6 WeeksANUFACTURER STANDARD LEAD TIME6 WeeksCAD FREE STATUS / ROHS STATUSLead free / RoHOLATED POWERNoPUTS - SIDE 1/SIDE 28/0ETAILED DESCRIPTIONGeneral Purpose	
DISTURE SENSITIVITY LEVEL (MSL) 6 (Time on Labeled and Lead TIME) ANUFACTURER STANDARD LEAD TIME 6 Weeks AD FREE STATUS / ROHS STATUS Lead free / Roh OLATED POWER No PUTS - SIDE 1/SIDE 2 8/0 ETAILED DESCRIPTION General Purpose	
ANUFACTURER STANDARD LEAD TIME 6 Weeks AD FREE STATUS / ROHS STATUS Lead free / Roh OLATED POWER No PUTS - SIDE 1/SIDE 2 8/0 ETAILED DESCRIPTION General Purpose	
AD FREE STATUS / ROHS STATUS Lead free / RoH OLATED POWER No PUTS - SIDE 1/SIDE 2 8/0 ETAILED DESCRIPTION General Purpose	
OLATED POWER No PUTS - SIDE 1/SIDE 2 8/0 ETAILED DESCRIPTION General Purpose	
PUTS - SIDE 1/SIDE 2 8/0 ETAILED DESCRIPTION General Purpose	
TAILED DESCRIPTION General Purpose	Compliant
	Compliant
	Compliant
ATA RATE 2Mbps	Compliant Digital Isolator 2500Vrms 8 Channel 2Mbps 20-SSOP (0.154", 3.90mm Width)
OMMON MODE TRANSIENT IMMUNITY (MIN) -	
HANNEL TYPE Unidirectional	

Related Tags

Energy Micro (Silicon Labs) SI8382PF-IU	SI8382PF-IU Distributor	SI8382PF-IU Supplier
SI8382PF-IU Price	SI8382PF-IU Pictures	SI8382PF-IU Image
SI8382PF-IU PDF Datasheet	SI8382PF-IU Download Datasheet	SI8382PF-IU Datasheet
SI8382PF-IU Stock	Buy SI8382PF-IU	Buy Energy Micro (Silicon Labs) SI8382PF-IU
Energy Micro (Silicon Labs) SI8382PF-IU	Energy Micro (Silicon Labs) Supplier	Energy Micro (Silicon Labs) Distributor
Energy Micro (Silicon Labs) SI8382PF-IU	Energy Micro SI8382PF-IU	Energy Micro (Silicon Labs) SI8382PF-IU
Silicon Laboratories SI8382PF-IU	Silicon Labs SI8382PF-IU	

Related Products



Manufacturers: Energy Micro (Silicon Labs) Description: DGTL ISO 2.5KV 8CH 20QSOP In stock: 26 pcs



Manufacturers: Energy Micro (Silicon Labs) Description: DGTL ISO 2.5KV 8CH 20QSOP In stock: 668 pcs

RFQ



SI8382PS-IU

RFQ

Manufacturers: Energy Micro (Silicon Labs) Description: DGTL ISO 2.5KV 8CH 20QSOP In stock: 46 pcs

RFQ



SI8382PM-IUR

Manufacturers: Energy Micro (Silicon Labs) Description: DGTL ISO 2.5KV 8CH 20QSOP In stock: Out stock

RFQ



SI8382PS-IUR

SI8384P-IU



Manufacturers: Energy Micro (Silicon Labs) Description: DGTL ISO 2.5KV 8CH 20QSOP In stock: Out stock

RFQ



Manufacturers: Energy Micro (Silicon Labs) Description: DGTL ISO 2.5KV 8CH 20QSOP In stock: 784 pcs

RFQ



SI8380S-IUR

Manufacturers: Energy Micro (Silicon Labs) Description: DGTL ISO 2.5KV 8CH 20QSOP In stock: Out stock

RFQ



SI8382PM-IU

Manufacturers: Energy Micro (Silicon Labs) Description: DGTL ISO 2.5KV 8CH 20QSOP In stock: 46 pcs


RFQ



SI8382P-IUR

Manufacturers: Energy Micro (Silicon Labs) Description: DGTL ISO 2.5KV 8CH 20QSOP In stock: Out stock

RFQ



SI8382PF-IUR

Manufacturers: Energy Micro (Silicon Labs) Description: DGTL ISO 2.5KV 8CH 20QSOP In stock: Out stock

RFQ

Copyright © 2020 Reliable Distributor of Electronic Components - Ocean-Components.com

E-mail: Info@Ocean-Components.com

Address: Room 2102, Connaught Commercial Building, 185 Wan Chai Rd, Wan Chai, Hong Kong

