

C&K

MC00S6NCGF

Part Number:

Manufacturer/Brand:

Product description Datasheets: RoHs Status

Ship From Shipment Way MC00S6NCGF

C&K

SWITCH ROTARY 12POS 250MA 125V

MC00S6NCGF.pdf

Lead free / RoHS Compliant

Hong Kong

DHL/Fedex/TNT/UPS/EMS



REQUEST FOR QUOTATION

Image may be representation. See specifications for product details.

Specifications of MC00S6NCGF

MANUFACTURER C8K DESCRIPTION SWITCH ROTARY 12POS 250MA 125V LEAD FREE STATUS / ROHS STATUS Lead free / RaHS Compliant DATA SHEET ™ MC0056NCGF.pdf VOLTAGE RATING - DC 28V VOLTAGE RATING - AC 125V TERRINATION STYLE PC Pin SERIES M PANNEL CUTOUT DIMENSIONS Circular - 6.60mm Dia OPEPATTING FORCE 2.880 ~ 5.041gfm NUMBER OF POSITIONS 12 NUMBER OF POLES PER DECK 1 MOUNTING TYPE Panel Mount, Through Hole MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) MANUFACTURER STANDARD LEAD TIME 13 Weeks LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant LEAD FREE STATUS / ROHS STATUS Continuous PEATURES PROT - Dust Tight, Waterproof DEPTH BEHIND PANEL 10.42mm CURRENT RATING 250mA (AC/DC) CONTACT TIMING Non-Shorting (BBM) CONTACT TIMING SP12T ANGLE OF THROW 30°		
DESCRIPTION LEAD FREE STATUS / ROHS STATUS LEAD FREE STATUS	PART NUMBER	MC00S6NCGF
LEAD FREE STATUS / ROHS STATUS DATA SHEET VOLTAGE RATING - DC 28V VOLTAGE RATING - AC 125V TERMINATION STYLE PC PIN SERIES M PANEL CUTOUT DIMENSIONS Circular - 6.60mm Dia OPERATING FORCE 2.880 ~ 5.041gfm NUMBER OF POSITIONS 12 NUMBER OF POSITIONS 12 NUMBER OF POSITIONS 12 NUMBER OF POSITIONS 1 1 NUMBER OF FUES PER DECK 1 NUMBIT OF LES PER DECK 1 NOUNTING TYPE Panel Mount, Through Hole MOISTURE SENSITIVITY LEVEL (MSL) 1 1 1 1 1 1 1 1 1 1	MANUFACTURER	C&K
DATA SHEET 28V VOLTAGE RATING - DC 28V VOLTAGE RATING - AC 125V TERMINATION STYLE PC PIn SERIES M PANEL CUTOUT DIMENSIONS Circular - 6.60mm Dia OPERATING FORCE 2.880 ~ 5.041gfm NUMBER OF POSITIONS 12 NUMBER OF DELES PER DECK 1 NUMBER OF DELES PER DECK 1 MOUNTING TYPE Panel Mount, Through Hole MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) MANUFACTURER STANDARD LEAD TIME 13 Weeks LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant LINDEX STOPS Continuous FEATURES 1P67 - Dust Tight, Waterproof DETAILED DESCRIPTION Rotary Switch 12 Position SP12T 250mA (AC/DC) 125VAC Panel Mount, Through Hole DEPTH BEHIND PANEL 10.42mm CURRENT RATING 250mA (AC/DC) CONTACT TIMING Non-Shorting (BBM) CONTACT TIMISH Gold CURRENT FINSH Gold CURRENT FINSH 30°	DESCRIPTION	SWITCH ROTARY 12POS 250MA 125V
VOLTAGE RATING - DC 28V VOLTAGE RATING - AC 125V TERMINATION STYLE PC PIn SERIES M PANEL CUTOUT DIMENSIONS Circular - 6.60mm Dia OPERATING FORCE 2.880 ~ 5.041gfm NUMBER OF POSITIONS 12 NUMBER OF POLES PER DECK 1 MOUNTING TYPE Panel Mount, Through Hole MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) MANUFACTURER STANDARD LEAD TIME 13 Weeks LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant INDEX STOPS Continuous FEATURES 1P67 - Dust Tight, Waterproof DETAILED DESCRIPTION Rotary Switch 12 Position SP12T 250mA (AC/DC) 125VAC Panel Mount, Through Hole DEPTH BEHIND PANEL 10.42mm CURRENT RATING 250mA (AC/DC) CONTACT TIMING Non-Shorting (BBM) CONTACT HATERIAL Copper Alloy CONTACT FINISH Gold COLTACT FINISH Gold CIRCUIT PER DECK \$12T ANALIZED 30°	LEAD FREE STATUS / ROHS STATUS	Lead free / RoHS Compliant
TERMINATION STYLE PC PIN SERIES M PANEL CUTOUT DIMENSIONS CIRCUIAR - 6.60mm Dia OPERATING FORCE 2.880 ~ 5.041 gfm NUMBER OF POSITIONS 12 NUMBER OF POSITIONS 14 NUMBER OF POLES PER DECK 1 NUMBER OF POLES PER DECK 1 MOUNTING TYPE PANEl Mount, Through Hole MOISTURE SENSITIVITY LEVEL (MSL) 13 Weeks LEAD FREE STATUS / ROHS STATUS DETAILED DESCRIPTION ROATS Winkt 12 Position SP12T 250mA (AC/DC) 125VAC Panel Mount, Through Hole DEPTH BEHIND PANEL LURENT RATING CONTACT TIMING CONTACT TIMING CONTACT TIMING CONTACT FINISH Gold CIRCUIT PER DECK ANALE OF THROW 30°	DATA SHEET	MC00S6NCGF.pdf
FERMINATION STYLE SERIES M PANEL CUTOUT DIMENSIONS Circular - 6.60mm Dia OPERATING FORCE 2.880 ~ 5.041 gfm NUMBER OF POSITIONS 12 NUMBER OF POLES PER DECK 1 NUMBER OF DIECKS 1 MOUNTING TYPE Panel Mount, Through Hole MOISTURE SENSITIVITY LEVEL (MSL) 13 Weeks LEAD FREE STATUS / ROHS STATUS LEAD FREE STATUS / ROHS STATUS LEAD FREE STATUS / ROHS STATUS EVERTURES DETAILED DESCRIPTION ROTE TYPE CONTROL ROTE TYPE ROTE TYPE CONTROL ROTE TYPE ROTE TYPE ROTE TYPE CONTROL CURRENT RATING CONTACT TIMING NON-Shorting (BBM) CONTACT FINISH CONTACT FINISH CONTACT FINISH ANGLE OF THROW 30°	VOLTAGE RATING - DC	28V
SERIES M M PANEL CUTOUT DIMENSIONS CIrcular - 6.60mm Dia OPERATING FORCE 2.880 ~ 5.041gfm NUMBER OF POSITIONS 12 NUMBER OF POLES PER DECK 1 NUMBER OF DECKS 1 MOUNTING TYPE PANEL (MSL) 1 (Unlimited) MANUFACTURER STANDARD LEAD TIME 13 Weeks LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant INDEX STOPS Continuous FEATURES 1.967 - Dust Tight, Waterproof DETAILED DESCRIPTION ROTAGNAM 10.42mm CURRENT RATING 2.50mA (AC/DC) CONTACT TIMING CONTACT MATERIAL CONTACT MATERIAL CONTACT MATERIAL CONTACT FINISH Gold CIRCUIT PER DECK 3.00° ANGLE OF THROW 3.0	VOLTAGE RATING - AC	125V
Circular - 6.60mm Dia OPERATING FORCE 2.880 ~ 5.041gfm NUMBER OF POSITIONS 12 NUMBER OF POLES PER DECK 1 NUMBER OF DECKS 1 MOUNTING TYPE MOISTURE SENSITIVITY LEVEL (MSL.) MANUFACTURER STANDARD LEAD TIME LEAD FREE STATUS / ROHS STATUS LEAD FREE STATUS / ROHS STATUS / ROHS ST	TERMINATION STYLE	PC Pin
DEFRATING FORCE DEFRATING DEFRATING DEFRATING CONTACT TIMING CONTACT FINISH CONTACT FIR DECK ANDUBER OF POSITIONS 12 LEAD FRED LEA	SERIES	M
NUMBER OF POLES PER DECK NUMBER OF POLES PER DECK 1 NUMBER OF DECKS 1 MOUNTING TYPE MOISTURE SENSITIVITY LEVEL (MSL) MANUFACTURER STANDARD LEAD TIME LEAD FREE STATUS / ROHS STATUS LEA	PANEL CUTOUT DIMENSIONS	Circular - 6.60mm Dia
NUMBER OF POLES PER DECK NUMBER OF DECKS 1 MOUNTING TYPE MOUNTING TYPE MOUNTING TYPE MOUNTING TYPE MANUFACTURER STANDARD LEAD TIME LEAD FREE STATUS / ROHS STATUS LEAd free / ROHS Compliant LEAD FREE STATUS / ROHS STATUS LEAD FREE STATUS / ROHS	OPERATING FORCE	2.880 ~ 5.041gfm
NUMBER OF DECKS MOUNTING TYPE Panel Mount, Through Hole MOISTURE SENSITIVITY LEVEL (MSL) MANUFACTURER STANDARD LEAD TIME LEAD FREE STATUS / ROHS STATUS LEAd free / ROHS Compliant LEAD FREE STATUS / ROHS STATUS LEAD	NUMBER OF POSITIONS	12
MOUNTING TYPE MOISTURE SENSITIVITY LEVEL (MSL) MANUFACTURER STANDARD LEAD TIME 13 Weeks LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant INDEX STOPS Continuous FEATURES IP67 - Dust Tight, Waterproof DETAILED DESCRIPTION Rotary Switch 12 Position SP12T 250mA (AC/DC) 125VAC Panel Mount, Through Hole DEPTH BEHIND PANEL CURRENT RATING CURRENT RATING CONTACT TIMING Non-Shorting (BBM) CONTACT FINISH CONTACT FINISH Gold CIRCUIT PER DECK ANGLE OF THROW 30°	NUMBER OF POLES PER DECK	1
MOISTURE SENSITIVITY LEVEL (MSL) MANUFACTURER STANDARD LEAD TIME 13 Weeks LEAD FREE STATUS / ROHS STATUS LEAD FREE STATUS / ROHS STATUS /	NUMBER OF DECKS	1
MANUFACTURER STANDARD LEAD TIME 13 Weeks LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant INDEX STOPS Continuous FEATURES IP67 - Dust Tight, Waterproof DETAILED DESCRIPTION Rotary Switch 12 Position SP12T 250mA (AC/DC) 125VAC Panel Mount, Through Hole DEPTH BEHIND PANEL 10.42mm CURRENT RATING 250mA (AC/DC) CONTACT TIMING Non-Shorting (BBM) CONTACT TIMING CONTACT MATERIAL COPPER Alloy CONTACT FINISH GOId CIRCUIT PER DECK SP12T ANGLE OF THROW 30°	MOUNTING TYPE	Panel Mount, Through Hole
Lead free / RoHS Compliant INDEX STOPS Continuous FEATURES IP67 - Dust Tight, Waterproof DETAILED DESCRIPTION Rotary Switch 12 Position SP12T 250mA (AC/DC) 125VAC Panel Mount, Through Hole DEPTH BEHIND PANEL CURRENT RATING CONTACT TIMING Non-Shorting (BBM) CONTACT TIMISH Gold CIRCUIT PER DECK ANGLE OF THROW Lead free / RoHS Compliant Lead free / RoHS Compliant Angle of THROW Lead free / RoHS Compliant Continuous Angle of THROW Lead free / RoHS Compliant Continuous Angle of THROW Lead free / RoHS Compliant Continuous Angle of THROW Lead free / RoHS Compliant Angle of THROW Lead free / RoHS Angle of THROW Lead free / RO	MOISTURE SENSITIVITY LEVEL (MSL)	1 (Unlimited)
INDEX STOPS Continuous FEATURES IP67 - Dust Tight, Waterproof Rotary Switch 12 Position SP12T 250mA (AC/DC) 125VAC Panel Mount, Through Hole DEPTH BEHIND PANEL 10.42mm CURRENT RATING 250mA (AC/DC) CONTACT TIMING Non-Shorting (BBM) CONTACT TATERIAL CONTACT FINISH CONTACT FINISH CIRCUIT PER DECK ANGLE OF THROW CONTACT HARD CONTACT	MANUFACTURER STANDARD LEAD TIME	13 Weeks
FEATURES DETAILED DESCRIPTION Rotary Switch 12 Position SP12T 250mA (AC/DC) 125VAC Panel Mount, Through Hole DEPTH BEHIND PANEL CURRENT RATING CONTACT TIMING CONTACT MATERIAL CONTACT FINISH CIRCUIT PER DECK ANGLE OF THROW IP67 - Dust Tight, Waterproof Rotary Switch 12 Position SP12T 250mA (AC/DC) 125VAC Panel Mount, Through Hole 10.42mm 250mA (AC/DC) 250mA (AC/DC) COPPER MION COPPER MION COPPER MION COPPER MION SP12T ANGLE OF THROW IP67 - Dust Tight, Waterproof Rotary Switch 12 Position SP12T 250mA (AC/DC) 125VAC Panel Mount, Through Hole 10.42mm Copper Mion Sp12T ANGLE OF THROW IP67 - Dust Tight, Waterproof Rotary Switch 12 Position SP12T 250mA (AC/DC) 125VAC Panel Mount, Through Hole 10.42mm Copper Mion Sp12T ANGLE OF THROW IP67 - Dust Tight, Waterproof Rotary Switch 12 Position SP12T 250mA (AC/DC) 125VAC Panel Mount, Through Hole 10.42mm Copper Mion Sp12T ANGLE OF THROW IP67 - Dust Tight, Waterproof Rotary Switch 12 Position SP12T 250mA (AC/DC) 125VAC Panel Mount, Through Hole 10.42mm Copper Mion Sp12T ANGLE OF THROW IP67 - Dust Tight, Waterproof Rotary Switch 12 Position SP12T 250mA (AC/DC) 125VAC Panel Mount, Through Hole COPPER MION Sp12T ANGLE OF THROW IP67 - Dust Tight, Waterproof Rotary Switch 12 Position SP12T 250mA (AC/DC) 125VAC Panel Mount, Through Hole COPPER MION Sp12T ANGLE OF THROW IP67 - Dust Tight, Waterproof Rotary Switch 12 Position SP12T 250mA (AC/DC) 125VAC Panel Mount, Through Hole COPPER MION Sp12T ANGLE OF THROW IP67 - Dust Tight, Waterproof Rotary Switch 12 Position SP12T 250mA (AC/DC) 125VAC Panel Mount, Through Hole Sp12T ANGLE OF THROW IP67 - Dust Tight, Waterproof Sp12T ANGLE OF THROW IP67 - Dust Tight, Waterproof Sp12T ANGLE OF THROW IP67 - Dust Tight, Waterproof IP6	LEAD FREE STATUS / ROHS STATUS	Lead free / RoHS Compliant
DETAILED DESCRIPTION Rotary Switch 12 Position SP12T 250mA (AC/DC) 125VAC Panel Mount, Through Hole DEPTH BEHIND PANEL 10.42mm CURRENT RATING 250mA (AC/DC) CONTACT TIMING Non-Shorting (BBM) CONTACT MATERIAL CONTACT FINISH Gold CIRCUIT PER DECK ANGLE OF THROW Rotary Switch 12 Position SP12T 250mA (AC/DC) 125VAC Panel Mount, Through Hole 10.42mm COMPACT Mount, Through Hole 10.42mm Compac	INDEX STOPS	Continuous
DEPTH BEHIND PANEL CURRENT RATING 250mA (AC/DC) CONTACT TIMING Non-Shorting (BBM) CONTACT FINISH CONTACT FINISH CIRCUIT PER DECK ANGLE OF THROW 10.42mm 250mA (AC/DC) 250	FEATURES	IP67 - Dust Tight, Waterproof
CONTACT TIMING CONTACT TIMING CONTACT MATERIAL CONTACT FINISH CIRCUIT PER DECK ANGLE OF THROW 250mA (AC/DC) Non-Shorting (BBM) Copper Alloy Copper Alloy Gold SP12T ANGLE OF THROW 250mA (AC/DC) Non-Shorting (BBM) Copper Alloy Copper Alloy Sp12T	DETAILED DESCRIPTION	Rotary Switch 12 Position SP12T 250mA (AC/DC) 125VAC Panel Mount, Through Hole
CONTACT TIMING CONTACT MATERIAL CONTACT FINISH CIRCUIT PER DECK ANGLE OF THROW Non-Shorting (BBM) Copper Alloy Gold SP12T 30°	DEPTH BEHIND PANEL	10.42mm
CONTACT MATERIAL Copper Alloy CONTACT FINISH CIRCUIT PER DECK ANGLE OF THROW COPPER Alloy Copper Alloy Gold SP12T 30°	CURRENT RATING	250mA (AC/DC)
CONTACT FINISH CIRCUIT PER DECK ANGLE OF THROW Gold SP12T 30°	CONTACT TIMING	Non-Shorting (BBM)
CIRCUIT PER DECK SP12T ANGLE OF THROW 30°	CONTACT MATERIAL	Copper Alloy
ANGLE OF THROW 30°	CONTACT FINISH	Gold
	CIRCUIT PER DECK	SP12T
ACTUATOR TYPE Round (3.17mm Dia), Slotted	ANGLE OF THROW	30°
	ACTUATOR TYPE	Round (3.17mm Dia), Slotted

Related Tags

13.59mm

C&K MC00S6NCGF	MC00S6NCGF Distributor	MC00S6NCGF Supplier
MC00S6NCGF Price	MC00S6NCGF Pictures	MC00S6NCGF Image
MC00S6NCGF PDF Datasheet	MC00S6NCGF Download Datasheet	MC00S6NCGF Datasheet
MC00S6NCGF Stock	Buy MC00S6NCGF	Buy C&K MC00S6NCGF
C&K MC00S6NCGF	C&K Supplier	C&K Distributor
C&K MC00S6NCGF	C&K Components MC00S6NCGF	

Related Products



ACTUATOR LENGTH

MC00S3NZQD Manufacturers: C&K

Description: SWITCH ROTARY 12POS 250MA 125V In stock: Out stock

RFQ



MC00S1NCGF

Manufacturers: C&K

Description: SWITCH ROTARY 12POS 250MA 125V In stock: Out stock

RFQ



MC00S2NCQF

Manufacturers: C&K

Description: SWITCH ROTARY 12POS 250MA 125V In stock: Out stock

RFQ



MC00S6NCQD

Manufacturers: C&K

Description: SWITCH ROTARY 12POS 250MA 125V In stock: 10 pcs

RFQ



MC010A1

Manufacturers: GE Critical Power

Description: DC DC CONVERTER 5V 10W In stock: Out stock

RFQ



MC00S1NZGF

Manufacturers: C&K Description: SWITCH ROTARY 12POS 250MA 125V

In stock: Out stock

RFQ



MC00S6NCGD Manufacturers: C&K

Description: SWITCH ROTARY 12POS 250MA 125V In stock: Out stock

RFQ



MC00S1NZGD Manufacturers: C&K

Description: SWITCH ROTARY 12POS 250MA 125V

In stock: Out stock

RFQ



MC010B Manufacturers: GE Critical Power

Description: DC DC CONVERTER 12V 10W In stock: Out stock

RFQ



MC016D104KAR Manufacturers: AVX Corporation

Description: CAP CER 0.1UF 6.3V X5R RADIAL In stock: Out stock

RFQ



MC010A Manufacturers: GE Critical Power

Description: DC DC CONVERTER 5V 10W In stock: Out stock

RFQ



MC016C822KAR

Manufacturers: AVX Corporation

Description: CAP CER 8200PF 6.3V X7R RADIAL In stock: Out stock

RFQ













