

Omron Automation & Safety

MK2P-I-AC24

Part Number:

Manufacturer/Brand:

Product description Datasheets:

RoHs Status Ship From

Shipment Way

MK2P-I-AC24.pdf Lead free / RoHS Compliant

MK2P-I-AC24

Hong Kong DHL/Fedex/TNT/UPS/EMS

Omron Automation & Safety

RELAY GEN PURPOSE DPDT 10A 24V

REQUEST FOR QUOTATION

Image may be representation. See specifications for product details.

PART NUMBER MK2P-I-AC24 MANUFACTURER Omron Automation & Safety DESCRIPTION RELAY GEN PURPOSE POPT 10A 24V LEAD FREE STATUS / ROHS STATUS Plug In, 8 Pin (Octai) SWITCHING VOLTAGE (MIN) 7.2 VAC TERMINATION STYLE Plug In, 8 Pin (Octai) SWITCHING VOLTAGE (MIN) SERIES MK RELASE TIME 20ms RELAY TYPE General Purpose PACKAGING Bulk OPERATING TEMPERATURE -10°C40°C OPERATE TIME 20ms MOUNTING TYPE Socketable MOUNTING TYPE SOCKETABLE STATUS / ROHS STATUS Lead free / RoHS Compliant FEATURES MOCHANICAL Indicator DETAILED DESCRIPTION General Purpose Relay DPDT (2 Form C) 24VAC Coil Socketable CONTACT MATERIAL Silver (Ag) CONTACT FORM DPDT (2 Form C) COIL VOLTAGE COIL TYPE NON Labeling COIL TYPE SOCKETABLE Silver (Ag) COIL TYPE NON Labeling COIL TYPE NON Labeling COIL TYPE COIL TYPE SOCKETABLE SHAME Silver (Ag) COIL TYPE NON Labeling COIL TYPE NON Labeling COIL TYPE SOCKETABLE SHAME Silver (Ag) COIL TYPE NON Labeling SILVER SILVE		Specifications of MK2P-I-AC24
MANUFACTURER Omron Automation & Safety DESCRIPTION RELAY GEN PURPOSE DPDT 10A 24V LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant DATA SHEET ■ MKZP-1-ACZ-4.pdf TURN ON VOLTAGE (MAX) 19.2 VAC TURN OFF VOLTAGE (MIN) 7.2 VAC TERMINATION STYLE Plug In, 8 Pin (Octal) SWITCHING VOLTAGE 250VAC, 250VDC - Max SERIES MK RELEASE TIME 20ms RELAY TYPE General Purpose PACKAGING Bulk OTHER NAMES MK2PLAC24 OPERATING TEMPERATURE -10°C ~ 40°C OPERATE TIME 20ms MOUNTING TYPE Socketable MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant FEATURES Mechanical Indicator DETAILED DESCRIPTION General Purpose Relay DPDT (2 Form C) 24VAC Coil Socketable CONTACT BATING (CURRENT) 10A CONTACT FORM DPDT (7 Form C) COIL VOLTAGE 24VAC COIL TYPE N		Specifications of Pikzr 1-Acz+
DESCRIPTION RELAY GEN PURPOSE DPDT 10A 24V LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant DATA SHEET DATA SHEET SHEET DATA	PART NUMBER	MK2P-I-AC24
LEAD FREE STATUS / ROHS STATUS DATA SHEET DATA SHEE	MANUFACTURER	Omron Automation & Safety
DATA SHEET TURN ON VOLTAGE (MAX) 19.2 VAC TURN OFF VOLTAGE (MIN) 7.2 VAC TERMINATION STYLE Plug In, 8 Pin (Octal) SWITCHING VOLTAGE 250VAC, 250VDC - Max SERIES MK RELEASE TIME 20ms RELAY TYPE General Purpose PACKAGING OTHER NAMES MKZPLAC24 OPERATING TEMPERATURE -10°C ~ 40°C OPERATE TIME 20ms MOUNTING TYPE Socketable MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) LEAD FREE STATUS / ROHS STATUS LEAD free TATUS / ROHS STATUS DETAILED DESCRIPTION General Purpose Relay DPDT (2 Form C) 24VAC Coil Socketable CONTACT MATERIAL SINVER (Ag) COIL VOLTAGE 24VAC COIL TYPE Non Latching COIL RESISTANCE 68 Ohms COIL POWER 2.3 VA	DESCRIPTION	RELAY GEN PURPOSE DPDT 10A 24V
TURN ON VOLTAGE (MIXY) 19.2 VAC TURN OFF VOLTAGE (MIN) 7.2 VAC TERMINATION STYLE Plug In, 8 Pin (Octal) SWITCHING VOLTAGE 250VAC, 250VDC - Max SERLES MK RELEASE TIME 20ms RELAY TYPE General Purpose PACKAGING Bulk OTHER NAMES MK2PJAC24 OPERATING TEMPERATURE -10°C ~ 40°C OPERATE TIME 20ms MOUNTING TYPE Socketable MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant FEATURES Mechanical Indicator DETAILED DESCRIPTION General Purpose Relay DPDT (2 Form C) 24VAC Coil Socketable CONTACT RATING (CURRENT) 10A CONTACT MATERIAL Silver (Ag) CONTACT FORM DPDT (2 Form C) COIL VOLTAGE 24VAC COIL TYPE Non Latching COIL RESISTANCE 68 Ohms COIL POWER 2.3 VA	LEAD FREE STATUS / ROHS STATUS	Lead free / RoHS Compliant
TURN OFF VOLTAGE (MIN) 7.2 VAC TERMINATION STYLE Plug In, 8 Pin (Octal) SWITCHING VOLTAGE 250VAC, 250VDC - Max SERIES MK RELEASE TIME 20ms RELAY TYPE General Purpose PACKAGING Bulk OTHER NAMES MK2PLAC24 OPERATING TEMPERATURE -10°C ~ 40°C OPERATE TIME 20ms MOUNTING TYPE Socketable MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant FEATURES Mechanical Indicator DETAILED DESCRIPTION General Purpose Relay DPDT (2 Form C) 24VAC Coil Socketable CONTACT RATING (CURRENT) 10A CONTACT FORM DPDT (2 Form C) COIL VOLTAGE 24VAC COIL TYPE NO LABCHING COIL RESISTANCE 68 Ohms COIL POWER 2.3 VA	DATA SHEET	MK2P-I-AC24.pdf
TERMINATION STYLE Plug In, 8 Pin (Octal) SWITCHING VOLTAGE 250VAC, 250VDC - Max SERIES MK RELEASE TIME 20ms RELAY TYPE General Purpose PACKAGING Bulk OTHER NAMES MK2PIAC24 OPERATING TEMPERATURE -10°C ~ 40°C OPERATE TIME 20ms MOUNTING TYPE Socketable MOISTING TYPE SOCKetable MOISTING TYPE NOHS STATUS Lead free / ROHS Compliant FEATURES Mechanical Indicator DETAILED DESCRIPTION General Purpose Relay DPDT (2 Form C) 24VAC Coil Socketable CONTACT MATERIAL Silver (Ag) CONTACT FORM DPDT (2 Form C) COIL VOLTAGE 24VAC COIL TYPE Non Latching COIL RESISTANCE 68 Ohms COIL POWER 2.3 VA	TURN ON VOLTAGE (MAX)	19.2 VAC
SERIES MK RELEASE TIME 20ms RELAY TYPE General Purpose PACKAGING Bulk OTHER NAMES MK2PIAC24 OPERATING TEMPERATURE -10°C ~ 40°C OPERATE TIME 20ms MOUNTING TYPE Socketable MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compilant FEATURES Mechanical Indicator DETAILED DESCRIPTION General Purpose Relay DPDT (2 Form C) 24VAC Coil Socketable CONTACT MATERIAL Silver (Ag) CONTACT MATERIAL SPORT COIL TYPE NON Latching COIL RESISTANCE 68 Ohms COIL POWER 2.3 VA	TURN OFF VOLTAGE (MIN)	7.2 VAC
SERIES MK RELASE TIME 20ms RELAY TYPE General Purpose PACKAGING Bulk OTHER NAMES MKZPIAC24 OPERATING TEMPERATURE -10°C ~ 40°C OPERATE TIME 20ms MOUNTING TYPE Socketable MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant FEATURES Mechanical Indicator DETAILED DESCRIPTION General Purpose Relay DPDT (2 Form C) 24VAC Coil Socketable CONTACT RATING (CURRENT) 10A CONTACT MATERIAL Silver (Ag) CONTACT FORM DPDT (2 Form C) COIL VOLTAGE 24VAC COIL TYPE NO Latching COIL RESISTANCE 68 Ohms COIL POWER 2.3 VA	TERMINATION STYLE	Plug In, 8 Pin (Octal)
RELAY TYPE General Purpose PACKAGING Bulk OTHER NAMES MKZPIAC24 OPERATING TEMPERATURE -10°C ~ 40°C OPERATE TIME 20ms MOUNTING TYPE Socketable MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant FEATURES Mechanical Indicator DETAILED DESCRIPTION General Purpose Relay DPDT (2 Form C) 24VAC Coil Socketable CONTACT RATING (CURRENT) 10A CONTACT MATERIAL Silver (Ag) CONTACT FORM DPDT (2 Form C) COIL VOLTAGE 24VAC COIL TYPE Non Latching COIL RESISTANCE 68 Ohms COIL POWER 2.3 VA	SWITCHING VOLTAGE	250VAC, 250VDC - Max
RELAY TYPE General Purpose PACKAGING Bulk OTHER NAMES MK2PIAC24 OPERATING TEMPERATURE -10°C ~ 40°C OPERATE TIME 20ms MOUNTING TYPE Socketable MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant FEATURES Mechanical Indicator DETAILED DESCRIPTION General Purpose Relay DPDT (2 Form C) 24VAC Coil Socketable CONTACT RATING (CURRENT) 10A CONTACT MATERIAL Silver (Ag) CONTACT FORM DPDT (2 Form C) COIL VOLTAGE 24VAC COIL TYPE Non Latching COIL RESISTANCE 68 Ohms COIL POWER 2.3 VA	SERIES	MK
PACKAGING OTHER NAMES MK2PIAC24 OPERATING TEMPERATURE -10°C ~ 40°C OPERATE TIME 20ms MOUNTING TYPE Socketable MOISTURE SENSITIVITY LEVEL (MSL) LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant FEATURES Mechanical Indicator DETAILED DESCRIPTION General Purpose Relay DPDT (2 Form C) 24VAC Coil Socketable CONTACT RATING (CURRENT) LONTACT MATERIAL Silver (Ag) CONTACT FORM DPDT (2 Form C) COIL VOLTAGE 24VAC COIL TYPE Non Latching COIL RESISTANCE 68 Ohms COIL POWER	RELEASE TIME	20ms
OTHER NAMES OPERATING TEMPERATURE -10°C ~ 40°C OPERATE TIME 20ms MOUNTING TYPE Socketable MOISTURE SENSITIVITY LEVEL (MSL) LEAD FREE STATUS / ROHS STATUS LEAd free / ROHS Compliant FEATURES Mechanical Indicator DETAILED DESCRIPTION General Purpose Relay DPDT (2 Form C) 24VAC Coil Socketable CONTACT RATING (CURRENT) CONTACT FORM DPDT (2 Form C) COIL VOLTAGE 24VAC COIL TYPE Non Latching COIL RESISTANCE 68 Ohms COIL POWER	RELAY TYPE	General Purpose
OPERATING TEMPERATURE OPERATE TIME 20ms MOUNTING TYPE Socketable MOISTURE SENSITIVITY LEVEL (MSL) LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant FEATURES Mechanical Indicator DETAILED DESCRIPTION General Purpose Relay DPDT (2 Form C) 24VAC Coil Socketable CONTACT RATING (CURRENT) 10A CONTACT FORM DPDT (2 Form C) COIL VOLTAGE 24VAC COIL TYPE Non Latching COIL RESISTANCE 68 Ohms COIL POWER 2.3 VA	PACKAGING	Bulk
OPERATE TIME MOUNTING TYPE Socketable MOISTURE SENSITIVITY LEVEL (MSL) LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant FEATURES Mechanical Indicator DETAILED DESCRIPTION General Purpose Relay DPDT (2 Form C) 24VAC Coil Socketable CONTACT RATING (CURRENT) LOA CONTACT MATERIAL Silver (Ag) CONTACT FORM DPDT (2 Form C) COIL VOLTAGE 24VAC COIL TYPE Non Latching COIL RESISTANCE 68 Ohms COIL POWER 2.3 VA	OTHER NAMES	MK2PIAC24
MOUNTING TYPE SOCKETABLE MOISTURE SENSITIVITY LEVEL (MSL) LEAD FREE STATUS / ROHS STATUS LEAD free / ROHS Compliant FEATURES Mechanical Indicator DETAILED DESCRIPTION General Purpose Relay DPDT (2 Form C) 24VAC Coil Socketable CONTACT RATING (CURRENT) 10A CONTACT MATERIAL Silver (Ag) CONTACT FORM DPDT (2 Form C) COIL VOLTAGE 24VAC COIL TYPE Non Latching COIL RESISTANCE 68 Ohms COIL POWER 2.3 VA	OPERATING TEMPERATURE	-10°C ~ 40°C
MOISTURE SENSITIVITY LEVEL (MSL) LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant FEATURES Mechanical Indicator DETAILED DESCRIPTION General Purpose Relay DPDT (2 Form C) 24VAC Coil Socketable CONTACT RATING (CURRENT) 10A CONTACT MATERIAL Silver (Ag) CONTACT FORM DPDT (2 Form C) COIL VOLTAGE 24VAC COIL TYPE Non Latching COIL POWER 2.3 VA	OPERATE TIME	20ms
LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant FEATURES Mechanical Indicator DETAILED DESCRIPTION General Purpose Relay DPDT (2 Form C) 24VAC Coil Socketable CONTACT RATING (CURRENT) 10A CONTACT MATERIAL Silver (Ag) CONTACT FORM DPDT (2 Form C) COIL VOLTAGE 24VAC COIL TYPE Non Latching COIL RESISTANCE 68 Ohms COIL POWER	MOUNTING TYPE	Socketable
FEATURES Mechanical Indicator General Purpose Relay DPDT (2 Form C) 24VAC Coil Socketable CONTACT RATING (CURRENT) 10A CONTACT MATERIAL Silver (Ag) CONTACT FORM DPDT (2 Form C) COIL VOLTAGE 24VAC COIL TYPE Non Latching COIL RESISTANCE 68 Ohms COIL POWER 2.3 VA	MOISTURE SENSITIVITY LEVEL (MSL)	1 (Unlimited)
DETAILED DESCRIPTION General Purpose Relay DPDT (2 Form C) 24VAC Coil Socketable CONTACT RATING (CURRENT) 10A CONTACT MATERIAL Silver (Ag) CONTACT FORM DPDT (2 Form C) COIL VOLTAGE 24VAC COIL TYPE Non Latching COIL RESISTANCE 68 Ohms COIL POWER 2.3 VA	LEAD FREE STATUS / ROHS STATUS	Lead free / RoHS Compliant
CONTACT RATING (CURRENT) CONTACT MATERIAL Silver (Ag) CONTACT FORM DPDT (2 Form C) COIL VOLTAGE 24VAC COIL TYPE Non Latching COIL RESISTANCE 68 Ohms COIL POWER 2.3 VA	FEATURES	Mechanical Indicator
CONTACT MATERIAL Silver (Ag) CONTACT FORM DPDT (2 Form C) COIL VOLTAGE 24VAC COIL TYPE Non Latching COIL RESISTANCE 68 Ohms COIL POWER 2.3 VA	DETAILED DESCRIPTION	General Purpose Relay DPDT (2 Form C) 24VAC Coil Socketable
CONTACT FORM DPDT (2 Form C) COIL VOLTAGE 24VAC COIL TYPE Non Latching COIL RESISTANCE 68 Ohms COIL POWER 2.3 VA	CONTACT RATING (CURRENT)	10A
COIL VOLTAGE COIL TYPE Non Latching COIL RESISTANCE 68 Ohms COIL POWER 24VAC Non Latching 68 Ohms	CONTACT MATERIAL	Silver (Ag)
COIL TYPE Non Latching COIL RESISTANCE 68 Ohms COIL POWER 2.3 VA	CONTACT FORM	DPDT (2 Form C)
COIL RESISTANCE 68 Ohms COIL POWER 2.3 VA	COIL VOLTAGE	24VAC
COIL POWER 2.3 VA	COIL TYPE	Non Latching
	COIL RESISTANCE	68 Ohms
COIL CURRENT 88.0mA	COIL POWER	2.3 VA
	COIL CURRENT	88.0mA

Related Tags

Omron Automation & Safety MK2P-I-AC24	MK2P-I-AC24 Distributor	MK2P-I-AC24 Supplier
MK2P-I-AC24 Price	MK2P-I-AC24 Pictures	MK2P-I-AC24 Image
MK2P-I-AC24 PDF Datasheet	MK2P-I-AC24 Download Datasheet	MK2P-I-AC24 Datasheet
MK2P-I-AC24 Stock	Buy MK2P-I-AC24	Buy Omron Automation & Safety MK2P-I-AC24
Omron Automation & Safety MK2P-I-AC24	Omron Automation & Safety Supplier	Omron Automation & Safety Distributor
Omron Automation & Safety MK2P-I-AC24	Omron Automation and Safety MK2P-I-AC24	

Related Products



MK2P-I-AC50 Manufacturers: Omron Automation & Safety

Description: RELAY GEN PURPOSE DPDT 10A 50V

In stock: Out stock

RFQ

Description: RELAY GEN PURPOSE DPDT 10A 12V In stock: Out stock

Manufacturers: Omron Automation & Safety

RFQ

MK2P-I-AC12



MK2P-I-AC220

Manufacturers: Omron Automation & Safety Description: RELAY GEN PURPOSE DPDT 10A 220V

In stock: Out stock

RFQ



MK2P-I-AP3 DC24

Manufacturers: Omron Automation & Safety Description: RELAY GEN PURPOSE DPDT 10A 24V In stock: Out stock

RFQ



MK2P-I-AC240 Manufacturers: Omron Automation & Safety

Description: RELAY GEN PURPOSE DPDT 10A 240V

In stock: Out stock **RFQ**



MK2P-I-AC6

Manufacturers: Omron Automation & Safety Description: RELAY GEN PURPOSE DPDT 10A 6V

In stock: Out stock **RFQ**



MK2P-I-AP3 AC24 Manufacturers: Omron Automation & Safety

Description: RELAY GEN PURPOSE DPDT 10A 24V In stock: Out stock

RFQ



MK2P-I-AC110 Manufacturers: Omron Automation & Safety

Description: RELAY GEN PURPOSE DPDT 10A 110V In stock: Out stock

RFQ



MK2P-I-AC100

Description: RELAY GEN PURPOSE DPDT 10A 100V In stock: Out stock

Manufacturers: Omron Automation & Safety

RFQ



MK2P-I DC120 Manufacturers: Omron Automation & Safety

Description: RELAY GEN PURPOSE DPDT 10A 120V In stock: Out stock

RFQ



MK2P-I-AC120 Manufacturers: Omron Automation & Safety

Description: RELAY GEN PURPOSE DPDT 10A 120V In stock: Out stock

RFQ



MK2P-I-AP3 AC120 Manufacturers: Omron Automation & Safety Description: RELAY GEN PURPOSE DPDT 10A 120V

In stock: Out stock **RFQ**



Copyright © 2020 Reliable Distributor of Electronic Components - Ocean-Components.com











