

500SSP3S3M7QEA **😑** • E-Switch Part Number: Manufacturer/Brand: Product description

Datasheets: RoHs Status Ship From Shipment Way 500SSP3S3M7QEA E-Switch

1.500SSP3S3M7QEA.pdf 2.500SSP3S3M7QEA.pdf

SWITCH SLIDE SPDT 5A 120V

Lead free / RoHS Compliant

Hong Kong DHL/Fedex/TNT/UPS/EMS

REQUEST FOR QUOTATION

Image may be representation. See specifications for product details.

PART NUMBER SOSSP3SSM7QEA MANUFACTURER E-SWITCH SWITCH SLIDE SPDT SA 120V LEAD FREE STATUS / ROHS STATUS LEAD FREE SUBJECT / ROHS STATUS LEAD FREE SUBJECT / ROHS STATUS LEAD FREE SUBJECT / ROHS STATUS LEAD FREE STATUS / ROHS STATUS LEAD FREE S		Specifications of 500SSP3S3M7QEA	
MANUFACTURER E-Switch DESCRIPTION SWITCH SLIDE SPOT 5A 120V LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant DATA SHEET 23 1.5005SP33M7QEA.pdf VOLTAGE RATING - DC 28V VOLTAGE RATING - AC 120V SWITCH TRAVEL PC Pin SWITCH FUNCTION On-Off-On SERIES 500 PACKAGING Bulk OPERATING FORCE - OPERATING FORCE - MOUNTING TYPE Through Hole, Right Angle, Vertical MOUNTING TYPE 30,000 Cycles MECHANICAL LIFE 30,000 Cycles MEAN FLUE STATUS / ROHS STATUS Lead free / RoHS Compliant FEATURES EDONY Sealed Terminals ELECTICAL LIFE 30,000 Cycles DETAILED DESCRIPTION Side Switch SPDT Through Hole, Right Angle, Vertical CURRENT RATING Not Specified CONTACT THING Not Specified CONTACT THING Side Switch SPDT Through Hole, Right Angle, Vertical CONTACT THING Sive CONTACT THING Sive			
DESCRIPTION LEAD FREE STATUS / ROHS STATUS LEAD FREE STATUS / ROHS STATUS DATA SHEET DIATA S	PART NUMBER		
Lead free f RoHS Compliant Data SHEET Da	MANUFACTURER	E-Switch	
DATA SHET 1.500SSP3S3M7QEA.pdf VOLTAGE RATING - DC 28V VOLTAGE RATING - AC 120V TERMINATION STYLE PCP IN SWITCH FANVEL 2.16mm SWITCH FANVEL 0n-Off-On SWITCH FUNCTION 0n-Off-On PACKAGING Bulk OPERATING TEMPERATURE -30°C ~ 85°C OPERATING TEMPERATURE 1 (Unlimited) MOUNTING TYPE Through Hole, Right Angle, Vertical MICHANICAL LIFE 30,000 Cycles MANUFACTURER STANDARD LEAD TIME 9 Weels LEED FEES STATUS / ROHS STATUS Lead free / ROHS Compliant EELECTRICAL LIFE 30,000 Cycles EELECTRICAL LIFE 30,000 Cycles EELECTRICAL LIFE 30,000 Cycles ELECTRICAL LIFE 30,000 Cycles CURRENT RATING Silde Switch SPOTT Through Hole, Right Angle, Vertical CURRENT RATING Not Specified CUNTACT TIMING Not Specified CONTACT TIMISH Silver CUNTACT FINISH Silver CRUIT ACTUAL TYPE Standard	DESCRIPTION	SWITCH SLIDE SPDT 5A 120V	
DATA SHEET 2.500SSP3S3M7QEA.pdf VOLTAGE RATING - DC 28V VOLTAGE RATING - AC 120V TERMINATION STYLE PC Pin SWITCH TRAVEL 2.16mm SWITCH FUNCTION 0n-00F-0n SERIES 500 PACKAGING Bulk OPERATING TEMPERATURE -30°C ~ 85°C OPERATING FORCE - MOUNTING TYPE Through Hole, Right Angle, Vertical MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) MECHANICAL LIFE 30,000 Cycles MANUFACTURER STATUS / ROHS STATUS Lead free / RoHS Compliant FEATURES Epoxy Sealed Terminals ELECTRICAL LIFE 30,000 Cycles DETAILED DESCRIPTION Silde Switch SPDT Through Hole, Right Angle, Vertical CURRENT RATING Not Specified CONTACT TIMING Not Specified CONTACT TIMING Copper Alloy CONTACT FINISH Silver CIRCUIT SPDT ACTUATOR TYPE Sandard ACTUATOR MATERIAL Polyamide (PA), Nylon	LEAD FREE STATUS / ROHS STATUS	Lead free / RoHS Compliant	
VOLTAGE RATING - AC 120V TERMINATION STYLE PC Pin SWITCH TRAVEL 2.16mm SWITCH FUNCTION On-Off-On SERIES 500 PACKAGING Bulk OPERATING TEMPERATURE -30°C ~ 85°C OPERATING FORCE - MOUNTING TYPE Through Hole, Right Angle, Vertical MICHANICAL LIFE 30,000 Cycles MANUFACTURER STANDARD LEAD TIME 9 Weeks LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant FEATURES Epoxy Sealed Terminals ELECTRICAL LIFE 30,000 Cycles DETAILED DESCRIPTION Silde Switch SPDT Through Hole, Right Angle, Vertical CURRENT RATING SA (AC/OC) CONTACT TIMING Not Specified CONTACT TIMING Opper Alloy CONTACT FINISH Silver CIRCUIT SPOT ACIUTATOR NYPE Standard ACIUTATOR MATERIAL Spotyminde (PA), Nylon	DATA SHEET	_	
TERMINATION STYLE PC Pin SWITCH TRAVEL 2.16mm SWITCH FUNCTION On-Oif-On SERIES 500 PACKAGING Bulk OPERATING TEMPERATURE -30°C ~ 85°C OPERATING FORCE - MOUNTING TYPE Through Hole, Right Angle, Vertical MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) MECHANICAL LIFE 30,000 Cycles MANUFACTURER STANDARD LEAD TIME 9 Weeks LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant FEATURES Epoxy Sealed Terminals ELECTRICAL LIFE 30,000 Cycles DETAILED DESCRIPTION Sidie Switch SPDT Through Hole, Right Angle, Vertical CURRENT RATING 5M CSpecified CONTACT TIMING Not Specified CONTACT MATERIAL Copper Alloy CONTACT FINISH Silver CICLUIT SPDT ACIUJATOR MATERIAL Stondard ACIUJATOR MATERIAL Polyamide (PA), Nylon	VOLTAGE RATING - DC	28V	
SWITCH TRAVEL 2.16mm SWITCH FUNCTION On-Oif-On SERIES 500 PACKAGING Bulk OPERATING TEMPERATURE -30°C ~ 85°C OPERATING FORCE - MOUNTING TYPE Through Hole, Right Angle, Vertical MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) MECHANICAL LIFE 30,000 Cycles MANUFACTURER STANDARD LEAD TIME 9 Weeks LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant EEATURES Epoxy Seeled Terminals ELECTRICAL LIFE 30,000 Cycles DETAILED DESCRIPTION Sidies Switch SPDT Through Hole, Right Angle, Vertical CURRENT RATING 50 (AC/DC) CONTACT TIMING Not Specified CONTACT MATERIAL Copper Alloy CONTACT FINISH Silver CIUTIAL TOR MATERIAL Sindard ACIUTATOR MATERIAL Foliander (PA), Nylon	VOLTAGE RATING - AC	120V	
SERTIES On-Off-On SERIES 500 PACKAGING Bulk OPERATING TEMPERATURE -30°C ~ 85°C OPERATING FORCE - MOUNTING TYPE Through Hole, Right Angle, Vertical MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) MECHANICAL LIFE 30,000 Cycles MANUFACTURER STANDARD LEAD TIME 9 Weeks LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant FEATURES Epoxy Sealed Terminals ELECTRICAL LIFE 30,000 Cycles DETAILED DESCRIPTION Silde Switch SPDT Through Hole, Right Angle, Vertical CURRENT RATING SA (AC/DC) CONTACT TIMING Not Specified CONTACT TIMING Sopper Alloy CONTACT FINISH Silver CIRCUIT SPDT ACTUATOR TYPE Standard ACTUATOR MATERIAL Polyamide (PA), Nylon	TERMINATION STYLE	PC Pin	
SERIES PACKAGING PACKAGING PACKAGING PACKAGING POPERATING TEMPERATURE -30°C ~ 85°C POPERATING FORCE - MOUNTING TYPE MINOUTHING TYPE MINOUTHING TYPE MINOUTHING TYPE MINOUTHING TYPE MINOUTHING TYPE MANUFACTURES ENSITIVITY LEVEL (MSL) MINOUTHING MECHANICAL LIFE MANUFACTURER STANDARD LEAD TIME BEAG FREE STATUS / ROHS STATUS LEAD FREE STATUS / ROHS STATUS LEAD FREE STATUS / ROHS STATUS LEAD FREE STATUS / ROHS STATUS LECTRICAL LIFE MOUNT IN THE MINOUTH IN THE MINOU	SWITCH TRAVEL	2.16mm	
PACKAGINGBulkOPERATING TEMPERATURE-30°C ~ 85°COPERATING FORCE-MOUNTING TYPEThrough Hole, Right Angle, VerticalMOISTURE SENSITIVITY LEVEL (MSL)1 (Unlimited)MECHANICAL LIFE30,000 CyclesMANUFACTURER STANDARD LEAD TIME9 WeeksLEAD FREE STATUS / ROHS STATUSLead free / ROHS CompliantEELECTRICAL LIFE30,000 CyclesDETAILED DESCRIPTIONSilde Switch SPDT Through Hole, Right Angle, VerticalCURRENT RATINGNot SpecifiedCONTACT TIMINGNot SpecifiedCONTACT TIMISHCOPPER AlloyCONTACT FINISHSilverCIRCUITSPDTACTUATOR TYPEStandardACTUATOR MATERIALPolyamide (PA), Nylon	SWITCH FUNCTION	On-Off-On	
OPERATING TEMPERATURE OPERATING FORCE MOUNTING TYPE ACTUATOR TYPE ACTUATOR MATERIAL OPERATING AND CASSOC THORUSH AND SPOT ACTUATOR MATERIAL OND CASSOC POLYMANTERIAL ACTUATOR MATERIAL POLYMANTERIAL POLYMANTERIAL	SERIES	500	
DEPERATING FORCE MOUNTING TYPE Through Hole, Right Angle, Vertical MOISTURE SENSITIVITY LEVEL (MSL) MECHANICAL LIFE 30,000 Cycles MANUFACTURER STANDARD LEAD TIME 9 Weeks LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant FEATURES EDETAILES EDETAILES BOYON Sealed Terminals ELECTRICAL LIFE 30,000 Cycles DETAILED DESCRIPTION Slide Switch SPDT Through Hole, Right Angle, Vertical CONTACT TIMING Not Specified CONTACT TIMING CONTACT TIMING CONTACT FINISH CRUIT ACTUATOR TYPE ACTUATOR TYPE SIANDARD SIANDARD SIANDARD SIANDARD SOPPT Standard FONYMIC (PA), Nylon	PACKAGING	Bulk	
MOUNTING TYPE MOISTURE SENSITIVITY LEVEL (MSL) MCHANICAL LIFE MANUFACTURER STANDARD LEAD TIME LEAD FREE STATUS / ROHS STATUS / ROHS STATUS LEAD FREE STATUS / ROHS STATUS / ROHS STATUS / ROHS STATUS / ROHS STATUS / ROH	OPERATING TEMPERATURE	-30°C ~ 85°C	
MOISTURE SENSITIVITY LEVEL (MSL) MECHANICAL LIFE MANUFACTURER STANDARD LEAD TIME MEAD FREE STATUS / ROHS STATUS LEAD FREE STATUS / ROHS STATUS EBDOXY Sealed Terminals ELECTRICAL LIFE MONOTOCYCLES DETAILED DESCRIPTION CURRENT RATING CONTACT TIMING CONTACT TIMING CONTACT FINISH CIRCUIT ACTUATOR TYPE ACTUATOR MATERIAL DIAMAGE 1. (Unlimited) Medses 30,000 Cycles BDOXY Sealed Terminals EDDOXY Sealed Terminals ACTUATOR MATERIAL COPPER AION ACTUATOR MATERIAL COPPER AION SIVER SIVER STANDARD SIVER STANDARD SIVER STANDARD STAN	OPERATING FORCE	-	
MECHANICAL LIFE 30,000 Cycles MANUFACTURER STANDARD LEAD TIME 9 Weeks LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant FEATURES 50,000 Cycles DETAILED DESCRIPTION SIdes SPDT Through Hole, Right Angle, Vertical CURRENT RATING 50,000 Cycles CONTACT TIMING Not Specified CONTACT TIMING CONTACT FINISH Silver CIRCUIT ACTUATOR TYPE SEAD STATUS SILVER SPDT THROUGH HOLE AND SILVER S	MOUNTING TYPE	Through Hole, Right Angle, Vertical	
MANUFACTURER STANDARD LEAD TIME 9 Weeks LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant FEATURES EDXY Sealed Terminals ELECTRICAL LIFE 30,000 Cycles DETAILED DESCRIPTION Slide Switch SPDT Through Hole, Right Angle, Vertical CURRENT RATING 5A (AC/DC) CONTACT TIMING Not Specified CONTACT TIMING COPPER Alloy CONTACT FINISH SliVer CIRCUIT SPDT ACTUATOR TYPE Standard Polyamide (PA), Nylon	MOISTURE SENSITIVITY LEVEL (MSL)	1 (Unlimited)	
LEAD FREE STATUS / ROHS STATUS FEATURES Epoxy Sealed Terminals ELECTRICAL LIFE 30,000 Cycles DETAILED DESCRIPTION Slide Switch SPDT Through Hole, Right Angle, Vertical CURRENT RATING CONTACT TIMING CONTACT TIMING CONTACT MATERIAL CONTACT FINISH CIRCUIT ACTUATOR TYPE Standard Polyamide (PA), Nylon	MECHANICAL LIFE	30,000 Cycles	
ELECTRICAL LIFE 30,000 Cycles DETAILED DESCRIPTION Slide Switch SPDT Through Hole, Right Angle, Vertical CURRENT RATING 5A (AC/DC) CONTACT TIMING Not Specified CONTACT FINISH Sliver CIRCUIT SPDT ACTUATOR TYPE Standard Polyamide (PA), Nylon	MANUFACTURER STANDARD LEAD TIME	9 Weeks	
BEECTRICAL LIFE 30,000 Cycles DETAILED DESCRIPTION Slide Switch SPDT Through Hole, Right Angle, Vertical CURRENT RATING 5A (AC/DC) CONTACT TIMING Not Specified CONTACT MATERIAL Copper Alloy CONTACT FINISH Sliver CIRCUIT SPDT ACTUATOR TYPE Standard Polyamide (PA), Nylon	LEAD FREE STATUS / ROHS STATUS	Lead free / RoHS Compliant	
DETAILED DESCRIPTION Slide Switch SPDT Through Hole, Right Angle, Vertical CURRENT RATING CONTACT TIMING CONTACT TIMING CONTACT MATERIAL CONTACT FINISH CIRCUIT ACTUATOR TYPE ACTUATOR MATERIAL Slide Switch SPDT Through Hole, Right Angle, Vertical ACQUARTICAL STATEMENT SALE CALLAGE SPDT Slide Switch SPDT Through Hole, Right Angle, Vertical ACCUATOR MATERIAL SALE SPDT Sale Switch SPDT Through Hole, Right Angle, Vertical SALE SPDT Sale Switch SPDT Through Hole, Right Angle, Vertical Sale Switch SPDT Through Hole, Right Angle, Split Angle, Spl	FEATURES	Epoxy Sealed Terminals	
CURRENT RATING 5A (AC/DC) CONTACT TIMING Not Specified CONTACT MATERIAL CONTACT MATERIAL CONTACT FINISH CIRCUIT ACTUATOR TYPE ACTUATOR MATERIAL 5A (AC/DC) Not Specified Copper Alloy Copper Alloy Silver SPDT Standard Polyamide (PA), Nylon	ELECTRICAL LIFE	30,000 Cycles	
CONTACT TIMING Not Specified CONTACT MATERIAL Copper Alloy CONTACT FINISH Silver CIRCUIT SPDT ACTUATOR MATERIAL Standard Polyamide (PA), Nylon	DETAILED DESCRIPTION	Slide Switch SPDT Through Hole, Right Angle, Vertical	
CONTACT MATERIAL Copper Alloy CONTACT FINISH Silver CIRCUIT SPDT ACTUATOR TYPE Standard Polyamide (PA), Nylon	CURRENT RATING	5A (AC/DC)	
CONTACT FINISH CIRCUIT ACTUATOR TYPE Standard Polyamide (PA), Nylon	CONTACT TIMING	Not Specified	
CIRCUIT SPDT ACTUATOR TYPE Standard ACTUATOR MATERIAL Polyamide (PA), Nylon	CONTACT MATERIAL	Copper Alloy	
ACTUATOR TYPE Standard ACTUATOR MATERIAL Polyamide (PA), Nylon	CONTACT FINISH	Silver	
ACTUATOR MATERIAL Polyamide (PA), Nylon	CIRCUIT	SPDT	
	ACTUATOR TYPE	Standard	
ACTUATOR LENGTH 9.04mm	ACTUATOR MATERIAL	Polyamide (PA), Nylon	
	ACTUATOR LENGTH	9.04mm	

Related Tags

E-Switch 500SSP3S3M7QEA	500SSP3S3M7QEA Distributor	500SSP3S3M7QEA Supplier
500SSP3S3M7QEA Price	500SSP3S3M7QEA Pictures	500SSP3S3M7QEA Image
500SSP3S3M7QEA PDF Datasheet	500SSP3S3M7QEA Download Datasheet	500SSP3S3M7QEA Datasheet
500SSP3S3M7QEA Stock	Buy 500SSP3S3M7QEA	Buy E-Switch 500SSP3S3M7QEA
E-Switch 500SSP3S3M7QEA	E-Switch Supplier	E-Switch Distributor
E-Switch 500SSP3S3M7OEA		

Related Products



Description: SWITCH SLIDE SPDT 5A 120V In stock: Out stock

RFQ



500SSP3S2M7QEA Manufacturers: E-Switch

Description: SWITCH SLIDE SPDT 5A 120V

In stock: Out stock

RFQ



500SSP3S4M6QEA Manufacturers: E-Switch

Description: SWITCH SLIDE SPDT 5A 120V In stock: Out stock

RFQ



500TDSS84 Manufacturers: Delta Electronics

Description: LINE FILTER 480VAC 500A CHASS In stock: Out stock

RFQ

500SSP3S2M2QEA



500SSP3S3VS2REA Manufacturers: E-Switch

Description: SWITCH SLIDE SPDT 0.4VA 20V In stock: Out stock

RFQ



Manufacturers: E-Switch

Description: SWITCH SLIDE SPDT 5A 120V In stock: Out stock

RFQ



500SSP3S3M1QEB Manufacturers: E-Switch

Description: SWITCH SLIDE SPDT 5A 120V In stock: Out stock

RFQ



Manufacturers: E-Switch Description: SWITCH SLIDE SPDT 5A 120V

500SSP3S4M7QEA

In stock: Out stock

RFQ



Manufacturers: E-Switch Description: SWITCH SLIDE SPDT 0.4VA 20V

500SSP3S3M7REA

In stock: Out stock

RFQ

Manufacturers: E-Switch Description: SWITCH SLIDE SPDT 5A 120V

500SSP3S3M1QEA

In stock: Out stock

RFQ

500SSP3S4M6QEB




Manufacturers: E-Switch Description: SWITCH SLIDE SPDT 5A 120V

500SSP3S3M2QEA

In stock: Out stock

RFQ





In stock: Out stock

RFQ











