

Image may be representation. See specifications for product details.

EX-19A-PN

Part Number:

Manufacturer/Brand: Product description

Datasheets: RoHs Status

Ship From Shipment Way

Hong Kong

Lead free / RoHS Compliant

EX-19A-PN

Panasonic

DHL/Fedex/TNT/UPS/EMS

EX-19A-PN.pdf

SENSOR PHOTO PNP 1M 12-24VDC

REQUEST FOR QUOTATION

MANUFACTURER STATUS / ROHS STATUS DESCRIPTION SENSOR PHOTO PNP 1M 12-24VDC Lead FREE STATUS / ROHS STATUS Lead free / ROHS Compliant Lead FREE STATUS / ROHS STATUS Lead free / ROHS Compliant Lead FREE STATUS / ROHS STATUS Lead free / ROHS Compliant Lead free / ROHS Complia		Specifications of EX-19A-PN
MANUFACTURER STATUS / ROHS STATUS DESCRIPTION SENSOR PHOTO PNP 1M 12-24VDC Lead FREE STATUS / ROHS STATUS Lead free / ROHS Compliant Lead FREE STATUS / ROHS STATUS Lead free / ROHS Compliant Lead FREE STATUS / ROHS STATUS Lead free / ROHS Compliant Lead free / ROHS Complia	'	
DESCRIPTION SENSOR PHOTO PNP 1M 12-24VDC Lead free / RoHS Compliant DATA SHEET DATA SHEET DEVINOR SERVER SERVIPLY 12 V ~ 24 V SERVIES EX-10 SENSING METHOD Through-Beam SENSING DISTANCE 39.37" (1m) SENSING DISTANCE 39.37" (1m) PNP - Open Collector/Light-ON OTHER NAMES 110-1853 OPERATING TEMPERATURE -25°C ~ 55°C MOISTURE SENSITIVITY LEVEL (MSL) MANUFACTURER STANDARD LEAD TIME 1 (Unlimited) MANUFACTURER STANDARD LEAD TIME LEAD FREE STATUS / ROHS STATUS LEAD FREE STATUS / ROHS STATUS	PART NUMBER	EX-19A-PN
LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant DATA SHEET LEX-19A-PN.pdf 12 V ~ 24 V SERIES EX-10 SENSING METHOD Through-Beam SENSING DISTANCE 39.37" (1m) SENSING DISTANCE 39.37" (1m) PNP - Open Collector/Light-ON OTHER NAMES 1110-1853 OPERATING TEMPERATURE -25°C ~ 55°C MOISTURE SENSITIVITY LEVEL (MSL) MANUFACTURER STANDARD LEAD TIME 1 (Unlimited) MANUFACTURER STATUS / ROHS STATUS LEAD FREE STATUS / ROHS STATU	MANUFACTURER	Panasonic
DATA SHEET DATA S	DESCRIPTION	SENSOR PHOTO PNP 1M 12-24VDC
VOLTAGE - SUPPLY 12 V ~ 24 V SERIES EX-10 Through-Beam SENSING METHOD Through-Beam SENSING DISTANCE 39.37" (1m) RESPONSE TIME 500µS OUTPUT CONFIGURATION PNP - Open Collector/Light-ON OTHER NAMES 1110-1853 OPERATING TEMPERATURE -25°C ~ 55°C MOISTURE SENSITIVITY LEVEL (MSL) MANUFACTURER STANDARD LEAD TIME 7 Weeks LIGHT SOURCE RED LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant INGRESS PROTECTION 1P67 CONNECTION METHOD CABLE LENGTH 7 8.740" (2000.00mm)	LEAD FREE STATUS / ROHS STATUS	Lead free / RoHS Compliant
EX-10 Through-Beam SENSING DISTANCE SENS	DATA SHEET	EX-19A-PN.pdf
Through-Beam SENSING METHOD SENSING DISTANCE 39.37" (1m) RESPONSE TIME 500µS DUTPUT CONFIGURATION PNP - Open Collector/Light-ON OTHER NAMES 1110-1853 DEFERATING TEMPERATURE 2-25°C ~ 55°C MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) MANUFACTURER STANDARD LEAD TIME READ FREE STATUS / ROHS STATUS LEAD FREE STATUS / ROHS STATUS LEAD FREE STATUS / ROHS STATUS CONNECTION METHOD CONNECTION METHOD CABLE LENGTH 78.740" (2000.00mm)	VOLTAGE - SUPPLY	12 V ~ 24 V
SENSING DISTANCE 39.37" (1m) RESPONSE TIME 500µS 0UTPUT CONFIGURATION PNP - Open Collector/Light-ON OTHER NAMES 1110-1853 OPERATING TEMPERATURE -25°C ~ 55°C MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) MANUFACTURER STANDARD LEAD TIME 7 Weeks LIGHT SOURCE Red LED LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant INGRESS PROTECTION IP67 CONNECTION METHOD CABLE LENGTH 78.740" (2000.00mm)	SERIES	EX-10
RESPONSE TIME 500µS OUTPUT CONFIGURATION PNP - Open Collector/Light-ON OTHER NAMES 1110-1853 OPERATING TEMPERATURE -25°C ~ 55°C MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) MANUFACTURER STANDARD LEAD TIME 7 Weeks LIGHT SOURCE Red LED LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant INGRESS PROTECTION IP67 CONNECTION METHOD CABLE LENGTH 78.740" (2000.00mm)	SENSING METHOD	Through-Beam
PNP - Open Collector/Light-ON OTHER NAMES 1110-1853 OPERATING TEMPERATURE -25°C ~ 55°C MOISTURE SENSITIVITY LEVEL (MSL) MANUFACTURER STANDARD LEAD TIME 7 Weeks LIGHT SOURCE LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant LINGRESS PROTECTION LONGECTION METHOD CABLE LENGTH 78.740" (2000.00mm)	SENSING DISTANCE	39.37" (1m)
DOPERATING TEMPERATURE -25°C ~ 55°C MOISTURE SENSITIVITY LEVEL (MSL) MANUFACTURER STANDARD LEAD TIME TO Weeks LIGHT SOURCE LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant LINGRESS PROTECTION LONGECTION METHOD CABLE LENGTH 78.740" (2000.00mm)	RESPONSE TIME	500μs
OPERATING TEMPERATURE -25°C ~ 55°C MOISTURE SENSITIVITY LEVEL (MSL) MANUFACTURER STANDARD LEAD TIME 7 Weeks Red LED LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant INGRESS PROTECTION IP67 CONNECTION METHOD CABLE LENGTH 78.740" (2000.00mm)	OUTPUT CONFIGURATION	PNP - Open Collector/Light-ON
MANUFACTURER STANDARD LEAD TIME 7 Weeks LIGHT SOURCE Red LED LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant INGRESS PROTECTION IP67 CONNECTION METHOD Cable CABLE LENGTH 78.740" (2000.00mm)	OTHER NAMES	1110-1853
MANUFACTURER STANDARD LEAD TIME 7 Weeks LIGHT SOURCE Red LED LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant INGRESS PROTECTION IP67 CONNECTION METHOD Cable CABLE LENGTH 78.740" (2000.00mm)	OPERATING TEMPERATURE	-25°C ~ 55°C
LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant INGRESS PROTECTION CONNECTION METHOD CABLE LENGTH 78.740" (2000.00mm)	MOISTURE SENSITIVITY LEVEL (MSL)	1 (Unlimited)
Lead free / RoHS Compliant INGRESS PROTECTION IP67 CONNECTION METHOD Cable CABLE LENGTH 78.740" (2000.00mm)	MANUFACTURER STANDARD LEAD TIME	7 Weeks
INGRESS PROTECTION IP67 CONNECTION METHOD Cable CABLE LENGTH 78.740" (2000.00mm)	LIGHT SOURCE	Red LED
CONNECTION METHOD Cable CABLE LENGTH 78.740" (2000.00mm)	LEAD FREE STATUS / ROHS STATUS	Lead free / RoHS Compliant
CABLE LENGTH 78.740" (2000.00mm)	INGRESS PROTECTION	IP67
	CONNECTION METHOD	Cable
ADJUSTMENT TYPE -	CABLE LENGTH	78.740" (2000.00mm)
	ADJUSTMENT TYPE	-

Related Tags

Panasonic EX-19A-PN	EX-19A-PN Distributor	EX-19A-PN Supplier
EX-19A-PN Price	EX-19A-PN Pictures	EX-19A-PN Image
EX-19A-PN PDF Datasheet	EX-19A-PN Download Datasheet	EX-19A-PN Datasheet
EX-19A-PN Stock	Buy EX-19A-PN	Buy Panasonic EX-19A-PN
Panasonic EX-19A-PN	Panasonic Supplier	Panasonic Distributor
Panasonic EX-19A-PN	Panasonic - Consumer Division EX-19A-PN	Panasonic - Consumer Electronics Corp. EX-19A-PN
Panasonic Battery Group EX-19A-PN	Panasonic Electric Works - ACSD EX-19A-PN	Panasonic Electronic Components - Semiconductor Pr EX- 19A-PN
Panasonic - ATG EX-19A-PN	Panasonic - BSG EX-19A-PN	Panasonic - DTG EX-19A-PN
Panasonic Electric Works EX-19A-PN	Panasonic Electronic Components EX-19A-PN	Panasonic Industrial Automation Sales EX-19A-PN

Related Products



Panasonic Semiconductor EX-19A-PN

EX-19B

Manufacturers: Panasonic

Description: SENSOR PHOTO NPN 1M 12-24VDC In stock: 26 pcs

RFQ



EX-19A

Manufacturers: Panasonic

Description: SENSOR PHOTO NPN 1M 12-24VDC In stock: 594 pcs

RFQ



EX-17

Manufacturers: Panasonic

Description: SENSOR PHOTO NPN 500MM 12-24VDC In stock: Out stock

RFQ



EX-19B-C5

Manufacturers: Panasonic

Description: SENSOR PHOTO NPN 1M 12-24VDC In stock: 4 pcs

RFQ



EX-17-1-12-327SN Manufacturers: Amphenol Industrial

Description: EX-STARLINE SERIES 3#12

In stock: Out stock

RFQ

<u>Amphenol</u>® Industrial

EX-17-1-12-333SN Manufacturers: Amphenol Industrial

Description: EX-STARLINE SERIES 4#16 In stock: Out stock

RFQ



EX-19A-PN-CN03-M8 Manufacturers: Panasonic

Description: SENSOR PHOTO PNP 1M 12-24VDC

In stock: Out stock **RFQ**

Panasonic

EX-19A-CN03-M8 Manufacturers: Panasonic

Description: SENSOR PHOTO NPN 1M 12-24VDC In stock: Out stock

RFQ



EX-19B-PN Manufacturers: Panasonic

Description: SENSOR PHOTO PNP 1M 12-24VDC

In stock: 27 pcs

RFQ

Panasonic

EX-19A-R Manufacturers: Panasonic

Description: SENSOR PHOTO NPN 1M 12-24VDC In stock: Out stock

RFQ



Manufacturers: Panasonic

EX-17E

Description: SENSOR PHOTO NPN 500MM 12-24VDC In stock: 5 pcs

RFQ

Panasonic

EX-19B-CN03-M8 Manufacturers: Panasonic

Description: SENSOR PHOTO NPN 1M 12-24VDC In stock: Out stock

RFQ













