

Grayhill

Grayhill, Inc.

97R02SRT

Part Number:

Manufacturer/Brand:

Product description Datasheets: RoHs Status

Ship From Shipment Way 97R02SRT

Grayhill, Inc.

SWITCH SLIDE DIP SPST 25MA 24V

97R02SRT.pdf

Lead free / RoHS Compliant

Hong Kong

DHL/Fedex/TNT/UPS/EMS



**REQUEST FOR QUOTATION** Image may be representation. See specifications for

product details.

PART NUMBER         97R025SRT           MANUFACTURER         Crayhill, Inc.           DESCRIPTION         SWITCH SLIDE DUP SPST 25MA 24V           LEAD FREE STATUS / ROHS STATUS         Lead free / ROHS Compliant           DATA SHEET         499702SRT.pdf           WASHABLE         Yes           VOLTAGE RATING         24VDC           TERRINATION STYLE         Gull Wing           SERIES         97           PITCH         0.050" (1.27mm), Half           PACKAGING         Tape & Recl (TR)           OPFRATING TEMPERATURE         40°C ~ 85°C           NUMBER OF POSITIONS         2           MOUNTING TYPE         Surface Mount           MOISTLINE SENSITIVITY LEVEL (MSL)         1,000 Oycles           MANUFACTURER STANDARD LEAD TIME         8 Weeks           LEAD FREE STATUS / ROHS STATUS         Lead free / ROHS Compliant           HEIGHT ABOVE BOARD         0.06" (1.55mm)           FEATURES         179e Seal           ELECTRICAL LIFE         1           DETAILED DESCRIPTION         DIP SWITCH SPST 2 Position Surface Mount Slide (Standard) Actuator 25mA 24VDC           CURRENT RATING         25mA           CONTACT MATERIAL         Copper Alloy           CONTACT FINISH         Gold		Specifications of 97R02SRT
MANUFACTURER         Grayhil, Inc.           DESCRIPTION         SWITCH SLIDE DIP SPST 25MA 24V           LEAD FREE STATUS / ROHS STATUS         Load free / RoHS Compliant           DATA SHEET         397802SRT.pdf           WASHABLE         Yes           VOLTAGE RATING         24VDC           TERMINATION STYLE         Gull Wing           SERIES         7           PITCH         0.950° (1.27mm), Half           PACKAGING         Tape & Recl (TR)           OPERATING TEMPERATURE         40°C ~ 85°C           MOUNTED STYLE SENSITIVITY LEVEL (MSL)         1 (Unlimited)           MOSTURE SENSITIVITY LEVEL (MSL)         1 (Webs           MANUFACTURER STANDARD LEAD TIME         1 800 Ces           MECHANICAL LIFE         0 404° (3.7mm)           LEAD FREE STATUS / ROHS STATUS         Lead free / RoHS Compliant           LEAD FREE STATUS / ROHS STATUS         Lead free / RoHS Compliant           HEIGHT ABOVE BOARD         0.61° (1.55mm)           FEATURES         1 pos Seal           ELECTICAL LIFE         2           CORTACT RATING         COPPE Alloy           CONTACT MATERIAL         Coppe Alloy           CONTACT FINSH         Gold           CONTACT FINSH         Cold		
DESCRIPTION         SWITCH SLIDE DIP SPST 25MA 24V           LEAD FREE STATUS / ROHS STATUS         Lead free / RoHS Compilant           DATA SHEET         1997 97802SRT.pdf           WASHABLE         Yes           VOLTAGE RATING         24VDC           TERNIHATION STYLE         Gull Wing           SERIES         97           PITCH         0.050° (1.27mm), Half           PACKAGING         Tape & Reel (TR)           OREATING TEMPERATURE         40°C ~ 85°C           MOUNTING TYPE         Surface Mount           MOUNTING TYPE         Surface Mount           MOISTURE SENSITIVITY LEVEL (MSL)         1 (Unlimited)           MECHANICAL LIFE         1,000 Cycles           MANUFACTURES STANDARD LEAD TIME         8 Weeks           LENGTH         0.148° (3.77mm)           LEAD FREE STATUS / ROHS STATUS         Lead free / RoHS Compliant           LEIGHT LABOVE BOARD         0.061° (1.55mm)           ELECTRICAL LIFE         -           DEFAILED DESCRIPTION         25mA           CONTACT MATERIAL         Copper Alloy           CONTACT FINISH         Geld           CONTACT FINISH         Geld           CONTACT FINISH         Geld           CONTACT FINISH         Geld<	PART NUMBER	97R02SRT
LEAD FREE STATUS / ROHS STATUS         Lead free / RoHS Compliant           DATA SHEET         1997R025RT.pdf           WASHABLE         Yes           VOLTAGE RATING         24VDC           TERMINATION STYLE         Gull Wing           SERIES         97           PITCH         0.050° (1.27mm), Half           PACKAGING         Tape & Reel (TR)           OPERATING TEMPERATURE         40°° C 85°C           NUMBER OF POSITIONS         2           MOUNTING TYPE         Surface Mount           MOISTURE SENSITIVITY LEVEL (MSL)         1 (Unlimited)           MECHANICAL LIFE         1,000 Cycles           MANUFACTURES STATUS / ROHS STATUS         8 Wecks           LEAD FREE STATUS / ROHS STATUS         Lead free / ROHS Compliant           HEIGHT ABOVE BOARD         0.061° (1.55mm)           FEATURES         Tape Seal           ELECTICAL LIFE         -           LECTICAL LIFE         -           CORTACT MATERIAL         Copper Alloy           CONTACT TATING         Copper Alloy           CONTACT TATING HALL         Copper Alloy           CONTACT FINISH         Gold           CONTACT TATING HALL         Gold           CONTACT TATING HALL         Copper Alloy	MANUFACTURER	Grayhill, Inc.
DATA SHEET         igg 970258T.pdf           WASHABLE         Yes           VOLTAGE RATING         24VDC           TERMINATION STYLE         Gull Wing           SERES         97           PITCH         0.550° (1.27mm), Half           PACKAGING         Tape & Reel (TR)           OPERATING TEMPERATURE         4.0°C ~ 85°C           NUMBER OF DOSITIONS         2           MOUNTING TYPE         Surface Mount           MOISTING ESENSITIVITY LEVEL (MSL)         1 (Unlimited)           MECHANICAL LIFE         1,000 Cycles           MANUFACTURER STANDARD LEAD TIME         8 Weeks           ELENGTH         0.48°6 (SOP) SIGNIAN           LEED AF REE STATUS / ROHS STATUS         1 (Lead free / RoHS Compliant           HEIGHT ABOVE BOARD         0.061° (1.55mm)           FEATURES         1 (SOP) Seel           ELECTRICAL LIFE         -           ELECTRICAL LIFE         -           CURRENT RATING         (Dip Switch SPST 2 Position Surface Mount Slide (Standard) Actuator 25mA 24VDC           CURRENT RATING         COPPER Alloy           CONTACT FINISH         Gold           CONTACT FINISH         ORJOHALD (Standard)           BODY MATERIAL         Polyamide (PA), Nyion	DESCRIPTION	SWITCH SLIDE DIP SPST 25MA 24V
Washable         Yes           VOLTAGE RATING         24VDC           TERMINATION STYLE         Sell Wing           SERIES         97           PITCH         0.050° (1.27mm), Helf           PACKAGING         Tape & Reel (TR)           OPERATING TEMPERATURE         40°C ~ 85°C           NUMBER OF POSITIONS         2           MOUNTING TYPE         Surface Mount           MOLISTURE SENSITIVITY LEVEL (MSL)         1 (Unlimited)           MECHANICAL LIFE         3 Weeks           LENGTH         0.488° (3.77mm)           LEAD FREE STATUS / ROHS STATUS         1 cad free / RoHS Compliant           HEIGHT ABOVE BOARD         0.661° (1.55mm)           FEATURES         Tape Seal           ELECTRICAL LIFE         -           DETAILED DESCRIPTION         Dip Switch SPST 2 Position Surface Mount Slide (Standard) Actuator 25mA 24VDC           CURRENT RATING         COpper Alloy           CONTACT HATERIAL         Gold           CONTACT FINISH         Gold           GOLD MATERIAL         Polyamide (PA), Nylon           BOLD MATERIAL         Polyamide (PA), Nylon	LEAD FREE STATUS / ROHS STATUS	Lead free / RoHS Compliant
VOLTAGE RATING         24VDC           TERMINATION STYLE         Gull Wing           SERIES         97           PITCH         0.050" (1.27mm), Half           PACKAGING         Tape & Reel (TR)           OPERATING TEMPERATURE         40°C ~ 85°C           NUMBER OF POSITIONS         2           MOUNTING TYPE         Surface Mount           MOISTURE SENSITIVITY LEVEL (MSL)         1 (Unlimited)           MECHANICAL LIFE         1,000 Cycles           MANUFACTURER STANDARD LEAD TIME         8 Weeks           LEAGTH         0.148" (3.77mm)           LEAD FREE STATUS / ROHS STATUS         Lead free / ROHS Compliant           HEIGHT ABOVE BOARD         0.06" (1.55mm)           FEATURES         Tape Seal           ELECTRICAL LIFE         -           DETAILED DESCRIPTION         Dip Switch SPST 2 Position Surface Mount Slide (Standard) Actuator 25mA 24VDC           CURRENT RATING         25mA           CONTACT MATERIAL         Gold           CONTACT FINISH         Gold           GOLY MATERIAL         SPST           BODY MATERIAL         SIIde (Standard)           BODY MATERIAL         SIIde (Standard)	DATA SHEET	97R02SRT.pdf
ETEMINATION STYLE         Gull Wing           SERIES         97           PITCH         0.050" (1.27mm), Half           PACKAGING         Tape & Reel (TR)           OPERATING TEMPERATURE         -40°C ~ 85°C           NUMBER OF POSITIONS         2           MOUNTING TYPE         Surface Mount           MOISTURE SENSITIVITY LEVEL (MSL)         1 (Unlimited)           MECHANICAL LIFE         1,000 Cycles           MANUFACTURER STANDARD LEAD TIME         8 Weeks           LENGTH         0.148" (3.77mm)           LEAD FREE STATUS / ROHS STATUS         Lead free / RoHS Compliant           HEIGHT ABOVE BOARD         0.061" (1.55mm)           FEATURES         Tape Seal           ELECTRICAL LIFE         -           DETAILED DESCRIPTION         Dip Switch SPST 2 Position Surface Mount Slide (Standard) Actuator 25mA 24VDC           CURRENT RATING         CONTACT MATERIAL           CONTACT MATERIAL         Gold           CONTACT FINISH         Gold           CONTACT FINISH         Gold           CONTACT FINISH         SPST           BODY MATERIAL         Polyamide (PA), Nylon           BODY MATERIAL         Silve (Standard)	WASHABLE	Yes
SERIES         97           PITCH         0.050° (1.27mm), Half           PACKAGING         Tape & Reel (TR)           OPERATING TEMPERATURE         40°C ~ 85°C           NUMBER OF POSITIONS         2           MOUNTING TYPE         Surface Mount           MOISTURE SENSITIVITY LEVEL (MSL)         1 (Unlimited)           MECHANICAL LIFE         1,000 Cycles           MANUFACTURER STANDARD LEAD TIME         8 Weeks           LENGTH         0.148° (3.77mm)           LEAD FREE STATUS / ROHS STATUS         Lead free / RoHS Compliant           HEIGHT ABOVE BOARD         0.061° (1.55mm)           FEATURES         Tape Seal           ELECTRICAL LIFE         -           DETAILED DESCRIPTION         Dip Switch SPST 2 Position Surface Mount Slide (Standard) Actuator 25mA 24VDC           CURRENT RATING         Coper Alloy           CONTACT MATERIAL         Coper Alloy           CONTACT FINISH         Gold           CICILITY         SPST           BODY MATERIAL         Polyamide (PA), Nylon           AUTOLITYPE         Silde (Standard)	VOLTAGE RATING	24VDC
PTCH         0.050" (1.27mm), Half           PACKAGING         Tape & Reel (TR)           OPERATING TEMPERATURE         40°C ~ 85°C           NUMBER OF POSITIONS         2           MOUNTING TYPE         Surface Mount           MOISTURE SENSITIVITY LEVEL (MSL)         1,000 Cycles           MANUFACTURER STANDARD LEAD TIME         8 Weeks           LENGTH         0.148" (3.77mm)           LEAD FREE STATUS / ROHS STATUS         Lead free / ROHS Compliant           HEIGHT ABOVE BOARD         1096 "1" (1.55mm)           FEATURES         Tape Seal           ELECTRICAL LIFE         -           DETAILED DESCRIPTION         Dip Switch SPST 2 Position Surface Mount Slide (Standard) Actuator 25mA 24VDC           CURRENT RATING         25mA           CONTACT MATERIAL         Copper Alloy           CONTACT FINISH         Gold           CURUIT         SPST           BODY MATERIAL         Polyamide (PA), Nylon           KOLIDATOR (PA)         Side (Standard)	TERMINATION STYLE	Gull Wing
PACKAGING  OPERATING TEMPERATURE  A40°C ~ 85°C  NUMBER OF POSITIONS  ZURÉAC MOUNT  MOUNTING TYPE  SURÍACE MOUNT  MOISTURE SENSITIVITY LEVEL (MSL)  MECHANICAL LIFE  1,000 Cycles  MANUFACTURER STANDARD LEAD TIME  8 Weeks  LENGTH  1,048° (3.77mm)  LEAD FREE STATUS / ROHS STATUS  LEGHT ABOVE BOARD  16EIGHT ABOVE BOARD  FEATURES  ELECTRICAL LIFE  10FE SEAI  ELECTRICAL LIFE  10FE SURÍAL  ELECTRICAL MATERIAL  10FE SURÍAL  ELECTRICAL MATERIAL  10FE SURÍAL  ELECTRICAL MATERIAL  10FE SURÍAL  10FE S	SERIES	97
OPERATING TEMPERATURE         -40°C ~ 85°C           NUMBER OF POSITIONS         2           MOUNTING TYPE         Surface Mount           MOISTURE SENSITIVITY LEVEL (MSL)         1 (Unlimited)           MECHANICAL LIFE         1,000 Cycles           MANUFACTURER STANDARD LEAD TIME         8 Weeks           LENGTH         0.148° (3.77mm)           LEAD FREE STATUS / ROHS STATUS         Lead free / RoHS Compliant           HEIGHT ABOVE BOARD         0.061° (1.55mm)           FEATURES         Tape Seal           ELECTRICAL LIFE         -           DETAILED DESCRIPTION         DIP Switch SPST 2 Position Surface Mount Slide (Standard) Actuator 25mA 24VDC           CURRENT RATING         25mA           CONTACT MATERIAL         Copper Alloy           CONTACT FINISH         Gold           CICKUIT         SPST           BODY MATERIAL         Polyamide (PA), Nylon           ACTUATOR TYPE         Slide (Standard)	PITCH	0.050" (1.27mm), Half
MUMBER OF POSITIONS  MOUNTING TYPE  Surface Mount  MOISTURE SENSITIVITY LEVEL (MSL)  MECHANICAL LIFE  MANUFACTURER STANDARD LEAD TIME  MECHANICAL LIFE  MANUFACTURER STANDARD LEAD TIME  MERCHANICAL LIFE  MANUFACTURER STANDARD LEAD TIME  MERCHANICAL LIFE  MERCHANICAL STANDARD LEAD TIME  MERCHANICAL STANDARD LEAD TIME  MERCHANICAL STANDARD LEAD TIME  MERCHANICAL STANDARD  MERCHANDARD  MERCHA	PACKAGING	Tape & Reel (TR)
MOUNTING TYPE  MOISTURE SENSITIVITY LEVEL (MSL)  MCHANICAL LIFE  MANUFACTURER STANDARD LEAD TIME  MECHANICAL LIFE  MANUFACTURER STANDARD LEAD TIME  MEGHANCAL LIFE  MANUFACTURER STANDARD LEAD TIME  MEGHANCAL LIFE  MEGHT ABOVE BOARD  LEAD FREE STATUS / ROHS STATUS  LEAD FREE STATUS / ROHS STATUS  MEGHT ABOVE BOARD  MOSIT (1.55mm)  FEATURES  Tape Seal  ELECTRICAL LIFE  DETAILED DESCRIPTION  DIP SWItch SPST 2 Position Surface Mount Slide (Standard) Actuator 25mA 24VDC  CURRENT RATING  CONTACT MATERIAL  CONTACT MATERIAL  CONTACT FINISH  Gold  CIRCUIT  BODY MATERIAL  ACTUATOR TYPE  SIIde (Standard)	OPERATING TEMPERATURE	-40°C ~ 85°C
MOISTURE SENSITIVITY LEVEL (MSL)  MECHANICAL LIFE  MANUFACTURER STANDARD LEAD TIME  8 Weeks  LENGTH  0.48" (3.77mm)  LEAD FREE STATUS / ROHS STATUS  DEFINITION  FEATURES  Tape Seal  LECTRICAL LIFE  DIP Switch SPST 2 Position Surface Mount Slide (Standard) Actuator 25mA 24VDC  CURRENT RATING  CONTACT MATERIAL  CONTACT FINISH  CONTACT FINISH  BODY MATERIAL  BODY MATERIAL  ACTUATOR TYPE  I (Unlimited)  1,000 Cycles  8 Weeks  8 Weeks  1,000 Cycles  1,0	NUMBER OF POSITIONS	2
MECHANICAL LIFE MANUFACTURER STANDARD LEAD TIME 8 Weeks  LENGTH 0.148" (3.77mm)  LEAD FREE STATUS / ROHS STATUS LEAD FREE STATUS / ROHS STATUS 1.6061" (1.55mm)  FEATURES Tape Seal  LECTRICAL LIFE 0.149 Switch SPST 2 Position Surface Mount Slide (Standard) Actuator 25mA 24VDC  CURRENT RATING CONTACT MATERIAL CONTACT MATERIAL CONTACT FINISH 6 Odd CIRCUIT BODY MATERIAL BODY MATERIAL BODY MATERIAL SIDE (PA), Nylon SIDE (Standard) SIDE (Standard) SIDE (Standard) SIDE (Standard) SIDE (PA), Nylon SIDE (Standard)	MOUNTING TYPE	Surface Mount
MANUFACTURER STANDARD LEAD TIME 8 Weeks  LENGTH 0.148" (3.77mm)  LEAD FREE STATUS / ROHS STATUS LEAD free / ROHS Compliant  HEIGHT ABOVE BOARD 0.061" (1.55mm)  FEATURES TATUS / ROHS STATUS 1.25mm)  FEATURES 1.25mm 1.25mm 1.25mm  DETAILLED DESCRIPTION 1.25mm 1.25mm  DIP Switch SPST 2 Position Surface Mount Slide (Standard) Actuator 25mA 24VDC 1.25mm  CONTACT MATERIAL 0.25mA 1.25mm  CONTACT FINISH 0.36mm 1.25mm 1.25mm  BODY MATERIAL 0.36mm 1.25mm 1	MOISTURE SENSITIVITY LEVEL (MSL)	1 (Unlimited)
LENGTH0.148" (3.77mm)LEAD FREE STATUS / ROHS STATUSLead free / RoHS CompliantHEIGHT ABOVE BOARD0.061" (1.55mm)FEATURESTape SealELECTRICAL LIFE-DETAILED DESCRIPTIONDip Switch SPST 2 Position Surface Mount Slide (Standard) Actuator 25mA 24VDCCURRENT RATING25mACONTACT MATERIALCopper AlloyCONTACT FINISHGoldCIRCUITSPSTBODY MATERIALPolyamide (PA), NylonACTUATOR TYPESlide (Standard)	MECHANICAL LIFE	1,000 Cycles
LEAD FREE STATUS / ROHS STATUS  HEIGHT ABOVE BOARD  FEATURES  FLECTRICAL LIFE  DETAILED DESCRIPTION  DIP Switch SPST 2 Position Surface Mount Slide (Standard) Actuator 25mA 24VDC  CURRENT RATING  CONTACT MATERIAL  CONTACT FINISH  GOId  CIRCUIT  BODY MATERIAL  BODY MATERIAL  ACTUATOR TYPE  Lead free / ROHS Compliant  Lead free / RoHS Com	MANUFACTURER STANDARD LEAD TIME	8 Weeks
HEIGHT ABOVE BOARD  FEATURES  Tape Seal  LECTRICAL LIFE  DETAILED DESCRIPTION  DIP Switch SPST 2 Position Surface Mount Slide (Standard) Actuator 25mA 24VDC  CURRENT RATING  CONTACT MATERIAL  CONTACT FINISH  GOId  CIRCUIT  BODY MATERIAL  Polyamide (PA), Nylon  Slide (Standard)	LENGTH	0.148" (3.77mm)
FEATURES FEA	LEAD FREE STATUS / ROHS STATUS	Lead free / RoHS Compliant
ELECTRICAL LIFE-DETAILED DESCRIPTIONDip Switch SPST 2 Position Surface Mount Slide (Standard) Actuator 25mA 24VDCCURRENT RATING25mACONTACT MATERIALCopper AlloyCONTACT FINISHGoldCIRCUITSPSTBODY MATERIALPolyamide (PA), NylonACTUATOR TYPESlide (Standard)	HEIGHT ABOVE BOARD	0.061" (1.55mm)
DETAILED DESCRIPTION Dip Switch SPST 2 Position Surface Mount Slide (Standard) Actuator 25mA 24VDC CURRENT RATING 25mA CONTACT MATERIAL CONTACT FINISH Gold CIRCUIT SPST SPST BODY MATERIAL Polyamide (PA), Nylon ACTUATOR TYPE Side (Standard)	FEATURES	Tape Seal
CURRENT RATING 25mA  CONTACT MATERIAL COpper Alloy  CONTACT FINISH Gold  CIRCUIT SPST  BODY MATERIAL Polyamide (PA), Nylon  ACTUATOR TYPE Slide (Standard)	ELECTRICAL LIFE	-
CONTACT MATERIAL Copper Alloy  CONTACT FINISH Gold  CIRCUIT SPST  BODY MATERIAL Polyamide (PA), Nylon  ACTUATOR TYPE Slide (Standard)	DETAILED DESCRIPTION	Dip Switch SPST 2 Position Surface Mount Slide (Standard) Actuator 25mA 24VDC
CONTACT FINISHGoldCIRCUITSPSTBODY MATERIALPolyamide (PA), NylonACTUATOR TYPESlide (Standard)	CURRENT RATING	25mA
CIRCUIT SPST BODY MATERIAL Polyamide (PA), Nylon ACTUATOR TYPE Slide (Standard)	CONTACT MATERIAL	Copper Alloy
BODY MATERIAL Polyamide (PA), Nylon  ACTUATOR TYPE Slide (Standard)	CONTACT FINISH	Gold
ACTUATOR TYPE Slide (Standard)	CIRCUIT	SPST
	BODY MATERIAL	Polyamide (PA), Nylon
ACTUATOR LEVEL Flush, Recessed	ACTUATOR TYPE	Slide (Standard)
	ACTUATOR LEVEL	Flush, Recessed

# **Related Tags**

Grayhill, Inc. 97R02SRT	97R02SRT Distributor	97R02SRT Supplier
97R02SRT Price	97R02SRT Pictures	97R02SRT Image
97R02SRT PDF Datasheet	97R02SRT Download Datasheet	97R02SRT Datasheet
97R02SRT Stock	Buy 97R02SRT	Buy Grayhill, Inc. 97R02SRT
Grayhill, Inc. 97R02SRT	Grayhill, Inc. Supplier	Grayhill, Inc. Distributor
Grayhill, Inc. 97R02SRT	Grayhill Inc. 97R02SRT	

## **Related Products**



97R02SR Manufacturers: Grayhill, Inc.

Description: SWITCH SLIDE DIP SPST 25MA 24V In stock: Out stock

**RFQ** 

Grayhill

Manufacturers: Grayhill, Inc.

Description: SWITCH SLIDE DIP SPST 25MA 24V In stock: Out stock

**RFQ** 

97R04SR



## 97R06RT

Manufacturers: Grayhill, Inc.

Description: SWITCH SLIDE DIP SPST 25MA 24V In stock: Out stock

**RFQ** 

Grayhill

## 97R04T

Manufacturers: Grayhill, Inc. Description: SWITCH SLIDE DIP SPST 25MA 24V

In stock: Out stock

**RFQ** 



## **97R02RT**

Manufacturers: Grayhill, Inc. Description: SWITCH SLIDE DIP SPST 25MA 24V

In stock: Out stock

**RFQ** 



## 97R02T

Manufacturers: Grayhill, Inc. Description: SWITCH SLIDE DIP SPST 25MA 24V

In stock: Out stock

**RFQ** 



#### 97R02ST Manufacturers: Grayhill, Inc.

Description: SWITCH SLIDE DIP SPST 25MA 24V

In stock: Out stock

**RFQ** 

#### 97R04S Manufacturers: Grayhill, Inc.

Description: SWITCH SLIDE DIP SPST 25MA 24V

In stock: Out stock

**RFQ** 



E-mail: Info@Ocean-Components.com

### **97R04SRT** Manufacturers: Grayhill, Inc.

Description: SWITCH SLIDE DIP SPST 25MA 24V In stock: Out stock

**RFQ** 



### **97R04ST** Manufacturers: Grayhill, Inc.

Description: SWITCH SLIDE DIP SPST 25MA 24V In stock: Out stock

**RFQ** 



**RFQ** 





In stock: Out stock

**RFQ** 



Address: Room 2102, Connaught Commercial Building, 185 Wan Chai Rd, Wan Chai, Hong Kong











