

OMRON

**Omron Automation & Safety** 

Part Number:

Manufacturer/Brand: Product description

MK3PND-5-S-DC110

Datasheets: RoHs Status

Ship From Shipment Way MK3PND-5-S-DC110

**Omron Automation & Safety** 

RELAY GEN PURPOSE 3PDT 10A 110V

MK3PND-5-S-DC110.pdf Lead free / RoHS Compliant

Hong Kong

DHL/Fedex/TNT/UPS/EMS



Image may be representation. See specifications for product details.

Specifications of MK3PND-5-S-DC110  PART NUMBER  MK3PND-5-S-DC110  RELAY CESP PURPOSE 3PDT 10A 110V  LEAD FREE STATUS / ROHS STATUS  Lead free / RoHS Complant  DATA SHEET  TURN ON VOLTAGE (MIX)  16.5 VDC  TURN OF YOUTAGE (MIX)  SWITCHING VOLTAGE (MIX)  SWITCHING VOLTAGE  SERIES  MK  RELEASE TIME  20ms  RELAY TYPE  General Purpose  PACKAGING  Bulk  OTHER NAMES  MC3PND-5-S-DC110  OPERATURE  30ms  MOUNTING TEMPERATURE  -10°C ~ 40°C  OPERATE TIME  30ms  MOUNTING TYPE  Socketable  MOISTURE SENSITIVITY LEVEL (MSL)  1 (Unlimited)  LEAD FREE STATUS / ROHS STATUS  Lead free / ROHS Complant  FEATURES  Dude, LED Indicator, Mechanical Indicator, Test Button  CONTACT RATURS (URRENT)  10A  CONTACT RATURS (URRENT)  10A  CONTACT FAITING (URRENT)  10A  CONTACT FORM  3PDT (3 Form C)  COIL POWER  1.5 W  COIL LOURENT  15.1 mA  COIL CURRENT  15.1 mA			
MANUFACTURER  DESCRIPTION  RELAY GEN PURPOSE 3PDT 10A 110V  LEAD FREE STATUS / ROHS STATUS  Lead free / ROHS Compilant  DATA SHEET  DATA		Specifications of MK3PND-5-S-DC110	
MANUFACTURER  DESCRIPTION  RELAY GEN PURPOSE 3PDT 10A 110V  LEAD FREE STATUS / ROHS STATUS  Lead free / ROHS Compilant  DATA SHEET  DATA			
DESCRIPTION RELAY GEN PURPOSE 3PDT 10A 110V  LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compilant  DATA SHEET  TURN ON VOLTAGE (MAX) 88 VDC  TURN OF VOLTAGE (MIN) 16.5 VDC  TURN OFF VOLTAGE (MIN) 16.5 VDC  TURNINATION STYLE Plug In, 11 PIN (Octal) SWITCHING VOLTAGE 250VAC, 250VDC - Max  SERIES MK  RELAYSES MK  RELASE TIME 20ms RELAY TYPE General Purpose PACKAGING Bulk  OTHER NAMES MK3PND5SDC110  OPERATING TEMPERATURE -10°C ~ 40°C  OPERATE TIME 30ms  MOUNTING TYPE Socketable MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compilant FEATURES DIODE, LED Indicator, Mechanical Indicator, Test Button  DETAILED DESCRIPTION General Purpose Relay 3PDT (3 Form C) 110VDC  CONTACT RATTING (CURRENT) CONTACT RATTING (CURRENT) COLL VOLTAGE 110VDC  COLL TYPE Non Latching COLL RESISTANCE 7.3 KOHMS COLL POWER 1.5 W	PART NUMBER	MK3PND-5-S-DC110	
LEAD FREE STATUS / ROHS STATUS  DATA SHEET  DAM MSPND-5-S-DC110.pdf  TURN ON VOLTAGE (MAX)  88 VDC  TURN OFF VOLTAGE (MIN)  16.5 VDC  TERMINATION STYLE  Plug In, 11 Pin (Octal)  SWITCHING VOLTAGE  250VAC, 250VDC - Max  SERIES  MK  RELEASE TIME  20ms  RELAY TYPE  General Purpose  PACKAGING  OPERATING TEMPERATURE  -10°C ~ 40°C  OPERATE TIME  30ms  MOUNTING TYPE  Socketable  MOUSTURE SENSITIVITY LEVEL (MSL)  Lead free / ROHS Compliant  FEATURES  Diode, LED Indicator, Mechanical Indicator, Test Button  DETAILED DESCRIPTION  General Purpose Relay 3PDT (3 Form C) 110VDC  COIL VOLTAGE  110VDC  COIL TYPE  Non Latching  COIL RESISTANCE  7.3 KOhms  COIL POWER  LIS W	MANUFACTURER	Omron Automation & Safety	
DATA SHEET  TURN ON VOLTAGE (MAX)  88 VDC  TURN OFF VOLTAGE (MIN)  16.5 VDC  TERMINATION STYLE  Plug In, 11 Pin (Octal)  SWITCHING VOLTAGE  250VAC, 250VDC - Max  SERIES  MK  RELEASE TIME  20ms  RELAY TYPE  General Purpose  PACKAGING  OTHER NAMES  MK3PNDSSDC110  OPERATING TEMPERATURE  -10°C ~ 40°C  OPERATE TIME  30ms  MOUNTING TYPE  Socketable  MOISTURE SENSITIVITY LEVEL (MSL)  LEAD FREE STATUS / ROHS STATUS  LEAD free F ARHS Compliant  FEATURES  DIOde, LED Indicator, Mechanical Indicator, Test Button  DETAILED DESCRIPTION  General Purpose Relay 3PDT (3 Form C) 110VDC  COIL VOLTAGE  110VDC  COIL VOLTAGE  110VDC  COIL TYPE  Non Latching  COIL RESISTANCE  7.3 KOhms  COIL POWER  1.5 W	DESCRIPTION	RELAY GEN PURPOSE 3PDT 10A 110V	
TURN ON VOLTAGE (MIXX)  88 VDC  TURN OFF VOLTAGE (MIN)  16.5 VDC  TERMINATION STYLE  Plug In, 11 Pin (Octal)  SWITCHING VOLTAGE  250VAC, 250VDC - Max  SERIES  MK  RELEASE TIME  20ms  RELAY TYPE  General Purpose  PACKAGING  DIVENAMES  MK3PNDSSDC110  OPERATING TEMPERATURE  -10°C ~ 40°C  OPERATE TIME  30ms  MOUNTING TYPE  Socketable  MOISTURE SENSITIVITY LEVEL (MSL)  1 (Unlimited)  LEAD FREE STATUS / ROHS STATUS  Lead free / ROHS Compliant  FEATURES  DIOde, LED Indicator, Mechanical Indicator, Test Button  DETAILED DESCRIPTION  General Purpose Relay 3PDT (3 Form C) 110VDC Coil Socketable  CONTACT RATING (CURRENT)  COLL VOLTAGE  110VDC  COLL TYPE  NON Latching  COLL RESISTANCE  7.3 KOhms  COLL POWER  1.5 W	LEAD FREE STATUS / ROHS STATUS	Lead free / RoHS Compliant	
TURN OFF VOLTAGE (MIN)  TERMINATION STYLE  Plug In, 11 Pin (Octal)  SWITCHING VOLTAGE  250VAC, 250VDC - Max  SERIES  MK  RELEASE TIME  20ms  RELAY TYPE  General Purpose  Bulk  OTHER NAMES  MK3PND5SDC110  OPERATING TEMPERATURE  -10°C ~ 40°C  OPERATE TIME  30ms  MOUNTING TYPE  Socketable  MOISTURE SENSITIVITY LEVEL (MSL)  LEAD FREE STATUS / ROHS STATUS  Lead free / ROHS Compliant  FEATURES  Diode, LED Indicator, Mechanical Indicator, Test Button  DETAILED DESCRIPTION  General Purpose Relay 3PDT (3 Form C) 110VDC  CONTACT MATERIAL  Silver (Ag)  CONTACT FORM  3PDT (3 Form C)  COIL VOLTAGE  110VDC  COIL TYPE  Non Latching  COIL RESISTANCE  7.3 KOhms  COIL POWER	DATA SHEET	MK3PND-5-S-DC110.pdf	
TERMINATION STYLE Plug In, 11 Pin (Octal)  SWITCHING VOLTAGE 250VAC, 250VDC - Max  SERIES MK  RELEASE TIME 20ms  RELAY TYPE General Purpose  PACKAGING Bulk  OTHER NAMES MK3PNDSSDC110  OPERATING TEMPERATURE -10°C ~ 40°C  OPERATE TIME 30ms  MOUNTING TYPE Socketable  MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited)  LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant  FEATURES Diode, LED Indicator, Mechanical Indicator, Test Button  DETAILED DESCRIPTION General Purpose Relay 3PDT (3 Form C) 110VDC Coil Socketable  CONTACT RATING (CURRENT) 10A  CONTACT MATERIAL Silver (Ag)  CONTACT FORM 3PDT (3 Form C)  COIL TYPE Non Latching  COIL TYPE Non Latching  COIL RESISTANCE 7.3 KOhms  COIL POWER 1.5 W	TURN ON VOLTAGE (MAX)	88 VDC	
SWITCHING VOLTAGE  250VAC, 250VDC - Max  SERIES  MK  RELEASE TIME  20ms  RELAY TYPE  General Purpose  PACKAGING  Bulk  OTHER NAMES  MK3PNDSSDC110  OPERATING TEMPERATURE  -10°C ~ 40°C  OPERATE TIME  30ms  MOUNTING TYPE  Socketable  MOISTURE SENSITIVITY LEVEL (MSL)  1 (Unlimited)  LEAD FREE STATUS / ROHS STATUS  Lead free / ROHS Compliant  FEATURES  Diode, LED Indicator, Mechanical Indicator, Test Button  DETAILED DESCRIPTION  General Purpose Relay 3PDT (3 Form C) 110VDC Coil Socketable  CONTACT MATERIAL  SIIVEr (Ag)  CONTACT FORM  3PDT (3 Form C)  COIL YOLTAGE  110VDC  COIL TYPE  Non Latching  COIL RESISTANCE  7.3 KOhms  COIL POWER	TURN OFF VOLTAGE (MIN)	16.5 VDC	
RELEASE TIME 20ms RELAY TYPE General Purpose PACKAGING Bulk OTHER NAMES MK3PNDSSDC110 OPERATTINE 10°C ~ 40°C OPERATE TIME 30ms MOUNTING TYPE Socketable MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant FEATURES Diode, LED Indicator, Mechanical Indicator, Test Button DETAILED DESCRIPTION General Purpose Relay 3PDT (3 Form C) 110VDC Coil Socketable CONTACT MATERIAL Silver (Ag) CONTACT FORM 3PDT (3 Form C) COIL VOLTAGE 110VDC COIL TYPE No Latching COIL RESISTANCE 7.3 KOhms COIL POWER 1.5 W	TERMINATION STYLE	Plug In, 11 Pin (Octal)	
RELAY TYPE General Purpose  PACKAGING Bulk OTHER NAMES MK3PND5SDC110 OPERATING TEMPERATURE -10°C ~ 40°C OPERATE TIME 30ms MOUNTING TYPE Socketable MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant FEATURES Diode, LED Indicator, Mechanical Indicator, Test Button DETAILED DESCRIPTION General Purpose Relay 3PDT (3 Form C) 110VDC Coil Socketable  CONTACT RATING (CURRENT) 10A  CONTACT MATERIAL Silver (Ag)  CONTACT FORM 3PDT (3 Form C) OUL VOLTAGE 110VDC COIL TYPE Non Latching COIL RESISTANCE 7.3 KOhms COIL POWER	SWITCHING VOLTAGE	250VAC, 250VDC - Max	
RELAY TYPE General Purpose  Bulk OTHER NAMES MK3PND5SDC110  OPERATING TEMPERATURE -10°C ~ 40°C  OPERATE TIME 30ms  MOUNTING TYPE Socketable MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited)  LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant  FEATURES Diode, LED Indicator, Mechanical Indicator, Test Button  DETAILED DESCRIPTION General Purpose Relay 3PDT (3 Form C) 110VDC Coil Socketable  CONTACT RATING (CURRENT) CONTACT MATERIAL Silver (Ag)  CONTACT FORM 3PDT (3 Form C)  COIL YOLTAGE 110VDC  COIL TYPE Non Latching  COIL RESISTANCE 7.3 KOhms  COIL POWER	SERIES	MK	
PACKAGING  OTHER NAMES  MK3PNDSSDC110  OPERATING TEMPERATURE  -10°C ~ 40°C  OPERATE TIME  30ms  MOUNTING TYPE  Socketable  MOISTURE SENSITIVITY LEVEL (MSL)  LEAD FREE STATUS / ROHS STATUS  Lead free / ROHS Compliant  FEATURES  Diode, LED Indicator, Mechanical Indicator, Test Button  DETAILED DESCRIPTION  General Purpose Relay 3PDT (3 Form C) 110VDC Coil Socketable  CONTACT RATING (CURRENT)  CONTACT MATERIAL  Silver (Ag)  CONTACT FORM  3PDT (3 Form C)  COIL VOLTAGE  110VDC  COIL TYPE  Non Latching  COIL RESISTANCE  7.3 kOhms  COIL POWER	RELEASE TIME	20ms	
OTHER NAMES  MK3PND5SDC110  OPERATING TEMPERATURE  -10°C ~ 40°C  OPERATE TIME  30ms  MOUNTING TYPE  Socketable  MOISTURE SENSITIVITY LEVEL (MSL)  LEAD FREE STATUS / ROHS STATUS  LEED Indicator, Mechanical Indicator, Test Button  DETAILED DESCRIPTION  General Purpose Relay 3PDT (3 Form C) 110VDC Coil Socketable  CONTACT RATING (CURRENT)  CONTACT MATERIAL  CONTACT FORM  3PDT (3 Form C)  COIL VOLTAGE  110VDC  COIL TYPE  Non Latching  COIL RESISTANCE  7.3 kOhms  COIL POWER	RELAY TYPE	General Purpose	
OPERATING TEMPERATURE OPERATE TIME 30ms  MOUNTING TYPE Socketable  MOISTURE SENSITIVITY LEVEL (MSL) LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant  FEATURES Diode, LED Indicator, Mechanical Indicator, Test Button  DETAILED DESCRIPTION General Purpose Relay 3PDT (3 Form C) 110VDC Coil Socketable  CONTACT RATING (CURRENT) 10A  CONTACT MATERIAL CONTACT FORM 3PDT (3 Form C)  COIL YOLTAGE 110VDC  COIL TYPE Non Latching  COIL RESISTANCE 7.3 KOhms  COIL POWER	PACKAGING	Bulk	
OPERATE TIME 30ms  MOUNTING TYPE Socketable  MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited)  LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant  FEATURES Diode, LED Indicator, Mechanical Indicator, Test Button  DETAILED DESCRIPTION General Purpose Relay 3PDT (3 Form C) 110VDC Coil Socketable  CONTACT RATING (CURRENT) 10A  CONTACT MATERIAL Silver (Ag)  CONTACT FORM 3PDT (3 Form C)  COIL VOLTAGE 110VDC  COIL VOLTAGE 110VDC  COIL TYPE Non Latching  COIL RESISTANCE 7.3 kOhms  COIL POWER 1.5 W	OTHER NAMES	MK3PND5SDC110	
MOUNTING TYPE  Socketable  MOISTURE SENSITIVITY LEVEL (MSL)  Lead free / ROHS Compliant  FEATURES  Diode, LED Indicator, Mechanical Indicator, Test Button  DETAILED DESCRIPTION  General Purpose Relay 3PDT (3 Form C) 110VDC Coil Socketable  CONTACT RATING (CURRENT)  CONTACT MATERIAL  Silver (Ag)  CONTACT FORM  3PDT (3 Form C)  COIL VOLTAGE  110VDC  COIL VOLTAGE  7.3 kOhms  COIL POWER  1.5 W	OPERATING TEMPERATURE	-10°C ~ 40°C	
MOISTURE SENSITIVITY LEVEL (MSL)  LEAD FREE STATUS / ROHS STATUS  Lead free / RoHS Compliant  FEATURES  Diode, LED Indicator, Mechanical Indicator, Test Button  DETAILED DESCRIPTION  General Purpose Relay 3PDT (3 Form C) 110VDC Coil Socketable  CONTACT RATING (CURRENT)  10A  CONTACT MATERIAL  Silver (Ag)  CONTACT FORM  3PDT (3 Form C)  COIL VOLTAGE  110VDC  COIL VOLTAGE  7.3 kOhms  COIL POWER  1.5 W	OPERATE TIME	30ms	
LEAD FREE STATUS / ROHS STATUS  Lead free / RoHS Compliant  FEATURES  Diode, LED Indicator, Mechanical Indicator, Test Button  General Purpose Relay 3PDT (3 Form C) 110VDC Coil Socketable  CONTACT RATING (CURRENT)  10A  CONTACT MATERIAL  Silver (Ag)  CONTACT FORM  3PDT (3 Form C)  COIL VOLTAGE  110VDC  COIL TYPE  Non Latching  COIL POWER  1.5 W	MOUNTING TYPE	Socketable	
Diode, LED Indicator, Mechanical Indicator, Test Button  DETAILED DESCRIPTION  General Purpose Relay 3PDT (3 Form C) 110VDC Coil Socketable  CONTACT RATING (CURRENT)  10A  CONTACT MATERIAL  Silver (Ag)  CONTACT FORM  3PDT (3 Form C)  COIL VOLTAGE  110VDC  COIL TYPE  Non Latching  COIL RESISTANCE  7.3 kOhms  COIL POWER  1.5 W	MOISTURE SENSITIVITY LEVEL (MSL)	1 (Unlimited)	
DETAILED DESCRIPTION General Purpose Relay 3PDT (3 Form C) 110VDC Coil Socketable  CONTACT RATING (CURRENT) 10A  CONTACT MATERIAL Silver (Ag)  CONTACT FORM 3PDT (3 Form C)  COIL VOLTAGE 110VDC  COIL TYPE Non Latching  COIL RESISTANCE 7.3 kOhms  COIL POWER 1.5 W	LEAD FREE STATUS / ROHS STATUS	Lead free / RoHS Compliant	
CONTACT RATING (CURRENT)  CONTACT MATERIAL  CONTACT FORM  CONTACT FORM  COIL VOLTAGE  COIL TYPE  Non Latching  COIL RESISTANCE  COIL POWER  100A  Silver (Ag)  3PDT (3 Form C)  110VDC  Non Latching  7.3 kOhms  1.5 W	FEATURES	Diode, LED Indicator, Mechanical Indicator, Test Button	
CONTACT MATERIAL  CONTACT FORM  3PDT (3 Form C)  COIL VOLTAGE  110VDC  COIL TYPE  Non Latching  COIL RESISTANCE  7.3 kOhms  COIL POWER  1.5 W	DETAILED DESCRIPTION	General Purpose Relay 3PDT (3 Form C) 110VDC Coil Socketable	
CONTACT FORM 3PDT (3 Form C)  COIL VOLTAGE 110VDC  COIL TYPE Non Latching  COIL RESISTANCE 7.3 kOhms  COIL POWER 1.5 W	CONTACT RATING (CURRENT)	10A	
COIL VOLTAGE 110VDC  COIL TYPE Non Latching  COIL RESISTANCE 7.3 kOhms  COIL POWER 1.5 W	CONTACT MATERIAL	Silver (Ag)	
COIL TYPE Non Latching COIL RESISTANCE 7.3 kOhms COIL POWER 1.5 W	CONTACT FORM	3PDT (3 Form C)	
COIL RESISTANCE 7.3 kOhms COIL POWER 1.5 W	COIL VOLTAGE	110VDC	
COIL POWER 1.5 W	COIL TYPE	Non Latching	
	COIL RESISTANCE	7.3 kOhms	
COIL CURRENT 15.1mA	COIL POWER	1.5 W	
	COIL CURRENT	15.1mA	

# **Related Tags**

Omron Automation & Safety MK3PND-5-S-DC110	MK3PND-5-S-DC110 Distributor	MK3PND-5-S-DC110 Supplier
MK3PND-5-S-DC110 Price	MK3PND-5-S-DC110 Pictures	MK3PND-5-S-DC110 Image
MK3PND-5-S-DC110 PDF Datasheet	MK3PND-5-S-DC110 Download Datasheet	MK3PND-5-S-DC110 Datasheet
MK3PND-5-S-DC110 Stock	Buy MK3PND-5-S-DC110	Buy Omron Automation & Safety MK3PND-5-S-DC110
Omron Automation & Safety MK3PND-5-S-DC110	Omron Automation & Safety Supplier	Omron Automation & Safety Distributor
Omron Automation & Safety MK3PND-5-S-DC110	Omron Automation and Safety MK3PND-5-S-DC110	

## **Related Products**



MK3PND-5-I-DC6 Manufacturers: Omron Automation & Safety

Description: RELAY GEN PURPOSE 3PDT 10A 6V

In stock: Out stock

**RFQ** 



MK3PN-S AC220 Manufacturers: Omron Automation & Safety

Description: RELAY GEN PURPOSE 3PDT 10A 220V In stock: Out stock

**RFQ** 



#### MK3PNV-5-I AC6 Manufacturers: Omron Automation & Safety

Description: RELAY GEN PURPOSE 3PDT 10A 6V In stock: Out stock

**RFQ** 



#### MK3PNV-5-I-AC12 Manufacturers: Omron Automation & Safety

Description: RELAY GEN PURPOSE 3PDT 10A 12V

In stock: Out stock

**RFQ** 



#### MK3PND-5-S-DC24 Manufacturers: Omron Automation & Safety

Description: RELAY GEN PURPOSE 3PDT 10A 24V In stock: Out stock

**RFQ** 



#### **MK3PNV-5-I-AC110** Manufacturers: Omron Automation & Safety

Description: RELAY GEN PURPOSE 3PDT 10A 110V In stock: Out stock

**RFQ** 



#### MK3PND-5-I-DC12 Manufacturers: Omron Automation & Safety

Description: RELAY GEN PURPOSE 3PDT 10A 12V In stock: Out stock

**RFQ** 



#### MK3PND-5-S-DC6 Manufacturers: Omron Automation & Safety

Description: RELAY GEN PURPOSE 3PDT 10A 6V In stock: Out stock

**RFQ** 



### MK3PND-5-I-DC48 Manufacturers: Omron Automation & Safety

Description: RELAY GEN PURPOSE 3PDT 10A 48V In stock: Out stock

**RFQ** 

#### MK3PND-5-I-DC110 Manufacturers: Omron Automation & Safety

Description: RELAY GEN PURPOSE 3PDT 10A 110V In stock: Out stock

MK3PND-5-I-DC24



## MK3PND-5-S-DC48

In stock: Out stock

**Copyright © 2020 Reliable Distributor of Electronic Components - Ocean-Components.com** 

Description: RELAY GEN PURPOSE 3PDT 10A 48V

Manufacturers: Omron Automation & Safety



**RFQ** 

Manufacturers: Omron Automation & Safety

Description: RELAY GEN PURPOSE 3PDT 10A 24V In stock: Out stock

**RFQ** 



Address: Room 2102, Connaught Commercial Building, 185 Wan Chai Rd, Wan Chai, Hong Kong

E-mail: Info@Ocean-Components.com











