



Image may be representation. See specifications for product details.

BD05

Part Number:

Manufacturer/Brand:

Product description

Datasheets: RoHs Status

Ship From

Shipment Way

BD05

C&K

SWITCH SLIDE DIP SPST 100MA 5V

Lead free / RoHS Compliant

BD05.pdf

Hong Kong

DHL/Fedex/TNT/UPS/EMS

REQUEST FOR QUOTATION

Specifications of BD05

PART HUMBER BDDS MANUFACTURER CBK DESCRIPTION SWITCH SLIDE DIP SPST 100MA 5V LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compilant DATA SHEET ■ BDDS, pdf WASHABLE Yes VOLTAGE RATING YEN SERIES BD PITCH 0.100° (2.54mm), Full PACKAGING Tube OTHER NAMES "SBDOS OFFER TING TEMPERATURE 40°C ~ 8°C NUMBER OF POSITIONS 5 MOUNTING TYPE Through Hole MOUNTING TYPE 1(valimited) MECHANICAL LIFE 1(valimited) MECHANICAL LIFE 1(valimited) MERITAR TRANDARD LEAD TIME 12 Weeks LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant LEED FREE STATUS / ROHS STATUS Lead free / RoHS Compliant LEED FREE STATUS / ROHS STATUS <td< th=""><th></th><th>Specifications of BD05</th></td<>		Specifications of BD05
MANUFFACTURER C&K DESCRIPTION SWITCH SLIDE DIP SPST 100MA 5V LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant DATA SHEET SDDS.pdf WASHABLE Yes VOLTAGE RATING SDDC TERRINATION STYLE PC PIN SERIES BD PITCH 0.100° (2.54mm), Full PACKAGING Tube OTHER NAMES "BDOS OFMANDISTATE SEMPERATURE 40°C ~ 85°C NUMBER OF POSITIONS 5 MOUNTING TYPE Through Hole MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) MECHANICAL LIFE 10,000 Cycles MANUFACTURER STANDARD LEAD TIME 12 Weeks LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant HEIGHT ABOVE BOARD 2.29° (7.54mm) FEATURES 1 ELECTRICAL LIFE 10,000 Cycles DETAILED DESCRIPTION Dip Switch SPST 5 Position Through Hole Slide (Standard) Actuator 100mA SVDC CURRENT RATING 5000 M		
DESCRIPTION LEAD FREE STATUS / ROHS STATUS LEAD FREE STATUS / ROHS STATUS DATA SHEET WASHABLE YES VOLTAGE RATING SYDC TERNINATION STYLE PC PIN SERIES BD DATO * (1.54mm), Full TUBE PACKAGING TUBE **** **** **** **** **** ***		
Lead free / RoHS Campliant DATA SHEET WASHABLE VES VOLTAGE RATING VES VOLTAGE RATING VED PC PIN SERIES BD PITCH DATA SHEET WASHABLE VOLTAGE RATING DITUR PCALAGING TUBB PCALAGING TUBB COTHER NAMES CONDOUG CONDOUG CONDOUG MOUNTING TYPE MOUNTING TYPE MOUNTING TYPE MOUNTING TYPE MOUNTING TYPE MOUNTING TYPE MOUNTING SENSITIVITY LEVEL (MSL) MECHANICAL LIFE MOUNTAGE SENSITIVITY LEVEL (MSL) MECHANICAL LIFE MOUNTAGE STATUS MANUFACTURES STATUS MANUFACTURES STATUS LEAD FREE STATUS / ROHS STATUS LEAD FREE STATU	MANUFACTURER	C&K
DATA SHEET Generating VOLTAGE RATING VOLCAGE RATING VOLTAGE RATING VOLCAGE RATING SERIES DP SERIES BD PITCH 0.100° (2.54mm), Full PACKAGING Tube OTHER NAMES "BDOS CKN3004 OPERATING TEMPERATURE 40°C ~ 85°C NUMBER OF POSITIONS 5 MOUNTING TYPE Through Hole MOISTING ESENSITIVITY LEVEL (MSL) 1 (Unlimited) MECHANICAL LIFE 10,000 Cycles MANUFACTURER STANDARD LEAD TIME 12 Weeks LENGTH 0.299° (7.54mm) FEATURES 0.299° (7.54mm) FEATURES 0.299° (7.54mm) FEATURES 1 (0000 Cycles ELECTRICAL LIFE 1 (0000 Cycles DETAILED DESCRIPTION 10,000 Cycles DETAILED DESCRIPTION 10000 Cycles DETAILED DESCRIPTION 10000 Cycles CURRENT RATING 10000 Cycles DETAILED DESCRIPTION 10000 Cycles CURRENT RATING 10000 Cycles CONT	DESCRIPTION	SWITCH SLIDE DIP SPST 100MA 5V
WSHABLE Yes VOLTAGE RATING SVDC TERMINATION STYLE PC Pin SERIES BD PITCH 0.100" (2.54mm), Full PACKAGING Tube OTHER NAMES *RDDOS OPERATING TEMPERATURE 40°C ~ 85°C NUMBER OF POSITIONS 5 MOUNTING TYPE Through Hole MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) MECHANICAL LIFE 10,000 Cycles MANUFACTURER STANDARD LEAD TIME 12 Weeks LENGTH 2.580" (14.73mm) LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant HEIGHT ABOVE BOARD 2.297" (7.54mm) FEATURES 1 ELECTRICAL LIFE 10,000 Cycles DETAILED DESCRIPTION DIP Switch SPST 5 Position Through Hole Silde (Standard) Actuator 100mA SVDC CURRENT RATING 100mA CONTACT MATERIAL Phosphor Bronze CONTACT FINISH 6 old CIOUT SPST BOUM MATERIAL Polybutylene Terophthalate (PBT), Glass Filled	LEAD FREE STATUS / ROHS STATUS	Lead free / RoHS Compliant
VOLTAGE RATING SVDC TERMINATION STYLE PC PIN SERIES BD PITCH 0.100" (2.54mm), Full PACKAGING Tube OTHER NAMES "BD05" AXX3004 OPERATING TEMPERATURE 40°C ~ 85°C NUMBER OF POSITIONS 5 MOUNTING TYPE Through Hole MOINTING TYPE 1 (Unlimited) MECHANICAL LIFE 1,000 Cycles MANUFACTURER STANDARD LEAD TIME 1 (Weeks LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant FEATURES - ELECTRICAL LIFE 1,000 Cycles DETAILED DESCRIPTION 1,000 Cycles DETAILED ACK 1,000 Cycles DETAILED ACK	DATA SHEET	BD05.pdf
TERMINATION STYLE PC PIN SERIES BD PITCH 0.100" (2.54mm), Full PACKAGING Tube OTHER NAMES "BDDS CKN3004 OPERATING TEMPERATURE 40°C ~ 85°C NUMBER OF POSITIONS 5 MOUNTING TYPE Through Hole MOINTING SENSITIVITY LEVEL (MSL) 1 (Unlimited) MECHANICAL LIFE 1,000 Cycles MANUFACTURER STANDARD LEAD TIME 12 Weeks LEAGTH 0.580" (1.4.73mm) LEAGT FREE STATUS / ROHS STATUS Lead free / RoHS Compliant HEIGHT ABOVE BOARD 0.297" (7.54mm) FEATURES - ELECTRICAL LIFE 1,000 Cycles DETAILED DESCRIPTION 100 DIP Switch SPST 5 Position Through Hole Slide (Standard) Actuator 100m 4 SVDC CURRENT RATING 100mA CONTACT MATERIAL Gold CONTACT FINISH Gold CICKLUT SPST BODY MATERIAL Polybutylene Terephthalate (PBT), Glass Filled	WASHABLE	Yes
SERIES BD PITCH 0.100" (2.54mm), Full PACKAGING Tube OTHER NAMES *BDD05 CKN3004 OPERATING TEMPERATURE 40°C ~ 85°C NUMBER OF POSITIONS 5 MOUNTING TYPE Through Hole MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) MECHALICAL LIFE 10,000 Cycles MANUPACTURER STANDARD LEAD TIME 12 Weeks LENGTH 0.580" (14.73mm) LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant HEIGHT ABOVE BOARD 2.97" (7.54mm) FEATURES - ELECTRICAL LIFE 10,000 Cycles DETAILED DESCRIPTION 10,000 Cycles CURRENT RATING 100mA CONTACT MATERIAL Phosphor Bronze CONTACT FINISH Gold CICUIT SPST BODY MATERIAL Polybutylene Terephthalate (PBT), Glass Filled	VOLTAGE RATING	5VDC
PTCH 0.100° (2.54mm), Full PACKAGING Tube OTHER NAMES *BD05° KN3004 OPERATING TEMPERATURE -40°C ~ 85°C NUMBER OF POSITIONS 5 MOUNTING TYPE Through Hole MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) MECHANICAL LIFE 10,000 Cycles LENGTH 0.580° (14.73mm) LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant HEIGHT ABOVE BOARD 0.297° (7.54mm) FEATURES - ELECTRICAL LIFE 10,000 Cycles ELECTRICAL LIFE 10,000 Cycles ELECTRICAL LIFE 10,000 Cycles ELECTRICAL LIFE 10,000 Cycles CURRENT RATING 100mA CONTACT MATERIAL Phosphor Bronze CONTACT FINISH 60id CURCUIT SPST BOY MATERIAL Polybutylene Terephthalate (PBT), Glass Filled	TERMINATION STYLE	PC Pin
PACKAGING Tube OTHER NAMES *BDOS CKN3004 OPERATING TEMPERATURE -40°C ~ 85°C NUMBER OF POSITIONS 5 MOUNTING TYPE Through Hole MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) MECHANICAL LIFE 10,000 Cycles MANUFACTURER STANDARD LEAD TIME 12 Weeks LERGTH 0.580° (14.73mm) LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant HEIGHT ABOVE BOARD 0.297" (7.54mm) FEATURES - ELECTRICAL LIFE 10,000 Cycles ELECTRICAL LIFE 10,000 Cycles ELECTRICAL LIFE 10,000 Cycles ELECTRICAL LIFE 10,000 Cycles CURRENT RATING 100 MA CONTACT MATERIAL 100mA CONTACT FINISH Gold CURCUIT SPST BODY MATERIAL Ploybutylene Terephthalate (PBT), Glass Filled	SERIES	BD
OTHER NAMES*BDOS CKN3004OPERATING TEMPERATURE-40°C ~ 85°CNUMBER OF POSITIONS5MOUNTING TYPEThrough HoleMOISTURE SENSITIVITY LEVEL (MSL)1 (Unlimited)MECHANICAL LIFE10,000 CyclesMANUFACTURER STANDARD LEAD TIME12 WeeksLENGTH0.580° (14.73mm)LEAD FREE STATUS / ROHS STATUSLead free / RoHS CompliantHEIGHT ABOVE BOARD0.297" (7.54mm)FEATURES-ELECTRICAL LIFE10,000 CyclesDETAILED DESCRIPTIONDip Switch SPST 5 Position Through Hole Slide (Standard) Actuator 100mA 5VDCCURRENT RATING100mACONTACT MATERIALPhosphor BronzeCONTACT FINISHGoldCICRUITSPSTBODY MATERIALPolybutylene Terephthalate (PBT), Glass Filled	PITCH	0.100" (2.54mm), Full
CKN3004 OPERATING TEMPERATURE -40°C ~ 85°C NUMBER OF POSITIONS MOUNTING TYPE MOISTURE SENSITIVITY LEVEL (MSL) MECHANICAL LIFE MANUFACTURER STANDARD LEAD TIME LENGTH LEAD FREE STATUS / ROHS STATUS LEAD FREE STATUS / ROHS STATUS LEIGHT ABOVE BOARD FEATURES LECTRICAL LIFE DETAILED DESCRIPTION DIP SWItch SPST 5 Position Through Hole Slide (Standard) Actuator 100mA 5VDC CURRENT RATING CONTACT FINISH CONTACT FINISH EON OF COBE OF SPST BOLDY MATERIAL A O°C ~ 85°C Through Hole 1 (Unlimited) 1 (U	PACKAGING	Tube
MOUNTING TYPE Through Hole MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) MCHANICAL LIFE 10,000 Cycles MANUFACTURER STANDARD LEAD TIME 12 Weeks LENGTH 20,800 (14.73mm) LEAD FREE STATUS / ROHS STATUS 12,000 (7.54mm) HEIGHT ABOVE BOARD 20,207" (7.54mm) FEATURES 20,207" (7.54mm) ELECTRICAL LIFE 10,000 Cycles ELECTRICAL LIFE 10,000 Cycles DETAILED DESCRIPTION 20,000 Cycles CURRENT RATING 100mA CONTACT MATERIAL 20,000 Cycles CONTACT FINISH 20,000 CYCLE	OTHER NAMES	
MOUNTING TYPE MOISTURE SENSITIVITY LEVEL (MSL) MECHANICAL LIFE MANUFACTURER STANDARD LEAD TIME LENGTH LENGTH LEAD FREE STATUS / ROHS STATUS LEAd free / ROHS Compliant LEGHT ABOVE BOARD ELECTRICAL LIFE DETAILED DESCRIPTION CURRENT RATING CONTACT HINISH CONTACT FINISH BODY MATERIAL BODY MATERIAL Through Hole 1. (Unlimited) 1. (Unlimite	OPERATING TEMPERATURE	-40°C ~ 85°C
MOISTURE SENSITIVITY LEVEL (MSL) MECHANICAL LIFE MANUFACTURER STANDARD LEAD TIME LEAD FREE STATUS / ROHS STATUS LEAD FREE STATUS / ROHS STATUS LEAD FREE STATUS / ROHS STATUS LEEGTH ABOVE BOARD FEATURES ELECTRICAL LIFE DIP SWItch SPST 5 Position Through Hole Slide (Standard) Actuator 100mA 5VDC CURRENT RATING CONTACT MATERIAL CONTACT FINISH GOld CIRCUIT BODY MATERIAL 1 (Unlimited) 10,000 Cycles 10,000 Cycles 10,000 Cycles 100mA CONTACT FINISH Gold CIRCUIT SPST Polybutylene Terephthalate (PBT), Glass Filled	NUMBER OF POSITIONS	5
MECHANICAL LIFE 10,000 Cycles MANUFACTURER STANDARD LEAD TIME 12 Weeks LENGTH 0.580" (14.73mm) LEAD FREE STATUS / ROHS STATUS LEAd free / ROHS Compliant HEIGHT ABOVE BOARD 0.297" (7.54mm) FEATURES 10,000 Cycles LECTRICAL LIFE 10,000 Cycles DETAILED DESCRIPTION 10 Dip Switch SPST 5 Position Through Hole Slide (Standard) Actuator 100mA 5VDC CURRENT RATING 100mA CONTACT MATERIAL 0.000 Cycles CONTACT FINISH 6.001 CIRCUIT SPST 5.001 DIP SWITCH SPST	MOUNTING TYPE	Through Hole
MANUFACTURER STANDARD LEAD TIME 12 Weeks LENGTH 0.580" (14.73mm) LEAD FREE STATUS / ROHS STATUS 12 Lead free / ROHS Compliant HEIGHT ABOVE BOARD 0.297" (7.54mm) FEATURES ELECTRICAL LIFE 10,000 Cycles DETAILED DESCRIPTION 100mA CURRENT RATING 100mA CONTACT MATERIAL 100mA CONTACT FINISH 6.61d (Standard) Actuator 100mA 5VDC CURCUIT 9PST GOId CURCUIT 9PST Polybutylene Terephthalate (PBT), Glass Filled	MOISTURE SENSITIVITY LEVEL (MSL)	1 (Unlimited)
LENGTH 0.580" (14.73mm) LEAD FREE STATUS / ROHS STATUS 1.297" (7.54mm) FEATURES ELECTRICAL LIFE 1.000 Cycles DETAILED DESCRIPTION 1.000 A 1.00	MECHANICAL LIFE	10,000 Cycles
LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant DEFATURES ELECTRICAL LIFE DIP Switch SPST 5 Position Through Hole Slide (Standard) Actuator 100mA 5VDC CURRENT RATING CONTACT MATERIAL CONTACT FINISH CIRCUIT BODY MATERIAL BODY MATERIAL Lead free / RoHS Compliant Lead free / RoHS Lead free /	MANUFACTURER STANDARD LEAD TIME	12 Weeks
HEIGHT ABOVE BOARD 0.297" (7.54mm) FEATURES - CONTACT FINISH CONTACT SILECT SI	LENGTH	0.580" (14.73mm)
FEATURES ELECTRICAL LIFE DIP SWITCH SPST 5 Position Through Hole Slide (Standard) Actuator 100mA 5VDC CURRENT RATING CONTACT MATERIAL CONTACT FINISH CIRCUIT BODY MATERIAL Polybutylene Terephthalate (PBT), Glass Filled	LEAD FREE STATUS / ROHS STATUS	Lead free / RoHS Compliant
ELECTRICAL LIFE10,000 CyclesDETAILED DESCRIPTIONDip Switch SPST 5 Position Through Hole Slide (Standard) Actuator 100mA 5VDCCURRENT RATING100mACONTACT MATERIALPhosphor BronzeCONTACT FINISHGoldCIRCUITSPSTBODY MATERIALPolybutylene Terephthalate (PBT), Glass Filled	HEIGHT ABOVE BOARD	0.297" (7.54mm)
DETAILED DESCRIPTION Dip Switch SPST 5 Position Through Hole Slide (Standard) Actuator 100mA 5VDC CURRENT RATING 100mA CONTACT MATERIAL Phosphor Bronze CONTACT FINISH Gold CIRCUIT SPST BODY MATERIAL Polybutylene Terephthalate (PBT), Glass Filled	FEATURES	-
CURRENT RATING 100mA CONTACT MATERIAL Phosphor Bronze CONTACT FINISH Gold CIRCUIT SPST BODY MATERIAL Polybutylene Terephthalate (PBT), Glass Filled	ELECTRICAL LIFE	10,000 Cycles
CONTACT MATERIAL Phosphor Bronze CONTACT FINISH Gold CIRCUIT SPST BODY MATERIAL Polybutylene Terephthalate (PBT), Glass Filled	DETAILED DESCRIPTION	Dip Switch SPST 5 Position Through Hole Slide (Standard) Actuator 100mA 5VDC
CONTACT FINISH CIRCUIT SPST BODY MATERIAL Polybutylene Terephthalate (PBT), Glass Filled	CURRENT RATING	100mA
CIRCUIT SPST BODY MATERIAL Polybutylene Terephthalate (PBT), Glass Filled	CONTACT MATERIAL	Phosphor Bronze
BODY MATERIAL Polybutylene Terephthalate (PBT), Glass Filled	CONTACT FINISH	Gold
	CIRCUIT	SPST
ACTUATOR TYPE Slide (Standard)	BODY MATERIAL	Polybutylene Terephthalate (PBT), Glass Filled
	ACTUATOR TYPE	Slide (Standard)

Related Tags

Raised

C&K BD05	BD05 Distributor	BD05 Supplier
BD05 Price	BD05 Pictures	BD05 Image
BD05 PDF Datasheet	BD05 Download Datasheet	BD05 Datasheet
BD05 Stock	Buy BD05	Buy C&K BD05
C&K BD05	C&K Supplier	C&K Distributor
C&K BD05	C&K Components BD05	

Related Products



ACTUATOR LEVEL

BD03

Manufacturers: C&K Description: SWITCH SLIDE DIP SPST 100MA 5V

In stock: 566 pcs

RFQ

BD04AV2

Manufacturers: C&K Description: SWITCH SLIDE DIP SPST 100MA 5V

In stock: Out stock

RFQ



BD06AV

Manufacturers: C&K

Description: SWITCH SLIDE DIP SPST 100MA 5V In stock: Out stock

RFQ

BD06

Manufacturers: C&K Description: SWITCH SLIDE DIP SPST 100MA 5V

In stock: 984 pcs

RFQ



BD03AV Manufacturers: C&K

Description: SWITCH SLIDE DIP SPST 100MA 5V In stock: 241 pcs

RFQ



BD02AV2

Manufacturers: C&K Description: SWITCH SLIDE DIP SPST 100MA 5V

In stock: Out stock

RFQ



BD04

Manufacturers: C&K Description: SWITCH SLIDE DIP SPST 100MA 5V

In stock: Out stock **RFQ**

BD04AV Manufacturers: C&K

Description: SWITCH SLIDE DIP SPST 100MA 5V

In stock: 187 pcs **RFQ**



BD05AV2

Manufacturers: C&K Description: SWITCH SLIDE DIP SPST 100MA 5V

In stock: Out stock

RFQ



Manufacturers: C&K Description: SWITCH SLIDE DIP SPST 100MA 5V

BD06AV2

In stock: Out stock

RFQ



BD05AV

Manufacturers: C&K



Manufacturers: C&K Description: SWITCH SLIDE DIP SPST 100MA 5V

BD07















