### 7201J1A3QE2 Details PDF



CeK	С&К
	M
	D R Si
<b>C</b> s	SI SI

# 7201J1A3QE2

t Number:
nufacturer/Brand:
duct description
tasheets:
Hs Status
p From

hipment Way

#### 7201J1A3QE2

C&K SWITCH ROCKER DPDT 5A 120V 1.7201J1A3QE2.pdf 2.7201J1A3QE2.pdf Lead free / RoHS Compliant Hong Kong DHL/Fedex/TNT/UPS/EMS

### **REQUEST FOR QUOTATION**

Image may be representation. See specifications for product details.

PART LUMBER     720131A3QE2       MANUFACTURER     C&K       PRESCRIPTION     SMITCH ROCKER DPDT SA 120V       LEAD FREE STATUS / ROHS STATUS     Lead free / RoHS Compliant.       LEAD FREE STATUS / ROHS STATUS     Lead free / RoHS Compliant.       DVLTAGE RATING - DC     28V       VOLTAGE RATING - AC     120V       TERMIJANTON STALE     PC Pin       SWITCH RUNCTON     On-On       SWITCH RUNCTON     SWITCH RUNCTON       PAREL CUTOUT DIMENSIONS     -       SWITCH RUNCTON     SWITCH RUNCTON       PAREL CUTOUT DIMENSIONS     -       RUNCHACILLER     SWITCH RUNCTON       RUNCHACILLER     SWITCH RUNCTON       RUNCHACILLER     I. Uminiand       RUCHACILLER     I. Uminiand       RUCHACILLER		Specifications of 7201J1A3QE2
MANUFACTURERC&KDESCRIPTIONSWITCH NOCKER DPDT 5A L20VLEAD FREE STATUS / ROHS STATUSLead free / ROHS CompliantLEAD FREE STATUS / ROHS STATUSLead free / ROHS CompliantDATA SHEET1.72011/JAQEP.pdfVOLTAGE RATING - DC28VVOLTAGE RATING - DC28VVOLTAGE RATING - AC120VTERNINATION STVLEDC PnSMITCH FUNCTIONOn-OnSRIES7000PANEL CUTOUT DIMENSIONS-PANEL CUTOUT DIMENSIONS-PACKAGINGBulkORGUNE SENSITIVITY LEVEL (MSL)1 (Unimed)MOINTING TYPEThrough Hole, Right AngleMOINTING TYPE1 (Unimed)INGENARCALURE STANDARD LEAD TIME1 WeaksLLUNINATION VOLTAGE (NOMINAL)-ILLUNINATION TYPE, COLOR-ILLUNINATION TYPE, COLOR1000 OydesDETALED SEQUERTIONSocker Switch DPDT SA (AC/DC) 120V Through Hole, Right AngleCURRENT RATINGSocker Switch DPDT SA (AC/DC) 120V Through Hole, Right AngleCURRENT RATINGSocker Switch DPDT SA (AC/DC) 120V Through Hole, Right AngleCURRENT RATINGSocker Switch DPDT SA (AC/DC) 120V Through Hole, Right AngleCURRENT RATINGSocker Switch DPDT SA (AC/DC) 120V Through Hole, Right AngleCURRENT RATINGSocker Switch DPDT SA (AC/DC) 120V Through Hole, Right AngleCURRENT RATINGSocker Switch DPDT SA (AC/DC) 120V Through Hole, Right AngleCURRENT RATINGSocker Switch DPDT SA (AC/DC) 120V Through Hole, Right AngleCURRENT RATINGSocker Switch DPDT SA (AC/DC)		
DESCRIPTIONSWITCH ROCKER PPOT SA 120VLEAD FREE STATUS / ROHS STATUSLead free / ROHS CompliantDATA SHEET1.2201JLA3QE2.pdfVOLTAGE RATING - DC28VVOLTAGE RATING - AC120VTERMINATION STYLEPC PinSWITCH FUNCTIONOn-OnSERIES7000PARLE QUTUUT DIMENSIONS-PACKAGINGBulkOUTAGE RATING FLIPFERATURE-0°C ~ 85°CMOUNTING TYPEThoogh Hole, Right AngleMOUNTING TYPE1 (Unlimited)MICHARE STATUS / ROHS STATUSLead free / KoHS CompliantILLMINATION VOLTAGE (NOMINAL)-ILLUMINATION TYPE, COLOR-FRETESFOOSMOUNTING TYPE1 WeaksILLUMINATION TYPE, COLOR-ILLUMINATION TYPE, COLOR100,000 CyclusILLUMINATION TYPE, COLOR100,000 CyclusILLUMINATION TYPE, COLOR6AckEr Switch DPDT SA (AC/DC) L20V Through Hole, Right AngleICRUITDPDTACTUATOR TYPEConcave (Standard V)	PART NUMBER	7201J1A3QE2
LEAD FREE STATUS / ROHS STATUSLaad free / RoHS CompliantDATA SHEETClarAGE RATING - DC28VVOLTAGE RATING - AC28VVOLTAGE RATING - AC120VTERMINATION STYLEPC PinSWITCH FUNCTIONOn-OnSERIES7000PACAGINGBulkOPERATING TEMPERATURE-0°C ~ 8°CMOUNTING TYPE10Unimited)MOUNTING TYPE10Unimited)MOLTAGE RATING / DC ANS11UekisRECHARING LLIFE-0°C ~ 8°CMOUNTING TYPE10Unimited)MOLTAGER STATUS / ROHS STATUSLead free / ROHS CompliantILLUMINATION TYPE, COLOR-0RECHARICAL LIFE-0MANUFACTURER STANDARD LEAD TIME11WeeksLEAD FREE STATUS / ROHS STATUSLead free / ROHS CompliantILLUMINATION TYPE, COLOR-0ILLUMINATION TYPE, COLOR-0ICLURICAL LIFE100,000 CyclesICLURICAL LIFE100,000 CyclesICLURICAL LIFE00,000 CyclesICLURICAL LIFE00,000 CyclesICLURICAL LIFE00,000 CyclesICLURICAL LIFE00,000 CyclesICLURICAL LIFE00,000 Cycles<	MANUFACTURER	C&K
DATA SHEETDE 1.22011A3QE2.pdfVOLTAGE RATING - DC28VVOLTAGE RATING - AC120VTERMINATION STYLEPC PinSWITCH FUNCTIONOn-OnSRIERS7000PANEL CUTOUT DIMENSIONS-PACKAGINGBulkOPGRATING TEMPERATURE-30°C # 85°CMOUTING TYPEThrough Hole, Right AngleMOUTING TYPE1 (Unlimet)MAULGCLUFER STANDARD LEAD TIME11 WeeksLEAD FREE STATUS / RONS STATUSLead free / RoHS CompliantINGRESS PROTECTION-INGRESS PROTECTION-ILLUMINATION VOLTAGE (NOMINAL)-ILLUMINATION TYPE, COLOR-PEATURESEposy Sealed TerminalsELECTRICAL LIFE10000 CyclesILLUMINATION TYPE, COLOR-ICRUES PROTECTION-ICRUES PROTECTION-ICRUES PROTECTION-ICRUES PROTECTION-ICRUES PROTECTION-ICRUES PROTECTION-ICRUER STANDARD LEAD TIME100000 CyclesICRUER TATINGSA (AC/DC)ICRUER TATINGSA (AC/DC)ICRUER TATINGSA (AC/DC)ICRUER TATINGSA (AC/DC)ICRUER TATINGBlackICRUER TATINGEDPOTICRUER TATING TYPEDIPOTICRUER TATING TYPECONCANC (Standard V)	DESCRIPTION	SWITCH ROCKER DPDT 5A 120V
DATA SHEET     D2 22011143QE2.pdf       VOLTAGE RATING - DC     28V       VOLTAGE RATING - AC     120V       TERMINATION STYLE     PC Pin       SWITCH FUNCTION     On-On       SWITCH FUNCTION     On-On       PAREL CUTOUT DIMENSIONS     -       PAREL CUTOUT DIMENSIONS     -       PAREL CUTOUT DIMENSIONS     -       POPRATING TEMPERATURE     30°C ~ 85°C       MOINTING TYPE     Through Hole, Right Angle       MOISTURE SENSITIVITY LEVEL (MSL)     1 (Unimed)       MANUFACTURER STANDARD LEAD TIME     1 Weeks       LEAD FREE STATUS / ROH'S STATUS     Lead free / RoHS Compliant       ILUMINATION VOLTAGE (MOMINAL)     -       ILUMINATION VOLTAGE (MOMINAL)     -       PEATURES     Epory Sealed Terminals       ELECTRICAL LIFE     10,000 Cycles       PEATURES     Epory Sealed Terminals       CURRENT RATING     SA (AC/DC)       CURRENT RATING     SA (AC/DC)       CURRENT RATING     SA (AC/DC)       CURRENT RATING     Biack	LEAD FREE STATUS / ROHS STATUS	Lead free / RoHS Compliant
Volträge Ratting - ACI20VITERNINATION STVLERC PinSWITCH FUNCTIONOn-OnSERLES7000PAREL CUTOUT DIMENSIONS-PACKAGINGBulkOPERATING TEMPERATURE-30°C ~ 85°CMOUNTING TYPEThrough Hole, Right AngleMOUSTURE SENSITIVITY LEVEL (MSL)1 (Unlimited)MECHANICAL LIFE-MANUFACTURER STANDARD LEAD TIME11 WeeksLEAD FREE STATUS / ROHS STATUSLead free / ROHS CompliantILUMINATION YOPE, COLOR-FEATURESEpoxy Sealed TerminalsELECTRICAL LIFE100,000 CyclesDETAILED DESCRIPTIONSC (AC/DC)CURRENT RATINGSA (AC/DC)COLOR - ACTUATOR/CAPBlackCIRCUITDPDTACTUATOR TYPEConcave (Standard V)	DATA SHEET	
TERMINATION STYLEPC PinSWITCH FUNCTIONOn-OnSERIES7000PANEL CUTOUT DIMENSIONS-PACKAGINGBulkOPERATING TEMPERATUREBulkOPERATING TEMPERATURE30°C ~ 85°CMOUNTING TYPEThrough Hole, Right AngleMOUNTING TYPE1 (Unlimited)MOSTURE SENSITIVITY LEVEL (MSL)1 (Unlimited)MANUFACTURER STANDARD LEAD TIME1 WeeksLEAD FREE STATUS / ROHS STATUSLead free / RoHS CompliantILLUMINATION VOLTAGE (NOMINAL)-LILUMINATION TYPE, COLOR6FEATURESEpoxy Sealed TerminalsELECTRICAL LIFE100,000 CyclesDETAILED DESCRIPTIONSA (AC/DC)CURRENT RATINGSA (AC/DC)CURRENT RATINGSA (AC/DC)CURRENT RATINGSA (AC/DC)CURRENT RATINGDPDTACTUATOR TYPEConcave (Standard V)	VOLTAGE RATING - DC	28V
SWITCH FUNCTIONOn-OnSERIES7000PANEL CUTOUT DIMENSIONS-PACKAGINGBulkOPERATING TEMPERATURE30° ~ 85°CMOUNTING TYPEThrough Hole, Right AngleMOUNTING TYPE1 (Unlimited)MOISTURE SENSITIVITY LEVEL (MSL)1 (Unlimited)MECHANICAL LIFE-MANUFACTURER STANDARD LEAD TIME11 WeeksILLUMINATION VOLTAGE (NOMINAL)-ILLUMINATION VOLTAGE (NOMINAL)-FECTURESFpoxy Sealed TerminalsILLUMINATION TYPE, COLORAck/CPCDETAILED DESCRIPTIONSA (AC/DC)CURRENT RATINGSA (AC/DC)COLOR - ACTUATOR/CAPBiakCIRCUITOPDTACTUATOR TYPEConcare (Standard V)	VOLTAGE RATING - AC	120V
SERIES700PANEL CUTOUT DIMENSIONS-PACKAGINGBulkPACKAGING- 30°C ~ 85°CMOUNTING TEMPERATURE- 30°C ~ 85°CMOUNTING TYPEThrough Hole, Right AngleMOISTURE SENSITIVITY LEVEL (MSL)1 (Unlimited)MECHANICAL LIFE-MANUFACTURER STANDARD LEAD TIME1 WeeksLEAD FREE STATUS / ROHS STATUSLead free / ROHS CompliantILUMINATION VOLTAGE (NOMINAL)-ILUMINATION VOLTAGE (NOMINAL)-ELECTRICAL LIFEEpoxy Sealed TerminalsELECTRICAL LIFE100,000 CyclesDETAILED DESCRIPTIONSACKER Switch DPDT SA (AC/DC) 120V Through Hole, Right AngleCURRENT RATINGSA (AC/DC)COLOR - ACTUATOR/CAPBlackACTUATOR TYPEConcave (Standard V)	TERMINATION STYLE	PC Pin
PAREL CUTOUT DIMENSIONS-PACKAGINGBulkPACKAGINGSo°C ~ 85°CMOUNTING TEMPERATURE-MOUNTING TYPEI(Unlimited)MOISTURE SENSITIVITY LEVEL (MSL)1 (Unlimited)MECHANICAL LIFE-MANUFACTURER STANDARD LEAD TIME11 WeeksLEAD FREE STATUS / ROHS STATUSLead free / ROHS CompliantINGRESS PROTECTION-ILLUMINATION VOLTAGE (NOMINAL)-FEATURESEpoxy Sealed TerminalsELECTRICAL LIFE00,000 CyclesDETAILED DESCRIPTIONSA (AC/DC)CURRENT RATINGSA (AC/DC)COLOR - ACTUATOR/CAPBlackCIRCUITDPDTACTUATOR TYPEConcave (Standard V)	SWITCH FUNCTION	On-On
PACKAGINGBulkOPERATING TEMPERATURE-30°C ~ 85°CMOUNTING TYPEThrough Hole, Right AngleMOISTURE SENSITIVITY LEVEL (MSL)1 (Unlimited)MECHANICAL LIFE-MANUFACTURER STANDARD LEAD TIME11 WeeksLEAD FREE STATUS / ROHS STATUSLead free / ROHS CompliantINGRESS PROTECTION-ILLUMINATION VOLTAGE (NOMINAL)-FEATURESEpoxy Sealed TerminalsELECTRICAL LIFE00,000 CyclesCURRENT RATINGSA (AC/OC)CURRENT RATINGSA (AC/OC)CURRENT RATINGDPDTCOLOR - ACTUATOR/CAPBlackACTUATOR TYPEConcave (Standard V)	SERIES	7000
OPERATING TEMPERATURE-30°C ~ 85°CMOUNTING TYPEThrough Hole, Right AngleMOISTURE SENSITIVITY LEVEL (MSL)1 (Unlimited)MECHANICAL LIFE-MANUFACTURER STANDARD LEAD TIME11 WeeksLEAD FREE STATUS / ROHS STATUSLead free / ROHS CompliantINGRESS PROTECTION-ILLUMINATION VOLTAGE (NOMINAL)-FEATURESEpoxy Sealed TerminalsELECTRICAL LIFE100,000 CyclesCURRENT RATINGSA (AC/DC)CURRENT RATINGSA (AC/DC)CURRENT RATINGSA (AC/DC)COLOR - ACTUATOR/CAPBlackACTUATOR TYPECOncave (Standard V)	PANEL CUTOUT DIMENSIONS	-
MOUNTING TYPEThrough Hole, Right AngleMOISTURE SENSITIVITY LEVEL (MSL)1 (Unlimited)MECHANICAL LIFE-MANUFACTURER STANDARD LEAD TIME11 WeeksLEAD FREE STATUS / ROHS STATUSLead free / ROHS CompliantINGRESS PROTECTION-ILLUMINATION VOLTAGE (NOMINAL)-ILLUMINATION TYPE, COLOR-FEATURESEpoxy Sealed TerminalsELECTRICAL LIFE100,000 CyclesOLTRENT RATINGSA (AC/DC)CURRENT RATINGSA (AC/DC)COLOR - ACTUATOR/CAPBlackACTUATOR TYPEOppTACTUATOR TYPEConcave (Standard V)	PACKAGING	Bulk
MOISTURE SENSITIVITY LEVEL (MSL)1 (Unlimited)MECHANICAL LIFE-MANUFACTURER STANDARD LEAD TIME11 WeeksLEAD FREE STATUS / ROHS STATUSLead free / ROHS CompliantINGRESS PROTECTION-ILLUMINATION VOLTAGE (NOMINAL)-ILLUMINATION TYPE, COLOR-FEATURESEpoxy Sealed TerminalsELECTRICAL LIFE100,000 CyclesICURRENT RATING-CURRENT RATINGSA (AC/DC)COLOR - ACTUATOR/CAPBlackCIRCUITDPDTACTUATOR TYPEConcave (Standard V)	OPERATING TEMPERATURE	-30°C ~ 85°C
MECHANICAL LIFE-MANUFACTURER STANDARD LEAD TIME11 WeeksLEAD FREE STATUS / ROHS STATUSLead free / ROHS CompliantINGRESS PROTECTION-ILLUMINATION VOLTAGE (NOMINAL)-ILLUMINATION TYPE, COLOR-FEATURESEpoxy Sealed TerminalsELECTRICAL LIFE100,000 CyclesDETAILED DESCRIPTIONSckcer Switch DPDT 5A (AC/DC) 120V Through Hole, Right AngleCURRENT RATING5A (AC/DC)COLOR - ACTUATOR/CAPBlackACTUATOR TYPEDPDT	MOUNTING TYPE	Through Hole, Right Angle
MANUFACTURER STANDARD LEAD TIME11 WeeksIEAD FREE STATUS / ROHS STATUSLead free / ROHS CompliantINGRESS PROTECTION-ILLUMINATION VOLTAGE (NOMINAL)-ILLUMINATION TYPE, COLOR-FEATURESEpoxy Sealed TerminalsELECTRICAL LIFE100,000 CyclesDETAILED DESCRIPTIONRocker Switch DPDT 5A (AC/DC) 120V Through Hole, Right AngleCURRENT RATINGSA (AC/DC)COLOR - ACTUATOR/CAPBlackACTUATOR TYPEDPDT	MOISTURE SENSITIVITY LEVEL (MSL)	1 (Unlimited)
LEAD FREE STATUS / ROHS STATUSLead free / RoHS CompliantINGRESS PROTECTION-ILLUMINATION VOLTAGE (NOMINAL)-ILLUMINATION TYPE, COLOR-FEATURESEpoxy Sealed TerminalsELECTRICAL LIFE100,000 CyclesDETAILED DESCRIPTIONRocker Switch DPDT 5A (AC/DC) 120V Through Hole, Right AngleCURRENT RATINGSA (AC/DC)COLOR - ACTUJATOR/CAPBlackCIRCUITDPDTACTUATOR TYPEConcave (Standard V)	MECHANICAL LIFE	-
INGRESS PROTECTION-ILLUMINATION VOLTAGE (NOMINAL)-ILLUMINATION TYPE, COLOR-FEATURESEpoxy Sealed TerminalsELECTRICAL LIFE100,000 CyclesDETAILED DESCRIPTIONRocker Switch DPDT 5A (AC/DC) 120V Through Hole, Right AngleCURRENT RATING5A (AC/DC)COLOR - ACTUATOR/CAPBlackCIRCUITDPDTACTUATOR TYPEConcave (Standard V)	MANUFACTURER STANDARD LEAD TIME	11 Weeks
ILLUMINATION VOLTAGE (NOMINAL)-ILLUMINATION TYPE, COLOR-FEATURESEpoxy Sealed TerminalsELECTRICAL LIFE100,000 CyclesDETAILED DESCRIPTIONRocker Switch DPDT 5A (AC/DC) 120V Through Hole, Right AngleCURRENT RATING5A (AC/DC)COLOR - ACTUATOR/CAPBlackCIRCUITDPDTACTUATOR TYPEConcave (Standard V)	LEAD FREE STATUS / ROHS STATUS	Lead free / RoHS Compliant
ILLUMINATION TYPE, COLOR-FEATURESFpoy Sealed TerminalsFLECTRICAL LIFE100,000 CyclesDETAILED DESCRIPTIONRocker Switch DPDT 5A (AC/DC) 120V Through Hole, Right AngleCURRENT RATING5A (AC/DC)COLOR - ACTUATOR/CAPBlackCIRCUITDPDTACTUATOR TYPEConcave (Standard V)	INGRESS PROTECTION	-
FEATURESEpoxy Sealed TerminalsELECTRICAL LIFE100,000 CyclesDETAILED DESCRIPTIONRocker Switch DPDT 5A (AC/DC) 120V Through Hole, Right AngleCURRENT RATING5A (AC/DC)COLOR - ACTUATOR/CAPBlackCIRCUITDPDTACTUATOR TYPEConcave (Standard V)	ILLUMINATION VOLTAGE (NOMINAL)	-
ELECTRICAL LIFE100,000 CyclesDETAILED DESCRIPTIONRocker Switch DPDT 5A (AC/DC) 120V Through Hole, Right AngleCURRENT RATING5A (AC/DC)COLOR - ACTUATOR/CAPBlackCIRCUITDPDTACTUATOR TYPEConcave (Standard V)	ILLUMINATION TYPE, COLOR	-
DETAILED DESCRIPTIONRocker Switch DPDT 5A (AC/DC) 120V Through Hole, Right AngleCURRENT RATING5A (AC/DC)COLOR - ACTUATOR/CAPBlackCIRCUITDPDTACTUATOR TYPEConcave (Standard V)	FEATURES	Epoxy Sealed Terminals
CURRENT RATING5A (AC/DC)COLOR - ACTUATOR/CAPBlackCIRCUITDPDTACTUATOR TYPEConcave (Standard V)	ELECTRICAL LIFE	100,000 Cycles
COLOR - ACTUATOR/CAP Black   CIRCUIT DPDT   ACTUATOR TYPE Concave (Standard V)	DETAILED DESCRIPTION	Rocker Switch DPDT 5A (AC/DC) 120V Through Hole, Right Angle
CIRCUIT DPDT   ACTUATOR TYPE Concave (Standard V)	CURRENT RATING	5A (AC/DC)
ACTUATOR TYPE Concave (Standard V)	COLOR - ACTUATOR/CAP	Black
	CIRCUIT	DPDT
	ACTUATOR TYPE	Concave (Standard V)
ACTUATOR MARKING No Marking	ACTUATOR MARKING	No Marking

## **Related Tags**

C&K 7201J1A3QE2	7201J1A3QE2 Distributor	7201J1A3QE2 Supplier
7201J1A3QE2 Price	7201J1A3QE2 Pictures	7201J1A3QE2 Image
7201J1A3QE2 PDF Datasheet	7201J1A3QE2 Download Datasheet	7201J1A3QE2 Datasheet
7201J1A3QE2 Stock	Buy 7201J1A3QE2	Buy C&K 7201J1A3QE2
C&K 7201J1A3QE2	C&K Supplier	C&K Distributor
C&K 7201J1A3QE2	C&K Components 7201J1A3QE2	

## **Related Products**

	7201J1AGE2		7201J1A3GE2
	Manufacturers: C&K	0 1/	Manufacturers: C&K
2.	Description: SWITCH ROCKER DPDT 5A 120V In stock: Out stock	2.	Description: SWITCH ROCKER DPDT 5A 120V In stock: Out stock
	RFQ		RFQ
	7201J1ABE3		7201J19ZQI32
	Manufacturers: C&K	0 1/	Manufacturers: C&K
-2.	Description: SWITCH ROCKER DPDT 0.4VA 20V	-2.1	Description: SWITCH ROCKER DPDT 5A 120V
	In stock: Out stock		In stock: Out stock
	RFQ		RFQ
	7201J1A3LE2		7201J1ABE2
	Manufacturers: C&K	1	Manufacturers: C&K
-2.	Description: SWITCH ROCKER DPDT 5A 120V		Description: SWITCH ROCKER DPDT 0.4VA 20V
	In stock: Out stock	11111	In stock: 327 pcs
	RFQ	61.1	RFQ

7201J1AGE1

7201J1A3BE2



Manufacturers: C&K Description: SWITCH ROCKER DPDT 5A 120V In stock: Out stock

RFQ



Manufacturers: C&K Description: SWITCH ROCKER DPDT 0.4VA 20V In stock: Out stock

RFQ

#### 7201J1A3ME2 7201J1ABE1 Manufacturers: C&K Manufacturers: C&K **C**&K **C**&K Description: SWITCH ROCKER DPDT 5A 120V Description: SWITCH ROCKER DPDT 0.4VA 20V In stock: Out stock In stock: Out stock RFQ RFQ 7201J1A3BE1 7201J1AME2 Manufacturers: C&K Manufacturers: C&K C&K C&K Description: SWITCH ROCKER DPDT 0.4VA 20V Description: SWITCH ROCKER DPDT 5A 120V In stock: Out stock In stock: Out stock RFQ RFQ

#### Copyright @ 2020 Reliable Distributor of Electronic Components - Ocean-Components.com

E-mail: Info@Ocean-Components.com

Address: Room 2102, Connaught Commercial Building, 185 Wan Chai Rd, Wan Chai, Hong Kong

