## SH-7070MC Details PDF





Image may be representation. See specifications for product details.

# SH-7070MC

Part Number:
Manufacturer/Brand:
Product description
Datasheets:
RoHs Status
Ship From
Shipment Way

# SH-7070MC Copal Electronics SW ROTARY DIP HEX COMP 100MA 5V SH-7070MC.pdf Lead free / RoHS Compliant Hong Kong DHL/Fedex/TNT/UPS/EMS

## **REQUEST FOR QUOTATION**

PART NUMBER     SH-7070MC       MANUFACTURER     Copal Electronics       DESCRUTTON     SM ROTARY DIP HEC COMP LODMA SV       LEAD FREE STATUS / ROHS STATUS     Lead free / RoHS Compliant       DATA SHERT     Cold free / RoHS Compliant       DATA SHERT     Cold free / RoHS Compliant       VOLTAGE RATING     SVC       TERNINATION STYLE     RC Pin       SERTES     SH-7000       OTTAGE RATING     SVC       OTTAGE RATING     SVC       OTTAGE RATING     SVC       SERTES     SH-7000       OTTAGE RATING     SVC       NUMERC OF OSTITONS     16       NUMFRCTURER STATUSE RONSTITUTY LEVEL (MSI)     1 (Ultimited)       MUMER SE STATUS / ROHS STATUS     Lodd free / RoHS Compliant       HEGAT ABOVE BOAND     1 (SVC		Specifications of SH-7070MC
MAURPACTURERCopal ElectomicsDESCRIPTIONSW ROTARY DIP HEX COMP 100MA SVLEAD FREE STATUSLead free / RaNS CompliantDATA SHEETSS 1-7070MC.pdfWASHAUELYosVOLTAGE NATINGSV0CREMINIATION STYLERC PinSERIFSSH-7000PITCHOL007 (L2.5hmm), FullPACKAGINGTubeOTHER NAMESSS 1-722.15SW ROTARY DIP HEX COMP LOOKSS 1-722.15OTHER NAMESSS 1-722.15OTHER NAMESSS 1-722.15OTHER NAMESSS 1-722.15OTHER NAMESSS 1-722.15OTHER NAMESSS 1-722.15OTHER NAMESSS 1-722.15MURBER OF POSITIONS16NUMBER OF POSITIONS16NUMBER OF POSITIONS10MURBER OF POSITIONS10MURBER OF POSITIONS10 (Volimited)MURDER STATUS LEAD TIME10 WealsILINTHLORD LEAD TIMELINTHLORD CONTACT MARIALINTHLORD LEAD TIMELINTHCONTACT TIMESLINTHCONTACT TIMESLINTHCONTACT TIMESLINTHGONACONTACT TINISHGAPA ANDCONTACT TINISHGAPA ANDCONTACT TINISHGAPA CONTACT MARIACONTACT TINISHGAPANESALIGL (PPS) <tr< th=""><th></th><th></th></tr<>		
DescriptionSix RATRY DIP HEX CMP 100M 3VLEAD FREE STATUS / ROHS STATUSLead free / RoHS CompliantDATA SHEETSix 97070MC.pdfWASHABLEYesVILTAGE RATINGSVCCILTAGE RATINGPC PinSERLES9147000PITCHDuf0 (2.54mm), FullPACAGINGSix 3221-5OTHER INAMESSix 3222-15OTHER INAMESSix 3222-15NUMBER OF POSITIONSSix 3222-15MINDER OF POSITIONSSix 3222-15MINDER STATUSSix 3222-15ILCHARTING LIEPESix 3222-15ELECTRICAL LIEPESix 3222-15ELECTRICAL LIEPESix 3222-15DISTATE RATINGSix 3222-15CONTACT RATINGGoleCONTACT RATINGGoleCONTACT RATINGGoleCONTACT RINSHGoley Six MUSA <tr< td=""><td>PART NUMBER</td><td>SH-7070MC</td></tr<>	PART NUMBER	SH-7070MC
LEAD FREE STATUS / ROHS STATUSLead free / RohS CompliantDATA SHEETSH-7070K cpdfWASHABLEYesVOLTAGE RATINGSVDCTEMULATION STYLEP PinSERIESSH-7070 (2.54mm), FullPACKAGINGTubePACKAGINGTubeOTHER NAMESSS-1222-5SH-7070 XDSS-1222-5SH-7070 XDSS-1222-5SH-7070 XDSS-1222-5OTHER NAMES40°C ~ 85°CNUMBER OF POSITIONS16MOUTING TYPENovel HoleMOUTING TYPE1000 HoleMOUTING TYPE0.28°C / 0.50°CMOUTING TYPE1040KMOUTING TYPE1040KMOUTING TYPE0.28°C / 0.50°CMOUTING TYPE0.28°C / 0.50°CMOUTING TYPE1040KMOUTING TYPE0.28°C / 0.50°CMOUTING TYPE0.28°C / 0.50°CMOUTING TYPE1040KMOUTING TYPE0.28°C / 0.50°CLEAGTH0.28°C / 0.50°CLEAGTH0.28°C / 0.50°CLEAGTH0.28°C / 0.50°CLEAGTH0.28°C / 0.50°CLEAGTH0.146° (0.70°C)FEATURES0.146° (0.70°C)LEAGTHARING0.50°CLEAGTHARING0.50°CLEAGTHARING0.50°CLEAGTHARING0.50°CLEAGTHARING0.50°CLEAGTHARING0.50°CLEAGTHARING0.50°CLEAGTHARING0.50°CLEAGTHARING0.50°CLEAGTHARING0.50°CLEAGTHARING0.	MANUFACTURER	Copal Electronics
DATA SHEETSi SH-7000C.pdfWASHABLEYosVOLTAGE RATINGSVDCTERMINATION STYLEPC PinSRIFSSH-7000PTCH0.100 (2.5mm), FuilPACKAGINGTubeOTHER NAMESSSH-7221-5SRIFSSH-7000OTHER NAMESSH-7000OTHER NAMESSH-7000OTHER NAMESSH-7000OTHER NAMESSH-7000OTHER NAMESSH-7000OTHER NAMESSH-7000OTHER NAMESSH-7000OTHER NAMESSH-7000OTHER NAMESSH-7000OTHER NAMESSH-7000NUBRER OF POSITIONS16MOUTSTURE SENSITIVITY LEVEL (MSL)In OrgoMOUTSTURE SENSITIVITY LEVEL (MSL)In OrgoMURFACTURER STANDARD LEAD TIMEIn SH-RAKS CompliantLEGATH ADOVE BOARDSH-7000LEGATH ADOVE BOARDIn ONG SEPSELGATA LIFEIn ONG SEPSELGATALLIFEIn ONG SEPSCINTACT MERIALCopper AllonCINTACT MERIALCopper AllonCINTACT MERIALGoper AllonCINTACT FINSHGalCINTACT FINSHGoldCIONTACT FINSHFoldenal ComplementFOLTALET, FINSHPolynenyschafter Statifier (PSS)CINTACT FINSHFoldenal ComplementFOLTALET, FINSHFoldenal ComplementFOLTALET, FINSHFoldenal ComplementFOLTALET, FINSHFoldenal ComplementFOLTALET, FINSHFoldenal ComplementFOLTALET, FINSHFoldenal	DESCRIPTION	SW ROTARY DIP HEX COMP 100MA 5V
WashableYesVolTade RATINGSVCTERMINATION STYLEPC PinSERIESSH-7000PITCH0.100° (2.54mm), FullPACKAGINGTubOTHER NAMESSSG-1221-SOTHER NAMESSGS-1221-SOVERATING TEMPERATURE-0°C ~ 85°CNUMBER OF POSITIONS16MOUNTING TYPETurough HoleMOUNTING TYPE1 (Unlimited)MOUNTING TYPE1 (Unlimited)MOUNTING TYPE1 (Verschaftlage Status) (Verschaftlage Status)MOUNTING TYPE0.287° (2.30mm)MECHANICAL LIFE0.287° (2.30mm)LEAD FLOR STATUS ADDARD LEAD TIME0.46° (3.70mm)LEAD FLOR STATUS ADDARD LEAD TIME0.40° (3.70mm)ELECTRICAL LIFE0.000 SepsELECTRICAL LIFE0.000 SepsELECTRICAL LIFE0.000 SepsCONTACT MATERIAL0.000 SepsCONTACT MATERIALCoper AlioyCONTACT FINISHGodCONTACT FINISHGodCONTACT FINISHGodCONTACT FINISHFeademinal ComplementFORTULEFeademinal ComplementCONTACT FINISHGodCONTACT FINISHFeademinal ComplementCONTACT FINISHFeademinal ComplementCONTAC	LEAD FREE STATUS / ROHS STATUS	Lead free / RoHS Compliant
VCITAGE RATINGSVCTERMINATION STYLEPC PASERIESSH-7000PITCH0.100° (2.54mm), FullPACKAGINGTubeOTHER NAMESG33-1221-5OTHER NAMES40°C ~ 85°CNUMBER OF POSITIONS16MOUNTING TYPEThough HoleMOUNTING TYPE1(Unimited)MOUNTING TYPE1(Unimited)MOUNTING TYPE1.10kekMAUFACTURER STANDARD LEAD TIME1.10kekLEATRING1.287° (7.30mn)LEAD FREE STATUS / ROHS STATUS1.646 (7.00m)FEATURES0.146° (3.00m)FEATURES0.146° (3.00m)FEATURES1.00SERSECURRENT TATURE1.00SERSECURRENT TATURE1.00SERSE<	DATA SHEET	BH-7070MC.pdf
TERNINATION STYLEPC PinSERIESSH-700PTCH0.10° (2.54mm), FullPACAGINGTubeOTHER NAMESSi3:121-5 SH7070MCOPERATURE TEMPERATURE-0°C × 65°CNUMBER OF POSITIONS6MOUNTING TYPETubugh HoleMOUNTING TYPE1 (Unimited)MOUNTING TYPE0.2677 (30mn)ILENGTH0.2677 (30mn)LENGTH0.166 (3000 Regulatione)FERSTUS / ROPE BOARD0.166 (3000 Regulatione)CURRENT RATING0.160 Regulatione)CURRENT RATING0.160 Regulatione)CURRENT RATING0.160 Regulatione)CONTACT FINISH0.161 Readecimal Complement 16 Position Through Hole Rotary for Tool Actuatione)CONTACT FINISH0.162 Regulatione)CONTACT FINISH0.162 Regulatione)GOUY MATERIAL0.162 Regulatione)GOUY MATERIAL0.162 REGULATIONCONTACT FINISH0.162 Regulatione)GOUY MATERIAL0.162 REGULATION <td< td=""><td>WASHABLE</td><td>Yes</td></td<>	WASHABLE	Yes
SRIES9H700PTCH0.10° (25mm), FullPACKAGINGTubOTHER NAMES35-1221-5OTHER NAMES-40° C 95°CNUMERC OF POSITIONS40°C 40°CMOUNTING TYPETorogh HoleMOUNTING TYPE(Milmid)MAUFACTURER STANDAD LEDD TIME1MAUFACTURER STANDAD LEDD TIME1MAUFACTURER STANDAD LEDD TIME1MAUFACTURER STANDAD LEDD TIME1LEGTH ADOVE DADAS2.02°C (2000)FATURES0.02°C (2000)FATURES1.00°C (2000)FATURES1.00°C (2000)FATURES1.00°C (2000)COTACT MING0.00°C (2000)COTACT MING0.00°C (2000)COTACT FINSH0.00°C (2000)<	VOLTAGE RATING	5VDC
PICH0.00° (2.54mm), FullPACKAGINGTubeOTHER NAMESSi3-1221-5 Si7/070MCOPERATING TEMPERATURE-40°C - 85°CNUMBER OF POSITIONS6MOUNTING TYPETorogh HoleMOUNTING TYPE(Unlimited)MOLFARATURE STANDARD LEAD TIME1 (Velnimed)MAUFACTURER STANDARD LEAD TIME1 VelesLENGTH0.287° (7.30mn)LEAD FRE STATUS / ROHS STATUSLed fre/ ROHS CompliantLEGTRIACULIFE0.406 (3.00m)FATURES0.406 (3.00m)FATURES1.900 StatECTRIACULIFE0.900 StatCORACT MITERIAL0.900 StatCORACT ATING0.900 ALCORTACT TINSHGoldCORTACT FUNSHGoldCORTACT FUNSHGoldCORTACT FUNSHGaldCORTACT FUNSHHexadeninal Complement 1.6 Position Tinrough Hole Rotary for Tool Actuator 1.000 ASCORTACT FUNSHGoldCORTACT FUNSHGoldCORTACT FUNSHGaldCARCUTHexadeninal Complement 1.6 Position Tinrough Hole Rotary for Tool Actuator 1.000 ASCORTACT FUNSHGoldCORTACT FUNSHGoldCONTACT FUNSHGoldCONTACT FUNSHHexadeninal Complement 1.6 Position Tinrough Hole Rotary for Tool Actuation 1.000 ASCONTACT FUNSHGoldCONTACT FUNSHGoldCONTACT FUNSHHexadeninal Complement 1.6 Position Tinrough Hole Rotary FUNSHCONTACT FUNSHGoldCONTACT FUNSHHexadeninal Complement 1.6 Position Time 1.000 AS <td>TERMINATION STYLE</td> <td>PC Pin</td>	TERMINATION STYLE	PC Pin
PACKAGINGTubeOTHER NAMES\$\$31215OTHER NAMES40°C ~ 85°CNUMBER OF POSITIONS16MOUNTING TYPETinoigh HoleMOISTURE SENSITIVITY LEVEL (MSL)( Unlimited)MECHANICAL LIFE-MANUFACTURER STANDARD LEAD TIME1 WedsLENGTH028°C 7030m)LENGTH028°C 7030m)LEIGHT ABOVE BOARD0146' (370m)FETRES-ELECTRICAL LIFE0100 StepsELECTRICAL LIFE0100 StepsELECTRICAL LIFE0100 StepsCONTACT MATERIAL000 StepsCONTACT MATERIAL000 StepsCONTACT MATERIAL000 StepsCONTACT MATERIAL000 StepsCONTACT FINISH000 StepsCONTACT FINISH	SERIES	SH-7000
OTHER NAMES\$63-1221-5 SH7070KOPERATING TEMPERATURE-40°C ~ 85°CNUMBER OF POSITIONS16MOUNTING TYPEThrough HoleMOISTURE SENSITIVITY LEVEL (MSL)1 (Unimited)MECHANICAL LIFE-MANUFACTURER STANDARD LEAD TIME1 WeeksLENGTH0.287° (7.30mn)LEGHT ABOVE BOARD0.146° (3.70mn)ELEGHT ABOVE BOARD0.146° (3.70mn)ELEGTAL LIFE0.000 StepsELECTICAL LIFE10,000 StepsCURRENT RATINGDip Switch Hexadecimal Complement 16 Position Through Hole Rotary for Tool Actuator 100m ASTOCCURRENT RATINGGoldCONTACT MATERIALGoldCONTACT FINISHGoldCURLUTMexadecimal ComplementFATUREXGoldCURATURALMexadecimal ComplementCONTACT FINISHGoldCURATURALMontenentCONTACT FINISHMexadecimal ComplementCONTACT FINISHGoldCURATURALMontenentCONTACT FINISHMexadecimal ComplementCONTACT TYPEMexadecimal ComplementCONT	PITCH	0.100" (2.54mm), Full
CITRER MARIESSH7070MCOPERATING TEMPERATURE-40°C ~ 85°CNUMBER OF POSITIONS16MOUNTING TYPEThrough HoleMOUNTING TYPE1 (Unlinited)MARUFACTURE SENSITIVITY LEVEL (MSL)1 (Unlinited)MANUFACTURER STANDARD LEAD TIME-MANUFACTURER STANDARD LEAD TIME11 WeeksLENGTH0.287" (7.30mm)LEAD FREE STATUS / ROHS STATUSLead free / ROHS CompliantHEIGHT ABOVE BOARD0.146" (3.70mm)ELECTRICAL LIFE1.000 StepsDETAILED DESCRIPTIONDip Switch Hexadecimal Complement 16 Position Through Hole Rotary for Tool Actuator 100m AS VOCCURRENT RATINGCopper AlloyCONTACT FINISHGoldGROUT ATTERIALCopper AlloyBODY MATERIALPhylpengengtife (PPS)ACTUATOR TYPERotary for Tool	PACKAGING	Tube
NUMBER OF POSITIONS16MOUNTING TYPEThrough HoleMOISTURE SENSITIVITY LEVEL (MSL)I (Unlimited)MECHANICAL LIFE-MANUFACTURER STANDARD LEAD TIME11 WeeksLENGTH0.287" (7.30mm)LEAD FREE STATUS / ROHS STATUSKed free / ROHS CompliantHEIGHT ABOVE BOARD0.146" (3.70mm)ELCTRICAL LIFE0.000 StepsELCTRICAL LIFE1000 StepsCURRENT RATINGOig Waith Hexadecimal Complement 16 Position Through Hole Rotary for Tool Actuaton 100mA STATUSCURRENT RATINGGodCONTACT FINISHGodCONTACT FINISHHexadecimal Complement 16BODY MATERIALPolynenysching (PS)ACTUATOR TYPERotary Forol	OTHER NAMES	
MOURTING TYPEThrough HoleMOURTING TYPE1 (Unlimited)MOISTURE SENSITIVITY LEVEL (MSL)1 (Unlimited)MECHANICAL LIFE-MANUFACTURER STANDARD LEAD TIME1 WeeksLENGTH0.287° (7.30mm)LEAD FREE STATUS / ROHS STATUSLed free / ROHS CompliantHEIGHT ABOVE BOARD0.146° (3.70mm)FEATURES-ELCTRICAL LIFE0.000 StepsCURRENT RATINGDips Witch Hexadecimal Complement 16 Position Through Hole Rotary for Ol Actuator 100mA SVCECURRENT RATINGGoper AlloyCONTACT FINISHGoldCONTACT FINISHHexadecimal ComplementFOR MATERIALGoldCONTACT FINISHBoxy pensitified (PPS)ACTUATOR TYPERotary for Tool	OPERATING TEMPERATURE	-40°C ~ 85°C
MOISTURE SENSITIVITY LEVEL (MSL)1 (Unlimited)MECHANICAL LIFE-MANUFACTURER STANDARD LEAD TIME11 WeeksLENGTH0.287" (7.30mm)LEAD FREE STATUS / ROHS STATUSLead free / ROHS CompliantHEIGHT ABOVE BOARD0.146" (3.70mm)FEATURES-ELECTRICAL LIFE0.000 StepsCURRENT RATINGDip Switch Hexadecimal Complement 16 Position Through Hole Rotary for Tool Actuator 100m A STOCCURRENT RATINGGoldCONTACT FINISHGoldBODY MATERIALPolyphenylene Sulfide (PPS)ACUATOR TYPERotary for Tool	NUMBER OF POSITIONS	16
MECHANICAL LIFE.MANUFACTURER STANDARD LEAD TIME1 WeksLENGTH0.83" (7.00m)LEAD FREE STATUS / ROHS STATUSLead free / ROHS CompliantHEIGHT ABOVE BOARD0.146" (3.00m)FEATURES.ELECTRICAL LIFE1.000 SepsDETAILED DESCRIPTIONDip Switch Hexadecimal Complement 16 Position Through Hole Rotary for Tool Actuator 100m ASTCONTACT MATERIALGoldCONTACT FINISHGoldCIRCUTTHexadecimal Complement 1BODY MATERIALPolyhenylene Sulfide (PPS)ALTOR TYPERotary for Tool	MOUNTING TYPE	Through Hole
MANUFACTURER STANDARD LEAD TIME11 WeeksLENGTH0.287 (7.30mm)LEAD FREE STATUS / ROHS STATUSLead free / ROHS CompliantHEIGHT ABOVE BOARD0.146" (3.70mm)FEATURES-ELECTRICAL LIFE10,000 StepsDETAILED DESCRIPTIONDip Switch Hexadecimal Complement 16 Position Through Hole Rotary for Tool Actuator 100mA SVDCCONTACT MATERIALColorer AlloyCONTACT FINISHGoldCIRCUTTHexadecimal ComplementBODY MATERIALPolybenylene Sulfide (PPS)ACUATOR TYPERotary for Tool	MOISTURE SENSITIVITY LEVEL (MSL)	1 (Unlimited)
Lend0.287" (.30mm)LEAD FREE STATUS / ROHS STATUSLead free / ROHS CompliantHEIGHT ABOVE BOARD0.146" (3.70mm)FEATURES-ELECTRICAL LIFE10,000 StepsDETAILED DESCRIPTIONDip Switch Hexadecimal Complement 16 Position Through Hole Rotary for Tool Actuator 100m A STOCCONTACT MATERIALCoper AlloyCONTACT FINISHGoldRODY MATERIALPolybenylenentBODY MATERIALPolybenylenentRODY MATERIALSolybenylenentROTY MATERIALSolybenylenentRODY MATERIALSolybenylenent <td< td=""><td>MECHANICAL LIFE</td><td>-</td></td<>	MECHANICAL LIFE	-
LEAD FREE STATUS / ROHS STATUSLead free / RoHS CompliantHEIGHT ABOVE BOARD0.146" (3.70mm)FEATURES-ELECTRICAL LIFE10,000 StepsDETAILED DESCRIPTIONDip Switch Hexadecimal Complement 16 Position Through Hole Rotary for Tool Actuator 100mA SVDCCURRENT RATING100mACONTACT MATERIALCopper AlloyCONTACT FINISHGoldCIRCUITHexadecimal ComplementBODY MATERIALPolyphenylene Sulfide (PPS)ACTUATOR TYPERotary for Tool	MANUFACTURER STANDARD LEAD TIME	11 Weeks
HEIGHT ABOVE BOARD0.146" (3.70mm)FEATURES-ELECTRICAL LIFE10,000 StepsDETAILED DESCRIPTIONDip Switch Hexadecimal Complement 16 Position Through Hole Rotary for Tool Actuator 100mA SVDCCURRENT RATING00mACONTACT MATERIALCoper AlloyCONTACT FINISHGoldGDDY MATERIALHexadecimal Complement 1BODY MATERIALPolypenyelneguentACTUATOR TYPERotary for Tool	LENGTH	0.287" (7.30mm)
FEATURES-ELECTRICAL LIFE0,000 StepsDETAILED DESCRIPTIONDip Switch Hexadecimal Complement 16 Position Through Hole Rotary for Tool Actuator 100mA SVDCCURRENT RATING00mACONTACT MATERIALCoper AlloyCONTACT FINISHGoldBODY MATERIALPolyhengenentBODY MATERIALPolyhengenentROTACT TYPERotary for Tool	LEAD FREE STATUS / ROHS STATUS	Lead free / RoHS Compliant
ELECTRICAL LIFE0,000 StepsDETAILED DESCRIPTIONDip Switch Hexadecimal Complement 16 Position Through Hole Rotary for Tool Actuator 100mA 5VDCCURRENT RATING00mACONTACT MATERIALCoper AlloyCONTACT FINISHGoldCIRCUITHexadecimal ComplementBODY MATERIALOlyphenylenettingACTUATOR TYPERotary for Tool	HEIGHT ABOVE BOARD	0.146" (3.70mm)
DETAILED DESCRIPTIONDip Switch Hexadecimal Complement 16 Position Through Hole Rotary for Tool Actuator 100mA 5VDCCURRENT RATING100mACONTACT MATERIALCopper AlloyCONTACT FINISHGoldCIRCUITHexadecimal ComplementBODY MATERIALPolyphenylene Sulfide (PPS)ACTUATOR TYPERotary for Tool	FEATURES	-
CURRENT RATING100mACONTACT MATERIALCopper AlloyCONTACT FINISHGoldCIRCUITHexadecimal ComplementBODY MATERIALPolyphenylene Sulfide (PPS)ACTUATOR TYPERotary for Tool	ELECTRICAL LIFE	10,000 Steps
CONTACT MATERIALCopper AlloyCONTACT FINISHGoldCIRCUITHexadecimal ComplementBODY MATERIALPolyphenylene Sulfide (PPS)ACTUATOR TYPERotary for Tool	DETAILED DESCRIPTION	Dip Switch Hexadecimal Complement 16 Position Through Hole Rotary for Tool Actuator 100mA 5VDC
CONTACT FINISHGoldCIRCUITHexadecimal ComplementBODY MATERIALPolyphenylene Sulfide (PPS)ACTUATOR TYPERotary for Tool	CURRENT RATING	100mA
CIRCUIT Hexadecimal Complement   BODY MATERIAL Polyphenylene Sulfide (PPS)   ACTUATOR TYPE Rotary for Tool	CONTACT MATERIAL	Copper Alloy
BODY MATERIAL Polyphenylene Sulfide (PPS)   ACTUATOR TYPE Rotary for Tool	CONTACT FINISH	Gold
ACTUATOR TYPE Rotary for Tool	CIRCUIT	Hexadecimal Complement
	BODY MATERIAL	Polyphenylene Sulfide (PPS)
ACTUATOR LEVEL Flush, Recessed	ACTUATOR TYPE	Rotary for Tool
	ACTUATOR LEVEL	Flush, Recessed

# **Related Tags**

Copal Electronics SH-7070MC	SH-7070MC Distributor	SH-7070MC Supplier
SH-7070MC Price	SH-7070MC Pictures	SH-7070MC Image
SH-7070MC PDF Datasheet	SH-7070MC Download Datasheet	SH-7070MC Datasheet
SH-7070MC Stock	Buy SH-7070MC	Buy Copal Electronics SH-7070MC
Copal Electronics SH-7070MC	Copal Electronics Supplier	Copal Electronics Distributor
Copal Electronics SH-7070MC	Copal Electronics Inc. SH-7070MC	Nidec Copal Electronics SH-7070MC

# **Related Products**



## SH-7051RH

Manufacturers: Cynergy3 Description: SQ FLGE MNT FLTSW REED In stock: Out stock

RFQ



#### SH-7052RH

SH-8096

Manufacturers: Cynergy3 Description: SQ FLGE MNT FLTSW REED In stock: Out stock

Manufacturers: Bud Industries, Inc.

RFQ



#### SH-7050TA

Manufacturers: Copal Electronics Description: SWITCH ROTARY DIP HEX 100MA 5V In stock: Out stock

RFQ

# ļ) - Constantina

## SH-7051 Manufacturers: Cynergy3 Description: SQ FLGE MNT FLOATSWITCH In stock: Out stock



Bud Industries, Inc.

## SH-7050TB

SH-7070TB

In stock: Out stock

**RFQ** 

Manufacturers: Copal Electronics Description: SWITCH ROTARY DIP HEX 100MA 5V In stock: Out stock

Description: SHELF ADJUSTABLE 3.5X24-36" BLK

RFQ



#### SH-8190

Manufacturers: Bud Industries, Inc. Description: SHELF VENTED STATIONARY UNVRSL In stock: Out stock

RFQ

RFQ



Manufacturers: Copal Electronics Description: SW ROTARY DIP HEX COMP 100MA 5V In stock: Out stock

RFQ

A Noter Group Company COPAL ELECTRONICS -All for dreams	<b>SH-7080TB</b> Manufacturers: Copal Electronics Description: SW ROTARY DIP GRAY CODE 100MA 5V In stock: Out stock	Panasonic	SH-72 Manufacturers: Panasonic Description: SENSOR 7.5MM GLASS BOAD In stock: Out stock
	RFQ		RFQ
	SH-7070TA		SH-7052
	Manufacturers: Copal Electronics Description: SW ROTARY DIP HEX COMP 100MA 5V In stock: Out stock		Manufacturers: Cynergy3 Description: SQ FLGE MNT FLTOATSWITCH In stock: Out stock
	RFQ		RFQ

#### Copyright © 2020 Reliable Distributor of Electronic Components - Ocean-Components.com

E-mail: Info@Ocean-Components.com

Address: Room 2102, Connaught Commercial Building, 185 Wan Chai Rd, Wan Chai, Hong Kong

