

**😑** • E-Switch

500SSP1S2M2REA

Part Number:

Manufacturer/Brand: Product description

Datasheets:

RoHs Status Ship From

Shipment Way

500SSP1S2M2REA

E-Switch

SWITCH SLIDE SPDT 0.4VA 20V

1.500SSP1S2M2REA.pdf 2.500SSP1S2M2REA.pdf

Lead free / RoHS Compliant Hong Kong

DHL/Fedex/TNT/UPS/EMS

**REQUEST FOR QUOTATION** 

Image may be representation. See specifications for product details.

Specifications of 500SSP152M2REA  PART HUMBER  SOGSP152M2REA  E-Switch  DESCRIPTION  SWITCH SLIDE SPOT 0.4VA 20V  LEAD FREE STATUS / ROHS STATUS  Lead free / ROHS Compliant  Lead free / ROHS Complia		Specifications of 500SSD1S2M2DEA
DESCRIPTION SWITCH SLIDE SPOT 0.4VA 20V  LEAD FREE STATUS / ROHS STATUS  LEAD free FRAHS Compilant  DATA SHEET  DA		Specifications of Judger 132112NLA
MANUFACTURER  E-Switch  DESCRIPTION  SWITCH SLIDE SPOT 0.4VA 20V  LEAD FREE STATUS / ROHS STATUS  Lead free / ROHS Compliant  Fig. 1.500SSP1SZMZREA_pdf  Liz 2.500SSP1SZMZREA_pdf  VOLTAGE RATING - DC  20V  VOLTAGE RATING - AC  20V  TERMINATION STYLE  PC Pin  SWITCH TRAVEL  2.16mm  SWITCH FUNCTION  On-On  SERIES  500  PACKAGING  DEFAILING FORCE   MOUNTING TYPE  Through Hole  MOUSTURE SENSITIVITY LEVEL (MSL)  MECHANICAL LIFE  30,000 Cycles  MANUFACTURER STANDARD LEAD TIME  9 Weeks  LEAD FREE STATUS / ROHS STATUS  Lead free / ROHS Compliant  FEATURES  EDON'S Seried Terminals  ELECTRICAL LIFE  30,000 Cycles  MANUFACTURER STANDARD LEAD TIME  9 Weeks  LEAD FREE STATUS / ROHS STATUS  Lead free / ROHS Compliant  FEATURES  EDON'S Seried Terminals  ELECTRICAL LIFE  30,000 Cycles  MOUNTING  CURRENT RATING  0.4VA (AC/DC)  CONTACT TIMING  Not Specified  CONTACT TIMING  CONTACT	PART NUMBER	500SSP1S2M2REA
Lead Free / RoHS Compliant  DATA SHEET  DATA SHEET SHEET ACC  DATA SHEET SHEET SHEET SH		
DATA SHEET  DATA S	DESCRIPTION	SWITCH SLIDE SPDT 0.4VA 20V
DATA SHEET  DATA SHEET  DO 20V  VOLTAGE RATING - DC  VOLTAGE RATING - AC  20V  TERMINATION STYLE  PC Pin  SWITCH TRAVEL  2.16mm  SWITCH FUNCTION  On-On  SERIES  500  PACKAGING  Bulk  OPERATING TEMPERATURE  -30°C ~ 85°C  OPERATING TEMPERATURE  OPERATING TYPE  MOUNTING TYPE  Through Hole  MOISTURE SENSITIVITY LEVEL (MSL)  MECHANICAL LIFE  30,000 Cycles  MANUFACTURER STANDARD LEAD TIME  1 Lead free / RoHS Compliant  FEATURES  ELECTRICAL LIFE  30,000 Cycles  MECHANICAL LIFE  30,000 Cycles  MECHANICAL LIFE  30,000 Cycles  DETAILED DESCRIPTION  Side Switch SPDT Through Hole  CURRENT RATING  0.4VA (AC/DC)  CONTACT TIMING  Not Specified  CONTACT FINISH  Gold  CIRCUIT  ACTUATOR MATERIAL  Polyamide (PA), Nylon	LEAD FREE STATUS / ROHS STATUS	Lead free / RoHS Compliant
VOLTAGE RATING - AC  TERMINATION STYLE  PC PIN  SWITCH TRAVEL  2.16mm  SWITCH FUNCTION  On-On  SERIES  500  PACKAGING  Bulk  OPERATING TEMPERATURE  -30°C ~ 85°C  OPERATING TEMPERATURE  OPERATING TYPE  MOUNTING TYPE  Through Hole  MOISTURE SENSITIVITY LEVEL (MSL)  I (Unlimited)  MECHANICAL LIFE  30,000 Cycles  MANUFACTURER STANDARD LEAD TIME  9 Weeks  LEAD FREE STATUS / ROHS STATUS  LEAD FREE STATUS / ROHS STATUS  LEAD FREE STATUS / ROHS STATUS  ELECTRICAL LIFE  30,000 Cycles  DETAILED DESCRIPTION  SIIde Switch SPDT Through Hole  CURRENT RATING  0.4VA (AC/DC)  CONTACT TIMING  NOT Specified  CONTACT TIMING  CONTACT FINISH  Gold  CIRCUIT  ACTUATOR MATERIAL  FOLIAMOR  SIRAMOR  SIAMOR  SIAM	DATA SHEET	
TERMINATION STYLE  SWITCH TRAVEL  2.16mm  On-On  SERIES  500  PACKAGING  BUIK  OPERATING TEMPERATURE  -30°C ~ 85°C  OPERATING FORCE  -Intrough Hole  MOISTURE SENSITIVITY LEVEL (MSL)  MECHANICAL LIFE  30,000 Cycles  MANUFACTURER STANDARD LEAD TIME  49 Weeks  LEAD FRE STATUS / ROHS STATUS  Lead free / RoHS Compliant  FEATURES  EDETAILED DESCRIPTION  SIIde Switch SPDT Through Hole  CURRENT RATING  0.4VA (AC/DC)  CONTACT TIMING  CONTACT TIMING  CONTACT FINISH  Gold  CIRCUIT  ACTUATOR MATERIAL  Polyamide (PA), Nyion	VOLTAGE RATING - DC	20V
SWITCH FUNCTION On-On  SERIES 500  PACKAGING BUK  OPERATING TEMPERATURE -30°C ~ 85°C  OPERATING FORCE MOUNTING TYPE Through Hole  MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited)  MECHANICAL LIFE 30,000 Cycles  MANUFACTURER STANDARD LEAD TIME 9 Weeks  LEAD FREE STATUS / ROHS STATUS LEPOX Seeled Terminals  ELECTRICAL LIFE 30,000 Cycles  DETAILED DESCRIPTION SIGNES WITCH SPDT Through Hole  CURRENT RATING 0.4VA (AC/DC)  CONTACT TIMING Not Specified  CONTACT TIMING GOld  CIRCUIT ACTUATOR MATERIAL 6.50 Gold  CIRCUIT SPDT  ACTUATOR MATERIAL 6.50 Polyamide (PA), Nylon	VOLTAGE RATING - AC	20V
SWITCH FUNCTION         On-On           SERIES         500           PACKAGING         Bulk           OPERATING TEMPERATURE         -30°C ~ 85°C           OPERATING FORCE         -           MOUNTING TYPE         Through Hole           MOISTURE SENSITIVITY LEVEL (MSL)         1 (Unlimited)           MECHANICAL LIFE         30,000 Cycles           MANUFACTURER STANDARD LEAD TIME         9 Weeks           LEAD FREE STATUS / ROHS STATUS         Lead free / RoHS Compliant           ELECTRICAL LIFE         30,000 Cycles           ELECTRICAL LIFE         30,000 Cycles           DETAILED DESCRIPTION         Slide Switch SPDT Through Hole           CURRENT RATING         0.4VA (AC/DC)           CONTACT TIMING         Not Specified           CONTACT MATERIAL         Copper Alloy           CONTACT FINISH         Gold           CIRCUIT         SPDT           ACTUATOR TYPE         Standard           ACTUATOR MATERIAL         Polyamide (PA), Nylon	TERMINATION STYLE	PC Pin
SERIES500PACKAGINGBulkOPERATING TEMPERATURE-30°C ~ 85°COPERATING FORCE-MOUNTING TYPEThrough HoleMOISTURE SENSITIVITY LEVEL (MSL)1 (Unlimited)MECHANICAL LIFE30,000 CyclesMANUFACTURER STANDARD LEAD TIME9 WeeksLEAD FREE STATUS / ROHS STATUSLead free / RoHS CompliantFEATURESEpoxy Sealed TerminalsELECTRICAL LIFE30,000 CyclesDETAILED DESCRIPTIONSide Switch SPDT Through HoleCURRENT RATING0.4VA (AC/DC)CONTACT TIMINGNot SpecifiedCONTACT TIMINGSodeCONTACT FINISHGoldCICRCUITSPDTACTUATOR TYPEStandardACTUATOR MATERIALPolyamide (PA), Nylon	SWITCH TRAVEL	2.16mm
PACKAGING Bulk OPERATING TEMPERATURE -30°C ~85°C OPERATING FORCE - CONTACT PITMENDER TO STATUS FORCE MOUNTING TYPE Through Hole MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) MECHANICAL LIFE 30,000 Cycles MANUFACTURER STANDARD LEAD TIME 9 Weeks LEAD FREE STATUS / ROHS STATUS LEAD (Fire / ROHS Compliant FEATURES EDESTRY STANDARD LEAD TIME 9 Spoxy Sealed Terminals ELECTRICAL LIFE 30,000 Cycles DETAILED DESCRIPTION SIIde Switch SPDT Through Hole CURRENT RATING 0.4VA (AC/DC) CONTACT TIMING Not Specified CONTACT TIMING COPPER Alloy CONTACT FINISH Gold CIRCUIT SPDT ACTUATOR TYPE STANDARD STANDARD SIANDARD STANDARD SIANDARD	SWITCH FUNCTION	On-On
OPERATING TEMPERATURE OPERATING FORCE  MOUNTING TYPE Through Hole MOISTURE SENSITIVITY LEVEL (MSL) MECHANICAL LIFE MANUFACTURER STANDARD LEAD TIME LEAD FREE STATUS / ROHS STATUS LEAd free / ROHS Compliant ELECTRICAL LIFE SO,000 Cycles  DETAILED DESCRIPTION Slide Switch SPDT Through Hole CONTACT TIMING CONTACT TIMING CONTACT TIMING CONTACT FINISH CIRCUIT ACTUATOR TYPE ACTUATOR TYPE SLOGGE STANDARD LEAD TIME SOBOLIT SOBO	SERIES	500
OPERATING FORCE-MOUNTING TYPEThrough HoleMOISTURE SENSITIVITY LEVEL (MSL)1 (Unlimited)MECHANICAL LIFE30,000 CyclesMANUFACTURER STANDARD LEAD TIME9 WeeksLEAD FREE STATUS / ROHS STATUSLead free / RoHS CompliantFEATURESEpoxy Sealed TerminalsELECTRICAL LIFE30,000 CyclesDETAILED DESCRIPTIONSlide Switch SPDT Through HoleCURRENT RATING0.4VA (AC/DC)CONTACT TIMINGNot SpecifiedCONTACT TIMINGCopper AlloyCONTACT FINISHGoldCIRCUITSPDTACTUATOR TYPEStandardACTUATOR MATERIALPolyamide (PA), Nylon	PACKAGING	Bulk
MOUNTING TYPE MOISTURE SENSITIVITY LEVEL (MSL) MECHANICAL LIFE MANUFACTURER STANDARD LEAD TIME MERCHANICAL LIFE MANUFACTURER STATUS / ROHS STATUS LEAD FREE STATUS / ROHS STATUS LEAD FREE STATUS / ROHS STATUS LEAD FREE STATUS / ROHS STATUS ELECTRICAL LIFE DETAILED DESCRIPTION Slide Switch SPDT Through Hole CURRENT RATING CONTACT TIMING Not Specified CONTACT TIMING CONTACT FINISH CONTACT FINISH CIRCUIT ACTUATOR TYPE ACTUATOR MATERIAL POlyamide (PA), Nylon	OPERATING TEMPERATURE	-30°C ~ 85°C
MOISTURE SENSITIVITY LEVEL (MSL)  MECHANICAL LIFE  30,000 Cycles  MANUFACTURER STANDARD LEAD TIME  9 Weeks  LEAD FREE STATUS / ROHS STATUS  Lead free / ROHS Compliant  FEATURES  ELECTRICAL LIFE  30,000 Cycles  DETAILED DESCRIPTION  Slide Switch SPDT Through Hole  CURRENT RATING  CONTACT TIMING  CONTACT TIMING  CONTACT TIMING  CONTACT FINISH  CONTACT FINISH  GOId  CIRCUIT  ACTUATOR TYPE  ACTUATOR MATERIAL  Polyamide (PA), Nylon	OPERATING FORCE	-
MECHANICAL LIFE 30,000 Cycles  MANUFACTURER STANDARD LEAD TIME 9 Weeks  LEAD FREE STATUS / ROHS STATUS LEAD free / ROHS Compliant  FEATURES EDXY Sealed Terminals  ELECTRICAL LIFE 30,000 Cycles  DETAILED DESCRIPTION Slide Switch SPDT Through Hole  CURRENT RATING 0.4VA (AC/DC)  CONTACT TIMING Not Specified  CONTACT TIMING Copper Alloy  CONTACT FINISH Gold  CIRCUIT SPDT  ACTUATOR TYPE Standard Polyamide (PA), Nylon	MOUNTING TYPE	Through Hole
MANUFACTURER STANDARD LEAD TIME 9 Weeks  LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant  FEATURES EDOXY Sealed Terminals  ELECTRICAL LIFE 30,000 Cycles  DETAILED DESCRIPTION Slide Switch SPDT Through Hole  CURRENT RATING 0.4VA (AC/DC)  CONTACT TIMING Not Specified  CONTACT TIMING COPPER Alloy  CONTACT FINISH Gold  CIRCUIT SPDT  ACTUATOR TYPE Standard Polyamide (PA), Nylon	MOISTURE SENSITIVITY LEVEL (MSL)	1 (Unlimited)
LEAD FREE STATUS / ROHS STATUS  FEATURES  EDOXY Sealed Terminals  ELECTRICAL LIFE  30,000 Cycles  DETAILED DESCRIPTION  Slide Switch SPDT Through Hole  CURRENT RATING  CONTACT TIMING  Not Specified  CONTACT MATERIAL  CONTACT FINISH  CIRCUIT  ACTUATOR TYPE  ACTUATOR MATERIAL  Lead free / RoHS Compliant  10,000 Cycles  10	MECHANICAL LIFE	30,000 Cycles
EECTRICAL LIFE 30,000 Cycles  DETAILED DESCRIPTION Slide Switch SPDT Through Hole  CURRENT RATING 0.4VA (AC/DC)  CONTACT TIMING Not Specified  CONTACT FINISH Gold  CIRCUIT SPDT  ACTUATOR TYPE Standard  Epoxy Sealed Terminals  60,000 Cycles  10,000 Cycles	MANUFACTURER STANDARD LEAD TIME	9 Weeks
ELECTRICAL LIFE 30,000 Cycles  DETAILED DESCRIPTION Slide Switch SPDT Through Hole  CURRENT RATING 0.4VA (AC/DC)  CONTACT TIMING Not Specified  CONTACT MATERIAL Copper Alloy  CONTACT FINISH Gold  CIRCUIT SPDT  ACTUATOR TYPE Standard  Polyamide (PA), Nylon	LEAD FREE STATUS / ROHS STATUS	Lead free / RoHS Compliant
DETAILED DESCRIPTION Slide Switch SPDT Through Hole  CURRENT RATING 0.4VA (AC/DC)  CONTACT TIMING Not Specified  CONTACT MATERIAL CONTACT FINISH CONTACT FINISH CIRCUIT ACTUATOR TYPE ACTUATOR MATERIAL Polyamide (PA), Nylon	FEATURES	Epoxy Sealed Terminals
CURRENT RATING 0.4VA (AC/DC)  CONTACT TIMING Not Specified  CONTACT MATERIAL Copper Alloy  CONTACT FINISH Gold  CIRCUIT SPDT  ACTUATOR TYPE Standard Polyamide (PA), Nylon	ELECTRICAL LIFE	30,000 Cycles
CONTACT TIMING  CONTACT MATERIAL  CONTACT MATERIAL  CONTACT FINISH  CIRCUIT  ACTUATOR TYPE  ACTUATOR MATERIAL  Not Specified  Copper Alloy  Gold  SPDT  Standard  Polyamide (PA), Nylon	DETAILED DESCRIPTION	Slide Switch SPDT Through Hole
CONTACT MATERIAL  CONTACT FINISH  CIRCUIT  ACTUATOR TYPE  ACTUATOR MATERIAL  COPPER Alloy  Copper Alloy  Gold  SPDT  Standard  Polyamide (PA), Nylon	CURRENT RATING	0.4VA (AC/DC)
CONTACT FINISH  CIRCUIT  ACTUATOR TYPE  ACTUATOR MATERIAL  Polyamide (PA), Nylon	CONTACT TIMING	Not Specified
CIRCUIT SPDT ACTUATOR TYPE Standard ACTUATOR MATERIAL Polyamide (PA), Nylon	CONTACT MATERIAL	Copper Alloy
ACTUATOR TYPE Standard  ACTUATOR MATERIAL Polyamide (PA), Nylon	CONTACT FINISH	Gold
ACTUATOR MATERIAL Polyamide (PA), Nylon	CIRCUIT	SPDT
	ACTUATOR TYPE	Standard
ACTUATOR LENCTH 7.24mm	ACTUATOR MATERIAL	Polyamide (PA), Nylon
ACTUATOR LENGTH 7.24IIIII	ACTUATOR LENGTH	7.24mm

# **Related Tags**

E-Switch 500SSP1S2M2REA	500SSP1S2M2REA Distributor	500SSP1S2M2REA Supplier
500SSP1S2M2REA Price	500SSP1S2M2REA Pictures	500SSP1S2M2REA Image
500SSP1S2M2REA PDF Datasheet	500SSP1S2M2REA Download Datasheet	500SSP1S2M2REA Datasheet
500SSP1S2M2REA Stock	Buy 500SSP1S2M2REA	Buy E-Switch 500SSP1S2M2REA
E-Switch 500SSP1S2M2REA	E-Switch Supplier	E-Switch Distributor
E-Switch 500SSP1S2M2REA		

# **Related Products**



## 500SSP1S2M7QEA

Manufacturers: E-Switch

Description: SWITCH SLIDE SPDT 5A 120V In stock: Out stock

**RFQ** 

Manufacturers: E-Switch

500SSP1S2M6QEA

Description: SWITCH SLIDE SPDT 5A 120V In stock: Out stock

**RFQ** 



#### 500SSP1S2M2QEA Manufacturers: E-Switch

Description: SWITCH SLIDE SPDT 5A 120V

In stock: 702 pcs

**RFQ** 



#### **500SSP1S1M7QEB** Manufacturers: E-Switch

Description: SWITCH SLIDE SPDT 5A 120V

In stock: Out stock

**RFQ** 



#### 500SSP1S2M6REA Manufacturers: E-Switch

Description: SWITCH SLIDE SPDT 0.4VA 20V In stock: Out stock

**RFQ** 



## **500SSP1S2M6QEB**

Manufacturers: E-Switch Description: SWITCH SLIDE SPDT 5A 120V In stock: Out stock

**RFQ** 



#### **500SSP1S1M6REA** Manufacturers: E-Switch

Description: SWITCH SLIDE SPDT 0.4VA 20V

In stock: Out stock **RFQ** 



#### 500SSP1S1M7REA Manufacturers: E-Switch

Description: SWITCH SLIDE SPDT 0.4VA 20V

In stock: Out stock **RFQ** 



### **500SSP1S2M7REA** Manufacturers: E-Switch

Description: SWITCH SLIDE SPDT 0.4VA 20V

In stock: Out stock

**RFQ** 

### **500SSP1S3M1QEB** Manufacturers: E-Switch

Description: SWITCH SLIDE SPDT 5A 120V

In stock: Out stock **RFQ** 



#### Manufacturers: E-Switch Description: SWITCH SLIDE SPDT 0.4VA 20V

**500SSP1S1M6REB** 

In stock: Out stock

**RFQ** 



#### **500SSP1S1M7QEA** Manufacturers: E-Switch Description: SWITCH SLIDE SPDT 5A 120V

In stock: Out stock **RFQ** 











