

Grayhill

Grayhill, Inc.

50S36-01-2-05N

Part Number:

Manufacturer/Brand:

Product description

RoHs Status Ship From

Shipment Way

Datasheets:

50S36-01-2-05N

Grayhill, Inc.

SWITCH ROTARY 5POS 150MA 115V 50S36-01-2-05N.pdf

Lead free / RoHS Compliant Hong Kong

DHL/Fedex/TNT/UPS/EMS



REQUEST FOR QUOTATION

Image may be representation. See specifications for product details.

PART NUMBER S056-61-2-05N MANUFACTURER Grayhill, Inc. LEAD FREE STATUS / ROHS STATUS Solder Lug SERIES S0 PANIEL CUTOUT DIMENSIONS Crudar - 6.45mm Dia Childra - 6.45mm Dia		Specifications of 50S36-01-2-05N
MANUFACTURER Grayhll, Inc. DESCRIPTION SWITCH ROTARY SPOS 150MA 115V LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant DATA SHEET \$30536-01-2-05N, pdf VOLTAGE RATING - DC 28V VOLTAGE RATING - AC 115V TERMINATION STYLE Solder Lug SCRIES 0 PANEL CUTOUT DIMENSIONS Grouler - 6.45mm Dia OFFEATING FORCE \$505601205N OFFEATING FORCE 5.761 ~ 17gfm NUMBER OF POSITIONS 5 NUMBER OF POSITIONS 1 MOUNTING TYPE Panel Mount MOUNTING TYPE Panel Mount MOUNTING TYPE Weeks LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant LEAD FREE STATUS / ROHS STATUS Rotary Switch 5 Position DPST 150mA (AC), 200mA (DC) 115VAC Panel Mount DETAILED DESCRIPTION Rotary Switch 5 Position DPST 150mA (AC), 200mA (DC) 115VAC Panel Mount DEPT HEILIND PANEL SOMA (AC), 200mA (DC) CONTACT TRATING Gold CONTACT FINISH <th></th> <th></th>		
DESCRIPTION SWITCH ROTARY SPOS 150MA 115V LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant DATA SHEET S0536-01-2-05N.pdf VOLTAGE RATING - DC 28V VOLTAGE RATING - AC 115V TERMINATION STYLE Solder Lug SPRISE 50 PORNEL CUTOUT DIMENSIONS Crouler - 6.45mm Dia OTHER NAMES 50536012USN OPERATING FORCE 5761 ~ 17gfm NUMBER OF POSITIONS 5 NUMBER OF POSITIONS 1 MOUNTING TYPE 9 mel Mount MOUNTING TYPE 9 mel Mount MOUNTING TYPE 9 weeks LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant INDEX STOPS Fixed FEATURES Shaft and Panel Sealed DETAILED DESCRIPTION Rotary Switch 5 Position DPST 150mA (AC), 200mA (DC) 115VAC Panel Mount DEPT HERIND PANEL 15.77mm CURRENT RATING Gold CONTACT THINSH Gold CONTACT FINISH Gold CURLED THROW 36° ACILLATOR T	PART NUMBER	50S36-01-2-05N
LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant DATA SHEET \$5036-01-2-05N.pdf VOLTAGE RATING - DC 28V VOLTAGE RATING - AC 115V TERMINATION STYLE Solder Lug SERIES 50 PARAL CUTOUT DIMENSIONS Circular - 6.45mm Dia OTHER NAMES 5053601205N OPERATING FORCE 5.761 ~ 17gm NUMBER OF POSITIONS 5 NUMBER OF DOLES PER DECK 2 NUMBER OF DOLES PER DECK 2 MOUNTING TYPE Panel Mount MOUNTING TYPE Panel Mount MANUFACTURES STATUS / ROHS STATUS 1 (Unlimited) MANUFACTURES STATUS / ROHS STATUS 1 (Each free / RoHS Compliant LEAD FREE STATUS / ROHS STATUS 1 (Roed free / RoHS Compliant INDEX STOPS Fixed DETAILED DESCRIPTION Rotary Switch 5 Position DPST 150mA (AC), 200mA (DC) 115VAC Panel Mount DETH BEHIND PANEL 18.77mm CONTACT TILLING Non-Shorting (BBM) CONTACT TILLING ON-Shorting (BBM) CONTACT TILLING Gold C	MANUFACTURER	Grayhill, Inc.
DATA SHEET \$6000-000-0000-0000-0000-0000-0000-0000	DESCRIPTION	SWITCH ROTARY 5POS 150MA 115V
VOLTAGE RATING - DC 28V VOLTAGE RATING - AC 115V TERMINATION STYLE Solder Lug SERIES 50 PANEL CUTOUT DIMENSIONS Circular - 6.45mm Dia OTHER NAMES 5083601205N OPERATING FORCE 5.761 ~ 17gfm NUMBER OF POLES PER DECK 2 NUMBER OF DELES PER DECK 2 MOUNTING TYPE Panel Mount MOUNTING TYPE Panel Mount MANUFACTURER STANDARD LEAD TIME 9 Weeks LEAD FREE STATUS / ROHS STATUS Led free / ROHS Compliant INDEX STOPS Fixed PETATURES Rotary Switch 5 Position DPST 150mA (AC), 200mA (DC) 115VAC Panel Mount DETH BELIND PANEL 18.77mm CURRENT RATING 150mA (AC), 200mA (DC) CONTACT TIMING Non-Shorting (BBM) CONTACT TIMING Gold CURTACT FIRISH Gold CURLEY FERDECK DPST ANGLE OF THROW 36° ANGLE OF THROW 46td (3.17mm Dia)	LEAD FREE STATUS / ROHS STATUS	Lead free / RoHS Compliant
VOLTAGE RATING - AC 115V TERMINATION STYLE Solder Lug SERIES 50 PANEL CUTOUT DIMENSIONS Circular - 6.45mm Dia OTHER NAMES 5053601205N OPERATING FORCE 5.761 ~ 17gfm NUMBER OF POSITIONS 5 NUMBER OF POLES PER DECK 2 NUMBER OF DECKS 1 MOUNTING TYPE Panel Mount MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) MANUFACTURER STANDARD LEAD TIME 9 Weeks LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant INDEX STOPS Fixed FEATURES Shaft and Panel Sealed DETAILED DESCRIPTION Rotary Switch S Position DPST 150mA (AC), 200mA (DC) 115VAC Panel Mount DEPTH BEHIND PANEL 1 S.77m CURRENT RATING 1 S0mA (AC), 200mA (DC) CONTACT TIMING Onn-Shorting (BBM) CONTACT FINISH Gold CRUIT FER DECK DPST ANGLE OF THROW 5 Selection Type ANGLE OF THROW 5 Selection Type	DATA SHEET	50S36-01-2-05N.pdf
ETERMINATION STYLE Solder Lug SERIES 50 PANEL CUTOUT DIMENSIONS Circular - 6.45mm Dia OTHER NAMES 505601205N OPERATING FORCE 5.761 ~ 17gfm NUMBER OF POSITIONS 5 NUMBER OF POLES PER DECK 2 NUMBER OF DECKS 1 MOUNTING TYPE Panel Mount MOUNTING TYPE 4 (unlimited) MOUNTING TYPE 9 Weeks LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant INDEX STOPS Fixed FEATURES Shaft and Panel Sealed DETAILED DESCRIPTION Rotary Switch 5 Position DPST 150mA (AC), 200mA (DC) 115VAC Panel Mount CURRENT RATING 150mA (AC), 200mA (DC) CONTACT TIMING Non-Shorting (BBM) CONTACT FINISH Gold CURLET FINISH Gold CULTU FER DECK DPST ANGLE OF THROW 36° ANGLE OF THROW Flatted (3.17mm Da)	VOLTAGE RATING - DC	28V
SERIES 50 PANEL CUTOUT DIMENSIONS Circular - 6.45mm Dia OTHER NAMES 5053601205N OPERATING FORCE 5.761 ~ 17gfm NUMBER OF POSITIONS 5 NUMBER OF POECKS 2 NUMBER OF DECKS 1 MOUNTING TYPE Panel Mount MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) MANUFACTURER STANDARD LEAD TIME 9 Weeks LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant INDEX STOPS Fixed FEATURES Shaft and Panel Sealed DETAILED DESCRIPTION Rotary Switch 5 Position DPST 150mA (AC), 200mA (DC) 115VAC Panel Mount DEPTH BEHIND PANEL 18.77mm CURRENT RATING 150mA (AC), 200mA (DC) CONTACT TIMING Non-Shorting (BBM) CONTACT FINISH Gold CURULT PER DECK DPST ANGLE OF THROW 36° ALLED OF THROW 16ted (3.17mm Dia)	VOLTAGE RATING - AC	115V
PANEL CUTOUT DIMENSIONS Circular - 6.45mm Dia OTHER NAMES 5053601205N OPERATING FORCE 5.761 ~ 17gfm NUMBER OF POSITIONS 5 NUMBER OF POLES PER DECK 2 NUMBER OF DECKS 1 MOUNTING TYPE Panel Mount MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) MANUFACTURER STANDARD LEAD TIME 9 Weeks LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant INDEX STOPS Fixed FEATURES Shaft and Panel Sealed DETAILED DESCRIPTION Rotary Switch 5 Position DPST 150mA (AC), 200mA (DC) 115VAC Panel Mount DETAILED BEHIND PANEL 18.77mm CURRENT RATING 150mA (AC), 200mA (DC) CONTACT TIMING Non-Shorting (BBM) CONTACT FINISH Gold CURLUT PER DECK DPST ANGLE OF THROW 16ted (3.17mm Dia)	TERMINATION STYLE	Solder Lug
OPERATING FORCE 5.761 ~ 17gfm NUMBER OF POSITIONS 5 NUMBER OF POLES PER DECK 2 NUMBER OF DECKS 1 MOUNTING TYPE Panel Mount MOUSTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) MANUFACTURER STANDARD LEAD TIME 9 Weeks LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant INDEX STOPS Fixed FEATURES Shaft and Panel Sealed DETAILED DESCRIPTION Rotary Switch 5 Position DP5T 150mA (AC), 200mA (DC) 115VAC Panel Mount DEFTH BEHIND PANEL 18.77mm CURRENT RATING 150mA (AC), 200mA (DC) CONTACT TIMING Non-Sorting (BBM) CONTACT FINISH Gold CURCUIT PER DECK DP5T ANGLE OF THROW 36° ALUATOR TYPE Balted (3.17mm Dia)	SERIES	50
OPERATING FORCE 5.61 ~ 17gfm NUMBER OF POSITIONS 5 NUMBER OF POLES PER DECK 2 NUMBER OF DECKS 1 MOUNTING TYPE Panel Mount MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) MANUFACTURER STANDARD LEAD TIME 9 Weeks LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant INDEX STOPS Fixed FEATURES Shaft and Panel Sealed DETAILED DESCRIPTION Rotary Switch 5 Position DPST 150mA (AC), 200mA (DC) 115VAC Panel Mount DEFTH BEHIND PANEL 150mA (AC), 200mA (DC) CONTACT TIMING Non-Shorting (BBM) CONTACT TIMING Sold CONTACT FINISH Gold CIRCUIT PER DECK DPST ANGLE OF THROW 36° ACTUATOR TYPE Flatted (3.17mm Dia)	PANEL CUTOUT DIMENSIONS	Circular - 6.45mm Dia
NUMBER OF POSITIONS NUMBER OF POLES PER DECK NUMBER OF DECKS MOUNTING TYPE MOUNTING TYPE MOUNTING TYPE MOUNTING TYPE MANUFACTURER STANDARD LEAD TIME LEAD FREE STATUS / ROHS STATUS INDEX STOPS Fixed FEATURES DETAILED DESCRIPTION ROTSPH BEHIND PANEL CURRENT RATING CURRENT RATING CONTACT TIMING NON-Shorting (BBM) CONTACT TIMING CONTACT TIMING CONTACT TIMISH Gold CIRCUIT PER DECK ANGLE OF THROW ANGLE OF THROW FIELD (3.17mm Dia) FIELD (3.17mm Dia)	OTHER NAMES	50S3601205N
NUMBER OF POLES PER DECK2NUMBER OF DECKS1MOUNTING TYPEPanel MountMOISTURE SENSITIVITY LEVEL (MSL)1 (Unlimited)MANUFACTURER STANDARD LEAD TIME9 WeeksLEAD FREE STATUS / ROHS STATUSLead free / RoHS CompliantINDEX STOPSFixedFEATURESShaft and Panel SealedDETAILED DESCRIPTIONRotary Switch 5 Position DPST 150mA (AC), 200mA (DC) 115VAC Panel MountDEPTH BEHIND PANEL18.77mmCURRENT RATING150mA (AC), 200mA (DC)CONTACT TIMINGNon-Shorting (BBM)CONTACT MATERIAL-CONTACT FINISHGoldCIRCUIT PER DECKDP5TANGLE OF THROW36°ANGLE OF THROWFlatted (3.17mm Dia)	OPERATING FORCE	5.761 ~ 17gfm
NUMBER OF DECKS1MOUNTING TYPEPanel MountMOISTURE SENSITIVITY LEVEL (MSL)1 (Unlimited)MANUFACTURER STANDARD LEAD TIME9 WeeksLEAD FREE STATUS / ROHS STATUSLead free / ROHS CompliantINDEX STOPSFixedFEATURESShaft and Panel SealedDETAILED DESCRIPTIONRotary Switch 5 Position DPST 150mA (AC), 200mA (DC) 115VAC Panel MountDEPTH BEHIND PANEL18.77mmCURRENT RATING150mA (AC), 200mA (DC)CONTACT TIMINGNon-Shorting (BBM)CONTACT TIMINGOddCONTACT FINISHGoldCIRCUIT PER DECKDPSTANGLE OF THROW36°ACTUATOR TYPEFatted (3.17mm Dia)	NUMBER OF POSITIONS	5
MOUNTING TYPE Panel Mount MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) MANUFACTURER STANDARD LEAD TIME 9 Weeks LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant INDEX STOPS FIXED Shaft and Panel Sealed DETAILED DESCRIPTION ROTAGE DEPTH BEHIND PANEL 18.77mm CURRENT RATING 150mA (AC), 200mA (DC) 115VAC Panel Mount CONTACT TIMING Non-Shorting (BBM) CONTACT FINISH Gold CURCULT PER DECK DP5T ANGLE OF THROW 36° ANGLE OF THROW 56° Flatted (3.17mm Dia)	NUMBER OF POLES PER DECK	2
MOISTURE SENSITIVITY LEVEL (MSL) MANUFACTURER STANDARD LEAD TIME 9 Weeks LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant INDEX STOPS Fixed FEATURES DETAILED DESCRIPTION ROTARY SWITCH 5 Position DP5T 150mA (AC), 200mA (DC) 115VAC Panel Mount DEPTH BEHIND PANEL LURRENT RATING CURRENT RATING CONTACT TIMING CONTACT TIMING CONTACT TIMING CONTACT FINISH CONTACT FINISH CIRCUIT PER DECK DP5T ANGLE OF THROW ACIONATOR TYPE Flatted (3.17mm Dia)	NUMBER OF DECKS	1
MANUFACTURER STANDARD LEAD TIME 9 Weeks LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant INDEX STOPS Fixed FEATURES Shaft and Panel Sealed DETAILED DESCRIPTION ROTAGNAM (AC), 200mA (DC) 115VAC Panel Mount DEPTH BEHIND PANEL 18.77mm CURRENT RATING 150mA (AC), 200mA (DC) CONTACT TIMING Non-Shorting (BBM) CONTACT TIMING Gold CONTACT FINISH GOld CIRCUIT PER DECK DPST ANGLE OF THROW 36° ACTUATOR TYPE FIREW STATUS FIXED STATUS STATUS SHORT SHO	MOUNTING TYPE	Panel Mount
LEAD FREE STATUS / ROHS STATUS INDEX STOPS Fixed FEATURES Shaft and Panel Sealed DETAILED DESCRIPTION ROTATY BEHIND PANEL 18.77mm 150mA (AC), 200mA (DC) 115VAC Panel Mount CURRENT RATING CONTACT TIMING Non-Shorting (BBM) CONTACT FINISH CONTACT FINISH ANGLE OF THROW ANGLE OF THROW ACLUATOR TYPE Flatted (3.17mm Dia)	MOISTURE SENSITIVITY LEVEL (MSL)	1 (Unlimited)
FEATURES Shaft and Panel Sealed DETAILED DESCRIPTION ROTAGY Switch 5 Position DP5T 150mA (AC), 200mA (DC) 115VAC Panel Mount DEPTH BEHIND PANEL 18.77mm CURRENT RATING 150mA (AC), 200mA (DC) CONTACT TIMING Non-Shorting (BBM) CONTACT FINISH Gold CIRCUIT PER DECK DP5T ANGLE OF THROW 36° Flatted (3.17mm Dia)	MANUFACTURER STANDARD LEAD TIME	9 Weeks
FEATURES Shaft and Panel Sealed DETAILED DESCRIPTION Rotary Switch 5 Position DP5T 150mA (AC), 200mA (DC) 115VAC Panel Mount 18.77mm CURRENT RATING 150mA (AC), 200mA (DC) CONTACT TIMING Non-Shorting (BBM) CONTACT FINISH Gold CIRCUIT PER DECK DP5T ANGLE OF THROW ACTUATOR TYPE Flatted (3.17mm Dia)	LEAD FREE STATUS / ROHS STATUS	Lead free / RoHS Compliant
DETAILED DESCRIPTION Rotary Switch 5 Position DP5T 150mA (AC), 200mA (DC) 115VAC Panel Mount DEPTH BEHIND PANEL LURRENT RATING 150mA (AC), 200mA (DC) CONTACT TIMING Non-Shorting (BBM) CONTACT FINISH CONTACT FINISH Gold CIRCUIT PER DECK ANGLE OF THROW Flatted (3.17mm Dia)	INDEX STOPS	Fixed
DEPTH BEHIND PANEL 18.77mm CURRENT RATING 150mA (AC), 200mA (DC) CONTACT TIMING Non-Shorting (BBM) CONTACT MATERIAL - CONTACT FINISH Gold CIRCUIT PER DECK DP5T ANGLE OF THROW 36° ACTUATOR TYPE FIRED SCORE STROME	FEATURES	Shaft and Panel Sealed
CURRENT RATING 150mA (AC), 200mA (DC) CONTACT TIMING Non-Shorting (BBM) CONTACT MATERIAL - CONTACT FINISH Gold CIRCUIT PER DECK DP5T ANGLE OF THROW 36° ACTUATOR TYPE FIRMS SHORT SH	DETAILED DESCRIPTION	Rotary Switch 5 Position DP5T 150mA (AC), 200mA (DC) 115VAC Panel Mount
CONTACT TIMING CONTACT MATERIAL CONTACT FINISH CONTACT FINISH CIRCUIT PER DECK DP5T ANGLE OF THROW ACTUATOR TYPE Flatted (3.17mm Dia)	DEPTH BEHIND PANEL	18.77mm
CONTACT MATERIAL - CONTACT FINISH Gold CIRCUIT PER DECK DP5T ANGLE OF THROW 36° ACTUATOR TYPE FIRM Dia)	CURRENT RATING	150mA (AC), 200mA (DC)
CONTACT FINISH Gold CIRCUIT PER DECK DP5T ANGLE OF THROW 36° ACTUATOR TYPE Flatted (3.17mm Dia)	CONTACT TIMING	Non-Shorting (BBM)
CIRCUIT PER DECK ANGLE OF THROW ACTUATOR TYPE DP5T 36° Flatted (3.17mm Dia)	CONTACT MATERIAL	-
ANGLE OF THROW 36° ACTUATOR TYPE Flatted (3.17mm Dia)	CONTACT FINISH	Gold
ACTUATOR TYPE Flatted (3.17mm Dia)	CIRCUIT PER DECK	DP5T
	ANGLE OF THROW	36°
ACTUATOR LENGTH 9.53mm	ACTUATOR TYPE	Flatted (3.17mm Dia)
	ACTUATOR LENGTH	9.53mm

Related Tags

Grayhill, Inc. 50S36-01-2-05N	50S36-01-2-05N Distributor	50S36-01-2-05N Supplier
50S36-01-2-05N Price	50S36-01-2-05N Pictures	50S36-01-2-05N Image
50S36-01-2-05N PDF Datasheet	50S36-01-2-05N Download Datasheet	50S36-01-2-05N Datasheet
50S36-01-2-05N Stock	Buy 50S36-01-2-05N	Buy Grayhill, Inc. 50S36-01-2-05N
Grayhill, Inc. 50S36-01-2-05N	Grayhill, Inc. Supplier	Grayhill, Inc. Distributor
Grayhill, Inc. 50S36-01-2-05N	Grayhill Inc. 50S36-01-2-05N	

Related Products



50S45-01-1-04N

Manufacturers: Grayhill, Inc. Description: SWITCH ROTARY 4POS 150MA 115V

In stock: Out stock

RFQ



50S36-01-2-03S

Manufacturers: Grayhill, Inc. Description: SWITCH ROTARY 3POS 150MA 115V

In stock: Out stock **RFQ**



50S45-01-1-06N Manufacturers: Grayhill, Inc.

Description: SWITCH ROTARY 6POS 150MA 115V In stock: Out stock

RFQ

Grayhill

50S36-01-2-04N Manufacturers: Grayhill, Inc.

Description: SWITCH ROTARY 4POS 150MA 115V

In stock: Out stock

RFQ



50S36-01-2-04S Manufacturers: Grayhill, Inc.

Description: SWITCH ROTARY 4POS 150MA 115V

In stock: Out stock

RFQ



50S45-01-1-03N Manufacturers: Grayhill, Inc.

Description: SWITCH ROTARY 3POS 150MA 115V In stock: Out stock

RFQ



Manufacturers: Grayhill, Inc.

50S36-01-2-03N

Description: SWITCH ROTARY 3POS 150MA 115V In stock: Out stock

RFQ



Grayhill


Manufacturers: Grayhill, Inc. Description: SWITCH ROTARY 5POS 150MA 115V

50S36-01-2-05S

In stock: Out stock

RFQ

Grayhill



50S36-01-2-02S

In stock: Out stock **RFQ**



Grayhill

Manufacturers: Grayhill, Inc. Description: SWITCH ROTARY 2POS 150MA 115V

50S45-01-1-02N

In stock: Out stock

RFQ

50S45-01-1-05N




50S36-01-2-02N Manufacturers: Grayhill, Inc. Description: SWITCH ROTARY 2POS 150MA 115V

In stock: Out stock

RFQ





In stock: Out stock

Manufacturers: Grayhill, Inc. Description: SWITCH ROTARY 5POS 150MA 115V

RFQ













Address: Room 2102, Connaught Commercial Building, 185 Wan Chai Rd, Wan Chai, Hong Kong