OHMITE



T10012SE

Ohmite SWITCH ROTARY 12POS 3A 120V

T10012SE.pdf

Lead free / RoHS Compliant Hong Kong

DHL/Fedex/TNT/UPS/EMS



Ohmite

REQUEST FOR QUOTATION

T10012SE

Manufacturer/Brand:

Product description

Part Number:

Datasheets:

RoHs Status

Ship From

Shipment Way

Image may be representation. See specifications for product details.

Specifications of T10012SE PART NUMBER T10012SE MANUFACTURER Ohmble DESCRIPTION SWITCH ROTARY 12POS 3A 120V LEAD FREE STATUS / ROHS STATUS SOME STATUS / ROHS STATUS SOME STATUS / ROHS STATUS LEAD FREE STATUS / ROHS		
MANUFACTURER Ohmite DESCRIPTION SWITCH ROTARY 12POS 3A 120V LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant DATA SHEET Text 100125E pef VOLTAGE RATING - DC 20V VOLTAGE RATING - AC 120V TERMINATION STYLE Solder Lug SFAIES T-100 PANEL CUTOUT DIMENSIONS Circular - 9.53mm Dia OTHER NAMES OHT100125E OPERATING FORCE - NUMBER OF POSITIONS 12 NUMBER OF POLES PER DECK 1 NUMBER OF DECKS 1 MOINTING TYPE Panel Mount MOINTING TYPE Panel Mount MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) MANUFACTURER STANDARD LEAD TIME 12 Weeks LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant INDEX STOPS Fixed FEATURES - DETAILED DESCRIPTION ROSTATY SWIRCH 12 POSITION SP12T 3A (AC/DC) 120VAC Panel Mount DEFT HERIND 34 93mm CURRENT RATING 3A (AC/DC) CO		Specifications of T10012SE
MANUFACTURER Ohmite DESCRIPTION SWITCH ROTARY 12POS 3A 120V Lead FREE STATUS / ROHS STATUS Lead free / RoHS Compliant DATA SHEET OT 10012SE pdf VOLTAGE RATING - DC VOLTAGE RATING - AC 120V VOLTAGE RATING - AC Solder Lug SERIES T-100 PANEL CUTOUT DIMENSIONS OTICUIAR - 9.53mm Dia OHT10012SE OHT10012SE - ND OPERATING FORCE - NUMBER OF POSITIONS 12 NUMBER OF POSITIONS 13 NUMBER OF POSITIONS 14 NOISTURE SENSITIVITY LEVEL (MSL.) 1 (Unlimited) MANUFACTURER SENSITIVITY LEVEL (MSL.) 1 (Unlimited) MOSITIVE SENSITIVITY	DADT NUMBER	T10013CF
DESCRIPTION SWITCH ROTARY 12POS 3A 12UV LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant DATA SHEET □ 10012SE.pdf VOLTAGE RATING - DC 20V VOLTAGE RATING - AC 120V TERMINATION STYLE Solder Lug SERIES T-100 PANEL CUTOUT DIMENSIONS Creular - 9.53mm Dia OTHER NAMES OHT10012SE OHT10012SE-ND OPERATING FORCE - NUMBER OF POSITIONS 12 NUMBER OF POLES PER DECK 1 MOUNTING TYPE Panel Mount MOUNTING TYPE Panel Mount MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) MANUFACTURER STANDARD LEAD TIME 12 Weeks LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant INDEX STOPS Fixed FEATURES - DETAILED DESCRIPTION Robarry Switch 12 Position SP12T 3A (AC/DC) 12DVAC Panel Mount DEPTH BEHIND PANEL 34.93mm CONTACT TRINIS Shorting (MBB) CONTACT FINISH - CIRCUIT PER DECK SP12T		
LEAD FREE STATUS / ROHS STATUS DATA SHEET DATA SHEET VOLTAGE RATING - DC 20V VOLTAGE RATING - AC 120V TERMINATION STYLE Solder Lug SERIES T-100 PANEL CUTOUT DIMENSIONS Circular - 9.53mm Dia OTHER NAMES OHT100125E - ND OPERATING FORCE - NUMBER OF POSITIONS 12 NUMBER OF POSITIONS 12 NUMBER OF POSITIONS 1 1 NUMBER OF POLES PER DECK 1 1 NUMBER OF POLES PER DECK 1 1 MOUNTING TYPE Panel Mount MOUSTURE SENSITIVITY LEVEL (MSL) MANUFACTURER STANDARD LEAD TIME 12 Weeks LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant INDEX STOPS Fixed FEATURES - DETAILED DESCRIPTION Rotary Switch 12 Position SP12T 3A (AC/DC) 120VAC Panel Mount DEPTH BEHIND PANEL CURRENT RATING 3A (AC/DC) CONTACT THING Shorting (MBB) CONTACT FINISH - CIRCUIT PER DECK ANGLE OF THROW - Flatted (6.35mm Dia)		
DATA SHEET ☑ T10012SE.pdf VOLTAGE RATING - DC 20V VOLTAGE RATING - AC 120V TERMINATION STYLE Solder Lug SERIES T-100 PANEL CUTOUT DIMENSIONS Circular - 9.53mm Dia OTHER NAMES OHT10012SE NDD OPERATING FORCE - NUMBER OF POSITIONS 12 NUMBER OF POLES PER DECK 1 NUMBER OF DELES PER DECK 1 NUMBER OF DELES PER DECK 1 MOUNTING TYPE Panel Mount MOLISTING ESENSITIVITY LEVEL (MSL) 1 (Unlimited) MANUFACTURER STANDARD LEAD TIME 12 Weeks LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant INDEX STOPS Fixed FEATURES - LEAD FREE STATUS / ROHS STATUS Rotary Switch 12 Position SP12T 3A (AC/DC) 120VAC Panel Mount DEFTH BEHIND PANEL 34 93mm CURRENT RATING 3A (AC/DC) CONTACT TIMING Shorting (MBB) CONTACT MATERIAL Silver Alloy CONTACT FINISH - CIRCULT FOR		
VOLTAGE RATING - DC 20V VOLTAGE RATING - AC 120V TERMINATION STYLE Solder Lug SERIES T-100 PANEL CUTOUT DIMENSIONS Circular - 9.53mm Dia OTHER NAMES OHT100125E-ND OPERATING FORCE - NUMBER OF POSITIONS 12 NUMBER OF POLES PER DECK 1 NUMBER OF DECKS 1 MOUNTING TYPE Panel Mount MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) MANUFACTURER STANDARD LEAD TIME 12 Weeks LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant INDEX STOPS Fixed FEATURES - DETAILED DESCRIPTION Rotary Switch 12 Position SP12T 3A (AC/DC) 120VAC Panel Mount DEFITH BEHIND PANEL 34-93mm CURRENT RATING 3A (AC/DC) CONTACT TIMING Shorting (MBB) CONTACT FINISH - CONTACT FINISH - CIRCUIT PER DECK SP12T ANGLE OF THROW - ACIUANOT TYPE Flatted (6.35mm Dia)		
VOLTAGE RATING - AC TERMINATION STYLE SORIES T-100 PANEL CUTOUT DIMENSIONS CITCUIAR - 9.53mm Dia OTHER NAMES OHT10012SE OHT10012SE-ND OPERATING FORCE - NUMBER OF POSITIONS 12 NUMBER OF POLES PER DECK 1 NUMBER OF DECKS 1 MOUNTING TYPE Panel Mount MOISTURE SENSITIVITY LEVEL (MSL) MANUFACTURER STANDARD LEAD TIME 12 Weeks LEAD FREE STATUS / ROHS STATUS DETAILED DESCRIPTION ROTAGE SENSITIVITY LEVEL (MSL) AN OUT ON THE MOISTURE THE MOISTURE SENSITIVITY LEVEL (MSL) AN OUT ON THE MOISTURE THE MOISTURE SENSITIVITY LEVEL (MSL) AN OUT ON THE MOISTURE THE MOISTURE SENSITIVITY LEVEL (MSL) AN OUT ON THE MOISTURE THE MOISTURE SENSITIVITY LEVEL (MSL) AN OUT ON THE MOISTURE THE MOISTURE SENSITIVITY LEVEL (MSL) AN OUT ON THE MOISTURE THE MOISTURE SENSITIVITY LEVEL (MSL) AN OUT ON THE MOISTURE THE MOIS	DATA SHEET	T10012SE.pdf
SERIES T-100 PANEL CUTOUT DIMENSIONS CIRCUIAR - 9.53mm Dia OTHER NAMES OHT10012SE OHT10012SE OHT10012SE-ND OPERATING FORCE - NUMBER OF POSITIONS 12 NUMBER OF POLES PER DECK 1 NUMBER OF DECKS 1 MOUNTING TYPE PANEL SENSITIVITY LEVEL (MSL) 1 (Unlimited) MANUFACTURER STANDARD LEAD TIME 12 Weeks LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant INDEX STOPS Fixed 9- PETAILED DESCRIPTION ROTAGN SHIPL 12 POSITION SP12T 3A (AC/DC) 120VAC Panel Mount DEPTH BEHIND PANEL 34-99mm CUIRRENT RATING 3A (AC/DC) CONTACT TIMING Shorting (MBB) CONTACT FINISH - CIRCUIT PER DECK SP12T ANGLE OF THROW - ACTUATOR TYPE FIRST	VOLTAGE RATING - DC	20V
SERIES T-100 PANEL CUTOUT DIMENSIONS Circular - 9.53mm Dia OTHER NAMES OHT100125E NDT0 OPERATING FORCE - NUMBER OF POSITIONS 12 NUMBER OF POLES PER DECK 1 NUMBER OF DECKS 1 MOUNTING TYPE Panel Mount MOSTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) MANUACTURER STANDARD LEAD TIME 12 Weeks LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant INDEX STOPS Fixed FEATURES - DETAILED DESCRIPTION Rotary Switch 12 Position SP12T 3A (AC/DC) 120VAC Panel Mount DEPTH BEHIND PANEL 34.93mm CURRENT RATING 3A (AC/DC) CONTACT TIMING Shorting (MBB) CONTACT MATERIAL Silver Alloy CONTACT FINISH - CIRCUIT PER DECK SP12T ANGLE OF THROW - ACIUATOR TYPE Flatted (6.35mm Dia)	VOLTAGE RATING - AC	120V
PANEL CUTOUT DIMENSIONS CITCUIR - 9.53mm Dia OTHER NAMES OHT100125E-ND OPERATING FORCE - NUMBER OF POSITIONS 12 NUMBER OF POLES PER DECK 1 NUMBER OF DECKS 1 MOUNTING TYPE PANEL MOUNT STANDARD LEAD TIME LEAD FREE STATUS / ROHS STATUS LEAD FR	TERMINATION STYLE	Solder Lug
OHTIONIZSE OHTIONIZSE OHTIONIZSE OHTIONIZSE OHTIONIZSE OHTIONIZSE NUMBER OF POSITIONS 12 NUMBER OF POLES PER DECK 1 NUMBER OF DECKS 1 MOUNTING TYPE Panel Mount MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) MANUFACTURER STANDARD LEAD TIME 12 Weeks LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant INDEX STOPS Fixed FEATURES - DETAILED DESCRIPTION ROLLY SWItch 12 Position SP12T 3A (AC/DC) 120VAC Panel Mount DEPTH BEHIND PANEL CURRENT RATING CONTACT TIMING CONTACT TIMING SONITY (MBB) CONTACT FINISH CURCUIT PER DECK ANGLE OF THROW FLATLED (6.35mm Dia)	SERIES	T-100
OPERATING FORCE POPERATING FORCE NUMBER OF POSITIONS 12 NUMBER OF POLES PER DECK NUMBER OF DECKS MOUNTING TYPE MOUNTING TYPE MANUFACTURER STANDARD LEAD TIME LEAD FREE STATUS / ROHS STATUS LEAD FREE STATUS / ROHS STATUS DETAILED DESCRIPTION ACAITY SWIRCH 12 POSITION SPI2T 3A (AC/DC) 120VAC Panel Mount DEPTH BEHIND PANEL CONTACT TIMING CONTACT TIMING CONTACT FINISH CONTACT FINISH CIRCUIT PER DECK ACUATOR TYPE Flated (6.35mm Dia) PLACE FLATER (1.30 PACE) FLATER OPERATION SPI2T AND ACCIDENT SPI2T AND ACCIDENT SPI2T SA (AC/DC) 120VAC PANEL SPI2T SA (AC	PANEL CUTOUT DIMENSIONS	Circular - 9.53mm Dia
NUMBER OF POSITIONS12NUMBER OF POLES PER DECK1NUMBER OF DECKS1MOUNTING TYPEPanel MountMOISTURE SENSITIVITY LEVEL (MSL)1 (Unlimited)MANUFACTURER STANDARD LEAD TIME12 WeeksLEAD FREE STATUS / ROHS STATUSLead free / ROHS CompliantINDEX STOPSFixedFEATURES-DETAILED DESCRIPTIONRotary Switch 12 Position SP12T 3A (AC/DC) 120VAC Panel MountDETH BEHIND PANEL34.93mmCURRENT RATINGShorting (MBB)CONTACT TIMINGShorting (MBB)CONTACT TIMINGSilver AlloyCONTACT FINISH-CIRCUIT PER DECKSP12TANGLE OF THROW-ACTUATOR TYPEFlatted (6.35mm Dia)	OTHER NAMES	
NUMBER OF POLES PER DECK NUMBER OF DECKS 1 MOUNTING TYPE Panel Mount MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) MANUFACTURER STANDARD LEAD TIME 12 Weeks LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant INDEX STOPS Fixed FEATURES - DETAILED DESCRIPTION ROLARY SWItch 12 Position SP12T 3A (AC/DC) 120VAC Panel Mount DEPTH BEHIND PANEL 34.93mm CURRENT RATING 3A (AC/DC) CONTACT TIMING CONTACT TIMING CONTACT TIMING CONTACT TIMING CONTACT FINISH - CIRCUIT PER DECK ANGLE OF THROW ACTUATOR TYPE Flatted (6.35mm Dia)	OPERATING FORCE	-
NUMBER OF DECKS1MOUNTING TYPEPanel MountMOISTURE SENSITIVITY LEVEL (MSL)1 (Unlimited)MANUFACTURER STANDARD LEAD TIME12 WeeksLEAD FREE STATUS / ROHS STATUSLead free / ROHS CompliantINDEX STOPSFixedFEATURES-DETAILED DESCRIPTIONRotary Switch 12 Position SP12T 3A (AC/DC) 120VAC Panel MountDETHI BEHIND PANEL34.93mmCURRENT RATING34 (AC/DC)CONTACT TIMINGShorting (MBB)CONTACT TIMINGSilver AlloyCONTACT FINISH-CONTACT FINISH-CIRCUIT PER DECK\$12TANGLE OF THROW-ANGLE OF THROW-ACTUATOR TYPEFlatted (6.35mm Dia)	NUMBER OF POSITIONS	12
MOUNTING TYPE MOISTURE SENSITIVITY LEVEL (MSL) MANUFACTURER STANDARD LEAD TIME LEAD FREE STATUS / ROHS STATUS FEATURES FEATURES DETAILED DESCRIPTION ROTARY SWITCH 12 POSITION SP12T 3A (AC/DC) 120VAC Panel Mount DEPTH BEHIND PANEL CURRENT RATING CURRENT RATING SINORY CONTACT TIMING SINORY SINORY CONTACT FINISH CONTACT FINISH CIRCUIT PER DECK ANGLE OF THROW FILE Flatted (6.35mm Dia)	NUMBER OF POLES PER DECK	1
MOISTURE SENSITIVITY LEVEL (MSL) MANUFACTURER STANDARD LEAD TIME LEAD FREE STATUS / ROHS STATUS LEAD FREE STATUS / ROHS STATUS FEATURES FEATURES DETAILED DESCRIPTION ROTARY SWITCH 12 Position SP12T 3A (AC/DC) 120VAC Panel Mount DEPTH BEHIND PANEL CURRENT RATING CONTACT TIMING CONTACT TIMING CONTACT TIMING CONTACT FINISH CURCUIT PER DECK ANGLE OF THROW ALL FLETCH SENSITIVITY LEVEL (MSL) 1 (Ulnimited) 12 Weeks Rotary Switch 12 Position SP12T 3A (AC/DC) ALL ANGLE OF THROW ALL ANGLE OF THROW FLETCH SENSITIVITY LEVEL (MSL) ALL ANGLE OF THROW ANGLE OF THROW ANGLE OF THROW ALL ANGLE OF THROW ANGLE OF TH	NUMBER OF DECKS	1
MANUFACTURER STANDARD LEAD TIME12 WeeksLEAD FREE STATUS / ROHS STATUSLead free / ROHS CompliantINDEX STOPSFixedFEATURES-DETAILED DESCRIPTIONRotary Switch 12 Position SP12T 3A (AC/DC) 120VAC Panel MountDEPTH BEHIND PANEL34.93mmCURRENT RATING3A (AC/DC)CONTACT TIMINGShorting (MBB)CONTACT TIMISH-CONTACT FINISH-CIRCUIT PER DECKSP12TANGLE OF THROW-ACTUATOR TYPEFlatted (6.35mm Dia)	MOUNTING TYPE	Panel Mount
LEAD FREE STATUS / ROHS STATUSLead free / RoHS CompliantINDEX STOPSFixedFEATURES-DETAILED DESCRIPTIONRotary Switch 12 Position SP12T 3A (AC/DC) 120VAC Panel MountDEPTH BEHIND PANEL34.93mmCURRENT RATING34 (AC/DC)CONTACT TIMINGShorting (MBB)CONTACT TIMISHSilver AlloyCONTACT FINISH-CIRCUIT PER DECK\$912TANGLE OF THROW-ACTUATOR TYPEFlatted (6.35mm Dia)	MOISTURE SENSITIVITY LEVEL (MSL)	1 (Unlimited)
FEATURES - CONTACT FINISH CONTACT PER DECK PACIDATE OF THROW CONTACT FINISH CONTACT FINISH ACTUATOR TYPE ACTUATOR	MANUFACTURER STANDARD LEAD TIME	12 Weeks
FEATURES DETAILED DESCRIPTION Rotary Switch 12 Position SP12T 3A (AC/DC) 120VAC Panel Mount DEPTH BEHIND PANEL 34.93mm CURRENT RATING 3A (AC/DC) CONTACT TIMING Shorting (MBB) CONTACT FINISH CONTACT FINISH CIRCUIT PER DECK ANGLE OF THROW ACTUATOR TYPE Flatted (6.35mm Dia)	LEAD FREE STATUS / ROHS STATUS	Lead free / RoHS Compliant
DETAILED DESCRIPTION Rotary Switch 12 Position SP12T 3A (AC/DC) 120VAC Panel Mount DEPTH BEHIND PANEL 34.93mm CURRENT RATING 3A (AC/DC) CONTACT TIMING Shorting (MBB) CONTACT MATERIAL Silver Alloy CONTACT FINISH - CIRCUIT PER DECK SP12T ANGLE OF THROW FINISH - ACTUATOR TYPE FINISH	INDEX STOPS	Fixed
DEPTH BEHIND PANEL 34.93mm CURRENT RATING 3A (AC/DC) CONTACT TIMING Shorting (MBB) CONTACT MATERIAL Silver Alloy CONTACT FINISH - CIRCUIT PER DECK SP12T ANGLE OF THROW - ACTUATOR TYPE FIRED SHORT S	FEATURES	-
CURRENT RATING SA (AC/DC) CONTACT TIMING Shorting (MBB) CONTACT MATERIAL Silver Alloy CONTACT FINISH CIRCUIT PER DECK SP12T ANGLE OF THROW ACTUATOR TYPE Flatted (6.35mm Dia)	DETAILED DESCRIPTION	Rotary Switch 12 Position SP12T 3A (AC/DC) 120VAC Panel Mount
CONTACT TIMING CONTACT MATERIAL CONTACT MATERIAL CONTACT FINISH CIRCUIT PER DECK ANGLE OF THROW ACTUATOR TYPE Shorting (MBB) Silver Alloy	DEPTH BEHIND PANEL	34.93mm
CONTACT MATERIAL CONTACT FINISH CIRCUIT PER DECK ANGLE OF THROW ACTUATOR TYPE Silver Alloy CIRCUIT Alloy Flatted (6.35mm Dia)	CURRENT RATING	3A (AC/DC)
CONTACT FINISH - CIRCUIT PER DECK SP12T ANGLE OF THROW - ACTUATOR TYPE Flatted (6.35mm Dia)	CONTACT TIMING	Shorting (MBB)
CIRCUIT PER DECK ANGLE OF THROW - ACTUATOR TYPE SP12T Flatted (6.35mm Dia)	CONTACT MATERIAL	Silver Alloy
ANGLE OF THROW - ACTUATOR TYPE Flatted (6.35mm Dia)	CONTACT FINISH	-
ACTUATOR TYPE Flatted (6.35mm Dia)	CIRCUIT PER DECK	SP12T
	ANGLE OF THROW	-
ACTUATOR LENGTH 12.70mm	ACTUATOR TYPE	Flatted (6.35mm Dia)
	ACTUATOR LENGTH	12.70mm

Related Tags

Ohmite T10012SE	T10012SE Distributor	T10012SE Supplier
T10012SE Price	T10012SE Pictures	T10012SE Image
T10012SE PDF Datasheet	T10012SE Download Datasheet	T10012SE Datasheet
T10012SE Stock	Buy T10012SE	Buy Ohmite T10012SE
Ohmite T10012SE	Ohmite Supplier	Ohmite Distributor
Ohmite T10012SE	Ohmite Mfg. Co. T10012SE	Ohmite Mfg. Co. T10012SE

Related Products



Manufacturers: Pulse Electronics Corporation Description: XFRMR 1:1.36/1 1.2MH SMD

In stock: Out stock

RFQ

T1001NLT



T1002BLKTOGGLECAP Manufacturers: E-Switch

Description: CAP TOGGLE BAT BLACK In stock: 526 pcs

RFQ



T10012

Manufacturers: Ohmite Description: SWITCH ROTARY 12POS 3A 120V

In stock: Out stock

RFQ



T10010SE Manufacturers: Ohmite

Description: SWITCH ROTARY 10POS 3A 120V In stock: Out stock

RFQ



T10011E Manufacturers: Ohmite

Description: SWITCH ROTARY 11POS 3A 120V In stock: Out stock

RFQ



T1003 Manufacturers: Pulse Electronics Corporation

Description: IC CHIP In stock: Out stock

RFQ



T10012E Manufacturers: Ohmite

Description: SWITCH ROTARY 12POS 3A 120V In stock: Out stock

RFQ

T1001WHTTOGGLECAP



Manufacturers: Ohmite Description: SWITCH ROTARY 12POS 3A 120V

T10012S

In stock: Out stock **RFQ**



Manufacturers: E-Switch Description: CAP TOGGLE BAT WHITE

In stock: Out stock

RFQ



T1001NL Manufacturers: Pulse Electronics Corporation

In stock: Out stock **RFQ**

Description: XFRMR 1:1.36/1 1.2MH SMD



Manufacturers: Ohmite Description: SWITCH ROTARY 11POS 3A 120V

T10011

In stock: Out stock

RFQ



Description: COMP STORAGE PLSTC 4.31"LX2.63"W

T1002 Manufacturers: Flambeau, Inc.

In stock: Out stock

RFQ











