



Image may be representation. See specifications for product details.

S-5725JCBH0-I4T1U

Part Number:

Manufacturer/Brand: Product description

Datasheets: RoHs Status

Ship From

Shipment Way

S-5725JCBH0-I4T1U

SII Semiconductor Corporation

MAGNETIC SWITCH LATCH SNT-4A

S-5725JCBH0-I4T1U.pdf

Lead free / RoHS Compliant Hong Kong

DHL/Fedex/TNT/UPS/EMS

REQUEST FOR QUOTATION

		Specifications of S-5725JCBH0-I4T1U
MANUFACTURER DESCRIPTION MAGNETIC SWITCH LATCH SNT-4A LEAD FREE STATUS / ROHS STATUS LEAD FREE STATUS / ROHS STATUS DATA SHEET DATA SHEET VOLTAGE - SUPPLY 2.7 V ~ 5.5 V TEST CONDITION 25°C TECHNOLOGY Hall Effect SUPPLIER DEVICE PACKAGE SNT-4A SERIES S-5725 SENSING RANGE POLARIZATION PACKAGING Tape & Reel (TR) PACKAGE / CASE OUTPUT TYPE PUSh-Pull OTHER NAMES OUTPUT TYPE PUSH-PUIL OTHER NAMES OPERATING TEMPERATURE MOISTURE SENSITIVITY LEVEL (MSL) MANUFACTURER STATUS / ROHS STATUS FUNCTION Lead free / ROHS Compliant FUNCTION Latch FEATURES DETAILED DESCRIPTION Digital Switch Latch Push-Pull Hall Effect SNT-		
DESCRIPTION MAGNETIC SWITCH LATCH SNT-4A LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant DATA SHEET VOLTAGE - SUPPLY 2.7 V ~ 5.5 V TEST CONDITION 25°C TECHNOLOGY Hall Effect SUPPLIER DEVICE PACKAGE SNT-4A SERIES S-5725 SENSING RANGE 2.7mT Trip, -2.7mT Release POLARIZATION South Pole PACKAGE / CASE OUTPUT TYPE PUSh-Pull OTHER NAMES OUTPUT TYPE PUSh-Pull OTHER NAMES DEFAILES DEFAILES DEFAILES LEAD FREE STATUS / ROHS STATUS LEad free / ROHS Compliant Latch FEATURES Digital Switch Latch Push-Pull Hall Effect SNT-4 Default SNT-4 Default SNT-4 Defaul	PART NUMBER	S-5725JCBH0-I4T1U
LEAD FREE STATUS / ROHS STATUS DATA SHEET CC S-5725JCBH0-I4T1U.pdf VOLTAGE - SUPPLY TEST CONDITION 25°C TECHNOLOGY Hall Effect SUPPLIER DEVICE PACKAGE SNT-4A SERIES S-5725 SENSING RANGE POLARIZATION South Pole PACKAGING Tape & Reel (TR) PACKAGE / CASE OUTPUT TYPE PUSh-Pull OTHER NAMES OUTPUT TYPE PUSh-Pull OTHER NAMES OPERATING TEMPERATURE MOISTURE SENSITIVITY LEVEL (MSL) MANUFACTURER STANDARD LEAD TIME LEAD FREE STATUS / ROHS STATUS LEAd free / ROHS Compliant FUNCTION Latch FEATURES DETAILED DESCRIPTION Digital Switch Latch Push-Pull Hall Effect SNT-44 DIGITAL SWITCH SUPPLING DI	MANUFACTURER	SII Semiconductor Corporation
DATA SHEET VOLTAGE - SUPPLY 2.7 V ~ 5.5 V TEST CONDITION 25°C TECHNOLOGY Hall Effect SUPPLIER DEVICE PACKAGE SNT-4A SERIES S-5725 SENSING RANGE POLARIZATION South Pole PACKAGING Tape & Reel (TR) PACKAGE / CASE 4-SMD, Flat Leads OUTPUT TYPE PUSH-PUIL OTHER NAMES OPERATING TEMPERATURE MOISTURE SENSITIVITY LEVEL (MSL) MANUFACTURER STANDARD LEAD TIME LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant FUNCTION Latch FEATURES DETAILED DESCRIPTION Digital Switch Latch Push-Pull Hall Effect SNT-4-6	DESCRIPTION	MAGNETIC SWITCH LATCH SNT-4A
VOLTAGE - SUPPLY 2.7 V ~ 5.5 V TEST CONDITION 25°C TECHNOLOGY Hall Effect SUPPLIER DEVICE PACKAGE SNT-4A SERIES S-5725 SENSING RANGE 2.7mT Trip, -2.7mT Release POLARIZATION South Pole PACKAGING Tape & Reel (TR) PACKAGE / CASE OUTPUT TYPE Push-Pull OTHER NAMES 1662-1669-2 S-5725JCBHO-14T1U-ND OPERATING TEMPERATURE -40°C ~ 85°C (TA) MOISTURE SENSITIVITY LEVEL (MSL) MANUFACTURER STANDARD LEAD TIME LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant FUNCTION Latch FEATURES - DETAILED DESCRIPTION Digital Switch Latch Push-Pull Hall Effect SNT-4A	LEAD FREE STATUS / ROHS STATUS	Lead free / RoHS Compliant
TEST CONDITION 25°C TECHNOLOGY Hall Effect SUPPLIER DEVICE PACKAGE SNT-4A SERIES S-5725 SENSING RANGE POLARIZATION South Pole PACKAGING Tape & Reel (TR) PACKAGE / CASE OUTPUT TYPE Push-Pull OTHER NAMES OPERATING TEMPERATURE MOISTURE SENSITIVITY LEVEL (MSL) MANUFACTURER STANDARD LEAD TIME LEAD FREE STATUS / ROHS STATUS FUNCTION Latch FEATURES DETAILED DESCRIPTION Digital Switch Latch Push-Pull Hall Effect SNT-4A	DATA SHEET	S-5725JCBH0-I4T1U.pdf
TECHNOLOGY SUPPLIER DEVICE PACKAGE SUPPLIER DEVICE PACKAGE SNT-4A SERIES S-5725 SENSING RANGE POLARIZATION South Pole PACKAGING Tape & Reel (TR) PACKAGE / CASE OUTPUT TYPE Push-Pull OTHER NAMES OPERATING TEMPERATURE MOISTURE SENSITIVITY LEVEL (MSL) MANUFACTURER STANDARD LEAD TIME LEAD FREE STATUS / ROHS STATUS DETAILED DESCRIPTION Hall Effect SNT-4A SNT-4A SNT-4A S-5725 South Pole A-4P & Reel (TR) FUNCTION Latch Hall Effect SNT-4A S-5725 Lead free / ROHS Compliant Latch Digital Switch Latch Push-Pull Hall Effect SNT-4A A-4P & ROHS Digital Switch Latch Push-Pull Hall Effect SNT-4A A-4P & ROHS Digital Switch Latch Push-Pull Hall Effect SNT-4A A-4P & ROHS Digital Switch Latch Push-Pull Hall Effect SNT-4A A-4P & ROHS A-4P & ROHS Digital Switch Latch Push-Pull Hall Effect SNT-4A A-4P & ROHS Digital Switch Latch Push-Pull Hall Effect SNT-4A A-4P & ROHS DIGITAL SWITCH DIGI	VOLTAGE - SUPPLY	2.7 V ~ 5.5 V
SUPPLIER DEVICE PACKAGE SERIES S-5725 SENSING RANGE 2.7mT Trip, -2.7mT Release POLARIZATION South Pole PACKAGING Tape & Reel (TR) PACKAGE / CASE 4-SMD, Flat Leads OUTPUT TYPE Push-Pull OTHER NAMES 1662-1669-2 S-5725JCBH0-14T1U-ND OPERATING TEMPERATURE -40°C ~ 85°C (TA) MOISTURE SENSITIVITY LEVEL (MSL) MANUFACTURER STANDARD LEAD TIME 100 Weeks LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant FUNCTION Latch FEATURES DETAILED DESCRIPTION Digital Switch Latch Push-Pull Hall Effect SNT-4-2-2-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1	TEST CONDITION	25°C
SERIES SENSING RANGE POLARIZATION South Pole PACKAGING PACKAGE / CASE OUTPUT TYPE OTHER NAMES OPERATING TEMPERATURE MOISTURE SENSITIVITY LEVEL (MSL) MANUFACTURER STANDARD LEAD TIME LEAD FREE STATUS / ROHS STATUS DETAILED DESCRIPTION South Pole 2.7mT Trip, -2.7mT Release 2.2mt Trip, -2.7mT Release 4.5mt Pole 4.5mt Po	TECHNOLOGY	Hall Effect
SENSING RANGE 2.7mT Trip, -2.7mT Release POLARIZATION South Pole PACKAGING Tape & Reel (TR) PACKAGE / CASE 4-SMD, Flat Leads OUTPUT TYPE Push-Pull OTHER NAMES 1662-1669-2 S-5725JCBH0-14T1U-ND OPERATING TEMPERATURE -40°C ~ 85°C (TA) MOISTURE SENSITIVITY LEVEL (MSL) MANUFACTURER STANDARD LEAD TIME LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant FUNCTION Latch FEATURES DETAILED DESCRIPTION Digital Switch Latch Push-Pull Hall Effect SNT-4A	SUPPLIER DEVICE PACKAGE	SNT-4A
POLARIZATION PACKAGING PACKAGING Tape & Reel (TR) A-SMD, Flat Leads OUTPUT TYPE Push-Pull OTHER NAMES OPERATING TEMPERATURE MOISTURE SENSITIVITY LEVEL (MSL) MANUFACTURER STANDARD LEAD TIME LEAD FREE STATUS / ROHS STATUS FUNCTION FEATURES DETAILED DESCRIPTION South Pole Aue A seel (TR) Tape & Reel (TR) Tape & Sevel tapes Tape & Tape & Tape & Tape Tape Tape Tape Tape Tape Tape Tape	SERIES	S-5725
PACKAGING PACKAGE / CASE OUTPUT TYPE OTHER NAMES OPERATING TEMPERATURE MANUFACTURER STANDARD LEAD TIME FUNCTION FEATURES DETAILED DESCRIPTION Tape & Reel (TR) 4-SMD, Flat Leads 4-SMD, Flat Leads 1662-1669-2 5-5725JCBH0-14T1U-ND 1662-1669-2 5-5725JCBH0-14T1U-ND 1 (Unlimited) 1 (Unlimited) Lead free / RoHS Compliant Lead free / RoHS Compliant Digital Switch Latch Push-Pull Hall Effect SNT-4A	SENSING RANGE	2.7mT Trip, -2.7mT Release
PACKAGE / CASE OUTPUT TYPE Push-Pull 662-1669-2 S-5725JCBH0-14T1U-ND OPERATING TEMPERATURE -40°C ~ 85°C (TA) MOISTURE SENSITIVITY LEVEL (MSL) MANUFACTURER STANDARD LEAD TIME LEAD FREE STATUS / ROHS STATUS FUNCTION Latch FEATURES DETAILED DESCRIPTION 4-SMD, Flat Leads 4-SMD, Flat Leads (4-SMD, Flat Leads (4-SM	POLARIZATION	South Pole
OUTPUT TYPE OTHER NAMES OTHER NAMES OPERATING TEMPERATURE OPERATING TEMPERATURE -40°C ~ 85°C (TA) MOISTURE SENSITIVITY LEVEL (MSL) MANUFACTURER STANDARD LEAD TIME 20 Weeks LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant FUNCTION FEATURES DETAILED DESCRIPTION Push-Pull A662-1669-2 S-5725JCBH0-14T1U-ND -40°C ~ 85°C (TA) L(Unlimited) 1 (Unlimited) Lead free / RoHS Compliant Lead free / RoHS Compliant Digital Switch Latch Push-Pull Hall Effect SNT-4A	PACKAGING	Tape & Reel (TR)
OTHER NAMES 1662-1669-2 S-5725JCBH0-I4T1U-ND OPERATING TEMPERATURE -40°C ~ 85°C (TA) MOISTURE SENSITIVITY LEVEL (MSL) MANUFACTURER STANDARD LEAD TIME 20 Weeks LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant FUNCTION Latch FEATURES - DETAILED DESCRIPTION Digital Switch Latch Push-Pull Hall Effect SNT-4A	PACKAGE / CASE	4-SMD, Flat Leads
OPERATING TEMPERATURE -40°C ~ 85°C (TA) MOISTURE SENSITIVITY LEVEL (MSL) MANUFACTURER STANDARD LEAD TIME 20 Weeks LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant FUNCTION Latch FEATURES - DETAILED DESCRIPTION S-5725JCBH0-I4T1U-ND -40°C ~ 85°C (TA) 1 (Unlimited) Lead free / RoHS Compliant Digital Switch Latch Push-Pull Hall Effect SNT-4A	OUTPUT TYPE	Push-Pull
MOISTURE SENSITIVITY LEVEL (MSL) MANUFACTURER STANDARD LEAD TIME LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant FUNCTION Latch FEATURES - DETAILED DESCRIPTION 1 (Unlimited) Lead free / RoHS Compliant Lead free / RoHS Compliant Latch - Digital Switch Latch Push-Pull Hall Effect SNT-4A	OTHER NAMES	
MANUFACTURER STANDARD LEAD TIME 20 Weeks LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant FUNCTION Latch FEATURES - DETAILED DESCRIPTION Digital Switch Latch Push-Pull Hall Effect SNT-4A	OPERATING TEMPERATURE	-40°C ~ 85°C (TA)
LEAD FREE STATUS / ROHS STATUS FUNCTION FEATURES DETAILED DESCRIPTION Lead free / RoHS Compliant Latch Latch - Digital Switch Latch Push-Pull Hall Effect SNT-4A	MOISTURE SENSITIVITY LEVEL (MSL)	1 (Unlimited)
FUNCTION Latch FEATURES - DETAILED DESCRIPTION Digital Switch Latch Push-Pull Hall Effect SNT-4A	MANUFACTURER STANDARD LEAD TIME	20 Weeks
FEATURES - DETAILED DESCRIPTION Digital Switch Latch Push-Pull Hall Effect SNT-4A	LEAD FREE STATUS / ROHS STATUS	Lead free / RoHS Compliant
DETAILED DESCRIPTION Digital Switch Latch Push-Pull Hall Effect SNT-4A	FUNCTION	Latch
	FEATURES	-
	DETAILED DESCRIPTION	Digital Switch Latch Push-Pull Hall Effect SNT-
CURRENT - SUPPLY (MAX) 2mA	CURRENT - SUPPLY (MAX)	2mA
CURRENT - OUTPUT (MAX) 2mA	CURRENT - OUTPUT (MAX)	2mA

Related Tags

SII Semiconductor Corporation S-5725JCBH0-I4T1U	S-5725JCBH0-I4T1U Distributor	S-5725JCBH0-I4T1U Supplier
S-5725JCBH0-I4T1U Price	S-5725JCBH0-I4T1U Pictures	S-5725JCBH0-I4T1U Image
S-5725JCBH0-I4T1U PDF Datasheet	S-5725JCBH0-I4T1U Download Datasheet	S-5725JCBH0-I4T1U Datasheet
S-5725JCBH0-I4T1U Stock	Buy S-5725JCBH0-I4T1U	Buy SII Semiconductor Corporation S-5725JCBH0-I4T1U
SII Semiconductor Corporation S-5725JCBH0-I4T1U	SII Semiconductor Corporation Supplier	SII Semiconductor Corporation Distributor
SII Semiconductor Corporation S-5725JCBH0-I4T1U		

Related Products



S-5725INBH0-I4T1U

Manufacturers: SII Semiconductor Corporation Description: MAGNETIC SWITCH LATCH SNT-4A

In stock: Out stock

RFQ



S-5725ICBH0-I4T1U Manufacturers: SII Semiconductor Corporation

Description: MAGNETIC SWITCH LATCH SNT-4A In stock: Out stock

RFQ



S-5731NNL2-M3T2U

Manufacturers: SII Semiconductor Corporation Description: MAGNETIC SWITCH UNIPOLAR SOT23-3

In stock: Out stock

RFQ



S-5731NSL2-M3T2U

Manufacturers: SII Semiconductor Corporation Description: MAGNETIC SWITCH UNIPOLAR SOT23-3

In stock: Out stock **RFQ**



S-5725JCBH1-I4T1U

Manufacturers: SII Semiconductor Corporation Description: MAGNETIC SWITCH LATCH SNT-4A

In stock: Out stock

RFQ



S-5725HCBH1-I4T1U

Manufacturers: SII Semiconductor Corporation Description: MAGNETIC SWITCH LATCH SNT-4A

In stock: Out stock **RFQ**



S-5731NSL1-M3T2U

Manufacturers: SII Semiconductor Corporation Description: MAGNETIC SWITCH UNIPOLAR SOT23-3

In stock: 100 pcs

RFQ



S-5725JNBH0-I4T1U Manufacturers: SII Semiconductor Corporation

Description: MAGNETIC SWITCH LATCH SNT-4A In stock: Out stock

RFQ



S-5725HCBH0-I4T1U Manufacturers: SII Semiconductor Corporation

Description: MAGNETIC SWITCH LATCH SNT-4A In stock: Out stock

RFQ



S-5725HNBH0-I4T1U

Description: MAGNETIC SWITCH LATCH SNT-4A In stock: Out stock

Manufacturers: SII Semiconductor Corporation

RFQ





S-5725ICBH1-I4T1U Manufacturers: SII Semiconductor Corporation

Description: MAGNETIC SWITCH LATCH SNT-4A In stock: Out stock

RFQ



S-5731RSL1-M3T2U

Manufacturers: SII Semiconductor Corporation Description: MAGNETIC SWITCH UNIPOLAR SOT23-3

RFQ

In stock: Out stock

E-mail: Info@Ocean-Components.com Address: Room 2102, Connaught Commercial Building, 185 Wan Chai Rd, Wan Chai, Hong Kong

Copyright © 2020 Reliable Distributor of Electronic Components - Ocean-Components.com













