APEM Inc.

GH46W000001

Part Number:

Manufacturer/Brand:

Product description Datasheets:

RoHs Status Ship From

Shipment Way

GH46W000001

APEM Inc.

SWITCH SLIDE DPDT 0.4VA 20V

Lead free / RoHS Compliant

GH46W000001.pdf

Hong Kong

DHL/Fedex/TNT/UPS/EMS



REQUEST FOR QUOTATION

Image may be representation. See specifications for product details.

| PART NUMBER GH46W00001 MANUFACTURER APEM Inc. DESCRIPTION SWTTCH SLIDE DPOT 0.4VA 20V LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant DATA SHEET SIGNER RATING - DC 20V VOLTAGE RATING - DC 20V VOLTAGE RATING - AC 20V VOLTAGE RATING - AC 20V VOLTAGE RATING - AC 20V SWITCH FUNCTION OP-On SERIES G PACKAGING Tube OPERATING FORCE - SWC - 85°C OPERATING FORCE - Through Hole, Right Angle MOLUTING TYPE MOISTURE SENSITIVITY LEVEL (MSL) I (Unlimited) MECHANICAL LIFE EAC FOR STATUS / ROHS STATUS Lead free / ROHS Compliant FEATURES EDETAILED SECRIPTION SIGNE STATUS / ROHS STATUS Lead free / ROHS Compliant FEATURES EDETAILED SECRIPTION SIGNE STATUS / ROHS STATUS Lead free / ROHS Compliant FEATURES EDETAILED SECRIPTION SIGNE SWITCH DEVIA THROUGH Hole, Right Angle CURRENT RATING OL-VA (ACDYC) CONTACT THING Not Specified CONTACT THING Not Specified CONTACT THING ON ACCOUNTED | | |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------|---------------------------------------------|
| MANUFACTURER APEM Inc. DESCRIPTION SWITCH SLIDE DPDT 0.4VA 20V LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant DATA SHEET 30 H460000001.pdf VOLTAGE RATING - DC 20V VOLTAGE RATING - AC 20V TERNINATION STYLE PC Pin SWITCH TRAVEL 2.20mm SWITCH HUNCTION On-On SWITCH FLOCK Tube OPERATING FORCE - OPERATING FORCE - MOUNTING TYPE Through Hole, Right Angle MICHANICAL LIFE - MECHANICAL LIFE - LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant ELECTICAL LIFE 60,000 Cycles CONTACT TRING 60,000 Cycles CONTACT TRING 60,000 Cycles < | | Specifications of GH46W000001 |
| MANUFACTURER APEN Inc. DESCRIPTION SWITCH SLIDE DPDT 0.4VA 20V LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant DATA SHEET 20V VOLTAGE RATING - DC 20V VOLTAGE RATING - AC 20V TERNIATION STYLE PC PIN SWITCH TRAVEL 2.20mn SWITCH FRAVEL 0n-0n SWITCH FRAVEL 10be PACXAGING Tube OPERATING TEMPERATURE 30°C ~ 85°C OPERATING FORCE 1 (Unlimited) MOUNTING TYPE Through Hole, Right Angle MICHANICAL LIFE - LEAD REES STATUS / ROHS STATUS Lead free / RoHS Compliant FEATURES Epony Sealed Terminals ELECTICAL LIFE 60,000 Cycles ELECTICAL LIFE 60,000 Cycles ECTAILED DESCRIPTION Sild SWING PDPT Through Hole, Right Angle CONTACT TRIING 60'60 CONTACT TRIING 60'60 CONTACT FINISH Geld CONTACT TRIINS Geld CRULTURY PE Standard | | |
| DESCRIPTION SWITCH SLIDE DPDT 0.4VA 20V LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compilant DATA SHEET Ged H46W000001.pdf VOLTAGE RATING - DC 20V VOLTAGE RATING - AC 20V SWITCH TRAVEL 2.20mm SWITCH FUNCTION On-On SERIES G PORCKAGING Tube OPERATING TEMPERATURE 30°C ~ 85°C OPERATING FORCE 1 MOUNTING TYPE Through Hole, Right Angle MOUNTING TYPE I (unlimited) MECHANICAL LIFE - LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compilant FEATURES Epony Sealed Terminals ELECTICAL LIFE 60,000 Cycles DETAILED DESCRIPTION Silde Swirtch Morph Hole, Right Angle CURRENT RATING 0.4VA (AC/DC) CONTACT FINISH Gold CONTACT FINISH Gold CRULT DPPT ACTUATOR TYPE Standard ACTUATOR TYPE Standard ACTUATOR MATERIAL Polyamide (PA), Nylon, Glass F | | |
| LEAD FREES STATUS / ROHS STATUS Lead free / ROHS Compliant DATA SHEET iii GH46W000001.pdf VOLTAGE RATING - DC 20V VOLTAGE RATING - AC 20V TERMINATION STYLE PC Pin SWITCH TRAVEL 2.20mm SWITCH FUNCTION On-On SERIES G PACKAGING Tube OPERATING FORCE - MOUNTING TYPE Through Hole, Right Angle MOUTING SENSITIVITY LEVEL (MSL) 1 (Unlimited) MECHANICAL LIFE - LEAD FREE STATUS / ROHS STATUS Ecad free / RoHS Compliant ELECTRICAL LIFE 60,000 Cycles ELECTRICAL LIFE 60,000 Cycles ELECTRICAL LIFE 60,000 Cycles CURRENT RATING 0.4VA (AC/DC) CONTACT TIMING Not Specified CONTACT TIMING 60d CONTACT FINISH Gold CRUIT POPT ACTUATOR TYPE Standard ACTUATOR TYPE Standard | | |
| DATA SHEET GH46W00001.pdf VOLTAGE RATING - DC 20V VOLTAGE RATING - AC 20V TERMINATION STYLE PC PIn SWITCH TRAVEL 2.20mm SWITCH FUNCTION 0n-On SERIES G PACKAGING Tube OPERATING TEMPERATURE -30°C ~ 85°C OPERATING FORCE - MOUNTING TYPE Through Hole, Right Angle MECHANICAL LIFE - LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant FEATURES Epoxy Sealed Terminals ELECTRICAL LIFE 50,000 Cycles DETAILED DESCRIPTION Silde Switch DPDT Through Hole, Right Angle CURRENT RATING 0,4VA (AC/DC) CONTACT TIMING Not Specified CONTACT FINISH Gold CURLIT FINISH Gold CURLIT FINISH Sindard CULTUATOR MYPE Sindard ACHALOR MYPE Sindard | | |
| VOLTAGE RATING - DC 20V VOLTAGE RATING - AC 20V SWITCH TRAVEL 2.20mm SWITCH FUNCTION 0n-On SERIES G PACKAGING Tube OPERATING TEMPERATURE -30°C ~ 85°C OPERATING TYPE Through Hole, Right Angle MOUNTING TYPE 1 (Unlimited) MECHANICAL LIFE - LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant FEATURES Epoxy Sealed Terminals ELECTRICAL LIFE 60,000 Cycles DETAILED DESCRIPTION Slide Switch DPDT Through Hole, Right Angle CURRENT RATING 0.4VA (AC/DC) CONTACT TIMING Not Specified CONTACT FINISH Gold CIRCUIT POPOT ACTUATOR TYPE Standard ACTUATOR MATERIAL Polyamide (PA), Nylon, Glass Filled | | |
| VOLTAGE RATING - AC 20V TERMINATION STYLE PC Pin SWITCH TRAVEL 2.20mm SWITCH FUNCTION On-On SERIES G PACKAGING Tube OPERATING TEMPERATURE -30°C ~ 85°C OPERATING FORCE - MOUNTING TYPE Through Hole, Right Angle MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) MECHANICAL LIFE - LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant ELECTRICAL LIFE 60,000 Cycles BETAILED DESCRIPTION Slide Switch DPDT Through Hole, Right Angle CURRENT RATING 0.4VA (AC/DC) CONTACT TIMING Not Specified CONTACT TIMING Not Specified CONTACT FINISH Gold CONTACT FINISH Gold CIUIT DPDT ACIUJATOR MATERIAL Broaderd ACIUJATOR MATERIAL Polyamide (PA), Nylon, Glass Filled | DATA SHEET | GH46W000001.pdf |
| TERMINATION STYLE PC Pin SWITCH TRAVEL 2.0mm SWITCH FUNCTION On-On SERIES G PACKAGING Tube OPERATING TEMPERATURE -30°C ~ 85°C OPERATING FORCE - MOUNTING TYPE Through Hole, Right Angle MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) MECHANICAL LIFE - EAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant ELECTRICAL LIFE 60,000 Cycles ELECTRICAL LIFE 60,000 Cycles DETAILED DESCRIPTION Sidie Switch DPDT Through Hole, Right Angle CURRENT RATING 0.4VA (AC/DC) CONTACT TIMING Not Specified CONTACT MATERIAL Brass CONTACT FINISH Gold CIUT DPDT ACIUTATOR TYPE Stendard ACIUTATOR NATERIAL Polyamide (PA), Nylon, Glass Filled | VOLTAGE RATING - DC | 20V |
| SWITCH TRAVEL 2.20mm SWITCH FUNCTION On-On SERIES G PACKAGING Tube OPERATING TEMPERATURE -30°C ~ 85°C OPERATING FORCE - MOUNTING TYPE Through Hole, Right Angle MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) MECHANICAL LIFE - LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant EELECTRICAL LIFE Epoxy Sealed Terminals ELECTRICAL LIFE 60,000 Cycles DETAILED DESCRIPTION Slide Switch DPDT Through Hole, Right Angle CURRENT RATING 0.4VA (AC/DC) CONTACT TIMING Not Specified CONTACT FINISH Gold CURCUIT DPDT ACTUATOR TYPE Standard ACTUATOR MATERIAL Polyamide (PA), Nylon, Glass Filled | VOLTAGE RATING - AC | 20V |
| SKITCH FUNCTION On-On SERIES G PACKAGING Tube OPERATING TEMPERATURE -30°C ~ 85°C OPERATING FORCE - MOUNTING TYPE Through Hole, Right Angle MCISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) MECHANICAL LIFE - LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant FEATURES Epoxy Sealed Terminals ELECTRICAL LIFE 60,000 Cycles DETAILED DESCRIPTION Slide Switch DPDT Through Hole, Right Angle CURRENT RATING 0.4VA (AC/DC) CONTACT TIMING Not Specified CONTACT MATERIAL Brass CONTACT FINISH Gold CIRCUIT DPDT ACTUATOR TYPE Standard ACTUATOR MATERIAL Polyamide (PA), Nylon, Glass Filled | TERMINATION STYLE | PC Pin |
| SERIES PACKAGING PACKAGING TUBE OPERATING TEMPERATURE OPERATING FORCE MOUNTING TYPE MOUNTING TYPE MOUNTING TYPE MECHANICAL LIFE LEAD FREE STATUS / ROHS STATUS ELECTRICAL LIFE EDOXY Sealed Terminals ELECTRICAL LIFE OUNCE SCRIPTION DETAILED DESCRIPTION CURRENT RATING CURRENT RATING CONTACT TIMING CONTACT TIMISH CONTACT TIMISH CONTACT TIMISH CONTACT TYPE ACTUATOR MATERIAL BOPDT Standard ACTUATOR MATERIAL Polyamide (PA), Nylon, Glass Filled | SWITCH TRAVEL | 2.20mm |
| PACKAGINGTubeOPERATING TEMPERATURE-30°C ~ 85°COPERATING FORCE-MOUNTING TYPEThrough Hole, Right AngleMOISTURE SENSITIVITY LEVEL (MSL)1 (Unlimited)MECHANICAL LIFE-LEAD FREE STATUS / ROHS STATUSLead free / RoHS CompliantFEATURESEpoxy Sealed TerminalsELECTRICAL LIFE60,000 CyclesDETAILED DESCRIPTIONSlide Switch DPDT Through Hole, Right AngleCURRENT RATING0.4VA (AC/DC)CONTACT TIMINGNot SpecifiedCONTACT MATERIALBrassCONTACT FINISHGoldCIRCUITDPDTACTUATOR TYPEStandardACTUATOR MATERIALStandardACTUATOR MATERIALPolyamide (PA), Nylon, Glass Filled | SWITCH FUNCTION | On-On |
| OPERATING TEMPERATURE OPERATING FORCE MOUNTING TYPE Through Hole, Right Angle MOISTURE SENSITIVITY LEVEL (MSL) MECHANICAL LIFE LEAD FREE STATUS / ROHS STATUS LEAd Free / RoHS Compliant FEATURES ELECTRICAL LIFE 60,000 Cycles DETAILED DESCRIPTION Slide Switch DPDT Through Hole, Right Angle CURRENT RATING ONTACT TIMING Not Specified CONTACT TIMING ONTACT FINISH CONTACT FINISH CIRCUIT ACTUATOR MYTERIAL BODY SIGNAL SENSAL CONTACT SINISH CIRCUIT ACTUATOR MYTERIAL BODY SINING | SERIES | G |
| OPERATING FORCE MOUNTING TYPE Through Hole, Right Angle MOISTURE SENSITIVITY LEVEL (MSL) MECHANICAL LIFE LEAD FREE STATUS / ROHS STATUS LEAd free / ROHS Compliant ELECTRICAL LIFE ELECTRICAL LIFE 60,000 Cycles DETAILED DESCRIPTION Slide Switch DPDT Through Hole, Right Angle CURRENT RATING CONTACT TIMING Not Specified CONTACT MATERIAL GOID CURTACT FINISH GOID ACTUATOR MATERIAL BARDAGE STANDAGE STANDAGE STANDAGE STANDAGE STANDAGE STANDAGE STANDAGE POlyamide (PA), Nylon, Glass Filled | PACKAGING | Tube |
| MOUNTING TYPE MOISTURE SENSITIVITY LEVEL (MSL) MECHANICAL LIFE LEAD FREE STATUS / ROHS STATUS LEAd Free / ROHS Compliant FEATURES ELECTRICAL LIFE 60,000 Cycles DETAILED DESCRIPTION Slide Switch DPDT Through Hole, Right Angle CURRENT RATING CONTACT TIMING CONTACT TIMING CONTACT TIMING CONTACT FINISH CONTACT FINISH CICRUIT ACTUATOR MYPE ACTUATOR MATERIAL BY SANDARY | OPERATING TEMPERATURE | -30°C ~ 85°C |
| MOISTURE SENSITIVITY LEVEL (MSL) MECHANICAL LIFE LEAD FREE STATUS / ROHS STATUS LEAD FREE STATUS / ROHS STATUS EDOXY Sealed Terminals ELECTRICAL LIFE 60,000 Cycles DETAILED DESCRIPTION Slide Switch DPDT Through Hole, Right Angle CURRENT RATING CONTACT TIMING CONTACT TIMING CONTACT TIMING CONTACT FINISH CONTACT FINISH CONTACT FINISH ACTUATOR MATERIAL ACTUATOR MATERIAL B (PA), Nylon, Glass Filled | OPERATING FORCE | - |
| MECHANICAL LIFE LEAD FREE STATUS / ROHS STATUS ELECTRICAL LIFE DETAILED DESCRIPTION CURRENT RATING CONTACT TIMING CONTACT FINISH CONTACT FINISH ACTUATOR TYPE ACTUATOR MATERIAL DEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant Elect RohS Complia | MOUNTING TYPE | Through Hole, Right Angle |
| LEAD FREE STATUS / ROHS STATUS EDATURES EDAT | MOISTURE SENSITIVITY LEVEL (MSL) | 1 (Unlimited) |
| ELECTRICAL LIFE 60,000 Cycles DETAILED DESCRIPTION Slide Switch DPDT Through Hole, Right Angle CURRENT RATING 0.4VA (AC/DC) CONTACT TIMING Not Specified CONTACT FINISH Gold CIRCUIT DPDT ACTUATOR TYPE Standard Polyamide (PA), Nylon, Glass Filled | MECHANICAL LIFE | - |
| ELECTRICAL LIFE 60,000 Cycles DETAILED DESCRIPTION Slide Switch DPDT Through Hole, Right Angle CURRENT RATING 0.4VA (AC/DC) CONTACT TIMING Not Specified CONTACT FINISH CONTACT FINISH CIRCUIT ACTUATOR TYPE ACTUATOR MATERIAL Polyamide (PA), Nylon, Glass Filled | LEAD FREE STATUS / ROHS STATUS | Lead free / RoHS Compliant |
| DETAILED DESCRIPTION Slide Switch DPDT Through Hole, Right Angle CURRENT RATING O.4VA (AC/DC) CONTACT TIMING Not Specified CONTACT MATERIAL Brass CONTACT FINISH CONTACT FINISH CIRCUIT DPDT ACTUATOR TYPE ACTUATOR MATERIAL Polyamide (PA), Nylon, Glass Filled | FEATURES | Epoxy Sealed Terminals |
| CURRENT RATING CONTACT TIMING Not Specified CONTACT MATERIAL Brass CONTACT FINISH CIRCUIT ACTUATOR TYPE ACTUATOR MATERIAL D.4VA (AC/DC) Not Specified Not Specified DPDT Standard Polyamide (PA), Nylon, Glass Filled | ELECTRICAL LIFE | 60,000 Cycles |
| CONTACT TIMING Not Specified CONTACT MATERIAL Brass CONTACT FINISH Gold CIRCUIT ACTUATOR TYPE ACTUATOR MATERIAL Polyamide (PA), Nylon, Glass Filled | DETAILED DESCRIPTION | Slide Switch DPDT Through Hole, Right Angle |
| CONTACT MATERIAL CONTACT FINISH CIRCUIT ACTUATOR TYPE ACTUATOR MATERIAL Brass Gold DPDT Standard Standard Polyamide (PA), Nylon, Glass Filled | CURRENT RATING | 0.4VA (AC/DC) |
| CONTACT FINISH CIRCUIT ACTUATOR TYPE ACTUATOR MATERIAL Sold Sold DPDT Standard Standard Polyamide (PA), Nylon, Glass Filled | CONTACT TIMING | Not Specified |
| CIRCUIT DPDT ACTUATOR TYPE Standard ACTUATOR MATERIAL Polyamide (PA), Nylon, Glass Filled | CONTACT MATERIAL | Brass |
| ACTUATOR TYPE Standard ACTUATOR MATERIAL Polyamide (PA), Nylon, Glass Filled | CONTACT FINISH | Gold |
| ACTUATOR MATERIAL Polyamide (PA), Nylon, Glass Filled | CIRCUIT | DPDT |
| | ACTUATOR TYPE | Standard |
| ACTUATOR LENGTH 4.70mm | ACTUATOR MATERIAL | Polyamide (PA), Nylon, Glass Filled |
| | ACTUATOR LENGTH | 4.70mm |

Related Tags

| APEM Inc. GH46W000001 | GH46W000001 Distributor | GH46W000001 Supplier |
|---------------------------|----------------------------------|----------------------------------|
| GH46W000001 Price | GH46W000001 Pictures | GH46W000001 Image |
| GH46W000001 PDF Datasheet | GH46W000001 Download Datasheet | GH46W000001 Datasheet |
| GH46W000001 Stock | Buy GH46W000001 | Buy APEM Inc. GH46W000001 |
| APEM Inc. GH46W000001 | APEM Inc. Supplier | APEM Inc. Distributor |
| APEM Inc. GH46W000001 | APEM Components, LLC GH46W000001 | APEM Components, LLC GH46W000001 |

Related Products



GH4001 Manufacturers: Industrial Fiber Optics, Inc.

Description: CBL FBR OPTIC 1000UM SMPLX 500M In stock: 31 pcs

RFQ



GH46S010001

Manufacturers: APEM Inc. Description: SWITCH SLIDE DPDT 3A 30V

In stock: Out stock

RFQ



GH49S010001

Manufacturers: APEM Inc. Description: SWITCH SLIDE DPDT 3A 30V

In stock: Out stock

RFQ

GH46W010001



GH46WW00001

Manufacturers: APEM Inc. Description: SWITCH SLIDE DPDT 0.4VA 20V

In stock: Out stock

RFQ



Manufacturers: APEM Inc. Description: SWITCH SLIDE DPDT 3A 30V

In stock: Out stock

RFQ

APEM

GH46P011201

Manufacturers: APEM Inc. Description: SWITCH SLIDE DPDT 3A 30V

In stock: Out stock

RFQ



GH4002 Manufacturers: Industrial Fiber Optics, Inc.

Description: CBL FBR OPTIC 1000UM DUPLX 500M In stock: 5 pcs

RFQ



GH49W000001 Manufacturers: APEM Inc.

Description: SWITCH SLIDE DPDT 0.4VA 20V In stock: Out stock

RFQ



GH49P010001 Manufacturers: APEM Inc.

Description: SWITCH SLIDE DPDT 3A 30V In stock: Out stock

RFQ



APEM

Manufacturers: APEM Inc. Description: SWITCH SLIDE DPDT 3A 30V

GH46P010001

In stock: Out stock

RFQ



Manufacturers: APEM Inc. Description: SWITCH SLIDE DPDT 0.4VA 20V

GH46P000001

In stock: Out stock

RFQ



GH46WW10001 Manufacturers: APEM Inc.

Description: SWITCH SLIDE DPDT 3A 30V In stock: Out stock

RFQ



Copyright © 2020 Reliable Distributor of Electronic Components - Ocean-Components.com













