

E-Switch Datasheets:

LS085R105F160V2A

Part Number:

Manufacturer/Brand: Product description

RoHs Status

Ship From Shipment Way LS085R105F160V2A

E-Switch

1.LS085R105F160V2A.pdf 2.LS085R105F160V2A.pdf

SWITCH SNAP ACT SPDT 0.4VA 20V

Lead free / RoHS Compliant Hong Kong

DHL/Fedex/TNT/UPS/EMS

REQUEST FOR QUOTATION

Image may be representation. See specifications for

product details.

| BANDIFACTURER DESCRIPTION SWITCH SNAP ACT SPDT 0.4VA 20V LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant DATA SHEET DATA SLESSER SHEET DATA SHEET | | Specifications of LS085R105F160V2A | |
|--|----------------------------------|------------------------------------|--|
| BESWITCH SNAP ACT SPDT 0.4VA 20V LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant DATA SHEET SWITCH SNAP ACT SPDT 0.4VA 20V LEAD FREE STATUS / ROHS STATUS LEAD FREE STATUS | | | |
| DESCRIPTION SWITCH SNAP ACT SPDT 0.4VA 20V LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant DATA SHEET VOLTAGE RATING - DC 20V VOLTAGE RATING - AC 2DV TERMINATION STYLE PC Pin SWITCH FUNCTION On-Mom SERIES LS RELEASE FORCE 40gf PRETRAVEL 0.106" (2.7mm) Bulk OVERTRAVEL OPERATING TEMPERATURE -25°C ~ 85°C OPERATING POSITION 0.815" (20.7mm) OPERATING FORCE 160gf MOUNTING TYPE Through Hole, Right Angle MOUNTING TYPE MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) MECHANICAL LIFE MANUFACTURER STANDARD LEAD TIME 11 Weeks LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant INGRESS PROTECTION FEATURES ELECTRICAL LIFE 50,000 Cycles DIFFERENTIAL TRAVEL CURRENT RATING 0.4VA (AC/DC) SPDT | PART NUMBER | LS085R105F160V2A | |
| LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant DATA SHEET DATA S | MANUFACTURER | E-Switch | |
| DATA SHEET DATA S | DESCRIPTION | SWITCH SNAP ACT SPDT 0.4VA 20V | |
| DATA SHEET VOLTAGE RATING - DC VOLTAGE RATING - AC 20V VOLTAGE RATING - AC 20V TERMINATION STYLE PC Pin SWITCH FUNCTION On-Mom SERIES LS RELEASE FORCE 40gf PRETRAVEL 0.106" (2.7mm) PACKAGING Bulk OVERTRAVEL - OPERATING TEMPERATURE -25°C ~ 85°C OPERATING POSITION 0.815" (20.7mm) OPERATING FORCE MOUNTING TYPE Through Hole, Right Angle MINISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) MECHANICAL LIFE MANUFACTURER STANDARD LEAD TIME 1.000,000 Cycles MANUFACTURES LEAD FREE STATUS / ROHS STATUS LEAD free / ROHS Compliant INGRESS PROTECTION - FEATURES ELECTRICAL LIFE 50,000 Cycles DIFFERENTIAL TRAVEL CURRENT RATING 0.4VA (AC/DC) SPDT | LEAD FREE STATUS / ROHS STATUS | Lead free / RoHS Compliant | |
| VOLTAGE RATING - AC TERMINATION STYLE PC Pin SWITCH FUNCTION On-Mom SERIES LS RELEASE FORCE 40gf PRETRAVEL 0.106" (2.7mm) PACKAGING Bulk OVERTRAVEL - OPERATING TEMPERATURE -25°C ~ 85°C OPERATING POSITION OPERATING FORCE 160gf MOUNTING TYPE Through Hole, Right Angle MOISTURE SENSITIVITY LEVEL (MSL) MECHANICAL LIFE MANUFACTURER STANDARD LEAD TIME LEAD FREE STATUS / ROHS STATUS LEAD FREE S | DATA SHEET | | |
| TERMINATION STYLE SWITCH FUNCTION On-Mom SERIES LS RELEASE FORCE #Ugf PRETRAVEL 0.106" (2.7mm) PACKAGING Bulk OVERTRAVEL - OPERATING TEMPERATURE -25°C ~ 85°C OPERATING POSITION OPERATING FORCE #MOUNTING TYPE Through Hole, Right Angle MOISTURE SENSITIVITY LEVEL (MSL) #MECHANICAL LIFE #MANUFACTURER STANDARD LEAD TIME LEAD FREE STATUS / ROHS STATUS LECTRICAL LIFE 50,000 Cycles DIFFERENTIAL TRAVEL CURRENT RATING 0.4VA (AC/DC) CICCULT SPDT | VOLTAGE RATING - DC | 20V | |
| SWITCH FUNCTION SERIES LS RELEASE FORCE 40gf PRETRAVEL 0.106" (2.7mm) PACKAGING Bulk OVERTRAVEL - OPERATING TEMPERATURE -25°C ~ 85°C OPERATING POSITION 0.815" (20.7mm) OPERATING FORCE 160gf MOUNTING TYPE Through Hole, Right Angle MOISTURE SENSITIVITY LEVEL (MSL) MECHANICAL LIFE 1,000,000 Cycles MANUFACTURER STANDARD LEAD TIME 11 Weeks LEAD FREE STATUS / ROHS STATUS LEAd free / ROHS Compliant INGRESS PROTECTION FEATURES ELECTRICAL LIFE 50,000 Cycles DIFFERENTIAL TRAVEL CURRENT RATING 0.4VA (AC/DC) SPDT | VOLTAGE RATING - AC | 20V | |
| LS RELEASE FORCE RELEASE FORCE RELEASE FORCE 40gf PRETRAVEL 0.106" (2.7mm) Bulk OVERTRAVEL - OPERATING TEMPERATURE -25°C ~ 85°C OPERATING POSITION 0.815" (20.7mm) OPERATING FORCE 160gf MOUNTING TYPE Through Hole, Right Angle MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) MECHANICAL LIFE 1,000,000 Cycles MANUFACTURER STANDARD LEAD TIME 11 Weeks LEAD FREE STATUS / ROHS STATUS LEAd free / ROHS Compliant INGRESS PROTECTION FEATURES ELECTRICAL LIFE 50,000 Cycles DIFFERENTIAL TRAVEL CURRENT RATING 0.4VA (AC/DC) SPDT | TERMINATION STYLE | PC Pin | |
| RELEASE FORCE 40gf PRETRAVEL 0.106" (2.7mm) Bulk OVERTRAVEL - OPERATING TEMPERATURE -25°C ~ 85°C OPERATING POSITION 0.815" (20.7mm) OPERATING FORCE 160gf MOUNTING TYPE Through Hole, Right Angle MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) MECHANICAL LIFE 1,000,000 Cycles MANUFACTURER STANDARD LEAD TIME 11 Weeks LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant INGRESS PROTECTION FEATURES ELECTRICAL LIFE 50,000 Cycles DIFFERENTIAL TRAVEL CURRENT RATING 0.4VA (AC/DC) CIRCUIT SPDT | SWITCH FUNCTION | On-Mom | |
| PRETRAVEL 0.106" (2.7mm) PACKAGING Bulk OVERTRAVEL - OPERATING TEMPERATURE -25°C ~ 85°C OPERATING POSITION 0.815" (20.7mm) OPERATING FORCE 160gf MOUNTING TYPE Through Hole, Right Angle MOISTURE SENSITIVITY LEVEL (MSL) MECHANICAL LIFE 1,000,000 Cycles MANUFACTURER STANDARD LEAD TIME 11 Weeks LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant INGRESS PROTECTION - FEATURES ELECTRICAL LIFE 50,000 Cycles DIFFERENTIAL TRAVEL CURRENT RATING 0.4VA (AC/DC) CIRCUIT SPDT | SERIES | LS | |
| PACKAGING OVERTRAVEL OPERATING TEMPERATURE OPERATING POSITION OPERATING PORCE MOUNTING TYPE MOUNTING TYPE MOUNTING TYPE MECHANICAL LIFE MANUFACTURER STANDARD LEAD TIME LEAD FREE STATUS / ROHS STATUS LEAD FREE STATUS / ROHS Compliant LEAD FREE STATUS / ROHS STATUS LEAD FREE STATUS / ROHS COMPLIANT LEAD FREE STATUS / ROHS CO | RELEASE FORCE | 40gf | |
| OVERTRAVEL OPERATING TEMPERATURE -25°C ~ 85°C OPERATING POSITION OPERATING FORCE 160gf MOUNTING TYPE Through Hole, Right Angle MOISTURE SENSITIVITY LEVEL (MSL) MECHANICAL LIFE 1,000,000 Cycles MANUFACTURER STANDARD LEAD TIME 11 Weeks LEAD FREE STATUS / ROHS STATUS LEAD free / RoHS Compliant INGRESS PROTECTION FEATURES ELECTRICAL LIFE 50,000 Cycles DIFFERENTIAL TRAVEL CURRENT RATING 0.4VA (AC/DC) CIRCUIT SPDT | PRETRAVEL | 0.106" (2.7mm) | |
| OPERATING TEMPERATURE -25°C ~ 85°C OPERATING POSITION 0.815" (20.7mm) OPERATING FORCE 160gf MOUNTING TYPE Through Hole, Right Angle MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) MECHANICAL LIFE 1,000,000 Cycles MANUFACTURER STANDARD LEAD TIME 11 Weeks LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant INGRESS PROTECTION - FEATURES ELECTRICAL LIFE 50,000 Cycles DIFFERENTIAL TRAVEL CURRENT RATING 0.4VA (AC/DC) CIRCUIT | PACKAGING | Bulk | |
| OPERATING POSITION OPERATING FORCE 160gf MOUNTING TYPE Through Hole, Right Angle MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) MECHANICAL LIFE 1,000,000 Cycles MANUFACTURER STANDARD LEAD TIME 11 Weeks LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant INGRESS PROTECTION - FEATURES - ELECTRICAL LIFE 50,000 Cycles DIFFERENTIAL TRAVEL - CURRENT RATING 0.4VA (AC/DC) CIRCUIT SPDT | OVERTRAVEL | - | |
| OPERATING FORCE MOUNTING TYPE MOUNTING TYPE MOISTURE SENSITIVITY LEVEL (MSL) MECHANICAL LIFE MANUFACTURER STANDARD LEAD TIME LEAD FREE STATUS / ROHS STATUS LEAD FREE STATUS / ROHS Compliant INGRESS PROTECTION - FEATURES ELECTRICAL LIFE 50,000 Cycles DIFFERENTIAL TRAVEL - CURRENT RATING 0.4VA (AC/DC) CIRCUIT SPDT | OPERATING TEMPERATURE | -25°C ~ 85°C | |
| MOUNTING TYPE Through Hole, Right Angle MOISTURE SENSITIVITY LEVEL (MSL) MECHANICAL LIFE 1,000,000 Cycles MANUFACTURER STANDARD LEAD TIME 11 Weeks LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant INGRESS PROTECTION - FEATURES ELECTRICAL LIFE 50,000 Cycles CURRENT RATING 0.4VA (AC/DC) SPDT | OPERATING POSITION | 0.815" (20.7mm) | |
| MOISTURE SENSITIVITY LEVEL (MSL) MECHANICAL LIFE 1,000,000 Cycles MANUFACTURER STANDARD LEAD TIME 11 Weeks LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant INGRESS PROTECTION - FEATURES - ELECTRICAL LIFE 50,000 Cycles DIFFERENTIAL TRAVEL CURRENT RATING 0.4VA (AC/DC) SPDT | OPERATING FORCE | 160gf | |
| MECHANICAL LIFE MANUFACTURER STANDARD LEAD TIME 11 Weeks LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant INGRESS PROTECTION FEATURES ELECTRICAL LIFE 50,000 Cycles DIFFERENTIAL TRAVEL CURRENT RATING 0.4VA (AC/DC) SPDT | MOUNTING TYPE | Through Hole, Right Angle | |
| MANUFACTURER STANDARD LEAD TIME LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant INGRESS PROTECTION FEATURES - ELECTRICAL LIFE 50,000 Cycles DIFFERENTIAL TRAVEL CURRENT RATING 0.4VA (AC/DC) SPDT | MOISTURE SENSITIVITY LEVEL (MSL) | 1 (Unlimited) | |
| LEAD FREE STATUS / ROHS STATUS INGRESS PROTECTION FEATURES ELECTRICAL LIFE DIFFERENTIAL TRAVEL CURRENT RATING CIRCUIT Lead free / RoHS Compliant - - 0.4VA (AC/DC) SPDT | MECHANICAL LIFE | 1,000,000 Cycles | |
| INGRESS PROTECTION FEATURES ELECTRICAL LIFE 50,000 Cycles DIFFERENTIAL TRAVEL CURRENT RATING 0.4VA (AC/DC) CIRCUIT SPDT | MANUFACTURER STANDARD LEAD TIME | 11 Weeks | |
| FEATURES - CIRCUIT - SPDT - CIRCUIT | LEAD FREE STATUS / ROHS STATUS | Lead free / RoHS Compliant | |
| ELECTRICAL LIFE 50,000 Cycles DIFFERENTIAL TRAVEL - CURRENT RATING 0.4VA (AC/DC) CIRCUIT SPDT | INGRESS PROTECTION | - | |
| DIFFERENTIAL TRAVEL - CURRENT RATING 0.4VA (AC/DC) CIRCUIT SPDT | FEATURES | - | |
| CURRENT RATING 0.4VA (AC/DC) CIRCUIT SPDT | ELECTRICAL LIFE | 50,000 Cycles | |
| CIRCUIT | DIFFERENTIAL TRAVEL | - | |
| | CURRENT RATING | 0.4VA (AC/DC) | |
| ACTUATOR TYPE Lever, Roller | CIRCUIT | SPDT | |
| | ACTUATOR TYPE | Lever, Roller | |

Related Tags

| E-Switch LS085R105F160V2A | LS085R105F160V2A Distributor | LS085R105F160V2A Supplier |
|--------------------------------|-------------------------------------|-------------------------------|
| LS085R105F160V2A Price | LS085R105F160V2A Pictures | LS085R105F160V2A Image |
| LS085R105F160V2A PDF Datasheet | LS085R105F160V2A Download Datasheet | LS085R105F160V2A Datasheet |
| LS085R105F160V2A Stock | Buy LS085R105F160V2A | Buy E-Switch LS085R105F160V2A |
| E-Switch LS085R105F160V2A | E-Switch Supplier | E-Switch Distributor |
| E-Switch LS085R105F160V2A | | |

Related Products



Manufacturers: E-Switch Description: SW SNAP ACT SPST-NC 0.4VA 20V

LS085R106F120C2B

In stock: Out stock

RFQ

LS085R105F160C1A Manufacturers: E-Switch

Description: SWITCH SNAP ACT SPDT 0.4VA 20V In stock: Out stock

RFQ



Manufacturers: E-Switch

LS085R105F160V1A

Description: SWITCH SNAP ACT SPDT 0.4VA 20V

In stock: Out stock **RFQ**

LS085R104F050C1A Manufacturers: E-Switch

Description: SWITCH SNAP ACT SPDT 0.4VA 20V In stock: Out stock

RFQ



LS085R106F120C1B

Manufacturers: E-Switch Description: SW SNAP ACT SPST-NC 0.4VA 20V

In stock: 32 pcs

RFQ

LS085R106F045S1A Manufacturers: E-Switch

Description: SWITCH SNAP ACT SPDT 0.4VA 20V

In stock: Out stock

RFQ



LS085R104F050V2B Manufacturers: E-Switch

Description: SW SNAP ACT SPST-NC 0.4VA 20V In stock: Out stock

RFQ

LS085R104F140C1C Manufacturers: E-Switch

Description: SW SNAP ACT SPST-NO 0.4VA 20V In stock: Out stock

RFQ



Description: SW SNAP ACT SPST-NO 0.4VA 20V In stock: Out stock

Manufacturers: E-Switch

LS085R106F120C1C

RFQ



Manufacturers: E-Switch Description: SWITCH SNAP ACT SPDT 0.4VA 20V

LS085R104F085C1A

In stock: 484 pcs

RFQ



LS085R105F250C1C Manufacturers: E-Switch

Description: SW SNAP ACT SPST-NO 0.4VA 20V In stock: 318 pcs

RFQ



LS085R105F100S1A Manufacturers: E-Switch

Description: SWITCH SNAP ACT SPDT 0.4VA 20V In stock: Out stock

RFQ

















