



Image may be representation. See specifications for product details.

#### MM12-60APS-ZCK

Part Number:

Manufacturor/Prands

Manufacturer/Brand:

Product description

Datasheets: Ship From

Shipment Way

MM12-60APS-ZCK

SICK

SEN PROX MAG PNP 60MM M12

MM12-60APS-ZCK.pdf

Hong Kong

DHL/Fedex/TNT/UPS/EMS



**REQUEST FOR QUOTATION** 

PART NUMBER  MM12-60APS-ZCK  MANUFACTURER  SICK  DESCRIPTION  SEN PROX MAG PNP 60MM M12  LEAD FREE STATUS / ROHS STATUS  DATA SHEET  VOLTAGE - SUPPLY  10 V ~ 30 V  TERMINATION STYLE  Connector  SHIELDING  Unshielded  SERIES  - SENSING DISTANCE  SENSING DISTANCE  SENSING DISTANCE  AUSBER  CVIII TYPE  AUGURANCE  CVIII TYPE  OTHER NAMES  OPERATING TEMPERATURE  -25°C ~ 75°C  MATERIAL - BODY  MANUFACTURER STANDARD LEAD TIME  1067  INDICATOR  DETAILED DESCRIPTION  PROXIMITY Sensor 2.362" (60mm) 1P67 Cylinder, Threaded - M12  DETAILED DESCRIPTION		Specifications of MM12-60APS-ZCK	
MANUFACTURER  DESCRIPTION  SEN PROX MAG PNP 60MM M12  LEAD FREE STATUS / ROHS STATUS  DATA SHEET  DATA SHEET  VOLTAGE - SUPPLY  10 V ~ 30 V  TERMINATION STYLE  Connector  SHIELDING  Unshielded  SERIES  SENSING DISTANCE  SENSING DISTANCE  RESPONSE FREQUENCY  ALKAGE / CASE  CVIINder, Threaded - M12  OUTPUT TYPE  OTHER NAMES  OPPANO, 3-WIRE  OPPANO, 3-WIRE  OPPANO, 3-WIRE  OPPANO MARES  MANUFACTURER STANDARD LEAD TIME  MANUFACTURER STANDARD LEAD TIME  MANUFACTURER STANDARD LEAD TIME  INGRESS PROTECTION  IBBO  MED MM12-60APS-ZCK.pdf  MM12-60APS-ZCK.pdf  AM12-60APS-ZCK.pdf  Connector  10 V ~ 30 V  10			
DESCRIPTION  LEAD FREE STATUS / ROHS STATUS  DATA SHEET  DATA SHEET  VOLTAGE - SUPPLY  10 V ~ 30 V  TERMINATION STYLE  Connector  SHIELDING  Unshielded  SERIES  - SENSING DISTANCE  RESPONSE FREQUENCY  HAY  PACKAGE / CASE  OUTPUT TYPE  OTHER NAMES  OPERATING TEMPERATURE  DEFRAUMAS  OPERATING TEMPERATURE  ABSE-1316  OPERATING TEMPERATURE  MATERIAL - BODY  MANUFACTURER STANDARD LEAD TIME  INGRESS PROTECTION  INGRESS PROTECTIO	PART NUMBER	MM12-60APS-ZCK	
LEAD FREE STATUS / ROHS STATUS         DATA SHEET       IMM12-60APS-ZCK.pdf         VOLTAGE - SUPPLY       10 V ~ 30 V         TERMINATION STYLE       Connector         SHELDING       Unshielded         SERIES       -         SENSING DISTANCE       2.362" (60mm)         RESPONSE FREQUENCY       1kHz         PACKAGE / CASE       Cylinder, Threaded - M12         OUTPUT TYPE       PNP-NO, 3-Wire         OTHER NAMES       1040070 1882-1316         OPERATING TEMPERATURE       -25°C ~ 75°C         MATERIAL - BODY       Nickel-Plated Brass         MANUFACTURER STANDARD LEAD TIME       3 Weeks         INGRESS PROTECTION       IP67         INDICATOR       LED	MANUFACTURER	SICK	
DATA SHEET  VOLTAGE - SUPPLY  10 V ~ 30 V  TERMINATION STYLE  Connector  SHIELDING  Unshielded  SERIES  - SENSING DISTANCE  SENSING DISTANCE  RESPONSE FREQUENCY  ACKAGE / CASE  OUTPUT TYPE  PNP-NO, 3-Wire  OTHER NAMES  OPERATING TEMPERATURE  ACKAGE / ASS  MANUFACTURER STANDARD LEAD TIME  MIKEL  MATERIAL - BODY  MIKEL Plated Brass  MANUFACTURER STANDARD LEAD TIME  INGRESS PROTECTION  INGEL PLATE AND	DESCRIPTION	SEN PROX MAG PNP 60MM M12	
VOLTAGE - SUPPLY         10 V ~ 30 V           TERMINATION STYLE         Connector           SHIELDING         Unshielded           SERIES         -           SENSING DISTANCE         2.362" (60mm)           RESPONSE FREQUENCY         1kHz           PACKAGE / CASE         Cylinder, Threaded - M12           OUTPUT TYPE         PNP-NO, 3-Wire           OTHER NAMES         1040070 1882-1316           OPERATING TEMPERATURE         -25°C ~ 75°C           MATERIAL - BODY         Nickel-Plated Brass           MANUFACTURES STANDARD LEAD TIME         3 Weeks           INGRESS PROTECTION         IP67           INDICATOR         LED	LEAD FREE STATUS / ROHS STATUS		
TERMINATION STYLE  SHIELDING  Unshielded  SERIES  - SENSING DISTANCE  SENSING DISTANCE  RESPONSE FREQUENCY  PACKAGE / CASE  Cylinder, Threaded - M12  OUTPUT TYPE  OTHER NAMES  THER NAMES  MATERIAL - BODY  MATERIAL - BODY  MATERIAL - BODY  MATERIAL - BODY  MICKEL STANDARD LEAD TIME  MICKEL SPROTECTION  INGRESS PROTECTION  INGRESS PROTECTION  INDICATOR  Connector  Unshielded  Unshielded  A. Connector  Inshielded  Ins	DATA SHEET	MM12-60APS-ZCK.pdf	
SHIELDING Unshielded SERIES - CACCOMMN SENSING DISTANCE 2.362" (60mm) RESPONSE FREQUENCY 1kHz PACKAGE / CASE Cylinder, Threaded - M12 OUTPUT TYPE PNP-NO, 3-Wire OTHER NAMES 1040070 1882-1316 OPERATING TEMPERATURE 2-5°C ~ 75°C MATERIAL - BODY Nickel-Plated Brass MANUFACTURER STANDARD LEAD TIME 3 Weeks INGRESS PROTECTION 1P67 LED	VOLTAGE - SUPPLY	10 V ~ 30 V	
SERIES - 2.362" (60mm)  RESPONSE FREQUENCY 1kHz  PACKAGE / CASE Cylinder, Threaded - M12  OUTPUT TYPE PNP-NO, 3-Wire  OTHER NAMES 0.4082 1.316  OPERATING TEMPERATURE - 2.5°C ~ 75°C  MATERIAL - BODY Nickel-Plated Brass  MANUFACTURER STANDARD LEAD TIME 3 Weeks  INGRESS PROTECTION 1P67  INDICATOR LED TIME LED LED LED LED LED LED LED LED LED LE	TERMINATION STYLE	Connector	
SENSING DISTANCE  RESPONSE FREQUENCY  IkHz  PACKAGE / CASE  Cylinder, Threaded - M12  OUTPUT TYPE  PNP-NO, 3-Wire  OTHER NAMES  OPERATING TEMPERATURE  -25°C ~ 75°C  MATURACTURER STANDARD LEAD TIME  INGRESS PROTECTION  IP67  LED	SHIELDING	Unshielded	
RESPONSE FREQUENCY  PACKAGE / CASE  Cylinder, Threaded - M12  OUTPUT TYPE  PNP-NO, 3-Wire  OTHER NAMES  OPERATING TEMPERATURE  ATTEMPERATURE  MATUFACTURER STANDARD LEAD TIME  INGRESS PROTECTION  INDICATOR  IRBQ:  INDICATOR  IRBQ:  INHI  INH	SERIES	-	
PACKAGE / CASE  OUTPUT TYPE  PNP-NO, 3-Wire  OTHER NAMES  OPERATING TEMPERATURE  ANDICATURER STANDARD LEAD TIME  INGRESS PROTECTION  INDICATOR  Cylinder, Threaded - M12  PNP-NO, 3-Wire  PNP-NO, 3-Wire  PNP-NO, 3-Wire  PNP-NO, 3-Wire  PNP-NO, 3-Wire  PNP-NO, 3-Wire  Newels  1040070  1882-1316  OPERATING TEMPERATURE  -25°C ~ 75°C  Nickel-Plated Brass  3 Weeks  INGRESS PROTECTION  IP67  LED	SENSING DISTANCE	2.362" (60mm)	
OUTPUT TYPE PNP-NO, 3-Wire  OTHER NAMES 1040070 1882-1316  OPERATING TEMPERATURE -25°C ~75°C  MATERIAL - BODY Nickel-Plated Brass  MANUFACTURER STANDARD LEAD TIME 3 Weeks  INGRESS PROTECTION IP67  INDICATOR LED	RESPONSE FREQUENCY	1kHz	
OTHER NAMES  1040070 1882-1316  OPERATING TEMPERATURE  -25°C ~ 75°C  MATERIAL - BODY  MANUFACTURER STANDARD LEAD TIME  3 Weeks  INGRESS PROTECTION  IP67  LED	PACKAGE / CASE	Cylinder, Threaded - M12	
OPERATING TEMPERATURE -25°C ~ 75°C  MATERIAL - BODY Nickel-Plated Brass  MANUFACTURER STANDARD LEAD TIME 3 Weeks  INGRESS PROTECTION IP67  INDICATOR LED	OUTPUT TYPE	PNP-NO, 3-Wire	
MATERIAL - BODY MANUFACTURER STANDARD LEAD TIME 3 Weeks INGRESS PROTECTION INDICATOR LED	OTHER NAMES		
MANUFACTURER STANDARD LEAD TIME 3 Weeks INGRESS PROTECTION IP67 INDICATOR LED	OPERATING TEMPERATURE	-25°C ~ 75°C	
INGRESS PROTECTION IP67 INDICATOR LED	MATERIAL - BODY	Nickel-Plated Brass	
INDICATOR LED	MANUFACTURER STANDARD LEAD TIME	3 Weeks	
	INGRESS PROTECTION	IP67	
DETAILED DESCRIPTION Proximity Sensor 2.362" (60mm) IP67 Cylinder, Threaded - M12	INDICATOR	LED	
	DETAILED DESCRIPTION	Proximity Sensor 2.362" (60mm) IP67 Cylinder, Threaded - M12	

## Related Tags

SICK MM12-60APS-ZCK	MM12-60APS-ZCK Distributor	MM12-60APS-ZCK Supplier
MM12-60APS-ZCK Price	MM12-60APS-ZCK Pictures	MM12-60APS-ZCK Image
MM12-60APS-ZCK PDF Datasheet	MM12-60APS-ZCK Download Datasheet	MM12-60APS-ZCK Datasheet
MM12-60APS-ZCK Stock	Buy MM12-60APS-ZCK	Buy SICK MM12-60APS-ZCK
SICK MM12-60APS-ZCK	SICK Supplier	SICK Distributor
SICK MM12-60APS-ZCK		

#### **Related Products**



#### MM12-60ANS-ZCK Manufacturers: SICK

Description: SEN PROX MAG NPN 60MM M12 In stock: 13 pcs

stock: 13 pcs

SICK Sensor Intelligence.

#### MM12-60ANO-ZUO Manufacturers: SICK

Description: NPN NC M12 MAGNETIC SENS
In stock: Out stock

RFQ



#### MM12-60APS-ZUK

Manufacturers: SICK
Description: PNP NO 2M CBL
In stock: Out stock

RFQ

SICK Sensor Intelligence.

#### MM12-60APO-ZUK

Manufacturers: SICK
Description: PNP NC 2M CBL
In stock: Out stock

RFQ



#### MM120-001164

Manufacturers: Vishay Precision Group
Description: STRAIN GAUGE INSTALLATION TESTER

In stock: 6 pcs

RFQ



## MM12-90APS-ZCO Manufacturers: SICK

Description: SEN PROX MAG PNP 5-90MM M12 In stock: 3 pcs

RFQ

KFQ



# MM12-90ANS-ZU0 Manufacturers: SICK

Description: NPN NO CBL
In stock: Out stock

RFQ



## MM1102FE-R58 Manufacturers: Ohmite

Description: RES 11K OHM 1W 1% AXIAL

In stock: Out stock

RFQ



# MM12-90APS-ZUO Manufacturers: SICK

Description: ADVANCED PNP NO 2M CBL In stock: Out stock

RFQ



#### MM10R0FE-R58 Manufacturers: Ohmite

Description: RES 10 OHM 1W 1% AXIAL In stock: Out stock

RFQ



# MM12-60ANS-ZUK Manufacturers: SICK Description: NPN NO 2M CBL

In stock: Out stock

RFQ

-----



#### Manufacturers: SICK

MM12-60APS-ZUA

Description: PNP NO 3M CBL
In stock: Out stock

RFQ

# E-mail: Info@Ocean-Components.com Address: Room 2102, Connaught Commercial Building, 185 Wan Chai Rd, Wan Chai, Hong Kong

**Copyright © 2020 Reliable Distributor of Electronic Components - Ocean-Components.com** 











