



Image may be representation. See specifications for product details.

TDA7265

Part Number:

Manufacturer/Brand:

Product description

RoHs Status Ship From

Datasheets:

Shipment Way

TDA7265

STMicroelectronics

IC AMP AUDIO PWR 25W MULTIWATT11

TDA7265.pdf

Lead free / RoHS Compliant

Hong Kong DHL/Fedex/TNT/UPS/EMS

REQUEST FOR QUOTATION

PART NUMBER TDA7265 MANUFACTURER STMicroelectronics DESCRIPTION IC AMP AUDIO PWR 25W MULTIWATT11 LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant DATA SHEET VOLTAGE - SUPPLY ±5 V ~ 25 V TYPE Class AB SUPPLIER DEVICE PACKAGE 11-Multiwatt SERIES - PACKAGING Tube PACKAGE / CASE Multiwatt-11 (Vertical, Bent and Staggered Leads) OUTPUT TYPE 2-Channel (Stereo) OTHER NAMES 497-3960-5 OPERATING TEMPERATURE MOUNTING TYPE MOUNTING TYPE MOUNTING TYPE Through Hole MOISTURE SENSITIVITY LEVEL (MSL) MAX OUTPUT POWER X CHANNELS @ LOAD MAX OUTPUT POWER X CHANNELS @ LOAD MANUFACTURER STANDARD LEAD TIME 36 Weeks LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant FEATURES Depop, Mute, Short-Circuit and Thermal Protection, Standby DETAILED DESCRIPTION Amplifier IC 2-Channel (Stereo) Class AB 11-Multiwatt		Specifications of TDA7265	
DESCRIPTION IC AMP AUDIO PWR 25W MULTIWATT11 LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant DATA SHEET DATA SHEET DATA SHEET Class AB SUPLIER DEVICE PACKAGE 11-Multiwatt SERIES - PACKAGING Tube PACKAGE / CASE Multiwatt-11 (Vertical, Bent and Staggered Leads) OUTPUT TYPE 2-Channel (Stereo) OTHER NAMES OPERATING TEMPERATURE 497-3960-5 OPERATING TEMPERATURE MOISTURE SENSITIVITY LEVEL (MSL) MAX OUTPUT POWER X CHANNELS © LOAD MAX OUTPUT POWER X CHANNELS © LOAD MAX OUTPUT POWER X CHANNELS © LOAD MANUFACTURER STATUS / ROHS STATUS Lead free / RoHS Compliant FEATURES Depop, Mute, Short-Circuit and Thermal Protection, Standby Amplifier IC 2-Channel (Stereo) Class AB 11-Multiwatt			
DESCRIPTION IC AMP AUDIO PWR 25W MULTIWATT11 LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant DATA SHEET ▼ TDA7265.pdf VOLTAGE - SUPPLY ±5 V ~ 25 V TYPE Class AB SUPPLIER DEVICE PACKAGE 11-Multiwatt SERIES - PACKAGING Tube PACKAGE / CASE Multiwatt-11 (Vertical, Bent and Staggered Leads) OUTPUT TYPE 2-Channel (Stereo) OTHER NAMES 497-3960-5 OPERATING TEMPERATURE * 20°C ~ 85°C (TA) MOUNTING TYPE MOISTURE SENSITIVITY LEVEL (MSL) MAX OUTPUT POWER X CHANNELS @ LOAD **MANUFACTURER STANDARD LEAD TIME* 36 Weeks LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant FEATURES Depop, Mute, Short-Circuit and Thermal Protection, Standby Amplifier IC 2-Channel (Stereo) Class AB 11-Multiwatt	PART NUMBER	TDA7265	
LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant DATA SHEET ☑ TDA7265.pdf VOLTAGE - SUPPLY ±5 V ~ 25 V TYPE Class AB SUPPLIER DEVICE PACKAGE 11-Multiwatt SERIES - PACKAGING Tube PACKAGE / CASE Multiwatt-11 (Vertical, Bent and Staggered Leads) OUTPUT TYPE 2-Channel (Stereo) OTHER NAMES 497-3960-5 OPERATING TEMPERATURE -20°C ~ 85°C (TA) MOUNTING TYPE Through Hole MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) MAX OUTPUT POWER X CHANNELS @ LOAD 25W x 2 @ 8 Ohm MANUFACTURER STANDARD LEAD TIME 36 Weeks LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant FEATURES Depop, Mute, Short-Circuit and Thermal Protection, Standby DETAILED DESCRIPTION Amplifier IC 2-Channel (Stereo) Class AB 11-Multiwatt	MANUFACTURER	STMicroelectronics	
DATA SHEET VOLTAGE - SUPPLY ±5 V ~ 25 V TYPE Class AB SUPPLIER DEVICE PACKAGE 11-Multiwatt SERIES - PACKAGING Tube PACKAGE / CASE Multiwatt-11 (Vertical, Bent and Staggered Leads) OUTPUT TYPE 2-Channel (Stereo) OTHER NAMES 497-3960-5 OPERATING TEMPERATURE *-20°C ~ 85°C (TA) MOUNTING TYPE MOISTURE SENSITIVITY LEVEL (MSL) MAX OUTPUT POWER X CHANNELS @ LOAD MAX OUTPUT POWER X CHANNELS @ LOAD MAX OUTPUT POWER X CHANNELS @ LOAD MANUFACTURER STANDARD LEAD TIME 16 Weeks LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compiliant FEATURES Depop, Mute, Short-Circuit and Thermal Protection, Standby Amplifier IC 2-Channel (Stereo) Class AB 11-Multiwatt	DESCRIPTION	IC AMP AUDIO PWR 25W MULTIWATT11	
VOLTAGE - SUPPLY TYPE Class AB SUPPLIER DEVICE PACKAGE 11-Multiwatt SERIES - PACKAGING Tube PACKAGE / CASE Multiwatt-11 (Vertical, Bent and Staggered Leads) OUTPUT TYPE 2-Channel (Stereo) OTHER NAMES 497-3960-5 OPERATING TEMPERATURE -20°C ~ 85°C (TA) MOUNTING TYPE Through Hole MOISTURE SENSITIVITY LEVEL (MSL) MAX OUTPUT POWER X CHANNELS @ LOAD 25W x 2 @ 8 Ohm MANUFACTURER STANDARD LEAD TIME 36 Weeks LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant FEATURES Depop, Mute, Short-Circuit and Thermal Protection, Standby DETAILED DESCRIPTION Amplifier IC 2-Channel (Stereo) Class AB 11-Multiwatt	LEAD FREE STATUS / ROHS STATUS	Lead free / RoHS Compliant	
TYPE Class AB SUPPLIER DEVICE PACKAGE 11-Multiwatt SERIES - PACKAGING Tube PACKAGE / CASE Multiwatt-11 (Vertical, Bent and Staggered Leads) OUTPUT TYPE 2-Channel (Stereo) OTHER NAMES 497-3960-5 OPERATING TEMPERATURE -20°C ~ 85°C (TA) MOUNTING TYPE Through Hole MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) MAX OUTPUT POWER X CHANNELS @ LOAD 25W x 2 @ 8 Ohm MANUFACTURER STANDARD LEAD TIME 16AD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant FEATURES Depop, Mute, Short-Circuit and Thermal Protection, Standby DETAILED DESCRIPTION Amplifier IC 2-Channel (Stereo) Class AB 11-Multiwatt	DATA SHEET	TDA7265.pdf	
SUPPLIER DEVICE PACKAGE SERIES - PACKAGING Tube PACKAGE / CASE Multiwatt-11 (Vertical, Bent and Staggered Leads) OUTPUT TYPE 2-Channel (Stereo) OTHER NAMES 497-3960-5 OPERATING TEMPERATURE -20°C ~ 85°C (TA) MOUNTING TYPE Through Hole MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) MAX OUTPUT POWER X CHANNELS @ LOAD 25W x 2 @ 8 Ohm MANUFACTURER STANDARD LEAD TIME 36 Weeks LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant FEATURES Depop, Mute, Short-Circuit and Thermal Protection, Standby DETAILED DESCRIPTION Amplifier IC 2-Channel (Stereo) Class AB 11-Multiwatt	VOLTAGE - SUPPLY	±5 V ~ 25 V	
PACKAGING Tube PACKAGE / CASE Multiwatt-11 (Vertical, Bent and Staggered Leads) OUTPUT TYPE 2-Channel (Stereo) OTHER NAMES 497-3960-5 OPERATING TEMPERATURE -20°C ~ 85°C (TA) MOUNTING TYPE Through Hole MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) MAX OUTPUT POWER X CHANNELS @ LOAD 25W x 2 @ 8 Ohm MANUFACTURER STANDARD LEAD TIME 36 Weeks LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant FEATURES Depop, Mute, Short-Circuit and Thermal Protection, Standby DETAILED DESCRIPTION Amplifier IC 2-Channel (Stereo) Class AB 11-Multiwatt	TYPE	Class AB	
PACKAGE / CASE Multiwatt-11 (Vertical, Bent and Staggered Leads) OUTPUT TYPE 2-Channel (Stereo) OTHER NAMES 497-3960-5 OPERATING TEMPERATURE -20°C ~ 85°C (TA) MOUNTING TYPE Through Hole MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) MAX OUTPUT POWER X CHANNELS @ LOAD 25W x 2 @ 8 Ohm MANUFACTURER STANDARD LEAD TIME 36 Weeks LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant FEATURES Depop, Mute, Short-Circuit and Thermal Protection, Standby DETAILED DESCRIPTION Amplifier IC 2-Channel (Stereo) Class AB 11-Multiwatt	SUPPLIER DEVICE PACKAGE	11-Multiwatt	
PACKAGE / CASE Multiwatt-11 (Vertical, Bent and Staggered Leads) OUTPUT TYPE 2-Channel (Stereo) OTHER NAMES 497-3960-5 OPERATING TEMPERATURE -20°C ~ 85°C (TA) MOUNTING TYPE Through Hole MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) MAX OUTPUT POWER X CHANNELS @ LOAD 25W x 2 @ 8 Ohm MANUFACTURER STANDARD LEAD TIME 36 Weeks LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant FEATURES Depop, Mute, Short-Circuit and Thermal Protection, Standby DETAILED DESCRIPTION Amplifier IC 2-Channel (Stereo) Class AB 11-Multiwatt	SERIES	-	
OUTPUT TYPE 2-Channel (Stereo) OTHER NAMES 497-3960-5 OPERATING TEMPERATURE -20°C ~ 85°C (TA) MOUNTING TYPE Through Hole MOISTURE SENSITIVITY LEVEL (MSL) MAX OUTPUT POWER X CHANNELS @ LOAD MANUFACTURER STANDARD LEAD TIME 16 Weeks LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant FEATURES Depop, Mute, Short-Circuit and Thermal Protection, Standby DETAILED DESCRIPTION Amplifier IC 2-Channel (Stereo) Class AB 11-Multiwatt	PACKAGING	Tube	
OTHER NAMES 497-3960-5 OPERATING TEMPERATURE -20°C ~ 85°C (TA) MOUNTING TYPE Through Hole MOISTURE SENSITIVITY LEVEL (MSL) MAX OUTPUT POWER X CHANNELS @ LOAD MANUFACTURER STANDARD LEAD TIME 36 Weeks LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant FEATURES Depop, Mute, Short-Circuit and Thermal Protection, Standby DETAILED DESCRIPTION Amplifier IC 2-Channel (Stereo) Class AB 11-Multiwatt	PACKAGE / CASE	Multiwatt-11 (Vertical, Bent and Staggered Leads)	
OPERATING TEMPERATURE -20°C ~ 85°C (TA) MOUNTING TYPE Through Hole MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) MAX OUTPUT POWER X CHANNELS @ LOAD 25W x 2 @ 8 Ohm MANUFACTURER STANDARD LEAD TIME 36 Weeks LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant FEATURES Depop, Mute, Short-Circuit and Thermal Protection, Standby DETAILED DESCRIPTION Amplifier IC 2-Channel (Stereo) Class AB 11-Multiwatt	OUTPUT TYPE	2-Channel (Stereo)	
MOUNTING TYPE Through Hole MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) MAX OUTPUT POWER X CHANNELS @ LOAD 25W x 2 @ 8 Ohm MANUFACTURER STANDARD LEAD TIME 36 Weeks LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant FEATURES Depop, Mute, Short-Circuit and Thermal Protection, Standby DETAILED DESCRIPTION Amplifier IC 2-Channel (Stereo) Class AB 11-Multiwatt	OTHER NAMES	497-3960-5	
MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) MAX OUTPUT POWER X CHANNELS @ LOAD 25W x 2 @ 8 Ohm MANUFACTURER STANDARD LEAD TIME 36 Weeks LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant FEATURES Depop, Mute, Short-Circuit and Thermal Protection, Standby DETAILED DESCRIPTION Amplifier IC 2-Channel (Stereo) Class AB 11-Multiwatt	OPERATING TEMPERATURE	-20°C ~ 85°C (TA)	
MAX OUTPUT POWER X CHANNELS @ LOAD 25W x 2 @ 8 Ohm MANUFACTURER STANDARD LEAD TIME 36 Weeks Lead free / RoHS Compliant FEATURES Depop, Mute, Short-Circuit and Thermal Protection, Standby DETAILED DESCRIPTION Amplifier IC 2-Channel (Stereo) Class AB 11-Multiwatt	MOUNTING TYPE	Through Hole	
MANUFACTURER STANDARD LEAD TIME 36 Weeks LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant FEATURES Depop, Mute, Short-Circuit and Thermal Protection, Standby DETAILED DESCRIPTION Amplifier IC 2-Channel (Stereo) Class AB 11-Multiwatt	MOISTURE SENSITIVITY LEVEL (MSL)	1 (Unlimited)	
LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant Depop, Mute, Short-Circuit and Thermal Protection, Standby DETAILED DESCRIPTION Amplifier IC 2-Channel (Stereo) Class AB 11-Multiwatt	MAX OUTPUT POWER X CHANNELS @ LOAD	25W x 2 @ 8 Ohm	
Depop, Mute, Short-Circuit and Thermal Protection, Standby DETAILED DESCRIPTION Amplifier IC 2-Channel (Stereo) Class AB 11-Multiwatt	MANUFACTURER STANDARD LEAD TIME	36 Weeks	
DETAILED DESCRIPTION Amplifier IC 2-Channel (Stereo) Class AB 11-Multiwatt	LEAD FREE STATUS / ROHS STATUS	Lead free / RoHS Compliant	
	FEATURES	Depop, Mute, Short-Circuit and Thermal Protection, Standby	
BASE PART NUMBER TDA7265	DETAILED DESCRIPTION	Amplifier IC 2-Channel (Stereo) Class AB 11-Multiwatt	
	BASE PART NUMBER	TDA7265	

Related Tags

TDA7265 PriceTDA7265 PicturesTDA7265 ImageTDA7265 PDF DatasheetTDA7265 Download DatasheetTDA7265 DatasheetTDA7265 StockBuy TDA7265Buy STMicroelectronics TDA7265STMicroelectronics TDA7265STMicroelectronics SupplierSTMicroelectronics Distributor	STMicroelectronics TDA7265	TDA7265 Distributor	TDA7265 Supplier
TDA7265 Stock Buy TDA7265 Buy STMicroelectronics TDA7265	TDA7265 Price	TDA7265 Pictures	TDA7265 Image
	TDA7265 PDF Datasheet	TDA7265 Download Datasheet	TDA7265 Datasheet
STMicroelectronics TDA7265 STMicroelectronics Supplier STMicroelectronics Distributor	TDA7265 Stock	Buy TDA7265	Buy STMicroelectronics TDA7265
konnection of the control of the con	STMicroelectronics TDA7265	STMicroelectronics Supplier	STMicroelectronics Distributor

Related Products



STMicroelectronics TDA7265

TDA7266

Manufacturers: STMicroelectronics Description: IC AMP AUDIO 7W STER MULTIWATT15

In stock: 169 pcs

RFQ



TDA7266D13TR

Manufacturers: STMicroelectronics

Description: IC AMP BRIDGE DUAL 5W POWERSO20 In stock: 600 pcs

RFQ



TDA7263M

Manufacturers: STMicroelectronics

Description: IC AMP AUDIO PWR 12W MULTIWATT11 In stock: Out stock

RFQ



TDA7265A

Manufacturers: STMicroelectronics

Description: IC AMP AUDIO AB DUAL MULTIWATT11 In stock: Out stock

RFQ



TDA7264

Manufacturers: STMicroelectronics Description: IC AMP AUDIO PWR 25W MULTIWATT8

In stock: 569 pcs

RFQ



TDA7266L

Manufacturers: STMicroelectronics

Description: IC AMP AUDIO 7W MONO AB 10SIP In stock: Out stock

RFQ



TDA7263

Manufacturers: STMicroelectronics Description: IC AMP AUDIO PWR 12W CLIPWATT11

In stock: 242 pcs

RFQ



TDA7261

Manufacturers: STMicroelectronics Description: IC AMP AUDIO PWR 32W MULTIWATT8

In stock: Out stock

RFQ



TDA7265B Manufacturers: STMicroelectronics

Description: IC AMP AUDIO AB DUAL MULTIWATT11 In stock: 294 pcs



TDA7262 Manufacturers: STMicroelectronics

Description: IC AMP AUDIO PWR HIFI MILTIWAT11

In stock: Out stock



TDA7266D Manufacturers: STMicroelectronics

Description: IC AMP AUDIO 5W STER POWERSO20 In stock: Out stock

RFQ



TDA7264A

Manufacturers: STMicroelectronics

In stock: Out stock **RFQ**

Description: IC AMP AUDIO PWR 25W MULTIWATT11



Copyright © 2020 Reliable Distributor of Electronic Components - Ocean-Components.com

E-mail: Info@Ocean-Components.com











