C&K





C&K

C&K

SD02H1SBR

Part Number:

Manufacturer/Brand:

Product description Datasheets:

RoHs Status Ship From Shipment Way SD02H1SBR

C&K

SWITCH SLIDE DIP SPST 100MA 25V

SD02H1SBR.pdf

Lead free / RoHS Compliant Hong Kong

DHL/Fedex/TNT/UPS/EMS

REQUEST FOR QUOTATION

Image may be representation. See specifications for product details.

PART NUMBER SOCIALISER MANUFACTURER CAK DESCRIPTION SWITCH SLIDE DIP SPST 100MA 25V LEAD FREE STATUS / ROHS STATUS SUBJECT / Ves VOLTAGE RATING 25 /VC TERNIMATION STYLE Guil Wing SERIES 50 PITCH 0.100° (2.54mm), Full PACKAGING Tape & Red (TR) OTHER NAMES SD02H1SSR-ND OPERATING TEMPERATURE -40°C- 85°C MOUNTING TYPE Surface Mount MOUSTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) MECHABICAL LIFE 2,000 Cycles MANUFACTURER STANDARD LEAD TIME 13 Weeks LENGTH LEAD FREE STATUS / ROHS STATUS LEAD FREE STATUS Tape Seal ELECTRICAL LIFE 2,000 Cycles DID switch SPST 2 Position Surface Mount Slide (Standard) Actuator 100mA 25VDC CURRENT RATING CONTACT MATERIAL Benyllium Copper CONTACT MATERIAL RESULTATOR LEVEL ACTUATOR LEVEL ACTUATOR LEVEL ACTUATOR LEVEL ACTUATOR LEVEL RESULTATOR LEVEL RESULTATOR LEVEL RESULTATOR LEVEL		
MANUFACTURER CAK DESCRIPTION SWITCH SLIDE DIP SPST 100MA 25V Lead FREE STATUS / ROHS STATUS Lead free / RoHS Compliant DATA SHEET SOD2HISBR.pdf WASHABLE Yes VOLTAGE RATING ZSVDC TEMINATION STYLE Gull Wing SERIES SD PITCH QL100" (2.54mm), Full PACKAGING Tape & Red (TR) OTHER NAMES CONSTILTORS CONSTILTORS CONSTILTORS COPERATING TEMPERATURE -40°C ~ 85°C NUMBER OF POSITIONS 2 MOUNTING TYPE SURface Mount MOISTING SENSITIVITY LEVEL (MSL) I (Unlimited) MECHANICAL LIFE 2,000 Cycles MANUFACTURER STANDARD LEAD TIME LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant HEIGHT ABOVE BOARD 0.180" (4.57mm) FEATURES Tape Seal ELECTRICAL LIFE 2,000 Cycles MOLECTRICAL LIFE 2,000 Cycles MOLECTR		Specifications of SD02H1SBR
MANUFACTURER CAK DESCRIPTION SWITCH SLIDE DIP SPST 100MA 25V Lead FREE STATUS / ROHS STATUS Lead free / RoHS Compliant DATA SHEET SOD2HISBR.pdf WASHABLE Yes VOLTAGE RATING ZSVDC TEMINATION STYLE Gull Wing SERIES SD PITCH QL100" (2.54mm), Full PACKAGING Tape & Red (TR) OTHER NAMES CONSTILTORS CONSTILTORS CONSTILTORS COPERATING TEMPERATURE -40°C ~ 85°C NUMBER OF POSITIONS 2 MOUNTING TYPE SURface Mount MOISTING SENSITIVITY LEVEL (MSL) I (Unlimited) MECHANICAL LIFE 2,000 Cycles MANUFACTURER STANDARD LEAD TIME LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant HEIGHT ABOVE BOARD 0.180" (4.57mm) FEATURES Tape Seal ELECTRICAL LIFE 2,000 Cycles MOLECTRICAL LIFE 2,000 Cycles MOLECTR	·	
DESCRIPTION SWITCH SLIDE DIP SPST 100MA 25V LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant DATA SHEET □ SD02HLSBR.pdf WASHABLE Yes VOLTACE RATING 25VDC TERMINATION STYLE Gull Wing SERIES SD PITCH 0.10° (2.54mm), Full PACKAGING Tape & Red (TR) OTHER NAMES CKM111.70TR SD02HLSBR-ND OPERATING TEMPERATURE -40° ~ 85°C NUMBER OF POSITIONS 2 MOUNTING TYPE Surface Mount MOISTING SENSITIVITY LEVEL (MSL) 1 (Unlimited) MECHANICAL LIFE 2,000 Cycles MANUFACTURER STANDARD LEAD TIME 13 Weeks LEAGTH 0.258° (6.55mm) LEAS FREE STATUS / ROHS STATUS Lead free / ROHS Compliant HEICHT ABOVE BOARD 0.180° (4.57mm) FEATURES Tape Seal ELECTRICAL LIFE 2,000 Cycles DETAILED DESCRIPTION Dip Switch SPST 2 Position Surface Mount Slide (Standard) Actuator 100mA 25VDC CURRENT RATING 100mA CONTACT FINISH	PART NUMBER	SD02H1SBR
LEAD FREE STATUS / ROHS STATUS LEAD free / ROHS Compliant WASHABLE WASHABLE Ves VOLTAGE RATING ZSVDC TERMINATION STYLE Guil Wing SERIES SD PITCH 0.100" (2.54mm), Full PACKAGING Tape & Reel (TR) OTHER NAMES CONSHITSBR-ND OPERATING TYPE SUSTACE Mount MOUNTING TYPE MOUNTING TYPE MANUFACTURER STANDARD LEAD TIME 13 Weeks LENGTH LEAD FREE STATUS / ROHS STATUS LEad free / ROHS Compliant HEIGHT ABOVE BOARD OTAGE NAMES Tape Seal LECTRICAL LIFE 2,000 Cycles MANUFACTURER STANDARD LEAD TIME 13 Weeks LENGTH LEAD FREE STATUS / ROHS STATUS LEAD free PROHED LEAD FREE STATUS / ROHS STATUS LEAD FREE STATUS / ROH	MANUFACTURER	C&K
DATA SHIEET WASHABLE Yes VOLTAGE RATING 25VDC TERMINATION STYLE Gull Wing SERIES SD PITCH 0.100° (2.54mm), Full PACKAGING Tape & Reel (TR) CHNILITOR'S SODHISBER-ND OPERATING TEMPERATURE -40°C ~ 85°C NUMBER OF POSITIONS 2 MOUNTING TYPE Surface Mount MOISTURE SENSITIVITY LEVEL (MSL) MECHARICAL LIFE 2,000 Cycles MANUFACTURER STANDARD LEAD TIME 13 Weeks LENGTH 0.258° (6.55mm) LEAD FREE STATUS / ROHS STATUS LEAD FREE STATUS / ROHS STATUS LECHICAL LIFE 2,000 Cycles DETAILED DESCRIPTION DIP SWIRCH SPST 2 Position Surface Mount Silde (Standard) Actuator 100mA 25VDC CURRENT RATING CONTACT MATERIAL Beryllium Copper CONTACT MATERIAL BOLY MATERIAL BOLY MATERIAL ACIUATOR TYPE SIIde (Standard) SIIde (Standard) SIIde (Standard) ACIUATOR TYPE SIIde (Standard) SIIde (Standard) ACIUATOR TYPE	DESCRIPTION	SWITCH SLIDE DIP SPST 100MA 25V
WASHABLE VOLTAGE RATING 25VDC TERMINATION STYLE Gull Wing SERIES SD PITCH 0.100" (2.54mm), Full PACKAGING Tape & Reel (TR) CENTILITORE SDOPLISSER-ND OPERATING TEMPERATURE 40°C ~ 85°C NUMBER OF POSITIONS 2 MOUNTING TYPE SURface Mount MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) MECHANICAL LIFE 2,000 Cycles MANUFACTURER STANDARD LEAD TIME 13 Weeks LENGTH 0.258" (6.55mm) LEAD FREE STATUS / ROHS STATUS LEACH HEIGHT ABOVE BOARD 0.180" (4.57mm) FEATURES Tape Seal ELECTRICAL LIFE 2,000 Cycles DETAILED DESCRIPTION DIS SWItch SPST 2 Position Surface Mount Slide (Standard) Actuator 100mA 25VDC CURRENT RATING 100mA CONTACT MATERIAL Beryllium Copper CONTACT FINISH GOLd CIRCUIT SPST BODY MATERIAL Polyphthalamide (PPA) ACTUATOR TYPE SIde (Standard) SIDE SWITCH STANDARD SIDE SIDE SIDE SIDE SIDE SIDE SIDE SID	LEAD FREE STATUS / ROHS STATUS	Lead free / RoHS Compliant
VOLTAGE RATING TERMINATION STYLE Gull Wing SERIES SD PITCH 0.100" (2.54mm), Full PACKAGING Tape & Reel (TR) OTHER NAMES CKN111/20TR SD02H158R-ND OPERATING TEMPERATURE 40°C ~ 85°C MOUNTING TYPE MOUNTING TYPE MOUNTING TYPE MANUFACTURER STANDARD LEAD TIME LENGTH 0.258" (6.55mm) LEAD FREE STATUS / ROHS STATUS LEAD FREE STATUS / ROHS STATUS LEEGHT ABOVE BOARD 0.180" (4.57mm) FEATURES ELECTRICAL LIFE 2,000 Cycles DETAILED DESCRIPTION DIP Switch SPST 2 Position Surface Mount Slide (Standard) Actuator 100mA 25VDC CURRENT RATING CONTACT MATERIAL Benyllium Copper CONTACT MATERIAL BOLD WATERIAL ACIUATOR TYPE Slide (Standard) ELEC (STANDARD ELEC (TRUE) ELEC (STANDARD ELEC (TRUE) ELEC (TRUE)	DATA SHEET	SD02H1SBR.pdf
TERMINATION STYLE Gull Wing SERIES SD PITCH 0.100" (2.54mm), Full PACKAGING Tape & Reel (TR) OTHER NAMES CKN11170TR SD02H1SBEND OPERATING TEMPERATURE -40°C ~ 85°C MUNBER OF POSITIONS 2 MOUNTING TYPE Surface Mount MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) MECHANICAL LIFE 2,000 Cycles MANUFACTURER STANDARD LEAD TIME 13 Weeks LENGTH 0.258" (6.55mm) LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant HEIGHT ABOVE BOARD 0.180" (4.57mm) FEATURES Tape Seal ELECTRICAL LIFE 2,000 Cycles DETAILED DESCRIPTION Dip Switch SPST 2 Position Surface Mount Slide (Standard) Actuator 100mA 25VDC CURRENT RATING 100mA CONTACT MATERIAL Beryllium Copper CONTACT FINISH Gold CRICUIT SPST BODY MATERIAL Polyphthalamide (PPA) ACIUATOR TYPE Slide (Standard)	WASHABLE	Yes
SERIES PITCH 0.100" (2.54mm), Full PACKAGING Tape & Reel (TR) OTHER NAMES CKN1117OTR SD02H15BR-ND OPERATING TEMPERATURE 40°C ~ B5°C NUMBER OF POSITIONS 2 MOUNTING TYPE SURface Mount MOISTURE SENSITIVITY LEVEL (MSL) MICHANICAL LIFE 2,000 Cycles MANUFACTURER STANDARD LEAD TIME LEAD FREE STATUS / ROHS STATUS LEAD FREE STATUS / ROHS STATUS LEGHT ABOVE BOARD 1.80°C (6.55mm) FEATURES ELECTRICAL LIFE 2,000 Cycles ELECTRICAL LIFE 3,000 Cycles ELECTRICAL LIFE 4,000 Cycles ELECTRICAL LIFE 5,000 Cycles ELECTRICAL LIFE 6,000 Cycles	VOLTAGE RATING	25VDC
PITCH 0.100" (2.54mm), Full PACKAGING Tape & Reel (TR) OTHER NAMES CKN11170TR SD02H15BR-ND OPERATING TEMPERATURE 40°C ~ 85°C NUMBER OF POSITIONS 2 MOUNTING TYPE Surface Mount MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) MECHANICAL LIFE 2,000 Cycles MANUFACTURER STANDARD LEAD TIME 13 Weeks LENGTH 0.258" (6.55mm) LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant HEIGHT ABOVE BOARD 0.180" (4.57mm) FEATURES Tape Seal ELECTRICAL LIFE 2,000 Cycles DETAILED DESCRIPTION Dip Switch SPST 2 Position Surface Mount Slide (Standard) Actuator 100mA 25VDC CURRENT RATING 100mA CONTACT MATERIAL Beryllium Copper CONTACT FINISH Gold CIRCUIT SPST BODY MATERIAL Polyphthalamide (PPA) ACTUATOR TYPE Slide (Standard)	TERMINATION STYLE	Gull Wing
PACKAGING Tape & Reel (TR) OTHER NAMES CKN1117OTR SD02H1SBR-ND OPERATING TEMPERATURE -40°C ~ 85°C NUMBER OF POSITIONS 2 MOUNTING TYPE SUFFACE MOUNT MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) MECHANICAL LIFE 2,000 Cycles MANUFACTURER STANDARD LEAD TIME 13 Weeks LENGTH 0,255° (6.55mm) LEAD FREE STATUS / ROHS STATUS LEAD TIME 246 (For HS Compliant 146) HEIGHT ABOVE BOARD 1,160° (4.57mm) FEATURES 1,200 Cycles ELECTRICAL LIFE 2,000 Cycles ELECTRICAL LIFE 2,000 Cycles ELECTRICAL LIFE 3,000 Cycles ELECTRICAL LIFE 5,000 Cycles ELECTRICAL MATERIAL 5,000 Cycles ELECTRICAL MATERIAL 5,000 Cycles ELECTRICAL MATERIAL 5,000 Cycles CONTACT MATERIAL 5,000 Cycles CONTACT FINISH 5,000 Cycles ELECTRICAL MATERIAL 5	SERIES	SD
OTHER NAMES CKN11170TR SD02HISBR-ND OPERATING TEMPERATURE -40°C ~ 85°C NUMBER OF POSITIONS 2 MOUNTING TYPE Surface Mount MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) MECHANICAL LIFE 2,000 Cycles MANUFACTURER STANDARD LEAD TIME 13 Weeks LENGTH 0.258° (6.55mm) LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant HEIGHT ABOVE BOARD 0.180° (4.57mm) FEATURES Tape Seal ELECTRICAL LIFE 2,000 Cycles CURRENT RATING 100mA CURRENT RATING 100mA CONTACT MATERIAL Beryllium Copper CONTACT FINISH Gold CURUIT SPST BODY MATERIAL Polyphthalamide (PPA) KOUATORT TYPE Slide (Standard)	PITCH	0.100" (2.54mm), Full
OPERATING TEMPERATURE OPERATING TEMPERATURE A40°C ~ 85°C NUMBER OF POSITIONS 2 MOUNTING TYPE MOISTURE SENSITIVITY LEVEL (MSL) MECHANICAL LIFE ANAUFACTURER STANDARD LEAD TIME 13 Weeks LENGTH 0.258° (6.55mm) LEAD FREE STATUS / ROHS STATUS LEAD FREE STATUS / ROHS STATUS LEGHT ABOVE BOARD 130° (4.57mm) FEATURES LECTRICAL LIFE 2,000 Cycles LECTRICAL LIFE 2,000 Cycles LECTRICAL LIFE 3,000 Cycles LECTRICAL LIFE 6,000 Cycles LECTRICAL LIFE 100mA CONTACT MATERIAL 6 Gold CONTACT FINISH CIRCUIT 5PST BODY MATERIAL FOLD SHIRLS SIIde (Standard) SIIDE SIID	PACKAGING	Tape & Reel (TR)
NUMBER OF POSITIONS2MOUNTING TYPESurface MountMOISTURE SENSITIVITY LEVEL (MSL)1 (Unlimited)MECHANICAL LIFE2,000 CyclesMANUFACTURER STANDARD LEAD TIME13 WeeksLENGTH0.258" (6.55mm)LEAD FREE STATUS / ROHS STATUSLead free / RoHS CompliantHEIGHT ABOVE BOARD0.180" (4.57mm)FEATURESTape SealELECTRICAL LIFE2,000 CyclesDETAILED DESCRIPTIONDip Switch SPST 2 Position Surface Mount Slide (Standard) Actuator 100mA 25VDCCURRENT RATING100mACONTACT MATERIALGoldCIRCUITSPSTBODY MATERIALSPSTBODY MATERIALSID (Standard)ACTUATOR TYPESlide (Standard)	OTHER NAMES	
MOUNTING TYPE SENSITIVITY LEVEL (MSL) 1 (Unlimited) MCHANICAL LIFE 2,000 Cycles MANUFACTURER STANDARD LEAD TIME 13 Weeks LENGTH 0.258" (6.55mm) LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant HEIGHT ABOVE BOARD 1.80" (4.57mm) FEATURES 1.000 Cycles ELECTRICAL LIFE 2,000 Cycles ELECTRICAL LIFE 2,000 Cycles DETAILED DESCRIPTION DIPSWITCH SPST 2 Position Surface Mount Slide (Standard) Actuator 100mA 25VDC CURRENT RATING 1.00mA CONTACT MATERIAL 6.001 CONTACT FINISH 6.001 CIRCUIT 5.PST BODY MATERIAL 7.PSE 5.DILG (Standard) Actual Cycles BODY MATERIAL 5.DILG (STANDARD CYCLES BODY MATERIAL 5.DILG (STANDAR	OPERATING TEMPERATURE	-40°C ~ 85°C
MOISTURE SENSITIVITY LEVEL (MSL) MECHANICAL LIFE 2,000 Cycles MANUFACTURER STANDARD LEAD TIME 13 Weeks LENGTH 12 LEAD FREE STATUS / ROHS STATUS LEAD FREE STATUS / ROHS STATUS / ROHS STATUS / ROHS STATUS / ROHS STATU	NUMBER OF POSITIONS	2
MECHANICAL LIFE 2,000 Cycles MANUFACTURER STANDARD LEAD TIME 13 Weeks LENGTH 0.258" (6.55mm) LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant HEIGHT ABOVE BOARD 0.180" (4.57mm) FEATURES 7ape Seal ELECTRICAL LIFE 2,000 Cycles DETAILED DESCRIPTION DIP SWitch SPST 2 Position Surface Mount Slide (Standard) Actuator 100mA 25VDC CURRENT RATING 100mA CONTACT MATERIAL Seryllium Copper CONTACT FINISH Gold CIRCUIT SPST BODY MATERIAL Slide (Standard) Actuator Seryllium Copper BODY MATERIAL SING Sold CIRCUIT SPST BODY MATERIAL Slide (Standard) Sold Sold CIRCUIT SPST BODY MATERIAL Sold Sold Sold Sold Sold Sold Sold Sold	MOUNTING TYPE	Surface Mount
MANUFACTURER STANDARD LEAD TIME 13 Weeks LENGTH 0.258" (6.55mm) LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant HEIGHT ABOVE BOARD 0.180" (4.57mm) FEATURES TAPES 1.2000 Cycles ELECTRICAL LIFE 2.000 Cycles DETAILED DESCRIPTION DIP Switch SPST 2 Position Surface Mount Slide (Standard) Actuator 100mA 25VDC CURRENT RATING 100mA CONTACT MATERIAL Beryllium Copper CONTACT FINISH Gold CIRCUIT SPST BODY MATERIAL Polyphthalamide (PPA) ACTUATOR TYPE SIGNED	MOISTURE SENSITIVITY LEVEL (MSL)	1 (Unlimited)
LENGTH 0.258" (6.55mm) LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant HEIGHT ABOVE BOARD 0.180" (4.57mm) FEATURES TATUS TYPE 0.2000 Cycles 1 ape Seal 2,000 Cycles 1 bip Switch SPST 2 Position Surface Mount Slide (Standard) Actuator 100mA 25VDC 1 bip Switch SPST 2 Position Surface Mount Slide (Standard) Actuator 100mA 25VDC 1 contact material Beryllium Copper 2 contact finish Gold 2 contact finish Polyphthalamide (PPA) 3 contact finish Surface Mount Slide (Standard) Actuator 100mA 25VDC 3 contact finish Surface Mount Slide (Standard) Actuator 100mA 25VDC 4 contact finish Surface Mount Slide (Standard) Actuator 100mA 25VDC 5 contact finish Surface Mount Slide (Standard) Actuator 100mA 25VDC 5 contact finish Surface Mount Slide (Standard) Actuator 100mA 25VDC 5 contact finish Surface Mount Slide (Standard) Actuator 100mA 25VDC 5 contact finish Surface Mount Slide (Standard) Actuator 100mA 25VDC 5 contact finish Surface Mount Slide (Standard) Actuator 100mA 25VDC 5 contact finish Surface Mount Slide (Standard) Actuator 100mA 25VDC 5 contact finish Surface Mount Slide (Standard) Actuator 100mA 25VDC 5 contact finish Surface Mount Slide (Standard) Actuator 100mA 25VDC 5 contact finish Surface Mount Slide (Standard) Actuator 100mA 25VDC 5 contact finish Surface Mount Slide (Standard) Actuator 100mA 25VDC 5 contact finish Surface Mount Slide (Standard) Actuator 100mA 25VDC 5 contact finish Surface Mount Slide (Standard) Actuator 100mA 25VDC 5 contact finish Surface Mount Slide (Standard) Actuator 100mA 25VDC 5 contact finish Surface Mount Slide (Standard) Actuator 100mA 25VDC 5 contact finish Surface Mount Slide (Standard) Actuator 100mA 25VDC 5 contact finish Surface Mount Slide (Standard) Actuator 100mA 25VDC 5 contact finish Surface Mount Slide (Standard) Actuator 100mA 25VDC 5 contact finish Surface Mount Slide (Standard) Actuator 100mA 25VDC 5 contact finish Surface Mount Slide (Standard) Actuator 100mA 25VDC 5 contact finish Surface Mount Slide (Standard) Actuator 100mA	MECHANICAL LIFE	2,000 Cycles
LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant HEIGHT ABOVE BOARD O.180" (4.57mm) Tape Seal ELECTRICAL LIFE 2,000 Cycles DETAILED DESCRIPTION Dip Switch SPST 2 Position Surface Mount Slide (Standard) Actuator 100mA 25VDC CURRENT RATING CONTACT MATERIAL Beryllium Copper CONTACT FINISH CONTACT FINISH CIRCUIT SPST BODY MATERIAL Polyphthalamide (PPA) Slide (Standard) Slide (Standard) Slide (Standard) Slide (Standard) Slide (Standard)	MANUFACTURER STANDARD LEAD TIME	13 Weeks
HEIGHT ABOVE BOARD FEATURES Tape Seal 2,000 Cycles DETAILED DESCRIPTION Dip Switch SPST 2 Position Surface Mount Slide (Standard) Actuator 100mA 25VDC CURRENT RATING 100mA CONTACT MATERIAL CONTACT FINISH Gold CIRCUIT BODY MATERIAL Polyphthalamide (PPA) Slide (Standard) Slide (Standard) Slide (Standard) Slide (Standard) ACTUATOR TYPE	LENGTH	0.258" (6.55mm)
FEATURES FEATURES Tape Seal LECTRICAL LIFE 2,000 Cycles DETAILED DESCRIPTION Dip Switch SPST 2 Position Surface Mount Slide (Standard) Actuator 100mA 25VDC CURRENT RATING CONTACT MATERIAL Beryllium Copper CONTACT FINISH CIRCUIT SPST BODY MATERIAL Polyphthalamide (PPA) Slide (Standard) Slide (Standard)	LEAD FREE STATUS / ROHS STATUS	Lead free / RoHS Compliant
ELECTRICAL LIFE 2,000 Cycles DETAILED DESCRIPTION Dip Switch SPST 2 Position Surface Mount Slide (Standard) Actuator 100mA 25VDC CURRENT RATING 100mA CONTACT MATERIAL Beryllium Copper CONTACT FINISH CONTACT FINISH SPST BODY MATERIAL Polyphthalamide (PPA) Slide (Standard) Slide (Standard)	HEIGHT ABOVE BOARD	0.180" (4.57mm)
DETAILED DESCRIPTION Dip Switch SPST 2 Position Surface Mount Slide (Standard) Actuator 100mA 25VDC CURRENT RATING 100mA CONTACT MATERIAL Beryllium Copper CONTACT FINISH CIRCUIT SPST BODY MATERIAL Polyphthalamide (PPA) Slide (Standard)	FEATURES	Tape Seal
CURRENT RATING 100mA CONTACT MATERIAL Beryllium Copper CONTACT FINISH Gold CIRCUIT SPST BODY MATERIAL Polyphthalamide (PPA) ACTUATOR TYPE Slide (Standard)	ELECTRICAL LIFE	2,000 Cycles
CONTACT MATERIAL Beryllium Copper CONTACT FINISH Gold CIRCUIT SPST BODY MATERIAL Polyphthalamide (PPA) ACTUATOR TYPE Slide (Standard)	DETAILED DESCRIPTION	Dip Switch SPST 2 Position Surface Mount Slide (Standard) Actuator 100mA 25VDC
CONTACT FINISH CIRCUIT BODY MATERIAL ACTUATOR TYPE Gold Gold SPST Polyphthalamide (PPA) Slide (Standard)	CURRENT RATING	100mA
CIRCUIT SPST BODY MATERIAL Polyphthalamide (PPA) ACTUATOR TYPE Slide (Standard)	CONTACT MATERIAL	Beryllium Copper
BODY MATERIAL Polyphthalamide (PPA) ACTUATOR TYPE Slide (Standard)	CONTACT FINISH	Gold
ACTUATOR TYPE Slide (Standard)	CIRCUIT	SPST
	BODY MATERIAL	Polyphthalamide (PPA)
ACTUATOR LEVEL Raised	ACTUATOR TYPE	Slide (Standard)
	ACTUATOR LEVEL	Raised

Related Tags

C&K SD02H1SBR	SD02H1SBR Distributor	SD02H1SBR Supplier
SD02H1SBR Price	SD02H1SBR Pictures	SD02H1SBR Image
SD02H1SBR PDF Datasheet	SD02H1SBR Download Datasheet	SD02H1SBR Datasheet
SD02H1SBR Stock	Buy SD02H1SBR	Buy C&K SD02H1SBR
C&K SD02H1SBR	C&K Supplier	C&K Distributor
C&K SD02H1SBR	C&K Components SD02H1SBR	

Related Products



SD02H0SBDR Manufacturers: C&K

Description: SWITCH SLIDE DIP SPST 100MA 25V In stock: 70461 pcs

RFQ



SD02S0503A

Manufacturers: Delta Electronics Description: DC DC CONVERTER 3.3V 2W

In stock: 10284 pcs **RFQ**



SD02H0SBR

Manufacturers: C&K

Description: SWITCH SLIDE DIP SPST 100MA 25V In stock: 52214 pcs

RFQ



SD02S0515A Manufacturers: Delta Electronics

Description: DC DC CONVERTER 15V 2W In stock: 10073 pcs

RFQ



SD02S0512A Manufacturers: Delta Electronics

Description: DC DC CONVERTER 12V 2W In stock: 10205 pcs

RFQ



SD02S0505A

Manufacturers: Delta Electronics Description: DC DC CONVERTER 5V 2W

In stock: 9569 pcs **RFQ**



SD02H0SB Manufacturers: C&K

Description: SWITCH SLIDE DIP SPST 100MA 25V

In stock: 80963 pcs

RFQ

SD02H0SK Manufacturers: C&K

In stock: 5313 pcs **RFQ**

Description: SWITCH SLIDE DIP SPST 100MA 25V



Manufacturers: C&K

SD02H1B

Description: SWITCH SLIDE DIP SPST 100MA 25V In stock: 98546 pcs

RFQ



SD02H1SB Manufacturers: C&K

Description: SWITCH SLIDE DIP SPST 100MA 25V In stock: 80760 pcs

RFQ



SD02H1SK Manufacturers: C&K

Description: SWITCH SLIDE DIP SPST 100MA 25V In stock: 5524 pcs

RFQ

Copyright © 2020 Reliable Distributor of Electronic Components - Ocean-Components.com



Description: DC DC CONVERTER 3.3V 2W

SD02S1203A Manufacturers: Delta Electronics

In stock: 9290 pcs **RFQ**













