

**😑** 🕝 E-Switch

**200MSP1T2B2M6QE** 

Part Number: Manufacturer/Brand:

Product description Datasheets:

RoHs Status Ship From Shipment Way 200MSP1T2B2M6QE

E-Switch

1.200MSP1T2B2M6QE.pdf 2.200MSP1T2B2M6QE.pdf

SWITCH TOGGLE SPDT 3A 120V

Lead free / RoHS Compliant Hong Kong

DHL/Fedex/TNT/UPS/EMS

**REQUEST FOR QUOTATION** 

Image may be representation. See specifications for product details.

PART NUMBER  AMANUFACTURER  E-Switch  ESCRIPTION  SWITCH TOGGLE SPDT 3A 120V  LEAD FREE STATUS / ROHS STATUS  POP 1  SWITCH FUNCTION  SWITCH FUNCTION  SWITCH FUNCTION  SERIES  200  PANEL CUTOUT DIMENSIONS  FACKAGING  BUIK  OPERATING TEMPERATURE  30°C ~ 85°C  MOUNTING TYPE  MOISTURE SPENSTITUTY LEVEL (MSL)  1 (Unlimited)  MOUNTING TURES SPENSTITUTY LEVEL (MSL)  1 (Unlimited)  MANUFACTURER STATUS / ROHS STATUS  LEAD FREE STATUS / ROHS STATUS  LILUMINATION VOLTAGE (NOMINAL)  LILUMINATION YOLTAGE (NOMINAL)  LILUMINATION YOLTAGE (NOMINAL)  FEATURES  EFECTIVES  FOR Some Sealed Teminals  LILUMINATION  CURRENT RATING  3 (AC/DC)  CIRCUIT  BUSHINS THREAD  ACTUATOR HAREAL  ACTUATOR HEREA  BESS, Chrome Plated  ACTUATOR LENGTH		Specifications of 200MSP1T2B2M6QE
MANUFACTURER         E-Switch           DESCRIPTION         SWITCH TOGGLE SPDT 3A 120V           LEAD FREE STATUS / ROHS STATUS         Lead free / RoHS Compliant           DATA SHEET         SWITCH TOGGLE SPDT 3A 120V           VOLTAGE RATING - DC         28V           VOLTAGE RATING - AC         120V           SWITCH FUNCTION STYLE         PC Pin           SWITCH FUNCTION         On-On           SERIES         200           PACKAGING         Bulk           OPERATING TEMPERATURE         -30°C ~ 85°C           MOUNTING TYPE         Through Hole, Right Angle           MOUNTING TYPE         1 (Unlimited)           MANUFACTURER STANDARD LEAD TIME         9 Wecks           LEAD FREE STATUS / ROHS STATUS         Lead free / RoHS Compliant           LEAD FREE STATUS / ROHS STATUS         Lead free / RoHS Compliant           LEAD FREE STATUS / ROHS STATUS         Lead free / RoHS Compliant           LEAD FREE STATUS / ROHS STATUS         Lead free / RoHS Compliant           LEAD FREE STATUS / ROHS STATUS         Lead free / RoHS Compliant           LILUMINATION VOLTAGE (NOMINAL)         -           LILUMINATION TYPE, COLOR         -           LELECTRICAL LIFE         TO SOJE SWITCH FURTHING           LECTRICAL LIFE         TO SOJE		
DESCRIPTION  LEAD FREE STATUS / ROHS STATUS  Lead free / ROHS Compilant  DATA SHEET  DATA	PART NUMBER	200MSP1T2B2M6QE
LEAD FREE STATUS / ROHS STATUS  DATA SHEET  DATA SHEET  20.2.00MSP1T782M6QE.pdf  2.2.00MSP1T782M6QE.pdf  2.2.00MSP1T782M6QE.p	MANUFACTURER	E-Switch
DATA SHEET         \$1.200MSP1T282M6QE.pdf           VOLTAGE RATING - DC         28V           VOLTAGE RATING - AC         120V           TERMINATION STYLE         PC PIn           SWITCH FUNCTION         0n-On           SERIES         200           PARCLAGING         Bulk           OPERATING TEMPERATURE         -30°C ~ 85°C           MOUNTING TYPE         Through Hole, Right Angle           MOUSTURE SENSITUTY LEVEL (MSL)         1 (Unlimited)           MANUFACTURES STATUS / ROHS STATUS         Lead free / ROHS Compliant           ILLUMINATION VOLTAGE (NOMINAL)         -           ILLUMINATION NOLTAGE (NOMINAL)         -           ILLUMINATION TYPE, COLOR         -           ILLUMINATION TYPE, COLOR         -           ELECTRICAL LIFE         30,000 Cycles           DETAILED DESCRIPTION         Toggle Switch SPDT Through Hole, Right Angle           CURRENT RATING         30,000 Cycles           DETAILED DESCRIPTION         Toggle Switch SPDT Through Hole, Right Angle           CURENT RATING         30,000 Cycles           DETAILED DESCRIPTION         Toggle Switch SPDT Through Hole, Right Angle           CURENT RATING         30,000 Cycles           BUSHING THREAD         Unthreaded           ACIUATO	DESCRIPTION	SWITCH TOGGLE SPDT 3A 120V
DATA SHEET         28V           VOLTAGE RATING - DC         28V           VOLTAGE RATING - AC         120V           TERMINATION STYLE         PC Pin           SWITCH FUNCTION         On-On           SERIES         200           PARCIAGING         Bulk           OPERATING TEMPERATURE         30°C ~ 85°C           MOUNTING TYPE         Through folke Right Angle           MOISTURE SENSITIVITY LEVEL (MSL)         1 (Unlimited)           MANUFACTURER STATUAS A DEAD TIME         9 Weeks           LEAD FREE STATUS / ROHS STATUS         Lead free / ROHS Compliant           ILLUMINATION VOLTAGE (NOMINAL)         -           ILLUMINATION VOLTAGE (NOMINAL)         -           IELUMINATION TYPE, COLOR         -           IELUMINATION         Non-Illuminated           FEATURES         Epoxy Seeled Terminals           ELECTRICAL LIFE         30,000 Cycles           DETAILED DESCRIPTION         Toggle Switch SPDT Through Hole, Right Angle           CURRENT RATING         3A (AC/DC)           CIRCUIT         SPDT           BUSHING THREAD         Unthreaded           ACTUATOR TYPE         Standard Round	LEAD FREE STATUS / ROHS STATUS	Lead free / RoHS Compliant
VOLTAGE RATING - AC         120V           TERMINATION STYLE         PC PIn           SWITCH FUNCTION         On-On           SERIES         200           PARL CUTOUT DIMENSIONS         -           PACKAGING         Bulk           OPERATING TEMPERATURE         -30°C ~ 85°C           MOUNTING TYPE         Through Hole, Right Angle           MOUNTING TYPE         1 (Unlimited)           MANUFACTURER STANDARD LEAD TIME         9 Weeks           LEAD FREE STATUS / ROHS STATUS         Lead free / RoHS Compliant           ILLUMINATION VOLTAGE (NOMINAL)         -           ILLUMINATION TYPE, COLOR         -           ILLUMINATION TYPE, COLOR         Non-Illuminated           FEATURES         Epoxy Sealed Terminals           ELECTRICAL LIFE         30,000 Cycles           DETAILED DESCRIPTION         Toggle Switch SPDT Through Hole, Right Angle           CURRENT RATING         3A (AC/DC)           CIRCUIT         SPDT           BUSHING THREAD         Unthreaded           ACIUATOR TYPE         Standard Round	DATA SHEET	
FERMINATION STYLE  SWITCH FUNCTION  On-On  SERIES  200  PANEL CUTOUT DIMENSIONS  - PACKAGING  Bulk  OPERATING TEMPERATURE  -30°C ~ 85°C  MOUNTING TYPE  MOUNTING TYPE  MOUSTURE SENSITIVITY LEVEL (MSL)  MANUFACTURER STANDAD LEAD TIME  49 Weeks  Lead free / ROHS Compliant  LEAD FREE STATUS / ROHS STATUS  LEAD FREE STATUS / ROHS STATUS  LEAD FREE STATUS / ROHS STATUS  LEUMINATION VOLTAGE (NOMINAL)  1-  LILUMINATION VOLTAGE (NOMINAL)  TEATURES  EDONY Sealed Terminals  ELECTRICAL LIFE  30,000 Cycles  DETAILED DESCRIPTION  TOGGIE SWITCH SPDT Through Hole, Right Angle  LURLED DESCRIPTION  TOGGIE SWITCH SPDT Through Hole, Right Angle  LURLED THROUGH SPDT  LILUMINATION  TOGGIE SWITCH SPDT Through Hole, Right Angle  LURLED THROUGH SPDT  LURLED	VOLTAGE RATING - DC	28V
SERIES         200           PANEL CUTOUT DIMENSIONS         -           PACKAGING         Bulk           OPERATING TEMPERATURE         -30°C ~ 85°C           MOUNTING TYPE         Through Hole, Right Angle           MOISTURE SENSITIVITY LEVEL (MSL)         1 (Unlimited)           MANUFACTURER STANDAD LEAD TIME         9 Weeks           LEAD FREE STATUS / ROHS STATUS         Lead free / ROHS Compliant           LILUMINATION VOLTAGE (NOMINAL)         -           ILLUMINATION TYPE, COLOR         -           ILLUMINATION TYPE, COLOR         Poovy Sealed Terminals           ELECTRICAL LIFE         30,000 Cycles           DETAILED DESCRIPTION         Toggle Switch SPDT Through Hole, Right Angle           CURRENT RATING         3A (AC/DC)           CURRENT RATING         SPDT           BUSHING THREAD         Unthreaded           ACTUATOR TYPE         Standard Round           ACTUATOR MATERIAL         Brass, Chrome Plated	VOLTAGE RATING - AC	120V
SERIES 200  PANEL CUTOUT DIMENSIONS - PACKAGING BUIK  OPERATING TEMPERATURE 30°C ~ 85°C  MOUSTING TYPE THOUGH HOIE, Right Angle  MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited)  MANUFACTURER STANDARD LEAD TIME 9 Weeks  LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant  LILUMINATION VOLTAGE (NOMINAL) -  LILUMINATION TYPE, COLOR -  LILUMINATION TYPE, COLOR SON SENSEL SENSITIVITY EVEL (MSL) 1 (Unlimited)  FEATURES 1 (UNDINATION SOLITAGE (NOMINAL) 1 (UNDI	TERMINATION STYLE	PC Pin
PACKAGING Buk  PACKAGING Buk  OPERATING TEMPERATURE -30°C ~ 85°C  MOUNTING TYPE THOUGH HOLE, RIGHT Angle  MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited)  MANUFACTURER STANDARD LEAD TIME 9Weeks  LEAD FREE STATUS / ROHS STATUS LEAD TIME 1 (Ead free / ROHS Compliant  LILUMINATION VOLTAGE (NOMINAL) -1 (EAD TIME 1 (EAD TIME 1 (EAD TIME 2 (EAD TIME 2 (EAD TIME 3 (EAD TI	SWITCH FUNCTION	On-On
PACKAGINGBulkOPERATING TEMPERATURE-30°C ~ 85°CMOUNTING TYPEThrough Hole, Right AngleMOISTURE SENSITIVITY LEVEL (MSL)1 (Unlimited)MANUFACTURER STANDARD LEAD TIME9 WeeksLEAD FREE STATUS / ROHS STATUSLead free / ROHS CompliantILLUMINATION VOLTAGE (NOMINAL)-ILLUMINATION TYPE, COLOR-ILLUMINATION TYPE, COLORNon-IlluminatedFEATURESEpoxy Sealed TerminalsELECTRICAL LIFE30,000 CyclesDETAILED DESCRIPTIONToggle Switch SPDT Through Hole, Right AngleCURRENT RATING3A (AC/DC)CURRENT RATINGSPDTBUSHING THREADUnthreadedACTUATOR TYPEStandard RoundACTUATOR MATERIALBress, Chrome Plated	SERIES	200
OPERATING TEMPERATURE         -30°C ~ 85°C           MOUNTING TYPE         Through Hole, Right Angle           MOISTURE SENSITIVITY LEVEL (MSL)         1 (Unlimited)           MANUFACTURER STANDARD LEAD TIME         9 Weeks           LEAD FREE STATUS / ROHS STATUS         Lead free / ROHS Compliant           INGRESS PROTECTION         -           ILLUMINATION VOLTAGE (NOMINAL)         -           ILLUMINATION TYPE, COLOR         Non-Illuminated           FEATURES         Epoxy Sealed Terminals           ELECTRICAL LIFE         30,000 Cycles           DETAILED DESCRIPTION         Toggle Switch SPDT Through Hole, Right Angle           CURRENT RATING         3A (AC/DC)           CURCUIT         SPDT           BUSHING THREAD         Unthreaded           ACTUATOR TYPE         Standard Round           ACTUATOR MATERIAL         Brass, Chrome Plated	PANEL CUTOUT DIMENSIONS	-
MOUNTING TYPE TYPE TYPE TYPE TYPE TYPE TYPE TYPE	PACKAGING	Bulk
MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited)  MANUFACTURER STANDARD LEAD TIME 9 Weeks  LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant  INGRESS PROTECTION  ILLUMINATION VOLTAGE (NOMINAL)  ILLUMINATION TYPE, COLOR  ILLUMINATION MON-Illuminated  FEATURES Epoxy Sealed Terminals  ELECTRICAL LIFE 30,000 Cycles  DETAILED DESCRIPTION TOggle Switch SPDT Through Hole, Right Angle  CURRENT RATING 3A (AC/DC)  CIRCUIT SPDT  BUSHING THREAD Unthreaded  ACTUATOR TYPE Standard Round  ACTUATOR MATERIAL BRASS STATUS STATUS STATUS STANDARD STATUS PLATED  ILLUMINATION TYPE Standard Round  ACTUATOR MATERIAL BRASS STATUS STANDARD ST	OPERATING TEMPERATURE	-30°C ~ 85°C
MANUFACTURER STANDARD LEAD TIME 9 Weeks  LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant  INGRESS PROTECTION  ILLUMINATION VOLTAGE (NOMINAL)  ILLUMINATION TYPE, COLOR  ILLUMINATION MON-Illuminated  FEATURES Epoxy Sealed Terminals  ELECTRICAL LIFE 30,000 Cycles  DETAILED DESCRIPTION TOggle Switch SPDT Through Hole, Right Angle  CURRENT RATING 3A (AC/DC)  CIRCUIT SPDT  BUSHING THREAD Unthreaded  ACTUATOR TYPE Standard Round  ACTUATOR MATERIAL STATUS STATUS STANDARD	MOUNTING TYPE	Through Hole, Right Angle
LEAD FREE STATUS / ROHS STATUS  LEAD FREE STATUS / ROHS STATUS  LEAD FREE STATUS / ROHS STATUS  LEAD free / ROHS Compliant  1LLUMINATION VOLTAGE (NOMINAL)  LLUMINATION TYPE, COLOR  LLUMINATION  Non-Illuminated  Epoxy Sealed Terminals  ELECTRICAL LIFE  30,000 Cycles  DETAILED DESCRIPTION  Toggle Switch SPDT Through Hole, Right Angle  CURRENT RATING  ALCYDC)  CIRCUIT  BUSHING THREAD  ACTUATOR TYPE  ACTUATOR MATERIAL  LEAD free / ROHS Compliant  ACTUATOR MATERIAL  ACTUATOR MATERIAL  Lead free / ROHS Compliant  ACTUATOR MATERIAL  ACTUA	MOISTURE SENSITIVITY LEVEL (MSL)	1 (Unlimited)
INGRESS PROTECTION - CLUMINATION VOLTAGE (NOMINAL) - CLUMINATION TYPE, COLOR - CLUMINATION TYPE, COLOR - CLUMINATION TYPE, COLOR - CLUMINATION TYPE, COLOR - CLUMINATION -	MANUFACTURER STANDARD LEAD TIME	9 Weeks
ILLUMINATION VOLTAGE (NOMINAL)  ILLUMINATION TYPE, COLOR  ILLUMINATION  Non-Illuminated  FEATURES  ELECTRICAL LIFE  30,000 Cycles  DETAILED DESCRIPTION  Toggle Switch SPDT Through Hole, Right Angle  CURRENT RATING  3A (AC/DC)  CIRCUIT  BUSHING THREAD  ACTUATOR TYPE  ACTUATOR MATERIAL  PAGE  1  1  1  1  1  1  1  1	LEAD FREE STATUS / ROHS STATUS	Lead free / RoHS Compliant
ILLUMINATION TYPE, COLOR  ILLUMINATION Non-Illuminated  FEATURES Epoxy Sealed Terminals  ELECTRICAL LIFE 30,000 Cycles  DETAILED DESCRIPTION Toggle Switch SPDT Through Hole, Right Angle  CURRENT RATING 3A (AC/DC)  CIRCUIT SPDT  BUSHING THREAD Unthreaded  ACTUATOR TYPE Standard Round  ACTUATOR MATERIAL BRASS STANDARD	INGRESS PROTECTION	-
FEATURES Epoxy Sealed Terminals  ELECTRICAL LIFE 30,000 Cycles  DETAILED DESCRIPTION Toggle Switch SPDT Through Hole, Right Angle  CURRENT RATING 3A (AC/DC)  CIRCUIT SPDT  BUSHING THREAD Unthreaded  ACTUATOR TYPE Standard Round  ACTUATOR MATERIAL	ILLUMINATION VOLTAGE (NOMINAL)	-
FEATURES  ELECTRICAL LIFE  30,000 Cycles  DETAILED DESCRIPTION  Toggle Switch SPDT Through Hole, Right Angle  CURRENT RATING  3A (AC/DC)  CIRCUIT  BUSHING THREAD  ACTUATOR TYPE  ACTUATOR MATERIAL  Epoxy Sealed Terminals  30,000 Cycles  Toggle Switch SPDT Through Hole, Right Angle  3A (AC/DC)  SPDT  SPDT  Standard Round  Brass, Chrome Plated	ILLUMINATION TYPE, COLOR	-
DETAILED DESCRIPTION Toggle Switch SPDT Through Hole, Right Angle CURRENT RATING 3A (AC/DC) CIRCUIT SPDT BUSHING THREAD Unthreaded ACTUATOR TYPE Standard Round ACTUATOR MATERIAL SPRING SPRING SPRING SPRING Plated	ILLUMINATION	Non-Illuminated
DETAILED DESCRIPTION Toggle Switch SPDT Through Hole, Right Angle  CURRENT RATING 3A (AC/DC)  CIRCUIT SPDT  BUSHING THREAD Unthreaded  ACTUATOR TYPE Standard Round  ACTUATOR MATERIAL Brass, Chrome Plated	FEATURES	Epoxy Sealed Terminals
CURRENT RATING  CIRCUIT  BUSHING THREAD  ACTUATOR TYPE  ACTUATOR MATERIAL  SA (AC/DC)  SPDT  Unthreaded  Unthreaded  Standard Round  Brass, Chrome Plated	ELECTRICAL LIFE	30,000 Cycles
CIRCUIT SPDT  BUSHING THREAD Unthreaded  ACTUATOR TYPE Standard Round  ACTUATOR MATERIAL Brass, Chrome Plated	DETAILED DESCRIPTION	Toggle Switch SPDT Through Hole, Right Angle
BUSHING THREAD Unthreaded  ACTUATOR TYPE Standard Round  ACTUATOR MATERIAL Brass, Chrome Plated	CURRENT RATING	3A (AC/DC)
ACTUATOR TYPE Standard Round  ACTUATOR MATERIAL Brass, Chrome Plated	CIRCUIT	SPDT
ACTUATOR MATERIAL Brass, Chrome Plated	BUSHING THREAD	Unthreaded
	ACTUATOR TYPE	Standard Round
ACTUATOR LENGTH 5.33mm	ACTUATOR MATERIAL	Brass, Chrome Plated
	ACTUATOR LENGTH	5.33mm

# **Related Tags**

E-Switch 200MSP1T2B2M6QE	200MSP1T2B2M6QE Distributor	200MSP1T2B2M6QE Supplier
200MSP1T2B2M6QE Price	200MSP1T2B2M6QE Pictures	200MSP1T2B2M6QE Image
200MSP1T2B2M6QE PDF Datasheet	200MSP1T2B2M6QE Download Datasheet	200MSP1T2B2M6QE Datasheet
200MSP1T2B2M6QE Stock	Buy 200MSP1T2B2M6QE	Buy E-Switch 200MSP1T2B2M6QE
E-Switch 200MSP1T2B2M6QE	E-Switch Supplier	E-Switch Distributor
E-Switch 200MSP1T2B2M6QE		

# **Related Products**



### **200MSP1T2B2M7RE** Manufacturers: E-Switch

Description: SWITCH TOGGLE SPDT 0.4VA 20V In stock: 659 pcs

**RFQ** 

## **200MSP1T2B2M2RE** Manufacturers: E-Switch

Description: SWITCH TOGGLE SPDT 0.4VA 20V

In stock: Out stock

**RFQ** 



## **200MSP1T2B2M6RE** Manufacturers: E-Switch

Description: SWITCH TOGGLE SPDT 0.4VA 20V


In stock: 858 pcs **RFQ** 

## **200MSP1T2B2M7QE** Manufacturers: E-Switch

Description: SWITCH TOGGLE SPDT 3A 120V

In stock: Out stock

**RFQ** 



# **200MSP1T2B1M6REH**

Manufacturers: E-Switch Description: SWITCH TOGGLE SPDT 0.4VA 20V

In stock: Out stock

**RFQ** 

# Manufacturers: E-Switch

**200MSP1T2B1M7QEH** 

Description: SWITCH TOGGLE SPDT 3A 120V In stock: Out stock

**RFQ** 



### 200MSP1T2B2VS2QE Manufacturers: E-Switch

Description: SWITCH TOGGLE SPDT 3A 120V In stock: Out stock

**RFQ** 

# Manufacturers: E-Switch

Description: SWITCH TOGGLE SPDT 0.4VA 20V

**200MSP1T2B2VS2RE** 

In stock: Out stock **RFQ** 

**200MSP1T2B3M1QE** 



### Manufacturers: E-Switch Description: SWITCH TOGGLE SPDT 0.4VA 20V

**200MSP1T2B1VS2RE** 

In stock: Out stock

**RFQ** 



### Manufacturers: E-Switch Description: SWITCH TOGGLE SPDT 3A 120V

In stock: Out stock


**RFQ** 



## **200MSP1T2B1M7QE** Manufacturers: E-Switch

In stock: 48 pcs

**RFQ** 







**200MSP1T2B2M2QE** 

In stock: Out stock

**RFQ** 











