product details.



MB00L2NZQD

Part Number:
Manufacturer/Brand:
Product description
Datasheets:
RoHs Status
Ship From
Shipment Way

### MB00L2NZQD

C&K SWITCH ROTARY 5POS 250MA 125V THE MB00L2NZQD.pdf

ocean-components.com

Lead free / RoHS Compliant Hong Kong DHL/Fedex/TNT/UPS/EMS

## **REQUEST FOR QUOTATION**

PART NUMBER     MINU XACUMARY       PART NUMARY URER     COK       DESCRIPTION     SWITCH ROT XAN SPOS 250NA 125V       LEAD FREE STATUS / ROHS STATUS     Lead free / ROHS Compliant       DATA SHEFT     Immon Xamany       VOLTAGE RATING - DC     28V       VOLTAGE RATING - AC     28V       VOLTAGE RATING - AC     Soler Ug       SRIES     M       PAREL CUTOUT DIMENSIONS     Greular - 6.60mm Dia       OTHER NAMES     Greular - 6.60mm Dia       ORIGE POSITIONS     REV GUE       ORIHER NAMES     SOLECUTOUT DIMENSIONS       ORIEL CUTOUT DIMENSIONS     SOLECUTING DIMENSIONS       ORIEL		Specifications of MB00L2NZQD
MNUFACTURERCKDESCRIPTIONSUTCH ROTARY SPOS 250MA 125VLEAD FREE STATUS / ROHS STATUSLead free / RoHS CompliantDATA SHEETBMB0D.1X2QD.pdfVOLTAGE RATING + OC25VVOLTAGE RATING + AC25VSTARINATION STIVLESole LuSERIESMPARLE CUTOUT DIMENSIONSCirculer - 6.00mm DiaOPHER MAMES2800 - 5.041gfmNUMERE OF POSCIPONS2.830 - 5.041gfmNUMERE OF POSCIPONS3.NUMERE OF POSCIPONS3.NUMERE OF POSCIPONS3.NUMERE OF POSCIPONS3.NUMERE OF POSCIPONS1.NUMERE OF POSCIPONS1.NUMERE OF POSCIPONS1.NUMERE OF POSCIPONS3.NUMERE OF POSCIPONS1.NUMERE OF POSCIPONS <td< th=""><th></th><th></th></td<>		
DESCRIPTIONSWITCH ROTARY SPOS 250MA 125VLEAD FREES TATUS / ROHS STATUSEad free / ROHS CompliantDATA SHEETSWISDU.2NZQD, pdfVOLTAGE RATING - OCSVVOLTAGE RATING - ACISVSERLESMRANEL CUTOUT DIMENSIONSCorcal - 6.60mn DiaOTHER NAMESSMIGU.2NZQD SURJAGE AGUND SIGNARCOOPERATING FORCE2880 ~ 5.01g/mOPERATING FORCE2880 ~ 5.01g/mNUMBER OF POSITIONSSNUMBER OF POSITIONS2.01g/mMURIER OF POSITIONS2.01g/mNUMBER OF POSITIONS1.01g/mMURIER DEF DECK2.01g/mNUMBER OF POSITIONS1.01g/mMURIER OF POSITIONS0.01g/mMURIER OF POSITIONS1.01g/mMURIER OF POSITIONS0.01g/mFITURES0.01g/mFITURES0.01g/mFITURES0.01g/mFITURES0.01g/mFITURES0.01g/mCONTACT TIMING0.01g/mCONTACT TIMING0.01g/mCONTACT TIMING0.01g/mCONTACT TIMING0.01g/m	PART NUMBER	MB00L2NZQD
LAD FREE STATUS / ROHS STATUSLad free / ROHS CompliantDATA SHEETEMBOL/L2QD pdfVICTAGE RATING - DCSIVVICTAGE RATING - ACSIGNSTRISSolder LugPANEL CUTOUT DIMENSIONSCorcular - Gom DiaDTHER MAMESSINOL/L2QD pdfOPEARTING FORCE2880 ~ S.041gfmNUMBER OF POSITIONSSNUMBER OF POSITIONSSNUMBER OF POSITIONSSNUMBER OF POSITIONSSNUMBER OF POSITIONSSINOLNUMBER OF POSITIONSSINOLNUMER OF POSITIONSSINOLNUMBER OF POSITIONSSINOLNUMBER OF POSITIONSSINOLNUMBER OF POSITIONSSINOLNUMBER OF POSITIONSSINOLSITING SINOLSINOLSITING SINOLSINOL <td>MANUFACTURER</td> <td>C&amp;K</td>	MANUFACTURER	C&K
DATA SHEETImmediateVOLTAGE RATING - DC29VVOLTAGE RATING - AC25VTERMINATION STYLESolder LugSRIFISMPANEL GUTOUT DIMENSIONSCircular - 6.0mm DiaDTHR NAMESMONOUD232QOPERATING FORCE2880 ~ 5.041gfmNUMBER OF POSITIONS5NUMBER OF POSITIONS2NUMBER OF POSITIONS2NUMBER OF POSITIONS1NUMBER OF POSITIONS1NUMPACTURER STATUS / ROHS STATUS1NUMPACTURER STATUS / ROHS STATUS1NUMPACTURER STATUS / ROHS STATUS2NUMPACTURER STATUS / ROHS STATUS2NOTICE STATUS / ROHS	DESCRIPTION	SWITCH ROTARY 5POS 250MA 125V
Voltrade RATING - DCSVVoltrade RATING - ACISVTERNINATION STVLESide LugSERIESMPAREL CUTOUT DIMENSIONSCirclar - 6.60m DiaTher NAMESSimoD/NZOPA Signol/NZOPA Signol/NZOPA Signol/NZOPA Signol/NZOPA Signol/NZOPAOPEARTING FORCE2800 - 5.41gfmNUMBER OF POSITIONSSNUMBER OF POSITIONSSNUMBER OF POSITIONSSNUMBER OF POSITIONS1MOUTING TYPEPanel MoutMOUTING TYPEIde free / RoHS CompliantMOUTING TYPEContinuousMOUTING TYPEContinuousMINIFACTURER STATUS / ROHS STATUSContinuousFEATURESContinuousPOTATURE SCRUETIONRady Schlarb Stopa Mach Color DistrictDETAILED DESCRIPTIONContinuousMINIFACTURER STATUS / ROHS STATUSContinuousEIGT DESCRUETIONRady Schlarb Stopa Mach Color District Schlarb Color District Color District Schlarb Color District Color District Schlarb Color District	LEAD FREE STATUS / ROHS STATUS	Lead free / RoHS Compliant
VICTAGE PATING - ACISVTERNINATION STYLESofe LagSERIESMPAREL CUTOUT DIMENSIONSCnailer - 6.60m DiaDTHER NAMESSofe Option DiaOTHER NAMESSofe Option DiaOPERATING FORCE2.800 ~ 5.01gfmNUMBER OF POSITIONSSNUMBER OF POSITIONSSNUMBER OF DOLS PER DECK2.800 ~ 5.01gfmNUMBER OF DOLS PER DECK1.01cmNUMBER OF DOLS PER DECK0.10cmNUMBER OF DOLS PER DECK1.01cmNUMBER OF DOLS PER DECK1.01cmNUMPACTURER STANDARD LEAD TIME1.01cmIL DOLS PER DECK0.01cmRET TURES0.01cmIL DOLS PER DECK0.01cmIL DOLS PER DECK <td>DATA SHEET</td> <td>MB00L2NZQD.pdf</td>	DATA SHEET	MB00L2NZQD.pdf
TERNINATION STYLESkale LugSKRESMPARLE LUTOUT DIMENSIONSGruler - 6.0mm DiaDTHER NAMESMABOL/NZQD SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/SKILOD/	VOLTAGE RATING - DC	28V
SRIESMPARL CUTOLT DIMENSIONSCrolar - 6.0mm DiaoTHER NAMESMBOUL/X2QD NOW S324250OFTER NAMESS800 - 2.000 NOW S324250OFERATING FORCE2.880 - 5.01gfmNUMER OF POSITIONSSNUMER OF POSITIONS3NUMER OF POSITIONS3NUMER OF POSITIONS1NUMER OF POSITIONS1 <td< td=""><td>VOLTAGE RATING - AC</td><td>125V</td></td<>	VOLTAGE RATING - AC	125V
PANEL CUTOLIT DIMENSIONSCarala - 6.00m DiaarbaceMB0012N2QD Solved Solved	TERMINATION STYLE	Solder Lug
orther NAMESBNODEXPAGE SNORMANDERSOFRATING FORCE.880 ~ .041gfmNUMBER OF POSITIONSSNUMBER OF POSITIONS2NUMBER OF POSITIONS1NUMBER OF POSITIONS.810 ~ .011MURER OF POSITIONS.101 MICH COLLNUMBER OF POSITIONS.101 MICH COLLNUMBER OF POSITIONS.101 MICH COLLMURER OF POSITIONS.101 MICH COLLMURER OF POSITIONS.101 MICH COLLMURER STANDARD LEDD TIME.101 MICH COLLMURACTURER STANDARD.101 MICH COLLMURACTURER STANDARD.1	SERIES	Μ
OTHER NAMESNUN043 MBDD/3324250OPERATING FORCE2.880 ~ 5.041gfmNUMBER OF POSITIONS5NUMBER OF DOLES PER DECK2NUMBER OF DOLES PER DECK1MUNDER OF DECKS1MUNTING TYPEPanel MountMOUNTING TYPE101(Imited)MINIFACTURER STANDARD LEAD TIME104(Rest And Sch	PANEL CUTOUT DIMENSIONS	Circular - 6.60mm Dia
NUMBER OF POSITIONS5NUMBER OF POLES PER DECK2NUMBER OF POLES PER DECK1NUMBER OF DECKS1MOUNTING TYPEPanel MountMOUNTING TYPE1MOUNTING TYPE1MANUFACTURER STANDARD LEAD TIME1LEAD FREE STATUS / ROHS STATUSCalfree / RoHS CompliantINDEX STOPSContinuousFEATURES-DETAILED DESCRIPTIONRear Svatich 5 Position DPST 250mA (AC/DC) 125VAC Panel MountDETH BEHIND PANELS0mA (AC/DC)CONTACT TIMINGSoma (AC/DC)CONTACT TIMINGCoper AlloyCONTACT FINISHGoper AlloyCONTACT FINISHSilverCIGUIT PER DECKPSTANGLE OF THROWScrewire SoltANGLE OF THROWScrewire SoltCUTART NPEScrewire SoltCUTART NPEScrewire Solt	OTHER NAMES	CKN10043 MB00L2NZQD-ND
NUMBER OF POLES PER DECK2NUMBER OF POLES PER DECK1NUMBER OF DECKSPael MountMOUNTING TYPEPael MountMOUNTING TYPE1 (Inlinited)MOUSTURE SENSITIVITY LEVEL (MSL)10 (Inlinited)MANUFACTURER STANDARD LEAD TIME13 VeeksLEAD FREE STATUS / ROHS STATUSContinuousIDEX STOPSContinuousPEATURES-DETAILED DESCRIPTIONAcory Switch SPASIDAGAC/D125VAC Panel MountDETH BEHIND PANELContac MountCONTACT TIMINGSoma (Ac/DC)CONTACT TIMINGGoper AllongCONTACT FINISHSiverCONTACT FINISHSiverANGLE OF THROWSPACACOMENTANGLE OF THROWSiverANGLE OF THROWSiverANGLE OF THROWSiver StatusANGLE OF THROWSiver Status	OPERATING FORCE	2.880 ~ 5.041gfm
NUMBER OF DECKS1NUMBER OF DECKSPael MountMOUNTING TYPEPael MountMOSTURE SENSITIVT LEVEL (MSL)I (Unimed)MANUFACTURER STANDARD LEAD TIMEI 30eksLEAD FREE STATUS / ROHS STATUSColfoor (Sangalanda)INEX STOPSContiousFATURES-DETAILED DESCRIPTIONRard Schald (Sangalanda)CONTACT TIMINGSinola (Sangalanda)CONTACT TIMINGSinola (Sangalanda)CONTACT FINISHSinola (Sangalanda)CONTACT FINISHSinola (Sangalanda)CARLET PECKSinola (Sangalanda)CARLET PECKSinola (Sangalanda)CARLET PECKSinola (Sangalanda)ANGLO FITHROWSinola (Sangalanda)CARLET PECKSinola (Sangalanda)ANGLO FITHROWSinola (Sangalanda)	NUMBER OF POSITIONS	5
MOUNTING TYPEPanel MountMOUNTING TYPEI(Unimited)MOUSTURE SENSITIVT LEVEL (MSL)I(Unimited)MANUFACTURER STANDARD LEAD TIMEI3 WeeksLEAD FREE STATUS / ROHS STATUSCad free / ROHS CompliantINDEX STOPSContinuousFATURES-DETAILED DESCRIPTIONAlong Mich Postion DPST 250mA (AC/DC) 125VAC Panel MountDETH BEHIND PANELSima (AC/DC)CONTACT TIMINGSima (AC/DC)CONTACT TIMINGSima (AC/DC)CONTACT FINISHSiverCONTACT FINISHSiverANGLE OF THROWSicerANGLE OF THROWSicer </td <td>NUMBER OF POLES PER DECK</td> <td>2</td>	NUMBER OF POLES PER DECK	2
MOISTURE SENSITIVITY LEVEL (MSL)I (Unimited)MANUFACTURER STANDARD LEAD TIME13 VeeksLEAD FREE STATUS / ROHS STATUSIcal free / ROHS CompliantINDEX STOPSContinuousFEATURES-DETAILED DESCRIPTIONRary Switch S Postion DPST 250mA (AC/DC) 125VAC Panel MountDEPTH BEHIND PANELSion (AC/DC)CONTACT TIMINGSion (AC/DC)CONTACT FINISHGoper AlongCONTACT FINISHSiverCARCUT PER DECKDFTANGLE OF THROWSiverANGLE OF THROWSiver	NUMBER OF DECKS	1
MANUFACTURER STANDARD LEAD TIME13 WeeksLAD FREE STATUS / ROHS STATUSLead free / ROHS CompliantINDEX STOPSOntinuousFATURES-PETALED DESCRIPTIONRotary Switch S Position DPST 250mA (AC/DC) 125VAC Panel MountDEPTH BEHIND PANEL148mmCURRENT RATINGS0mA (AC/DC)CONTACT TIMINGOper AlloyCONTACT FINISHOper AlloyCONTACT FINISHSilverANGLE OF THROWSilverANGLE OF THROWSilverANGLE OF THROWSilverANGLE OF THROWSilver	MOUNTING TYPE	Panel Mount
LEAD FREE STATUS / ROHS STATUSLead fee / ROHS CompliantINDEX STOPSContinuousFATURES-DETAILED DESCRIPTIONRom / Rom /	MOISTURE SENSITIVITY LEVEL (MSL)	1 (Unlimited)
INDEX STOPSContinuousFATURES-DETALED SCRIPTIONRody Switch S Position DPST 250mA (AC/DC) 125VAC Panel MountDEPTH BEHIND PANELAlomCURRENT RATINGS0mA (AC/DC)CONTACT TIMINGNon-Shorting (BBM)CONTACT FINISHGoper AlongCONTACT FINISHSilverAngLe OF THROWSDFAngle OF THROWSomAngle OF THROWSomAngle OF THROWSom SomAngle OF THROWSom Som SomAngle OF THROWSom Som SomAngle OF THROWSom Som SomAngle OF THROWSom SomAngle OF THROWSom Som SomAngle OF THROWSomAngle OF THROWSom Som SomAngle OF THROWSom SomAngle OF THROWSom SomAngle OF THROWSomAngle OF THROWSom <tr< td=""><td>MANUFACTURER STANDARD LEAD TIME</td><td>13 Weeks</td></tr<>	MANUFACTURER STANDARD LEAD TIME	13 Weeks
FEATURES-FEATURESRary SWICh S Position DPST 250MA (AC/DC) 125VAC Panel MountDEPTA BELIND PANEL848mCURRENT RATINGS0mA (AC/DC)CONTACT TIMINGNon-Shorting (BBM)CONTACT FINISHGoper AlloyCINTACT FINISHSilverCINTACT FUNCD5TANGLE OF THROWSilverANGLE OF THROWSilver	LEAD FREE STATUS / ROHS STATUS	Lead free / RoHS Compliant
DETAILED DESCRIPTIONRotary Switch 5 Position DPST 250mA (AC/DC) 125VAC Panel MountDEPTH BEHIND PANEL4.86mmCURRENT RATING50mA (AC/DC)CONTACT TIMINGNon-Shorting (BBM)CONTACT MATERIALCoper AlloyCONTACT FINISHikierAngle OF THROW95TANGLE OF THROW6°ATUATOR TYPESievering Store Stor	INDEX STOPS	Continuous
DEPTH BEHIND PANEL14.86mmCURRENT RATING50mA (AC/DC)CONTACT TIMINGNon-Shorting (BBM)CONTACT FINISHCoper AlloyCONTACT FINISHSilverCIRCUIT PER DECKDP5TANGLE OF THROWSicwarian SilverANGLE OF THROWSicwarian SilverANGLE OF THROWSicwarian Silver	FEATURES	-
CURRENT RATING250mA (AC/DC)CONTACT TIMINGNon-Shorting (BBM)CONTACT MATERIALCoper AlloyCONTACT FINISHSilverCIRCUIT PER DECKDP5TANGLE OF THROWSicwarian SilverANGLE OF THROWSicwarian SilverANGLE OF THROWSicwarian Silver	DETAILED DESCRIPTION	Rotary Switch 5 Position DP5T 250mA (AC/DC) 125VAC Panel Mount
CONTACT TIMINGNon-Shorting (BBM)CONTACT MATERIALCoper AlloyCONTACT FINISHSilverCRCUIT PER DECKDP5TANGLE OF THROW36°ACTUATOR TYPEScewdriver Slot	DEPTH BEHIND PANEL	14.86mm
CONTACT MATERIALCoper AlloyCONTACT FINISHSilverCIRCUIT PER DECKDP5TANGLE OF THROWGeACTUATOR TYPESieveriver Sold	CURRENT RATING	250mA (AC/DC)
CONTACT FINISH   Silver     CIRCUIT PER DECK   DP5T     ANGLE OF THROW   36°     ACTUATOR TYPE   Screwdriver Slott	CONTACT TIMING	Non-Shorting (BBM)
CIRCUIT PER DECKDP5TANGLE OF THROW36°ACTUATOR TYPEScrewdriver Slot	CONTACT MATERIAL	Copper Alloy
ANGLE OF THROW 36°   ACTUATOR TYPE Screwdriver Slot	CONTACT FINISH	Silver
ACTUATOR TYPE Screwdriver Slot	CIRCUIT PER DECK	DP5T
	ANGLE OF THROW	36°
ACTUATOR LENGTH Flush	ACTUATOR TYPE	Screwdriver Slot
	ACTUATOR LENGTH	Flush

# **Related Tags**

C&K MB00L2NZQD	MB00L2NZQD Distributor	MB00L2NZQD Supplier
MB00L2NZQD Price	MB00L2NZQD Pictures	MB00L2NZQD Image
MB00L2NZQD PDF Datasheet	MB00L2NZQD Download Datasheet	MB00L2NZQD Datasheet
MB00L2NZQD Stock	Buy MB00L2NZQD	Buy C&K MB00L2NZQD
C&K MB00L2NZQD	C&K Supplier	C&K Distributor
C&K MB00L2NZQD	C&K Components MB00L2NZQD	

## **Related Products**

000	MBOOL1NZQF Manufacturers: C&K Description: SWITCH ROTARY 5POS 250MA 125V In stock: 18 pcs	<b>C</b> &K	MB00L2NCQD Manufacturers: C&K Description: SWITCH ROTARY 5POS 250MA 125V In stock: Out stock RFQ
	MB00L2NCGD Manufacturers: C&K Description: SWITCH ROTARY 5POS 250MA 125V In stock: 10 pcs RFQ	<b>C</b> &K	MBOOL2NZQF Manufacturers: C&K Description: SWITCH ROTARY 5POS 250MA 125V In stock: Out stock RFQ
&K	<b>MBOOL3NZQF</b> Manufacturers: C&K Description: SWITCH ROTARY 5POS 250MA 125V In stock: Out stock	<b>C</b> &K	MB00L2NZGF Manufacturers: C&K Description: SWITCH ROTARY 5POS 250MA 125V In stock: Out stock

RFQ

MB00L3NCGD

#### MB00L3NCQD

RFQ



Manufacturers: C&K Description: SWITCH ROTARY 5POS 250MA 125V In stock: Out stock

RFQ

MB00L3NZGF



Manufacturers: C&K Description: SWITCH ROTARY 5POS 250MA 125V In stock: Out stock

RFQ

### MB00L3NCQF

MB00L2NCGF



Manufacturers: C&K Description: SWITCH ROTARY 5POS 250MA 125V In stock: Out stock

RFQ



Manufacturers: C&K Description: SWITCH ROTARY 5POS 250MA 125V In stock: Out stock

RFQ

### MB00L2NCQF



Manufacturers: C&K Description: SWITCH ROTARY 5POS 250MA 125V In stock: Out stock

RFQ



Manufacturers: C&K Description: SWITCH ROTARY 5POS 250MA 125V In stock: Out stock

RFQ

#### Copyright © 2020 Reliable Distributor of Electronic Components - Ocean-Components.com

E-mail: Info@Ocean-Components.com

Address: Room 2102, Connaught Commercial Building, 185 Wan Chai Rd, Wan Chai, Hong Kong

